HALLIBURTON

SAFETY DATA SHEET

Product Trade Name: APPALACHIAN BLEND CEMENT

Revision Date: 18-Apr-2015 Revision Number: 6

1. Identification

1.1. Product Identifier

Product Trade Name: APPALACHIAN BLEND CEMENT

Synonyms: None
Chemical Family: Cement
Internal ID Code HM004617

1.2 Recommended use and restrictions on use

Application: Cement

Uses Advised Against No information available

1.3 Manufacturer's Name and Contact Details

Manufacturer/Supplier Halliburton Energy Services

P.O. Box 1431

Duncan, Oklahoma 73536-0431

Emergency Telephone: (281) 575-5000

Prepared By Chemical Stewardship

Telephone: 1-580-251-4335

e-mail: fdunexchem@halliburton.com

1.4. Emergency telephone number

Emergency Telephone Number (281) 575-5000

2. Hazard(s) Identification

2.1 Classification in accordance with paragraph (d) of §1910.1200

Skin Corrosion / Irritation	Category 2 - H315
Serious Eye Damage / Eye Irritation	Category 1 - H318
Skin Sensitization	Category 1 - H317
Carcinogenicity	Category 1A - H350
Specific Target Organ Toxicity - (Single Exposure)	Category 3 - H335
Specific Target Organ Toxicity - (Repeated Exposure)	Category 1 - H372

2.2. Label Elements

Hazard Pictograms



Signal Word

Danger

Hazard Statements H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage H335 - May cause respiratory irritation

H350 - May cause cancer

H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary Statements

Prevention P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P260 - Do not breathe dust/fume/gas/mist/vapors/spray

P264 - Wash face, hands and any exposed skin thoroughly after handling

P270 - Do not eat, drink or smoke when using this product P271 - Use only outdoors or in a well-ventilated area

P272 - Contaminated work clothing should not be allowed out of the workplace P280 - Wear protective gloves/protective clothing/eye protection/face protection

Response P302 + P352 - IF ON SKIN: Wash with plenty of soap and water

P304 + P340 - IF INHALED: Remove to fresh air and keep at rest in a position

comfortable for breathing

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P332 + P313 - If skin irritation occurs: Get medical advice/attention P337 + P313 - If eye irritation persists: Get medical advice/attention P362 - Take off contaminated clothing and wash before reuse

Storage P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P405 - Store locked up

P501 - Dispose of contents/container in accordance with Disposal

local/regional/national/international regulations

Contains

Substances **CAS Number** Portland cement 65997-15-1 14808-60-7 Crystalline silica, quartz

2.3 Hazards not otherwise classified

None known

3. Composition/information on Ingredients

Substances	CAS Number	PERCENT (w/w)	GHS Classification - US
Portland cement	65997-15-1	60 - 100%	Skin Irrit. 2 (H315) Eye Corr. 1 (H318) Skin Sens. 1 (H317)
			STOT SE 3 (H335)
Crystalline silica, quartz	14808-60-7	1 - 5%	Carc. 1A (H350) STOT RE 1 (H372)

The exact percentage (concentration) of the composition has been withheld as proprietary.

4. First-Aid Measures

4.1. Description of first aid measures

Inhalation If inhaled, remove from area to fresh air. Get medical attention if respiratory

irritation develops or if breathing becomes difficult.

Revision Date: 18-Apr-2015

Eyes Immediately flush eyes with large amounts of water for at least 30 minutes. Seek

prompt medical attention.

Skin Wash with soap and water. Get medical attention if irritation persists.

Ingestion Under normal conditions, first aid procedures are not required.

4.2 Most important symptoms/effects, acute and delayed

Causes skin irritation. Causes eye irritation. May cause allergic skin reaction. Carcinogen. Breathing crystalline silica can cause lung disease, including silicosis and lung cancer. Crystalline silica has also been associated with scleroderma and kidney disease. May cause respiratory irritation. May cause damage to internal organs.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. Fire-fighting measures

5.1. Extinguishing media

Suitable Extinguishing Media

None - does not burn.

Extinguishing media which must not be used for safety reasons

None known.

5.2 Specific hazards arising from the substance or mixture

Special Exposure Hazards

None anticipated

5.3 Special protective equipment and precautions for fire-fighters

Special Protective Equipment for Fire-Fighters

Full protective clothing and approved self-contained breathing apparatus required for fire fighting personnel.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use appropriate protective equipment. Avoid creating and breathing dust.

See Section 8 for additional information

6.2. Environmental precautions

Prevent from entering sewers, waterways, or low areas.

6.3. Methods and material for containment and cleaning up

Collect using dustless method and hold for appropriate disposal. Consider possible toxic or fire hazards associated with contaminating substances and use appropriate methods for collection, storage and disposal.

7. Handling and storage

7.1. Precautions for Safe Handling

Handling Precautions

Avoid contact with eyes, skin, or clothing. This product contains quartz, cristobalite, and/or tridymite which may become airborne without a visible cloud. Avoid breathing dust. Avoid creating dusty conditions. Use only with adequate ventilation to keep exposure below recommended exposure limits. Wear a NIOSH certified, European Standard En 149, or equivalent respirator when using this product. Material is slippery when wet.

APPALACHIAN BLEND CEMENT Revision Date: 18-Apr-2015

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Storage Information

Store in a cool, dry location. Use good housekeeping in storage and work areas to prevent accumulation of dust. Close container when not in use. Product has a shelf life of 24 months.

8. Exposure Controls/Personal Protection

8.1 Occupational Exposure Limits

Substances	CAS Number	OSHA PEL-TWA	ACGIH TLV-TWA
Portland cement	65997-15-1	15 mg/m ³	TWA: 1 mg/m ³
Crystalline silica, quartz		10 mg/m³ %SiO2 + 2	TWA: 0.025 mg/m ³

8.2 Appropriate engineering controls

Engineering Controls

Use approved industrial ventilation and local exhaust as required to maintain

exposures below applicable exposure limits.

8.3 Individual protection measures, such as personal protective equipment

Respiratory Protection Wear a NIOSH certified, European Standard EN 149 (FFP2/FFP3), AS/NZS 1715,

or equivalent respirator when using this product.

Hand Protection Normal work gloves.

Skin Protection Wear clothing appropriate for the work environment. Dusty clothing should be

laundered before reuse. Use precautionary measures to avoid creating dust when

removing or laundering clothing.

Eye Protection Wear safety glasses or goggles to protect against exposure.

Other Precautions Eyewash fountains and safety showers must be easily accessible.

9. Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Physical State: Solid Color: Gray

Odor: Odorless Odor No information available

Threshold:

12.4

Property Values

Remarks/ - Method pH:

Freezing Point/Range No information available.

Melting Point/Range No data available **Boiling Point/Range** No data available Flash Point No data available Flammability (solid, gas) No data available upper flammability limit No data available lower flammability limit No data available **Evaporation rate** No data available **Vapor Pressure** No data available No data available **Vapor Density**

Specific Gravity 3.15

Water Solubility Insoluble in water Solubility in other solvents No data available Partition coefficient: n-octanol/water No data available

Autoignition Temperature No data available **Decomposition Temperature** No data available **Viscosity** No data available

Explosive Properties No information available No information available **Oxidizing Properties**

9.2. Other information

VOC Content (%) No data available

10. Stability and Reactivity

10.1. Reactivity

Not expected to be reactive.

10.2. Chemical Stability

Stable

10.3. Possibility of Hazardous Reactions

Will Not Occur

10.4. Conditions to Avoid

Keep away from any contact with water.

10.5. Incompatible Materials

Hydrofluoric acid.

10.6. Hazardous Decomposition Products

Amorphous silica may transform at elevated temperatures to tridymite (870 C) or cristobalite (1470 C).

11. Toxicological Information

11.1 Information on likely routes of exposure

Principle Route of Exposure Eye or skin contact, inhalation.

11.2 Symptoms related to the physical, chemical and toxicological characteristics

Acute Toxicity Inhalation

Inhaled crystalline silica in the form of quartz or cristobalite from occupational

sources is carcinogenic to humans (IARC, Group 1). There is sufficient evidence in experimental animals for the carcinogenicity of tridymite (IARC, Group 2A).

Breathing silica dust may cause irritation of the nose, throat, and respiratory passages. Breathing silica dust may not cause noticeable injury or illness even though permanent lung damage may be occurring. Inhalation of dust may also have serious chronic health effects (See "Chronic Effects/Carcinogenicity"

subsection below).

Causes severe eye irritation. Will damage tissue. **Eve Contact**

Skin Contact Causes severe skin irritation. May cause an allergic skin reaction. May cause

alkali burns with confined contact.

May cause abdominal pain, vomiting, nausea, and diarrhea. Ingestion

Chronic Effects/Carcinogenicity Silicosis: Excessive inhalation of respirable crystalline silica dust may cause a progressive, disabling, and sometimes-fatal lung disease called silicosis. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness, and reduced pulmonary function. This disease is exacerbated by smoking. Individuals with silicosis are predisposed to develop tuberculosis.

Revision Date: 18-Apr-2015

Cancer Status: The International Agency for Research on Cancer (IARC) has determined that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources can cause lung cancer in humans (Group 1 - carcinogenic to humans) and has determined that there is sufficient evidence in experimental animals for the carcinogenicity of tridymite (Group 2A - possible carcinogen to humans). Refer to IARC Monograph 68, Silica, Some Silicates and Organic Fibres (June 1997) in conjunction with the use of these minerals. The National Toxicology Program classifies respirable crystalline silica as "Known to be a human carcinogen". Refer to the 9th Report on Carcinogens (2000). The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica, quartz, as a suspected human carcinogen (A2).

There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of significant disease endpoints such as scleroderma (an immune system disorder manifested by scarring of the lungs, skin, and other internal organs) and kidney disease.

11.3 Toxicity data

Toxicology data for the components

toxicology data for the compensate				
Substances	CAS Number	LD50 Oral	LD50 Dermal	LC50 Inhalation
Portland cement	65997-15-1	> 2000 mg/kg (Rat)	> 2000 mg/kg	> 1 mg/L (Rat) 4h
Crystalline silica, quartz	14808-60-7	>15,000 mg/kg (Human)	No data available	No data available

Substances	CAS Number	Skin corrosion/irritation
Portland cement	65997-15-1	Irritating to skin. (Rabbit)
Crystalline silica, quartz	14808-60-7	Non-irritating to the skin

Substances	CAS Number	Eye damage/irritation
Portland cement	65997-15-1	Corrosive to eyes
Crystalline silica, quartz	14808-60-7	Mechanical irritation of the eyes is possible.

Substances	CAS Number	Skin Sensitization
Portland cement	65997-15-1	May cause sensitization by skin contact
Crystalline silica, quartz	14808-60-7	No information available.

Substances	CAS Number	Respiratory Sensitization
Portland cement	65997-15-1	No information available
Crystalline silica, quartz	14808-60-7	No information available

Substances	CAS Number	Mutagenic Effects
Portland cement	65997-15-1	Not regarded as mutagenic.
Crystalline silica, quartz	14808-60-7	Not regarded as mutagenic.

Substances	CAS Number	Carcinogenic Effects
Portland cement	65997-15-1	No information available.
Crystalline silica, quartz		Contains crystalline silica which may cause silicosis, a delayed and progressive lung disease. The IARC and NTP have determined there is sufficient evidence in humans of the carcinogenicity of crystalline silica with repeated respiratory exposure. Based on available scientific evidence, this substance is a threshold carcinogen with a mode of action involving indirect genotoxicity secondary to lung injury.

Substances	CAS Number	Reproductive toxicity
Portland cement	65997-15-1	No information available
Crystalline silica, quartz	14808-60-7	No information available

Substances	CAS Number	STOT - single exposure
Portland cement	65997-15-1	May cause respiratory irritation.
Crystalline silica, quartz	14808-60-7	No significant toxicity observed in animal studies at concentration requiring classification.

Substances	CAS Number	STOT - repeated exposure
Portland cement	65997-15-1	No information available
Crystalline silica, quartz	14808-60-7	Causes damage to organs through prolonged or repeated exposure if inhaled: (Lungs)

Substances	CAS Number	Aspiration hazard
Portland cement	65997-15-1	Not applicable
Crystalline silica, quartz	14808-60-7	Not applicable

12. Ecological Information

12.1. Toxicity
Ecotoxicity Effects

Product Ecotoxicity Data

No data available

Substance Ecotoxicity Data

Substances	CAS Number	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Toxicity to Invertebrates
Portland cement	65997-15-1	No information available	No information available	No information available	No information available
Crystalline silica, quartz	14808-60-7	No information available	LL0 (96h) 10,000 mg/L (Danio rerio) (similar substance)		LL50 (24h) > 10,000 mg/L (Daphnia magna) (similar substance)

12.2. Persistence and degradability

Substances	CAS Number	Persistence and Degradability
Portland cement		The methods for determining biodegradability are not applicable to inorganic substances.
Crystalline silica, quartz		The methods for determining biodegradability are not applicable to inorganic substances.

12.3. Bioaccumulative potential

Substances	CAS Number	Log Pow
Portland cement	65997-15-1	No information available
Crystalline silica, quartz	14808-60-7	No information available

12.4. Mobility in soil

Substances	Mobility
Portland cement	No information available
Crystalline silica, quartz	No information available

12.5 Other adverse effects

No information available

13. Disposal Considerations

13.1. Waste treatment methods

Disposal Method Bury in a licensed landfill according to federal, state, and local regulations.

Revision Date: 18-Apr-2015

Follow all applicable national or local regulations. **Contaminated Packaging**

14. Transport Information

US DOT

Not restricted **UN Number: UN Proper Shipping Name:** Not restricted **Transport Hazard Class(es):** Not applicable Not applicable **Packing Group: Environmental Hazards:** Not applicable

US DOT Bulk

DOT (Bulk) Not applicable

Canadian TDG

UN Number: Not restricted **UN Proper Shipping Name:** Not restricted Not applicable Transport Hazard Class(es): **Packing Group:** Not applicable **Environmental Hazards:** Not applicable

IMDG/IMO

Not restricted **UN Number: UN Proper Shipping Name:** Not restricted **Transport Hazard Class(es):** Not applicable **Packing Group:** Not applicable **Environmental Hazards:** Not applicable

IATA/ICAO

UN Number: Not restricted **UN Proper Shipping Name:** Not restricted **Transport Hazard Class(es):** Not applicable **Packing Group:** Not applicable **Environmental Hazards:** Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable

Special Precautions for User: None

15. Regulatory Information

US Regulations

US TSCA Inventory All components listed on inventory or are exempt.

EPA SARA Title III Extremely

Hazardous Substances

Not applicable

EPA SARA (311,312) Hazard

Acute Health Hazard Chronic Health Hazard **Class**

This product does not contain a toxic chemical for routine annual "Toxic Chemical **EPA SARA (313) Chemicals**

Release Reporting" under Section 313 (40 CFR 372).

EPA CERCLA/Superfund Reportable Spill Quantity Not applicable.

EPA RCRA Hazardous Waste

Classification

If product becomes a waste, it does NOT meet the criteria of a hazardous waste

as defined by the US EPA.

The California Proposition 65 regulations apply to this product. **California Proposition 65**

MA Right-to-Know Law One or more components listed.

NJ Right-to-Know Law One or more components listed.

One or more components listed. PA Right-to-Know Law

Canadian Regulations

Canadian DSL Inventory All components listed on inventory or are exempt.

16. Other information

Preparation Information

Prepared By

Chemical Stewardship Telephone: 1-580-251-4335

e-mail: fdunexchem@halliburton.com

Revision Date: 18-Apr-2015

Reason for Revision Update to Format SECTION: 2

Additional information

For additional information on the use of this product, contact your local Halliburton representative.

For questions about the Safety Data Sheet for this or other Halliburton products, contact Chemical Stewardship at 1-580-251-4335.

Key or legend to abbreviations and acronyms

bw – body weight

CAS - Chemical Abstracts Service

EC50 - Effective Concentration 50%

ErC50 – Effective Concentration growth rate 50%

LC50 - Lethal Concentration 50%

LD50 - Lethal Dose 50%

LL50 - Lethal Loading 50%

mg/kg - milligram/kilogram

mg/L - milligram/liter

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OEL - Occupational Exposure Limit

PEL – Permissible Exposure Limit

ppm - parts per million

STEL - Short Term Exposure Limit

TWA - Time-Weighted Average

UN - United Nations

h - hour

mg/m³ - milligram/cubic meter

mm - millimeter

mmHg - millimeter mercury

w/w - weight/weight

d - day

Key literature references and sources for data

www.ChemADVISOR.com/

Disclaimer Statement

This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

End of Safety Data Sheet