
Material Safety Data Sheet



Revision Date: 27-Mar-2012 Revision Number: 1

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Idemitsu Automatic Transmission Fluid Type-J, 12 x 1 Quart

Product Code: 10108-042E

Recommended use Automotive Lubricant

Contact Manufacturer Idemitsu Lubricants America,

701 Port Rd.

Jeffersonville, IN. 47130 Telephone: 812-285-8234 Fax: 812-285-8243

Contact Name: Robin Hutchens Email: rhutchens@ilacorp.com

Emergency Telephone Number Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

CAUTION!

Emergency Overview

Vapors may be irritating to eyes, nose, throat, and lungs

Appearance Clear Red Physical State: Liquid Odor: Mild

Mexico - Grade Slight risk, Grade 1

Potential Health Effects

Principle Routes of Exposure Skin, Eye

Acute Effects

Eyes Mild eye irritation.

Skin Mild skin irritation.

Inhalation Contains a petroleum-based mineral oil. May cause respiratory irritation or other pulmonary

effects following prolonged or repeated inhalation of oil mist at airborne levels above the recommended mineral oil mist exposure limit. Symptoms of respiratory irritation may include

coughing and difficulty breathing

Ingestion May be harmful if swallowed

Type-5, 12 X T Quart

Chronic Effects This product contains a petroleum-based mineral oil. Prolonged or repeated skin contact can

cause mild irritation and inflammation characterized by drying, cracking, (dermatitis) or oil

acne. Repeated or prolonged inhalation of petroleum-based mineral oil mists at

concentrations above applicable workplace exposure levels can cause respiratory irritation or

Revision Date: 27-Mar-2012

other pulmonary effects

See Section 11 for additional Toxicological information.

Potential Environmental Effects See Section 12 for additional Ecological information.

3. COMPOSITION/INFORMATION ON INGREDIENTS

While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this MSDS contains valuable information critical to the safe handling and proper use of the product. This MSDS should be retained and available for employees and other users of this product.

Non-Hazardous Components

100 100 000 000 000 000 000 000 000 000					
Chemical Name	CAS-No	Weight %			
Lubricating Base Stocks	Mixture	>85			

4. FIRST AID MEASURES

General Advice If symptoms persist, call a physician. Show this safety data sheet to the doctor in attendance.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. If eye irritation persists, consult a specialist.

Skin contactWash off immediately with soap and plenty of water while removing all contaminated clothes

and shoes. If skin irritation persists, call a physician.

Inhalation Move to fresh air in case of accidental inhalation of vapours or decomposition products. If

symptoms persist, call a physician.

Ingestion Do not induce vomiting without medical advice. Call a physician or Poison Control Center

immediately. Never give anything by mouth to an unconscious person.

Protection of First-aiders Use personal protective equipment. Avoid contact with skin, eyes and clothing.

5. FIRE-FIGHTING MEASURES

Flammable Properties NFPA: Class IIIB Combustible Liquid

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Hazardous combustion products Carbon oxides, Nitrogen oxides (NOx), Sulphur oxides, oxides of

phosphorus.

Specific Hazards Arising from the Chemical

Keep product and empty container away from heat and sources of ignition.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Type-J, 12 x 1 Quart

NFPA Health: 1 Flammability: 1 Instability: 0

6. ACCIDENTAL RELEASE MEASURES

adequate ventilation. Keep people away from and upwind of spill/leak.

Environmental Precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Spill Management

LARGE SPILLS Eliminate sources of ignition. Prevent additional discharge of material if possible to do so

without hazard. For small spills implement cleanup procedures; for large spills implement cleanup procedures and, if in public area, keep public away and advise authorities. Also, if this product is subject to CERCLA reporting (see Section 15 Regulatory Information) notify

Revision Date: 27-Mar-2012

the National Response Center.

WATER SPILLS Prevent liquid entering sewers, watercourses, or low areas. Contain spilled liquid with sand

or earth. Recover by pumping or with suitable absorbent. If liquid is too viscous for pumping, scrape up. Consult an expert on disposal of recovered material and ensure

conformity to local disposal regulations

7. HANDLING AND STORAGE

Handling Wear personal protective equipment. Do not breathe vapors or spray mist. Remove and wash

contaminated clothing before re-use.

Storage Keep in properly labeled containers. Keep container tightly closed in a dry and well-ventilated

place.

Safe Handling Advice Wear personal protective equipment. Remove and wash contaminated clothing before re-use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Other Exposure Guidelines (If Generated)

Chemical Name	OSHA PEL	ACGIH TLV	ACGIH OEL (STEL)	NIOSHT REL TWA	ILA IHG	ILA ROEG
Hydrogen sulfide	Ceiling: 20 ppm	TWA: 1 ppm STEL: 5 ppm	5 ppm			
Oil mist, mineral	TWA: 5 mg/m ³	TWA: 5 mg/m ³		TWA 5 mg/m ³ ST 10 mg/m ³		

Engineering measures Ensure adequate ventilation, especially in confined areas.

Personal Protective Equipment

Eye/face Protection Safety glasses with side-shields.

Skin Protection Wear protective gloves/clothing. Glove Type: Neoprene, Nitriles

10108-042E - Idemitsu Automatic Transmission Fluid Type-J, 12 x 1 Quart

Type o, 12 x 1 quart

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

Revision Date: 27-Mar-2012

provided in accordance with current local regulations.

General Hygiene Considerations When using, do not eat, drink or smoke. Clean equipment, work area and clothing regularly.

Handle in accordance with good industrial hygiene and safety practices...

9. PHYSICAL AND CHEMICAL PROPERTIES

AppearanceClear RedOdor:MildPhysical State:Liquid

 Flash Point
 174°C / 345°F

 Method
 COC ASTM D92

 Density
 0.85 g/cm³@15°C

Viscosity @ 40C= 34.88 cSt; @ 100C = 7.332 cSt

10. STABILITY AND REACTIVITY

Chemical Stability Stable under recommended storage conditions. Hazardous

polymerization does not occur.

Conditions to AvoidHeat, flames and sparksIncompatible MaterialsStrong oxidizing agents.

Hazardous decomposition products Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

LD50 Oral: > 7000 mg/kg **LD50 Dermal:** > 4000 mg/kg

Chronic Toxicity

Carcinogenicity:

The petroleum base oils contained in this product have been highly refined by a variety of processes including solvent extraction, hydrotreating, and dewaxing to remove aromatics and improve performance characteristics. All of the oils meet the IP-346 criteria of less than 3 percent PAH's and therefore none are listed as a carcinogen by NTP, IARC, or OSHA

12. ECOLOGICAL INFORMATION

Ecotoxicity

Type-0, 12 x 1 Qualt

12. ECOLOGICAL INFORMATION

Plants and animals may experience harmful or fatal effects when coated with petroleum products. Petroleum-based (mineral) lubricating oils normally will float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in the waterway may be sufficient to cause a fish kill or create an anaerobic environment.

This material contains phosphorus which is a controlled element for disposal in effluent waters in most sections of North America. Phosphorus is known to enhance the formation of algae. Severe algae growth can reduce oxygen content in the water possibly below levels necessary to support marine life.

13. DISPOSAL CONSIDERATIONS

Hazard characteristic and regulatory waste stream classification can change with product use. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition.

Waste Disposal Method This material, as supplied, is not a hazardous waste according to Federal regulations (40

CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local

Revision Date: 27-Mar-2012

regulations for additional requirements.

Contaminated Packaging Dispose of in accordance with local regulations.

14. TRANSPORT INFORMATION

DOT Not regulated

IATA Not regulated

IMDG/IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

All components in the product are on the following Inventory Lists: U.S.A. (TSCA), Canada (DSL/NDSL), Korea (ECL), China (IECSC).

Hazardous Components

USA

Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Type-J, 12 x T Quart

Revision Date: 27-Mar-2012

SARA 311/312 Hazardous Categorization

Acute Health HazardNoChronic Health HazardNoFire HazardNoSudden Release of Pressure HazardNoReactive HazardNo

CERCLA/SARA 302 & 304

Section 302 & 304 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 355.

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any HAPs.

State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	Weight %	California Prop. 65		Safe Harbor Limits for Cancer-causing Chemicals (NSRLs)
Benzene	71-43-2	<0.05	Carcinogen Developmental Male Reproductive	24µg/dayoral 49µg/dayinhalation	6.4 µg/day oral 13 µg/day inhalation

State Right-to-Know

This product does not contain any substances regulated by state right-to-know regulations.

Predominant Ingredients - NJRTK

Fredominant ingredients - NJK i K	
Chemical Name	CAS-No
2-Propenoic acid, 2-methyl-, dodecyl ester, polymer with eicosyl 2-methyl-2- propenoate, hexadecyl 2-methyl-2-propenoate, methyl 2-methyl-2-propenoate, octadecyl 2-methyl-2-propenoate, pentadecyl 2-met	63150-07-2
Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based, contg. solvent deasphalted residual oil	72623-84-8
Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based	72623-86-0
White mineral oil	8042-47-5
Alkenyl dicarboxylamide	ACC#147376

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

Non-controlled

Legend

NPRI - National Pollutant Release Inventory

Type-J, 12 x 1 Quart

16. OTHER INFORMATION

Revision Date: 27-Mar-2012

Prepared By Robin Hutchens

Preparation Date 15-Jan-2010

Revision Date: 27-Mar-2012

Revision Summary: Determine the product wasn't an OSHA Hazard. Added the NJRTK Predominant Ingredients .

Disclaimer:

The information provided on this MSDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet