

Product name: AZOLLA ZS 32 Page: 1/6

This sheet supersedes the one dated :2004-11-16

PRODUCT LABELS

LABELLING (standard or EU): Not concerned

R-phrases: R-52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

S-phrases: S-61 Avoid release to the environment. Refer to special instructions/Safety Data

Sheets.

TRANSPORT LABELLING: Not applicable.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY UNDERTAKING

Name of the product: AZOLLA ZS 32

Code No.:

Product application: Hydraulic antiwear oil

Supplier: TOTAL UK LIMITED

40 Clarendon Road

Watford. Hertfordshire. WD17 1TQ

UNITED KINGDOM Tel: 01923 694000 Fax: 01923 694400

*Contact: Specific Product Related Info: 01977 636200

*Emergency telephones : UK - 01923 694000

*Poisons Advice Centre: NHS Direct: 0845 46 47 / Textphone: 0845 606 46 47 *Burns Units: NHS Direct: 0845 46 47 / Textphone: 0845 606 46 47

See local details at end of sheet:

Manufacturer: TOTAL UK LIMITED

40 Clarendon Road

Watford. Hertfordshire. WD17 1TQ

UNITED KINGDOM Tel: 01923 694000 Fax: 01923 694400

2. HAZARDS IDENTIFICATION

Health effects: Under normal conditions of use, the product holds no danger of intoxication

Environmental impact: Do not discharge this product into the environment.

Physico-chemical hazards: No specific risk of fire or explosion under normal conditions of use

3. COMPOSITION/INFORMATION ON INGREDIENTS

PREPARATION

Chemical nature: Petroleum-derived severely refined mineral-base product

in which the polycyclic aromatic hydrocarbons (PCA or PAH) content, measured by

IP 346, is less than 3%



Product name: AZOLLA ZS 32 Page: 2/6

SDS n° :31373-44 Version :1.01 Version of :2005-02-11

This sheet supersedes the one dated :2004-11-16

Substances presenting a health hazard	EC No.	CAS No.	Content	Symbol(s)	R-phrases
Zinc alkyl di thiophosphate	272-028-3	68649-42-3	<0,6 %	Xi ,N	R-38, 41, 51/53
Alkyl phenol			<0,2 %	N	R-50/53

See section 16 for explanations of R-phrases:

4. FIRST AID MEASURES

IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.

Inhalation: Inhalation of heavy concentrations of vapour, fumes or spray, may cause mild

irritation of the throat.

Transport the person into fresh air, keep warm and allow to rest.

Ingestion: Possible risk of vomiting and diarrhoea.

Do not induce vomiting to avoid the risk of aspiration into the respiratory tract.

Give nothing to drink

Skin contact: If the skin is exposed to high-pressure spray, the product may enter the human body.

In all such cases the affected person must be taken to hospital, even if no sign of

injury can be detected.

Immediately remove all soiled or stained clothing.

Wash the affected area immediately and repeatedly with soap and water.

Eye contact: Keep eyes open and rinse immediately and repeatedly with water for at least 15

minutes.

Aspiration: If the product is believed to have entered the lungs (in case of vomiting, for

example), take the person to hospital for immediate care.

5. FIRE FIGHTING MEASURES

Flash point: See heading 9

Extinguishing media: - suitable:

Foam, carbon dioxide (CO2), powder.

- not recommended:

do not use water jets (stick jets) for extinguishing fire since they could help to

spread the flames.

Specific hazards: Vapours can build explosive mixtures with air.

Vapours are heavier than air and may spread on the ground to sources of ignition.

Hazardous combustion products: Incomplete combustion and thermolysis produces potentially toxic gases such as

CO, CO2, different hydrocarbons, aldehydes, etc. and soot. The inhalation of these

materials is very dangerous.

Protective measures for firefighters: Insulated breathing apparatus must be worn in confined premises with heavy

concentrations of fumes and gases.

Other: All combustion residues and contaminated water from fire-fighting should be

disposed of according to local regulations.

6. ACCIDENTAL RELEASE MEASURES

See sections 8 and 13.

Personal protection : Ensure good ventilation.

Remove sources of ignition. Do not smoke.



Product name: AZOLLA ZS 32 Page: 3/6

SDS n° :31373-44 Version :1.01 Version of :2005-02-11

This sheet supersedes the one dated :2004-11-16

After spillage / leakage : - On the soil:

Surfaces on which the product has been spilled may become slippery. Do not allow the product to enter sewers or rivers or contaminate the soil.

Recover with mechanical means such as pumps and skimmers.

Contain and collect the spilled product with sand or any other inert absorbant

material.
- On water:

Floating absorbant material, then mechanical recovery.

If the product is spilled in a river or in the sewers, notify the authorities of the

possible presence of surface effluent.

7. HANDLING AND STORAGE

HANDLING:

Prevention of user exposure: Ventilate extensively if the formation of vapours, fumes, mists or aerosol is a risk.

Make all the necessary arrangements in order to reduce exposure risk, notably to

products in use or to wastes.

Keep away from combustible substances; keep away from food and beverages.

Prevention of fire and explosion: Empty containers may contain flammable or explosive vapours.

There is a fire hazard associated with rags, paper or any other material used to

remove spills which become soaked with product.

Avoid accumulation of these: they are to be disposed off safely after use.

Precautions: Avoid static electricity build up with connection to earth.

Set up machinery and equipment so as to avoid the risk of accidental spills or splashes onto hot machine parts and electrical contacts (on joint failure, for

example).

. Oil leaks in a pressured circuit may result in a fine inflammable spray (the flammability limit for oil mist is depressed when concentrations of about 45g/m^3

are reached).

STORAGE:

Technical measures: Make the necessary arrangements to prevent water and soil pollution.

Storage precautions : - Suitable:

Store at room temperature, protected against contact with water and moisture, and

away from any source of ignition. Keep containers closed when not in use

- To be avoided:

Do not store exposed to the elements.

Incompatible products : Dangerous reaction with strong oxidizing agents.

Packaging materials : - Recommended:

Use only hydrocarbon-resistant containers, joints, pipes, etc.

Keep in original container if possible.

Otherwise, transfer all indications on the regulatory label to the new container.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Technical measures: Use the product in a properly ventilated atmosphere.

When working on enclosed place (tanks, reservoirs...), make sure that atmosphere is

not suffocating and/or wear recommended equipment.

. oil mist: 5mg/m3, for 8 hours

Definition of occupational exposure limits : OES = Occupational Exposure Standard.



Product name: AZOLLA ZS 32 Page : 4/6

SDS n° :31373-44 Version :1.01 Version of :2005-02-11

This sheet supersedes the one dated :2004-11-16

Hand protection : Impermeable hydrocarbon-proof gloves.

recommended material: nitrile, neoprene.

The break through times of the same type of glove of different manufacturers can be very different - even if the layer thickness is similar. Therefore the break through times have to be found out from the manufacturer of the protective gloves

themselves.

The demands on the gloves are determined by the conditions in practice (e.g. multiple use, mechanical load, temperature, strength and duration of exposition). Before choosing suitable gloves, it is recommended that the user tests the gloves.

Eye protection: Goggles, in case of risk of splashing.

Skin and body (other than the hands) protection: As required, wear a face mask, hydrocarbon-proof clothing, and safety boots (when

handling drums).

Don't wear rings, watches or anything similar which can retain the product and may

give rise to skin conditions.

Hygienic work practices: Avoid prolonged or repeated contact with the skin, particularly with used or waste

oil.

Immediately remove all soiled or stained clothing.

If the product comes into contact with the skin, wash the affected area immediately

and copiously with soap and water. Do not use abrasives, solvents or fuels.

Do not use cloths stained with the product to dry hands.

Do not put the product-soaked rags into the pockets of working clothes.

Do not eat, drink or smoke while handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Liquid.

Colour: Yellow.

Odour: Characteristic.

Density/specific gravity: 880 Kg/m3

Temperature (°C) 15

Flash point : $> 190 \,^{\circ}$ C (ASTM D 93)

Température d'auto-inflammation : > 250 ° C (ASTM E 659)

Comments on autoignition temperature: This temperature may be significantly lower under particular conditions (slow

oxidation on finely divided materials...).

Pour point: < -21 °C (ASTM D 97)

Partition coefficient (log Pow): Log Pow > 6

Temperature (°C) (20°C)

Viscosity: 32 mm2/s

Temperature (°C) 40

10. STABILITY AND REACTIVITY

Stability: The product is stable at normal storage, handling and use temperatures.

Conditions to avoid: Heat (temperatures above flash point), sparks, ignition points, flames, static

electricity

Materials to avoid: Avoid contact with strong oxidizers

Hazardous decomp. products: Incomplete combustion and thermolysis produces potentially toxic gases such as

CO, CO2, various hydrocarbons, aldehydes and soot.



Product name: AZOLLA ZS 32 Page: 5/6

SDS n° :31373-44 Version :1.01 Version of :2005-02-11

This sheet supersedes the one dated :2004-11-16

11. TOXICOLOGICAL INFORMATION

Acute toxicity / Local effect:

Inhalation, comments: - Inhalation :

Risk is improbable under normal conditions of use

Inhalation of high concentrations of vapour or aerosols may cause irritation of the

upper respiratory tract.

Skin contact, comments: - Contact with skin:

Risk is improbable under normal conditions of use.

If the skin is exposed to high-pressure spray, the product may enter the body. In all such cases the affected person must be taken to hospital, even if no sign of injury

can be detected

Ingestion, comments: - Ingestion :

In case of ingestion of small quantities, no important effect observed. in case of

ingestion of larger amounts: abdominal pain, diarrhea, ...

CHRONIC TOXICITY OR LONG-TERM TOXICITY:

Skin contact: Characteristic skin affections (oil blisters) may develop following prolonged and

repeated exposure through contact with stained clothing

Sensitization: To our knowledge, the product does not cause aggravated sensitivity.

12. ECOLOGICAL INFORMATION

Comments about ecotoxicity: The virgin product is considered to present no danger for land-growing organisms.

It is considered to present a little danger for aquatic life.

no information available for used product

Experimental data on the finished product are not available.

Mobility: - Air:

there is a slow loss by evaporation.

- Soil:

Given its physical and chemical characteristics, the product generally shows little

mobility in the ground.

- Water:

The product is insoluble; it spreads on the surface of the water

Persistence and degradability: No experimental information about the finished product.

However the "mineral oil" fraction of the new product is intrinsically biodegradable.

Some components of the product may not be biodegradable.

13. DISPOSAL CONSIDERATIONS

Waste disposal: Dispose of in a safe manner, in accordance with local regulations.

If need be, collection by an authorised waste contractor and regeneration or

incineration at an approved installation.

Waste class: 13 01 10

The waste classification is dependant on the composition of the product at the time

of disposal.

The waste classification mentioned here represents only a recommendation. The waste producer is responsible for the correct specification of the waste. The specification of the waste classification should be in arrangement with the

authorised waste disposal company.

Disposal of contaminated packaging : Proceed in compliance with the prevailing regulations.



Product name: AZOLLA ZS 32 Page: 6/6

SDS n° :31373-44 Version :1.01 Version of :2005-02-11

This sheet supersedes the one dated :2004-11-16

14. TRANSPORT INFORMATION

UN N°: not applicable

Road (ADR) / Rail (RID):

Class: Not restricted for transport.

Transport by barge (ADNR):

Marine (IMO-IMDG):

Air (ICAO/IATA):

15. REGULATORY INFORMATION

Risk phrases: R-52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Safety phrases: S-61 Avoid release to the environment. Refer to special instructions/Safety Data

Sheets.

EU directives: Hazardous preparations directive 1999/45/EC modified (Directive 2001/60/EC).

This product fulfills the requirements of the European directives:

76/769/EEC 2000/53/EC 2002/95/EC 2002/96/EC 2003/11/EC

16. OTHER INFORMATION

Explanations of R-phrases in section 2: R-38 Irritating to skin.

R-41 Risk of serious damage to eye.

R-51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

 $R\text{-}50/53 \ Very \ toxic \ to \ aquatic \ organisms, \ may \ cause \ long-term \ adverse \ effects \ in$

the aquatic environment.

*Revision date: 2005-02-11 *Supersedes the data sheet of: 2004-11-16

* Information revised since the previous version of the SDS:

SDS No.: LT-DS-1652

Safety Data Sheet status : Approved.

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.