

### Acetone

Version 2.3

Revision Date: 09/19/2016

# SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name

Acetone

**CAS Name** 

67-64-1

Recommended use of the chemical and restrictions on use

Recommended use

Intermediate

Solvent.

Manufacturer or supplier's details

Company Address Nexeo Solutions, LLC.

3 Waterway Square Place Suite 1000

The Woodlands, TX. 77380 United States of America

Emergency telephone number:

Health North America: 1-855-NEXEO4U (1-855-639-3648) Health International: 1-855-NEXEO4U (1-855-639-3648) Transport North America: CHEMTREC (1-800-424-9300)

Additional Information:

Responsible Party: Product Safety Group

E-Mail: msds@nexeosolutions.com SDS Requests: 1-855-429-2661 SDS Requests Fax: 1-281-500-2370 Website: www.nexeosolutions.com

#### **SECTION 2. HAZARDS IDENTIFICATION**

#### **GHS Classification**

Flammable liquids

: Category 2

Eye irritation

Category 2A

Specific target organ toxicity

- single exposure

: Category 3 (Central nervous system)

# GHS Label element

Hazard pictograms



Signal word

Danger

Hazard statements

: H225 Highly flammable liquid and vapour. H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

Prevention:

P210 Keep away from heat/sparks/open flames/hot surfaces.

No smoking.

P233 Keep container tightly closed.



# Acetone

Version 2.3

Revision Date: 09/19/2016

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/ attention

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

#### Other hazards

None known.

### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

: Substance

#### Hazardous components

CAS-No.	Chemical Name	Weight %	
67-64-1	Acetone	90 - 100	

Any Concentration shown as a range is due to batch variation.

#### **SECTION 4. FIRST AID MEASURES**

General advice

Move out of dangerous area.

Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may appear several hours later.

Do not leave the victim unattended.

If inhaled

: Consult a physician after significant exposure.

SDS Number: 100000001956 2 / 12 Acetone



# Acetone

Version 2.3

Revision Date: 09/19/2016

If unconscious place in recovery position and seek medical

advice.

In case of skin contact : If on sl

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact

Immediately flush eye(s) with plenty of water.

Remove contact lenses. Protect unharmed eye.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed

Keep respiratory tract clear. Do NOT induce vomiting.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media

Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical Water spray

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire-

fighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Flash back possible over considerable distance.

Do not allow vapor to accumulate in low or confined areas.

Hazardous combustion prod-

ucts

: Carbon oxides

Specific extinguishing meth-

ods

: Use a water spray to cool fully closed containers.

Further information

: Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

For safety reasons in case of fire, cans should be stored sepa-

rately in closed containments.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if nec-

essary.

Use personal protective equipment.



# Acetone

Version 2.3

Revision Date: 09/19/2016

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

tive equipment and emer-

gency procedures

Personal precautions, protec- : Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Environmental precautions

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

# **SECTION 7. HANDLING AND STORAGE**

Advice on protection against

fire and explosion

Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition. Vapours are heavier than air and may spread along floors. Do not pressurise, cut, weld,

braze, solder, drill, or grind on containers.

Advice on safe handling

Avoid formation of aerosol.

Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Container may be opened only under exhaust ventilation

Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage

No smoking.

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

Electrical installations / working materials must comply with

the technological safety standards.



# Acetone

Version 2.3

Revision Date: 09/19/2016

# SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

CAS-No.	Components	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
67-64-1	Acetone	TWA	250 ppm	ACGIH
0, 0, 1		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m3	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m3	OSHA Z-1
		TWA	750 ppm 1,800 mg/m3	OSHA P0
		STEL	1,000 ppm 2,400 mg/m3	OSHA P0

#### Personal protective equipment

Respiratory protection

No personal respiratory protective equipment normally re-

quired.

In the case of vapour formation use a respirator with an ap-

proved filter.

Hand protection

Remarks

The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection

Eye wash bottle with pure water

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection

Impervious clothing

Choose body protection according to the amount and concen-

tration of the dangerous substance at the work place.

Hygiene measures

When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

# SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

: liquid

Colour

Clear, Colorless

Odour

sweet, aromatic

Odour Threshold

62 ppm



# Acetone

Revision Date: 09/19/2016 Version 2.3

: 7 @ 10 g/l @ 20 - 25 °C (68 - 77 °F) pH

: -95.35 - -93.9 °C (-139.63 - -137.0 °F) Freezing Point (Melting

point/range)

: 56 - 56.05 °C (133 - 132.89 °F) Boiling Point (Boiling

point/boiling range)

Flash point : -18 - -17 °C (-0.40 - 1 °F) Method: closed cup

: 5.6 - 6.06 Evaporation rate

(Butyl Acetate = 1) : No data available Flammability (solid, gas)

: 14.30 %(V) Upper explosion limit

Lower explosion limit : 2.6 %(V)

: 180 - 185 mmHg @ 20 °C (68 °F) Vapour pressure

600 mmHg @ 50 °C (122 °F)

: 2 @ 20 °C (68 °F) Relative vapour density

(Air = 1.0)

: 0.786 - 0.789 @ 20 - 25 °C (68 - 77 °F) Relative density

Reference substance: (water = 1)

: 0.790 - 0.792 g/cm3 @ 20 °C (68 °F) Density

Solubility(ies)

: completely miscible Water solubility

: completely soluble Solubility in other solvents @ 20 °C (68 °F)

Solvent: organic solvents

Partition coefficient: n-

octanol/water

: log Pow: -0.24 - -0.2

: 465 - 560 °C Auto-ignition temperature

: No data available Thermal decomposition

Viscosity

: 0.32 - 0.33 mPa.s @ 20 °C (68 °F) Viscosity, dynamic

: 0.337 mm2/s @ 40 °C (104 °F) Viscosity, kinematic

Surface tension : 22.8 mN/m, 20 °C



### Acetone

Version 2.3

Revision Date: 09/19/2016

### SECTION 10. STABILITY AND REACTIVITY

Reactivity

: No dangerous reaction known under conditions of normal use.

Chemical stability

: Stable under normal conditions.

Possibility of hazardous reac-

: No hazards to be specially mentioned.

tions

Conditions to avoid

: Keep away from heat, flame, sparks and other ignition

sources.

Incompatible materials

: Strong oxidizing agents

#### SECTION 11. TOXICOLOGICAL INFORMATION

# Skin corrosion/irritation

#### Product:

Result: No skin irritation

### Serious eye damage/eye irritation

# Product:

Result: Irritating to eyes.

#### Components:

#### 67-64-1:

Species: Rabbit

Result: Irritating to eyes. Exposure time: 24 h

# Carcinogenicity

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

**OSHA** 

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcino-

gen by OSHA.

**NTP** 

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

**ACGIH** 

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcino-

gen by ACGIH.



### Acetone

Version 2.3

Revision Date: 09/19/2016

#### STOT - single exposure

### Components:

67-64-1:

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness. The substance or mixture is classified as

specific target organ toxicant, single exposure, category 3 with narcotic effects.

# Aspiration toxicity

#### Product:

May be harmful if swallowed and enters airways.

#### **Further information**

#### Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vom-

Concentrations substantially above the TLV value may cause narcotic effects.

Solvents may degrease the skin.

# SECTION 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

No data available

# Persistence and degradability

No data available

# Bioaccumulative potential

No data available

#### Mobility in soil

No data available

### Other adverse effects

#### Product:

Ozone-Depletion Potential

Regulation: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological infor-

mation

No data available



# Acetone

Version 2.3

Revision Date: 09/19/2016

### SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues

: Dispose of in accordance with all applicable local, state and

federal regulations.

For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact NEXEO's Environmental Services Group at 800-637-7922.

Contaminated packaging

Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

### **SECTION 14. TRANSPORT INFORMATION**

DOT (Department of Transportation):

UN1090, ACETONE, 3, II

IATA (International Air Transport Association):

UN1090, ACETONE, 3, II

IMDG (International Maritime Dangerous Goods):

UN1090, ACETONE, 3, II, Flash Point:-18 - -17 °C(-0.40 - 1 °F)

# **SECTION 15. REGULATORY INFORMATION**

WHMIS Classification

: B2: Flammable liquid

D2B: Toxic Material Causing Other Toxic Effects

# **EPCRA - Emergency Planning and Community Right-to-Know Act**

#### **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ	Calculated product RQ	
		(lbs)	(lbs)	
Acetone	67-64-1	5000	5000	
**Benzene	71-43-2	10	*	

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

# SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards

: Fire Hazard

Immediate (Acute) Health Hazard



		ıe	

Version 2.3

Revision Date: 09/19/2016

**SARA 302** 

: No chemicals in this material are subject to the reporting re-

guirements of SARA Title III, Section 302.

**SARA 313** 

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489):

67-64-1

Acetone

### Clean Water Act

The following Hazardous Substances are listed under the U.S. CleanWater Act, Section 311, Table 116.4A: 71-43-2 \*\*Benzene

The following Hazardous Chemicals are listed under the U.S. CleanWater Act, Section 311, Table 117.3: 71-43-2 \*\*Benzene

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

#### **US State Regulations**

### Massachusetts Right To Know

67-64-1 Acetone 71-43-2 \*\*Benzene 90 - 100 % 0 - 0.1 %

Pennsylvania Right To Know

67-64-1

Acetone

90 - 100 %

New Jersey Right To Know

67-64-1

Acetone

90 - 100 %

California Prop 65

WARNING! This product contains a chemical known to the

State of California to cause cancer.

71-43-2

\*\*Benzene

WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive

harm

71-43-2

\*\*Benzene

#### The components of this product are reported in the following inventories:

**TSCA** 

: On TSCA Inventory

DSL

: All components of this product are on the Canadian DSL

AICS

On the inventory, or in compliance with the inventory

NZIoC

On the inventory, or in compliance with the inventory

**ENCS** 

On the inventory, or in compliance with the inventory



# Acetone

Version 2.3

Revision Date: 09/19/2016

**KECI** 

: On the inventory, or in compliance with the inventory

PHIL

: On the inventory, or in compliance with the inventory

**IECSC** 

: On the inventory, or in compliance with the inventory


Special Notes:

: \*\* Other substances in the product which may present a

health or environmental hazard.

#### SECTION16. OTHER INFORMATION

#### NFPA:



Special hazard.

#### HMIS III:

HEALTH	2
FLANDIA DILITY	3
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High

4 =Extreme, \* = Chronic

The information accumulated is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made become available subsequently to the date hereof, we do not assume any responsibility for the results of its use. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by NEXEO™ Solutions EHS Product Safety Department (1-855-429-2661) MSDS@nexeosolutions.com.

**Revision Date** 

: 09/19/2016

Legacy SDS:

: R0004335

#### Material number:

16113324, 16111293, 16111229, 16109639, 16104184, 16045424, 16034875, 16066700, 16066699, 16066718, 16066717, 16101394, 16098884, 16075697, 16071303, 16070561, 16070557, 16069569, 16055833, 16055832, 16055831, 16055830, 16055829, 16062035, 16053090, 16050725, 16050368, 16049710, 16046507, 16045896, 16040423, 16038301, 16024443, 16024442, 16017790, 772814, 772813, 770579, 746703, 743460, 731755, 722683, 716725, 714790, 714016, 53967, 143817, 699233, 694280, 669662, 657544, 640730, 632517, 632516, 622972, 610607, 602401, 590044, 588482, 579567, 577332, 570345, 554132, 554043, 554368, 554299, 554204, 554084, 554042, 556643, 546857, 508583, 69081, 102957, 52701, 86730, 86576, 86729, 86575, 85459, 70349, 70195, 102439, 69676, 101837, 103107, 86726, 102776, 101843, 86578, 85462, 86731, 70348, 70194, 86057, 69078, 53968, 53814, 85456, 167020



Acetone

Version 2.3

Revision Date: 09/19/2016

ACGIH	American Conference of Gov-	LD50	Lethal Dose 50%	
	ernment Industrial Hygienists		The state of the s	
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level	
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency	
NDSL	Canada, Non-Domestic Sub- stances List	NIOSH	National Institute for Occupational Safety & Health	
CNS	Central Nervous System	NTP	National Toxicology Program	
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals	
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level	
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration	
EGEST	EOSCA Generic Exposure Sce- nario Tool	OSHA	Occupational Safety & Health Administration	
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit	
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances	
MAK	Germany Maximum Concentra- tion Values	PRNT	Presumed Not Toxic	
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act	
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit	
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.	
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value	
IECSC	Inventory of Existing Chemical Substances in China	TWA	Time Weighted Average	
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act	
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Copplex Reaction Products, and Biological Materials	
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Infor- mation System	
LC50		Lethal Con	centration 50%	