

MATERIAL SAFETY DATA SHEET

SECTION 1 — MANUFACTURER'S NAME & ADDRESS

Product identifier: Albatross Glide-EZ Silicone Lubricant

Product Number: 3003

Date Prepared: February 27, 2003 **Date Revised:** March 3, 2004

HMIS: H1 F3 R0 PX NFPA: H1 F3 R0 P-Level 3 Aerosol

Manufacturer's name and address: Refer to supplier

Supplier name and address:

ALBATROSS USA INC./EXPERT WORLDWIDE

36-41 36th Street 5439 San Fernando Road West Long Island City, New York Los Angeles, California United States United States

11106 United States United States 90039

718-392-6272 818-543-5850

Emergency Telephone #: Chemtrec (Day or Night) 800-424-9300

(For Chemical Emergency: Spill, Leak, Fire, Exposure or Accident)

This MSDS complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

IMPORTANT: Read this MSDS before handling and disposing of this product. Pass this information on to employees, customer, and users of this product.

SECTION 2 — HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components	OSHA	ACGIH	Other Limits Percentage
(CAS Numbers)	PEL-TWA	TLV-TWA	Recommended (Optional)
Isoparaffinic Hydrocarbon (64742-48-9)	NE ppm	NE ppm	400 ppm (Exxon)
Isobutane (75-28-5)	NE ppm	NE ppm	800 ppm (Aeropress)
Propane (74-98-6)	1000 ppm	NE ppm	1000 ppm (NIOSH) 15-30%

SECTION 3 — PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point (°F): (conc.) 205 Specific Gravity ($H_2O = 1$): 0.64

Vapor Pressure @ 70°F: 40 psig Melting Point (°F): NA

Vapor Density (Air = 1): > 1 Evaporation Rate (Butyl Acetate = 1): > 1

Solubility In Water: Negligible **VOC Content**: 640 gram per litre

Appearance & Odor: Clear colorless liquid with mild petroleum odor

SECTION 4 — FIRE & EXPLOSION HAZARD DATA

Flash Point (°F): 18, TCC Flammability Limit: LEL NA UEL NA

Extinguishing Media: Water, water fog, dry chemical, CO₂

Special Firefighting Procedures: Self-contained respiratory protection should be provided for fireman fighting in buildings or confined areas.

Unusual Fire & Explosion Hazards: Aerosols are under pressure. Exposure in excess of 120°F may cause bursting of can.

SECTION 5 — REACTIVITY DATA

Conditions to Avoid: NA Conditions to Avoid: High temperatures

Stability: Stable Hazardous Polymerization: Will not Occur

Incompatibility (Material to Avoid): Strong oxidizing agents and alkalies.

Hazardous Decomposition or By-products: Burns to form CO₂, CO and possible incompletely decomposed

materials

SECTION 6 — HEALTH HAZARD DATA

Route (s) of Entry: Inhalation? Yes Skin? Yes Ingestion? Yes

Health Hazards (Acute & Chronic): Eye irritant. May cause skin irritation. Prolonged inhalation may cause central nervous system depression.

Carcinogenity: NTP? No IARC Monographs? No OSHA Regulated? No

Signs & Symptoms of Exposure: Eye stinging, tearing, redness and swelling. May cause skin redness burning, drying and skin burns. Overexposure may cause dizziness, weakness, fatigue, nausea, headache and possible unconsciousness and even death.

Medical Conditions Generally Aggravated by Exposure: None known.

Emergency & First Aid Procedures: Flush eyes with water. Wash skin with soap and water. Remove patient to fresh air. Call a physician if necessary.

SECTION 7 — PRECAUTIONS FOR SAFE HANDLING & USE

Steps to be Taken in Case Material is Released or Spilled: Avoid inhalation of concentrated vapors. Absorb spilled material with appropriate absorbent.

Waste Disposal Method: Dispose of all waste in accordance with federal, state and local regulations.

Precautions to be Taken in Handling & Storage: Keep away from heat, sparks, open flame or direct sunshine.

Do not puncture or incinerate container.

Precautions: Intentional misuse by deliberately concentrating and inhaling vapour contents can be harmful of fatal.

SECTION 8 — CONTROL MEASURES

Respiratory Protection: Not necessary under normal use.

Ventilation: Local Exhaust: Yes Special: None

Mechanical (general): None Other: None

Protective Gloves: Rubber gloves.

Other Protective Clothing or Equipment: Plastic apron.

Work/Hygienic Practices: Wash thoroughly with soap and water after handle.

SECTION 9 — DOT SHIPPING INFORMATION

Proper Shipping Name: Consumer Commodity, Pressurized Aerosol Cans

Hazard Class: ORM-D

NOTICE:

This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information nor do we offer warranty against patent infringement.