

## **SAFETY DATA SHEETS**

**This SDS packet was issued with item:**

070830125

**The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).**

074390464 074390472 074390514 074390522 074390530

**The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).**

070830083 070830109 070830117 070830141 070830158 070830166 070830182 070830190 070830208 070830224  
070830232 070830240 070830265 070830273 070830281 070830307 070830315 070830323 074390381 074390399  
074390407 074390456

## 1. Substance / Preparation and Company name

Product Name: **Patterson** Admix Alloy Powder; Permite; Lojic +; GS-80, GS-80 Spherical; F400; Ultracaps +; Ultracaps S; SDI Admix; SDI Spherical and New **Ultrafine.** Capsules.

Product ID:

070830083	070830109	070830117	070830125	070830141	070830158
070830166	070830182	070830190	070830208	070830224	070830232
070830240	070830265	070830273	070830281	070830307	070830315
070830323	070900183	070900209	070900217	070900225	070900241
070900258	070900266	070900282	070900290	070900308	070900324
070900332	070900340	070900365	070900373	070900381	070900407
070900415	070900423	076209910	076209928	076209936	076209944
076209951	076209969	076316319	076316327	076316335	076316376
076316384	076316392	076316434	076316442	076316459	076316467
076316574	076316616	076316624	076316632	076316673	076316681
076316699	076316731	076316749	076316756	076316780	076316806
076316814	076316822	076316830	076316863	076316871	076316889
076316897	076316921	076316939	076316947	076316954	076316996
076317002	076317010	076317069	076317077	076317085	076317135
076317143	076317150	076317176	076318018	076318026	076318034
076318091	076318109	076318117	076318174	076318182	076318190
076318208	076318562	076318570	076318588	076318646	076318653
076318661	076318729	076318737	076318745	076318752	076318976
076318984	076319024	076319032	076319065	076319073	076319081
076319123	076319131	076319172	076319180	076319214	076319222
076319255	076319362	076319370	076319412	076319420	076319487
076319495	0272474377				

### Manufacturer / Supplier

Patterson Companies, Inc  
1031 Mendota Heights RoadSt.  
Paul, MN 55120

### Telephone:

703-527-3887

## 2. Composition / Information on ingredients

### Capsules

#### Hazardous ingredients:

	<u>Wt. %</u>	<u>CAS No.</u>	<u>EC No.</u>	<u>Index No.</u>
Mercury, metallic (40-50% of total product)	100	7439-97- 6	231-106-7	080-001-00

**MATERIAL SAFETY DATA SHEET**

Page 2 of 7

**Product:** Patterson Admix Alloy Powder; Permite; Lojic +; GS-80, GS-80 Spherical; F400; Ultracaps +; Ultracaps S; SDI Admix; SDI Spherical and New Ultrafine. Capsules.

**Date / Revised:** 5.02.2013

**Revision:** 11

---

**3. Hazard Identification:**

These products contain mercury. It is toxic if inhaled and acute exposure may cause allergic reactions including dermatitis, digestion and respiratory disorders.

**California Prop 65 Warning**

This product contains mercury, a chemical known to the State of California to cause birth defects or other reproductive harm.

**Classification according to Directive 790/2009/EC:**

	<b>T+</b>	Very toxic
	<b>N</b>	Dangerous for the environment
Risk phrases:	<b>61</b>	May cause harm to the unborn child
	<b>26</b>	Very toxic by inhalation
	<b>48/23</b>	Toxic: danger of serious damage to health by prolonged exposure through inhalation.
	<b>50/53</b>	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Safety phrases:	<b>45</b>	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
	<b>53</b>	Avoid exposure - obtain special instructions before use.
	<b>60</b>	This material and its container must be disposed of as hazardous waste.
	<b>61</b>	Avoid release to the environment. Refer to special instructions/Safety Data Sheet.
	<b>1/2</b>	Keep locked up and out of reach of children
	<b>7</b>	Keep container tightly closed.
	<b>9</b>	Keep container in a well ventilated place.
	<b>36/37/39</b>	Wear suitable protective clothing, gloves and eye/face protection.

---

**4. First Aid Measures**

General advice:	Contains metallic mercury. In case of accident or if you feel unwell, seek medical advice immediately (show label where possible).
If inhaled:	Very toxic by inhalation. Remove to fresh air. Seek medical attention. If not breathing give artificial respiration. May cause respiratory disorders including inflammation and fluid retention. Inhalation of mercury vapours at high concentration can cause dyspnea, coughing, fever, severe nausea, vomiting, excess salivation, kidney damage with renal shutdown.
If ingested:	Call a physician immediately. Give large amounts of water.
On skin contact:	Wash skin with soap and water. Remove contaminated clothing. May cause irritation and allergic reaction.
On contact with eyes:	Wash with clear, tepid water. If irritation persists, obtain medical attention. May cause irritation and allergic reaction.

---

## **MATERIAL SAFETY DATA SHEET**

Page 3 of 7

**Product:** Patterson Admix Alloy Powder; Permite; Lojic +; GS-80, GS-80 Spherical; F400; Ultracaps +; Ultracaps S; SDI Admix; SDI Spherical and New Ultrafine. Capsules.

**Date / Revised:** 5.02.2013

**Revision:** 11

---

### **5. Fire Fighting Measures**

- Suitable extinguishing media: As for adjacent fire. Avoid direct water stream. Do not allow water runoff to enter sewers and waterways. Remove product from the fire area if this can be done without risk.
- Special protective equipment: In fires involving large quantities of product, use self-contained breathing apparatus and full protective clothing.
- Further information: Hazardous decomposition products may be produced. (Sec. 10).

---

### **6. Accidental Release Measures**

- Spillages: Mercury presents a health hazard if incorrectly handled, and is dangerous for the environment. Spillages of mercury should be removed immediately, including from places which are difficult to access. Wearing protective clothing, use a plastic syringe to draw it up. Smaller quantities can be covered by sulphur powder and removed. Avoid inhalation of the vapour.
- Personal precautions: Wear appropriate MSHA approved respirator, gloves, safety goggles and protective clothing to prevent skin contact and inhalation.
- Environmental precautions: Prevent any spillage from entering drains or waterways.
- Methods for cleaning up: Avoid contact with skin and eyes, and avoid inhalation. Pick up with dust pan or method that does not break up mercury into smaller droplets, etc. Store in a sealed plastic container, away from heat and flame, until disposal via an approved Recycler and according to local regulations.

---

### **7. Handling and storage**

#### Handling

Do not breathe powder and avoid exposed mercury surfaces. Wear appropriate gloves, goggles/face protection and protective clothing to prevent skin contact. Wash thoroughly after handling. Keep away from food, drink and around animal feed stuffs.

#### Storage

Keep container tightly closed and dry. Storage in large quantities (as in warehouse) should be in a ventilated, cool area. Do not store in metal containers. Keep away from sources of ignition and elevated temperatures, recommended <25°C.

#### Distribution

During distribution, to our customers, this product can be transported in non-refrigerated conditions between 15° to 25° C. This product can also withstand temperatures up to 40° C for short periods (2 to 3 days) and intermittent peaks up to 50°C.

---

**MATERIAL SAFETY DATA SHEET**

Page 4 of 7

**Product:** Patterson Admix Alloy Powder; Permite; Lojic +; GS-80, GS-80 Spherical; F400; Ultracaps +; Ultracaps S; SDI Admix; SDI Spherical and New Ultrafine. Capsules.

**Date / Revised:** 5.02.2013

**Revision:** 11

---

**8. Exposure controls and personal protection**

8-Hour TWAs: Mercury - 0.025 mg/m<sup>3</sup> (Skin) (ACGIH); 0.05 mg/m<sup>3</sup> (Skin) (OSHA/UK & NOHSC/Australia); 0.1 mg/m<sup>3</sup> (Short term) (Germany);  
Silver - 0.01 mg/m<sup>3</sup> (OSHA/Germany); 0.1 mg/m<sup>3</sup> (ACGIH/U.K. & NOHSC/Australia)  
Tin - 2 mg/m<sup>3</sup> (OSHA/ACGIH/Germany & NOHSC/Australia); 5 mg/m<sup>3</sup> (U.K.);  
Copper - 1 mg/m<sup>3</sup> (OSHA/ACGIH/Germany/UK & NOHSC/Australia)  
Indium - 0.1 mg/m<sup>3</sup> (OSHA/UK & NOHSC/Australia)  
  
Zinc - 1 mg/m<sup>3</sup> (ACGIH)

These levels are not anticipated under foreseeable use conditions.

**Personal protective equipment**

Respiratory equipment: None required under normal use conditions.  
  
Hand protection: Impervious gloves.  
  
Eye protection: Safety goggles.  
  
General safety and hygiene measures: Use only as directed. Wash hands after use.

**9. Physical and chemical properties**

Form and Colour: Silver alloy powder and mercury in separate compartments of a plastic capsule.

Odour:	Odourless
Melting point / melting range:	(Mercury): -38.9°C
Boiling point / boiling range:	(Mercury): 356.6°C
Flash point:	Not applicable
Explosion limits:	Not applicable
Ignition temperature:	Not applicable
Vapour pressure:	(Mercury) 0.0012 mmHg at 20°C
Specific Gravity:	(Mercury) 13.6 g/cm <sup>3</sup>
% Volatiles:	Not applicable
Solubility in water:	Insoluble
Solubility in other solvents:	Insoluble in alcohol
pH value:	Not available
Octanol / water partition coefficient (log POW):	Not determined
Viscosity:	Not determined
Other information:	N/A

---

## **MATERIAL SAFETY DATA SHEET**

Page 5 of 7

**Product:** Patterson Admix Alloy Powder; Permite; Lojic +; GS-80, GS-80 Spherical; F400; Ultracaps +; Ultracaps S; SDI Admix; SDI Spherical and New Ultrafine. Capsules.

**Date / Revised:** 5.02.2013

**Revision:** 11

---

### **10. Stability and Reactivity**

Thermal decomposition: No decomposition under normal conditions

Substance(s) to avoid: Strong oxidizers

Hazardous reactions: Mixtures of mercury with acetylene, ammonia, chlorine dioxide, methyl azide, chlorates, nitrates, or hot sulfuric acid can be explosive. Readily amalgamates with most metals.

Hazardous decomposition products: Slightly volatile at room temperature, atmospheric pressure. When exposed to high temperatures, mercury vaporizes to extremely toxic fumes.

---

### **11. Toxicological information**

Critical hazards to man: Very toxic by inhalation. Toxic - danger of serious damage to health by prolonged exposure through inhalation. Acute exposure may cause allergic reactions including dermatitis, digestion and respiratory disorders. May cause harm to the unborn child..

Critical hazards to the environment: Dangerous for the environment.

None available regarding product. Some information supplied for ingredient(s).

LCLo / Inhalation / Rabbit: (Mercury) 29 mg/m<sup>3</sup>/30 Hour

Chronic Health Effects: Inhalation of mercury vapours, dusts or organic vapours, or skin absorption or mercury over long periods can cause mercurialism. Symptoms include tremors, inflammation of mouth and gums, excessive salivation, stomatitis, blue lines on gums, pain and numbness in extremities, weight loss, mental depression, and nervousness. Exposure may aggravate kidney disorders, chronic respiratory disease and nervous system disorders.

Alloy powder and mercury are in pre-dosed capsules, so the danger of exposure to mercury vapours is low.

---

### **12. Ecological information**

German "Wassergefährdungs Klasse (WGK):3

This product must not enter effluent, ground water, surface water or the soil.

**MATERIAL SAFETY DATA SHEET**

Page 6 of 7

**Product:** Patterson Admix Alloy Powder; Permite; Lojic +; GS-80, GS-80 Spherical; F400; Ultracaps +; Ultracaps S; SDI Admix; SDI Spherical and New Ultrafine. Capsules.

**Date / Revised:** 5.02.2013

Revision: 11

---

**13. Disposal considerations**

Product: Dispose of in accordance with local regulations.

***The 1991 Environmental Protection (Duty of Care) Regulations SI No. 2839 and amendments should be noted (United Kingdom).***

---

**14. Transport information**

IATA and IMDG:

Product: Amalgam Capsule

Contains: Mercury

Proper Shipping Name: Mercury contained in manufactured articles

UN Number: UN 3506

Packing Group: III

Class (sub risk): 8 (6.1) Corrosive & Toxic

IATA Limits: EQ - E0 (not permitted as excepted quantity)

LQ - Forbidden for passenger and cargo aircraft

CAO - no limit

PAX - no limit

IMDG Limits: LQ -5kg

EQ - E0 (not permitted as excepted quantity)

ADR/RID Class: UN 2809

Shipping name: Mercury

Class: 8

Packing Group: III

LQ - 5 kg

---

**15. Regulatory information**

These products are regulated by:

TGA

Medical Devices Directives 93/42/EEC

FDA

National regulations

---

***MATERIAL SAFETY DATA SHEET***

**Page 7 of 7**

**Product:** Patterson Admix Alloy Powder; Permite; Lojic +; GS-80, GS-80 Spherical; F400; Ultracaps +; Ultracaps S; SDI Admix; SDI Spherical and New Ultrafine. Capsules.

**Date / Revised:** 5.02.2013

**Revision:** 11

**16. Other information**

None



**Product:** Patterson Admix and Spherical Alloy Capsules.**Date / Revised:** 01.04.2015**Revision:** 1**1. Identification of the substance/mixture and of the Company/undertaking:**

1.1 Product identifier:

Product Name: Patterson Admix and Spherical Alloy Capsules.

1.2 Relevant identified use:

Relevant use:

Dental professional use: For filling of cavitated teeth by dental professionals.

1.3 Details of the supplier of the Safety Data Sheet:

**Manufacturer / Supplier**

Patterson Companies, Inc.  
1031 Mendota Heights Road  
St. Paul  
MN 55120, USA

**Telephone:**

800 328 5536

**Fax:**

651 686 9331

**Email:**[www.pattersoncompanies.com](http://www.pattersoncompanies.com)**Patterson's 24-Hour Emergency Response Number: 800 424 9300****2. Hazard Identification**

Classification of the substance/mixture:

**SIGNAL WORD: DANGER**

These products contain mercury. It is toxic if inhaled and acute exposure may cause allergic reactions including dermatitis, digestion and respiratory disorders.

**California Prop 65 Warning**

This product contains mercury, a chemical known to the State of California to cause birth defects or other reproductive harm.

**Product:** Patterson Admix and Spherical Alloy Capsules.

**Date / Revised:** 01.04.2015

**Revision:** 1

---

## 2. Hazard Identification continued....

### GHS Classification:

Acute Tox. 2  
Repr. 1B  
STOT RE 1  
Aquatic Acute 1  
Aquatic Chronic 1

Materials are contained in two compartments. However, under normal conditions of use, contact with these materials by the user is generally not expected.

### Hazard statement(s)

H330	Fatal if inhaled.
H360D	May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

### Precautionary statement(s):

#### Prevention:

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe fumes/vapours.
P264	Wash hands thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P284	Wear respiratory protection.
P280	Wear protective gloves/clothing.
P281	Use personal protective equipment as required.

#### Response:

P304+P340:	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P310	Immediately call a POISON CENTRE or doctor/physician.
P320	Specific treatment is urgent- refer to first aid instructions Section 4.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTRE or doctor/physician.
P321	Specific treatment, refer to First Aid instructions Section 4.
P330	Rinse mouth.
P363	Wash contaminated clothing before re-use.

#### Storage:

P405	Store locked up.
------	------------------

#### Disposal:

P501	Dispose of contents/ container to an approved waste disposal plant.
------	---

---

**Product:** Patterson Admix and Spherical Alloy Capsules.**Date / Revised:** 01.04.2015**Revision:** 1

---

### 3. Composition / Information on ingredients

#### Capsules

<u>Hazardous ingredients:</u>	<u>Wt.%</u>	<u>CAS No.</u>	<u>EC No.</u>	<u>Index No.</u>
Mercury, metallic (40-50% of total product)	100	7439-97-6	231-106-7	080-001-00

Hazard class: Acute Tox. 2, Repr 1B, STOT RE 1, Aquatic Acute 1, Aquatic Chronic 1.  
Hazard statement codes: H330, H360D, H372, H400, H410.

---

### 4. First Aid Measures

**General advice:** Contains metallic mercury. In case of accident or if you feel unwell, seek medical advice immediately (show label and instructions for use where possible).

**If inhaled:** Very toxic by inhalation. Remove to fresh air. Seek medical attention. If not breathing give artificial respiration.

May cause respiratory disorders including inflammation and fluid retention. Inhalation of mercury vapours at high concentration can cause dyspnea, coughing, fever, severe nausea, vomiting, excess salivation, kidney damage with renal shutdown.

**If ingested:** Call a physician immediately.  
Rinse mouth and give large amounts of water.

**On skin contact:** Wash skin with soap and water. Remove contaminated clothing. May cause irritation and allergic reaction. If irritation develops, if feeling unwell, or if concerned, get medical advice/attention.

**On contact with eyes:** Do not let victim rub eyes or keep them closed. Extensive irrigation with tepid water is required (at least 15 minutes). Obtain medical advice if irritation persists. May cause irritation and allergic reaction. If irritation develops, if feeling unwell, or if concerned, get medical advice/attention.

**Most important effects, acute and delayed:**

The most important known symptoms and effects are described in section 2 and/or in section 11.

**Indication of any immediate medical attention and special treatment needed:** No data available.

---

**Product:** Patterson Admix and Spherical Alloy Capsules.

**Date / Revised:** 01.04.2015

**Revision:** 1

---

## 5. Fire Fighting Measures

- Suitable extinguishing media: As for adjacent fire. Water spray, Foam, Carbon Dioxide, dry Chemical and other "ABC" Class may be used.
- Special protective equipment: In fires involving large quantities of product, use self-contained breathing apparatus and full protective equipment.
- Unusual Fire and Explosion Hazards: Mercury is not flammable and is relatively stable although it can react with many metals to form amalgams.
- Explosion Sensitivity to Mechanical Impact: Not sensitive.
- Explosion Sensitivity to Static Discharge: Not sensitive.
- Unsuitable extinguishing media: None specified.
- Specific hazards arising from the mixture:  
Mercury vapours generated during fires involving these products are toxic; additionally, this element can be irritating to contaminated tissue. Therefore, this product presents a severe health hazard to firefighters.
- Advice for firefighters:  
Wear self contained breathing apparatus and full protective equipment.  
Move fire exposed containers, if it can be done without risk to firefighters.  
Apply cooling water to sides of containers that are exposed to flame until well after fire is out.  
Decontaminate all equipment thoroughly after the conclusion of fire-fighting activities. If possible, prevent run-off water from entering storm drains, bodies of water, or other environmentally sensitive areas.
- Further information: Hazardous decomposition products may be produced. (Refer to Section 10).

---

## 6. Accidental Release Measures

- Spillages: Mercury presents a health hazard if incorrectly handled, and is dangerous for the environment. Spillages of mercury should be removed immediately, including from places which are difficult to access.  
Wearing protective clothing, use a plastic syringe to draw it up.  
Smaller quantities can be covered by sulphur powder and removed.  
Avoid inhalation of the vapour.
- Personal precautions: Wear appropriate MSHA approved respirator, gloves, safety goggles and protective clothing to prevent skin contact and inhalation.
- Environmental precautions: Prevent any spillage from entering drains or waterways.
- Methods for cleaning and containment of spills:  
Avoid contact with skin and eyes, and avoid inhalation. Pick up with dust pan or method that does not break up mercury into smaller droplets, etc. Store in a sealed plastic container, away from heat and flame, until disposal via an approved Recycler and according to local regulations. Ensure adequate ventilation.

**Product:** Patterson Admix and Spherical Alloy Capsules.

**Date / Revised:** 01.04.2015

**Revision:** 1

---

## 7. Handling and storage

<u>Handling:</u>	Do not breathe powder and avoid exposed mercury surfaces. Wear appropriate gloves, goggles/face protection and protective clothing to prevent skin contact. Wash thoroughly after handling. Keep away from food, drink and around animal feed stuffs.
<u>Storage:</u>	Store only in unopened original containers. Keep container tightly closed and dry. Storage in large quantities (as in warehouse) should be in a ventilated, cool area. Do not store in metal containers. Keep away from sources of ignition and elevated temperatures, recommended <25°C.
<u>Distribution:</u>	During distribution, to our customers, this product can be transported in non-refrigerated conditions between 15° to 25° C. This product can also withstand temperatures up to 40° C for short periods (2 to 3 days) and intermittent peaks up to 50°C.
Specific end use:	Apart from the use mentioned in section 1.2, there are no other uses for the product.

---

## 8. Exposure controls and personal protection

Control parameters:

Occupational exposure limits:

8-Hour TWAs: Mercury - 0.025 mg/m<sup>3</sup> (Skin) (ACGIH); 0.05 mg/m<sup>3</sup> (Skin) (OSHA/UK & NOHSC/Australia); 0.1 mg/m<sup>3</sup> (Short term) (Germany);

Silver - 0.01 mg/m<sup>3</sup> (OSHA/Germany); 0.1 mg/m<sup>3</sup> (ACGIH/U.K. & NOHSC/Australia)

Tin - 2 mg/m<sup>3</sup> (OSHA/ACGIH/Germany & NOHSC/Australia); 5 mg/m<sup>3</sup> (U.K.);

Copper - 1 mg/m<sup>3</sup> (OSHA/ACGIH/Germany/UK & NOHSC/Australia)

Indium - 0.1 mg/m<sup>3</sup> (OSHA/UK & NOHSC/Australia)

Zinc - 1 mg/m<sup>3</sup> (ACGIH)

These levels are not anticipated under foreseeable use conditions.

### Personal protective equipment

Respiratory equipment: None required under normal use conditions.

Hand protection: Impervious gloves.

Eye protection: Safety goggles.

General safety and hygiene measures: Use only as directed. Wash hands after use.

---

**Product:** Patterson Admix and Spherical Alloy Capsules.**Date / Revised:** 01.04.2015**Revision:** 1

---

**9. Physical and chemical properties**

Form and Colour:	Silver alloy powder and mercury in separate compartments of a plastic capsule. Silver alloy – grey fine metallic powder. Mercury – Silver-white heavy liquid metal.
Odour:	Odourless
Melting point / melting range:	(Mercury): -38.9°C
Boiling point / boiling range:	(Mercury): 356.6°C
Flash point:	Not applicable
Explosion limits:	Not applicable
Ignition temperature:	Not applicable
Vapour pressure:	(Mercury) 0.0012 mmHg at 20°C
Specific Gravity:	(Mercury) 13.6 g/cm <sup>3</sup>
% Volatiles:	Not applicable
Solubility in water:	Insoluble
Solubility in other solvents:	Insoluble in alcohol
pH value:	Not applicable.
Octanol / water partition coefficient (log POW):	Not determined
Viscosity:	Not determined
Relative vapour density (air = 1):	(Mercury): - 6.9
Auto-ignition temperature:	Not available
Decomposition temperature:	Not available

---

**10. Stability and Reactivity**

Reactivity:	No data available.
Chemical Stability:	Stable under recommended storage conditions.
Thermal decomposition:	No decomposition under normal conditions
Substance(s) to avoid:	Strong oxidizers
Hazardous reactions:	Mixtures of mercury with acetylene, ammonia, chlorine dioxide, methyl azide, chlorates, nitrates, or hot sulfuric acid can be explosive. Readily amalgamates with most metals.
Hazardous decomposition products:	Slightly volatile at room temperature, atmospheric pressure. When exposed to high temperatures, mercury vaporizes to extremely toxic fumes.

---

**Product:** Patterson Admix and Spherical Alloy Capsules.

**Date / Revised:** 01.04.2015

**Revision:** 1

---

## 11. Toxicological information

Critical hazards to man:	Very toxic by inhalation. Toxic - danger of serious damage to health by prolonged exposure through inhalation. Acute exposure may cause allergic reactions including dermatitis, digestion and respiratory disorders. May cause harm to the unborn child.
Critical hazards to the environment:	Dangerous for the environment.
Serious eye damage/irritation:	Irritating to eyes.
Skin corrosion/irritation:	May cause allergic skin reactions. May be irritant or corrosive.
Respiratory or skin sensitisation:	Very toxic by inhalation.
Ingestion:	Very hazardous by ingestion. May cause damage to blood, kidneys, liver, brain, peripheral nervous system, central nervous system.
Germ cell mutagenicity:	No data available.
Carcinogenicity:	Classified A5 (not suspected for human) by ACGIH. 3 (not classifiable for human) by IARC.
None available regarding product.	Some information supplied for ingredient(s).
LCLo / Inhalation / Rabbit:	(Mercury) 29 mg/m <sup>3</sup> /30 Hour
Chronic Health Effects:	Inhalation of mercury vapours, dusts or organic vapours, or skin absorption or mercury over long periods can cause mercurialism. Symptoms include tremors, inflammation of mouth and gums, excessive salivation, stomatitis, blue lines on gums, pain and numbness in extremities, weight loss, mental depression, and nervousness. Exposure may aggravate kidney disorders, chronic respiratory disease and nervous system disorders. May cause damage to blood, kidneys, liver, brain, peripheral nervous system, central nervous system.

Alloy powder and mercury are in pre-dosed capsules, so the danger of exposure to mercury vapours is low.

---

**Product:** Patterson Admix and Spherical Alloy Capsules.

**Date / Revised:** 01.04.2015

**Revision:** 1

---

## 12. Ecological information

German "Wassergefährdungs Klasse (WGK):3

This product must not enter effluent, ground water, surface water or the soil.

**Self-Assessment:** Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

**Ecotoxicity:** No data available.

**Persistence and biodegradability:** No data available.

**Bioaccumulative potential:** No data available.

**Mobility in soil:** No data available.

**Other adverse effects:** Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

---

## 13. Disposal considerations

**Product:** Dispose of in accordance with local and national regulations.

**Contaminated packaging:** Dispose of contaminated packaging as hazardous waste in accordance with local official regulations.

---

## 14. Transport information

**IATA:**

**Product:** Amalgam Capsule

**Contains:** Mercury

**Proper Shipping Name:** Mercury contained in manufactured articles

**UN Number:** UN 3506

**Packing Group:** III

**Class (sub risk):** 8 (6.1) Corrosive & Toxic

**IATA Limits:** EQ - E0 (not permitted as excepted quantity)

LQ - Forbidden for passenger and cargo aircraft

CAO - no limit

PAX - no limit

Not classified as Dangerous Goods for sea, road and rail transport.

---

## 15. Regulatory information



**Product:** Patterson Admix and Spherical Alloy Capsules.**Date / Revised:** 01.04.2015**Revision:** 1

---

These products are regulated by: FDA Medical Device Regulations

---

**16. Other information**

**Prepared by:** Patterson Companies, Inc.  
1031 Mendota Heights Road  
St. Paul  
MN 55120, USA

**Telephone:** 800 328 5536

The information contained in the Safety Data Sheet is based on data considered to be accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof.

**Date of preparation/revision:** 1<sup>st</sup> April 2015.

---