1. Identification

Product identifier American Safety Technologies MS-7CZ Gray Part A

Other means of identification

SKU# MS703R

Recommended use Not available.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Engineered Polymers
Address 130 Commerce Drive
Montgomeryville, PA 18936

United States

Telephone Customer Service 215-855-8450

Website www.itwengineeredpolymers.com

E-mail orders.na@itwep.com
Contact person EHS Department

Emergency phone number CHEMTREC 800-424-9300

International 703-527-3887

2. Hazard(s) identification

Physical hazards Flammable liquids Category 3 Health hazards Acute toxicity, oral Category 4 Acute toxicity, inhalation Category 4 Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2 Sensitization, skin Category 1 Reproductive toxicity Category 2 **Environmental hazards** Hazardous to the aquatic environment, acute Category 2

hazard

Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Flammable liquid and vapor. Harmful if swallowed. Causes skin irritation. May cause an allergic

skin reaction. Causes serious eye irritation. Harmful if inhaled. Suspected of damaging fertility or

Category 2

the unborn child.

Precautionary statement

Prevention

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not

be allowed out of the workplace. Avoid release to the environment. Wear protective

gloves/protective clothing/eye protection/face protection.

Response If swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth. If on skin (or hair): Take

off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash

before reuse. In case of fire: Use appropriate media to extinguish. Collect spillage.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information 85.43% of the mixture consists of component(s) of unknown acute dermal toxicity.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Nepheline Syenite		37244-96-5	30 - 60
Epoxy Resin:reaction Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin)		25068-38-6	10 - 30
Talc		14807-96-6	10 - 30
1,2,4-trimethylbenzene		95-63-6	1 - 5
1-methoxy-2-propanol		107-98-2	1 - 5
Aromatic Hydrocarbon Solvents		64742-95-6	1 - 5
Epoxy Resin		25036-25-3	1 - 5
Methyl Amyl Ketone (MAK)		110-43-0	1 - 5
Titanium Dioxide		13463-67-7	1 - 5
Zinc Phosphate		7779-90-0	1 - 5
Carbon Black		1333-86-4	0.1 - 1
Other components below reportable le	evels		3 - 7

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

present and easy to do. Continue mising. Get medical attention in initiation develops and persists.

vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis.

Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred

Get medical advice/attention if you feel unwell.

Most important symptoms/effects, acute and

delayed

Rash.

Indication of immediate medical attention and special

treatment needed

Ingestion

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information Take off all contaminated clothing immediately. IF exposed or concerned: Get medical

advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing

before reuse.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods
General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors and spray mists. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not taste or swallow. Avoid inhalation of vapors and spray mists. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value Form	
Aromatic Hydrocarbon Solvents (CAS 64742-95-6)	PEL	400 mg/m3	_
,		100 ppm	
Carbon Black (CAS 1333-86-4)	PEL	3.5 mg/m3	
Methyl Amyl Ketone (MAK) (CAS 110-43-0)	PEL	465 mg/m3	

Components	Туре	Value	Form
		100 ppm	
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust.
US. OSHA Table Z-3 (29 CFI	R 1910.1000)		
Components	Туре	Value	Form
Talc (CAS 14807-96-6)	TWA	0.3 mg/m3	Total dust.
,		0.1 mg/m3	Respirable.
		20 mppcf	·
		2.4 mppcf	Respirable.
Titanium Dioxide (CAS	TWA	5 mg/m3	Respirable fraction.
13463-67-7)		o mg/mo	ricophable fraction.
,		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit	Values		
Components	Туре	Value	Form
1,2,4-trimethylbenzene (CAS 95-63-6)	TWA	25 ppm	
(CAS 95-63-6) 1-methoxy-2-propanol (CAS	STEL	100 ppm	
107-98-2)	SILL	тоо ррпп	
	TWA	50 ppm	
Carbon Black (CAS	TWA	3 mg/m3	Inhalable fraction.
1333-86-4)			
Methyl Amyl Ketone (MAK) (CAS 110-43-0)	TWA	50 ppm	
Talc (CAS 14807-96-6)	TWA	2 mg/m3	Respirable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	Form
1,2,4-trimethylbenzene (CAS 95-63-6)	TWA	125 mg/m3	
(3.13 00 00 0)		25 ppm	
1-methoxy-2-propanol (CAS 107-98-2)	STEL	540 mg/m3	
		150 ppm	
	TWA	360 mg/m3	
		100 ppm	
Aromatic Hydrocarbon	TWA	400 mg/m3	
Solvents (CAS 64742-95-6)		•	
		100 ppm	
Carbon Black (CAS 1333-86-4)	TWA	0.1 mg/m3	
Methyl Amyl Ketone (MAK)	TWA	465 mg/m3	
((,AS 1()-43-())			
(CAS 110-43-0)		100 nnm	
(CAS 110-43-0) Talc (CAS 14807-96-6)	TWA	100 ppm 2 mg/m3	Respirable.

Exposure guidelines

US - California OELs: Skin designation

1-methoxy-2-propanol (CAS 107-98-2)

Can be absorbed through the skin.

Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Chemical respirator with organic vapor cartridge and full facepiece. Eye/face protection

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Chemical respirator with organic vapor cartridge and full facepiece. Respiratory protection Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Liquid. **Appearance Physical state** Liquid. **Form** Liquid. Color Grey. Odor Slight.

Odor threshold Not available. Hq Not available.

1650 °F (898.89 °C) estimated Melting point/freezing point Initial boiling point and boiling

248 °F (120 °C) estimated

range

Flash point 102.0 °F (38.9 °C) **Evaporation rate** Not available. Flammability (solid, gas) Not applicable. Upper/lower flammability or explosive limits

Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available. 8 mm Ha Vapor pressure Not available. Vapor density Relative density Not available.

Solubility(ies)

Solubility (water) Not available. Not available. Partition coefficient

(n-octanol/water)

Auto-ignition temperature 748.4 °F (398 °C) estimated

Decomposition temperature Not available. Not available. Viscosity

Other information

1.67 g/cm3 Density Not explosive. **Explosive properties** Flammable II Flammability class Oxidizing properties Not oxidizing.

Specific gravity 1.67

VOC 250 g/I Mixed components

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. Chemical stability

Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Avoid

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Harmful if inhaled.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eve contact Causes serious eye irritation.

Ingestion Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis, Rash.

Strong acids.

Information on toxicological effects

Acute toxicity Harmful if inhaled. Harmful if swallowed.

Components Species Test Results

1,2,4-trimethylbenzene (CAS 95-63-6)

Acute Dermal

LD50 Rabbit > 3160 mg/kg

Methyl Amyl Ketone (MAK) (CAS 110-43-0)

Acute Oral

LD50 Rat 1.67 g/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon Black (CAS 1333-86-4)

Talc (CAS 14807-96-6)

2B Possibly carcinogenic to humans.

2B Possibly carcinogenic to humans.

3 Not classifiable as to carcinogenicity to humans.

Titanium Dioxide (CAS 13463-67-7)

2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity Suspected of damaging fertility or the unborn child.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

Material name: American Safety Technologies MS-7CZ Gray Part A
MS703R Version #: 06 Revision date: 02-28-2017 Issue date: 04-20-2013

^{*} Estimates for product may be based on additional component data not shown.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Methyl Amyl Ketone (MAK) 1.98

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation

potential.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN number UN1263 UN proper shipping name Paint

Transport hazard class(es)

Class 3
Subsidiary risk Label(s) 3
Packing group III

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions B1, B52, IB3, T4, TP1, TP29

Packaging exceptions 150
Packaging non bulk 203
Packaging bulk 242

IATA

UN number UN1263 UN proper shipping name Paint

Transport hazard class(es)

Class 3
Subsidiary risk Packing group III
Environmental hazards No.
ERG Code 3L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

in ...

Other information Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN1263

UN proper shipping name F Transport hazard class(es)

Paint, MARINE POLLUTANT

Class 3 Subsidiary risk - **Packing group**

Environmental hazards

Marine pollutant Yes F-E, S-E **EmS**

Ш

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Not established.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

DOT



IATA; IMDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

1-methoxy-2-propanol (CAS 107-98-2) Listed. Zinc Phosphate (CAS 7779-90-0) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: De minimis concentration

1,2,4-trimethylbenzene (CAS 95-63-6) % 1.0 Zinc Phosphate (CAS 7779-90-0) % 1.0 N982

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

1,2,4-trimethylbenzene (CAS 95-63-6) Listed.
Zinc Phosphate (CAS 7779-90-0) Listed. N982

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
1,2,4-trimethylbenzene	95-63-6	1 - 5	
Zinc Phosphate	7779-90-0	1 - 5	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Methyl Amyl Ketone (MAK) (CAS 110-43-0) Other Flavoring Substances with OSHA PEL's

US state regulations WARNING: This product contains a chemical known to the State of California to cause cancer and

birth defects or other reproductive harm.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Carbon Black (CAS 1333-86-4)
Listed: February 21, 2003
Titanium Dioxide (CAS 13463-67-7)
Listed: September 2, 2011

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

1,2,4-trimethylbenzene (CAS 95-63-6) 1-methoxy-2-propanol (CAS 107-98-2)

Aromatic Hydrocarbon Solvents (CAS 64742-95-6)

Carbon Black (CAS 1333-86-4) Epoxy Resin (CAS 25036-25-3)

Talc (CAS 14807-96-6)

Titanium Dioxide (CAS 13463-67-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 04-20-2013 **Revision date** 02-28-2017

Version # 06

HMIS® ratings Health: 2*

Flammability: 2 Physical hazard: 0

NFPA ratings Health: 2

Flammability: 2 Instability: 0

Disclaimer ITW Engineered Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently

available.

Revision information This document has undergone significant changes and should be reviewed in its entirety.

Material name: American Safety Technologies MS-7CZ Gray Part A MS703R Version #: 06 Revision date: 02-28-2017 Issue date: 04-20-2013