Dentsply Aquasil

Dentsply Sirona Pty Ltd

Chemwatch: 4993-61

Version No: 6.1.1.1 Safety Data Sheet according to WHS and ADG requirements Chemwatch Hazard Alert Code: 2

Issue Date: 23/07/2019 Print Date: 25/09/2019 S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Dentsply Aquasil
Synonyms	Aquasil, Aquasil Ultra; Aquasil Ultra Xtra; Smart Wetting Impression Material; Vinyl Polysiloxane Impression Material; Aquasil Ultra Cordless Tissue Managing Wash Impression Material; Aquasil Ultra Cordless Tissue Managing Tray Impression Material; AQUASIL MONOPHASE,; AQUASIL RIGID,; AQUASIL LV.; AQUASIL Easy Mix PUTTY.; Smart Wetting Impression Material, AQUASIL ULTRA MONOPHASE,; AQUASIL ULTRA RIGID.; AQUASIL ULTRA XLV.; AQUASIL ULTRA LV.; AQUASIL ULTRA HEAVY? Smart Wetting Impression Material Super Fast Set.; Fast Setting and Regular Setting? Including AQUASIL ULTRA DECA Smart; Wetting Impression Material for Dynamic Mixing Machines and digit Targeted; Delivery Systems.; AQUASIL ULTRA Xtra? Wash, Tray and DECA Tray.
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant	identified	uses

Dental impression material

Use according to manufacturer's directions.

Details of the supplier of the safety data sheet

Registered company name	Dentsply Sirona Pty Ltd		
Address	11-21 Gilby Road Mount Waverley VIC 3149 Australia		
Telephone	1300 55 29 29		
Fax	1300 55 31 31		
Website	www.dentsplysirona.com.au		
Email	clientservices@dentsplysirona.com		

Emergency telephone number

Association / Organisation	Dentsply Sirona Pty Ltd
Emergency telephone numbers	1300 55 29 29
Other emergency telephone numbers	Not Available

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

CHEMWATCH HAZARD RATINGS

	Min	Max	
Flammability	0	i	
Toxicity	1		0 = Minimum
Body Contact	2	i	1 = Low 2 = Moderate
Reactivity	1		3 = High
Chronic	0		4 = Extreme

Poisons Schedule Not Applicable			
Classification [1] Skin Corrosion/Irritation Category 2			
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI		

Label elements

Hazard pictogram(s)



SIGNAL WORD WARNING

Hazard statement(s)

H315

Causes skin irritation.

Dentsply Aquasil

Issue Date: 23/07/2019 Print Date: 25/09/2019

Precautionary statement(s) Prevention

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement(s) Response

P321	Specific treatment (see advice on this label).		
P362	P362 Take off contaminated clothing and wash before reuse.		
P302+P352 IF ON SKIN: Wash with plenty of soap and water.			
P332+P313 If skin irritation occurs: Get medical advice/attention.			

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
14464-46-1	<30	<u>cristobalite</u>
68855-54-9	<30	diatomaceous earth, flux-calcined
68909-20-6	<10	silica amorphous, fumed, hydrophobic
13463-67-7	<10	titanium dioxide

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: • Wash out immediately with fresh running water. • Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. • Seek medical attention without delay; if pain persists or recurs seek medical attention. • Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: ► Immediately remove all contaminated clothing, including footwear. ► Flush skin and hair with running water (and soap if available). ► Seek medical attention in event of irritation.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor.
Ingestion	 If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- ▶ There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Advice for firefighters

Alert Fire Brigade and tell them location and nature of hazard.

- Wear breathing apparatus plus protective gloves in the event of a fire. Fire Fighting
 - ► Prevent, by any means available, spillage from entering drains or water courses.
 - ▶ Use fire fighting procedures suitable for surrounding area.

Version No: **6.1.1.1**

Dentsply Aquasil

Issue Date: 23/07/2019 Print Date: 25/09/2019

Fire/Explosion Hazard	 Non combustible. Not considered to be a significant fire risk. Expansion or decomposition on heating may lead to violent rupture of containers. Decomposes on heating and may produce toxic/irritating furnes. Decomposes on heating and produces toxic furnes of: carbon dioxide (CO2) silicon dioxide (SiO2) metal oxides other pyrolysis products typical of burning organic material.
HAZCHEM	Not Applicable

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Avoid contact with skin and eyes. Wear impervious gloves and safety goggles. Trowel up/scrape up.
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Pre	ecaut	ions	for	safe	handl	ing

Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps.
Other information	 Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers.

Conditions for safe storage, including any incompatibilities

 Polyethylene or polypropylene container. Packing as recommended by manufacturer. Check all containers are clearly labelled and free from leaks. 		▶ Packing as recommended by manufacturer.
	Storage incompatibility	► Avoid reaction with oxidising agents

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

I T						
Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	cristobalite	Cristobalite (respirable dust)	0.1 mg/m3	Not Available	Not Available	See Silica -Crystalline
Australia Exposure Standards	cristobalite	Silica - Crystalline: Cristobalite (respirable dust)	0.1 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	titanium dioxide	Titanium dioxide	10 mg/m3	Not Available	Not Available	(a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica.

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
cristobalite	Cristobalite	0.075 mg/m3	33 mg/m3	200 mg/m3
titanium dioxide	Titanium oxide; (Titanium dioxide)	30 mg/m3	330 mg/m3	2,000 mg/m3

Ingredient	Original IDLH	Revised IDLH
cristobalite	25 mg/m3	Not Available
diatomaceous earth, flux-calcined	Not Available	Not Available

Dentsply Aquasil

Issue Date: **23/07/2019**Print Date: **25/09/2019**

silica amorphous, fumed, hydrophobic	Not Available	Not Available
titanium dioxide	5,000 mg/m3	Not Available

Exposure controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "are "removes" air in the work environment.		
Personal protection		
Eye and face protection Eye and face protection Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describ of lenses or restrictions on use, should be created for each workplace or task.		
Skin protection	See Hand protection below	
Hands/feet protection ► Wear chemical protective gloves, e.g. PVC. ► Wear safety footwear or safety gumboots, e.g. Rubber		
Body protection	See Other protection below	
Other protection	▶ Overalls.▶ P.V.C. apron.▶ Barrier cream.	

Respiratory protection

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Various colored pastes, may be high	n viscosity paste or runny with peppermint odour; insoluble in water	r.
Physical state	Non Slump Paste	Relative density (Water = 1)	1.0-1.5
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	>200	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Applicable	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Applicable	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7

Issue Date: 23/07/2019 Print Date: 25/09/2019

Hazardous decomposition products

Serious Eye Damage/Irritation

Respiratory or Skin sensitisation

Mutagenicity

×

×

×

See section 5

products	AL INEOPMATION				
SECTION 11 TOXICOLOGIC					
nformation on toxicological	The material is not thought to produce respiratory irritation (as classified by EC Directives using animal models). Nevertheless inhalation of the material, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress. Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual. Effects on lungs are significantly enhanced in the presence of respirable particles.				
Ingestion	The material has NOT been classified by EC Directives or otl corroborating animal or human evidence.	her classification systems as "harmful	by ingestion". This is because of the lack of		
Skin Contact	This material can cause inflammation of the skin on contact in some persons. The material may accentuate any pre-existing dermatitis condition Irritation and skin reactions are possible with sensitive skin Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.				
Eye	There is some evidence to suggest that this material can caus	se eye irritation and damage in some p	persons.		
Chronic	Substance accumulation, in the human body, may occur and m There has been some concern that this material can cause ca				
	TOXICITY	IRRITATION			
Dentsply Aquasil	Oral (Rat) LD50: >2000 mg/kg* ^[2]	Not Available			
	(·,				
cristobalite	TOXICITY	IRRITATION			
	Not Available	Not Available			
diatomaceous earth,	TOXICITY	IRRITATION			
flux-calcined	Oral (rat) LD50: >2000 mg/kg ^[1]	Not Available			
	TOXICITY	IRRITATION			
silica amorphous, fumed, hydrophobic	Oral (rat) LD50: >5000 mg/kg ^[2]	Eye (rabbit): none			
.,,,		Skin (rabbit): none	[Degussa]		
	тохісіту	IRRITATION			
	dermal (hamster) LD50: >=10000 mg/kg ^[2]	Eye: no adverse eff	ect observed (not irritating) ^[1]		
titanium dioxide	Oral (rat) LD50: >2000 mg/kg ^[1]	Skin (human): 0.3 r	ng /3D (int)-mild *		
		Skin: no adverse ef	fect observed (not irritating) ^[1]		
Legend:	Value obtained from Europe ECHA Registered Substances	•	m manufacturer's SDS. Unless otherwise specified		
	data extracted from RTECS - Register of Toxic Effect of chen	nicai Substances			
	Inhalation (human) TCLo: 16 mppcf*/8H/17.9y-l * Millions of p WARNING: For inhalation exposure <u>ONLY</u> : This substance h	•	oup 1: CARCINOGENIC TO HUMANS		
CRISTOBALITE	The International Agency for Research on Cancer (IARC) has classified occupational exposures to respirable (<5 um) crystalline silica as being carcinogenic to humans. This classification is based on what IARC considered sufficient evidence from epidemiological studies of humans for the carcinogenicity of inhaled silica in the forms of quartz and cristobalite. Crystalline silica is also known to cause silicosis, a non-cancerous lung disease. Intermittent exposure produces; focal fibrosis, (pneumoconiosis), couch, dyspnoea, liver tumours.				
TITANIUM DIOXIDE	* IUCLID The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Exposure to titanium dioxide is via inhalation, swallowing or skin contact. When inhaled, it may deposit in lung tissue and lymph nodes causing dysfunction of the lungs and immune system. Absorption by the stomach and intestines depends on the size of the particle. It penetrated only the outermost layer of the skin, suggesting that healthy skin may be an effective barrier.				
DIATOMACEOUS EARTH, FLUX-CALCINED & SILICA AMORPHOUS, FUMED, HYDROPHOBIC	WARNING: This substance has been classified by the IARC For silica amorphous: When experimental animals inhale synthetic amorphous silica majority of SAS is excreted in the faeces and there is little acc without modification in animals and humans. SAS is not expec	a (SAS) dust, it dissolves in the lung flu umulation in the body. Following absor	id and is rapidly eliminated. If swallowed, the vast ption across the gut, SAS is eliminated via urine		
Acute Toxicity	×	Carcinogenicity	x		
Skin Irritation/Corrosion	~	Reproductivity	×		

STOT - Single Exposure

Aspiration Hazard

STOT - Repeated Exposure

X

×

×

Issue Date: 23/07/2019 Print Date: 25/09/2019

ьедена:



Data etitiei iiot avaliabie oi uoes iiot iii tie cittetia ioi ciassilicatioii Data available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
Dentsply Aquasil	Not Available	Not Available	Not Available	Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
cristobalite	Not Available	Not Available	Not Available	Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
diatomaceous earth, flux-calcined	Not Available	Not Available	Not Available	Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
silica amorphous, fumed, hydrophobic	Not Available	Not Available	Not Available	Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	>1-mg/L	2
titanium dioxide	EC50	48	Crustacea	>1-mg/L	2
	EC50	72	Algae or other aquatic plants	5.83mg/L	4
	NOEC	336	Fish	0.089mg/L	4

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
titanium dioxide	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
titanium dioxide	LOW (BCF = 10)

Mobility in soil

Ingredient	Mobility
titanium dioxide	LOW (KOC = 23.74)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal

- ▶ Recycle wherever possible or consult manufacturer for recycling options.
- ▶ Consult State Land Waste Authority for disposal.
- Bury or incinerate residue at an approved site.
- ▶ Recycle containers if possible, or dispose of in an authorised landfill.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Issue Date: 23/07/2019 Print Date: 25/09/2019

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

CRISTOBALITE IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards Australia Inventory of Chemical Substances (AICS)

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Work Health and Safety Regulations 2016 - Hazardous chemicals (other than lead)

requiring health monitoring

DIATOMACEOUS EARTH, FLUX-CALCINED IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

SILICA AMORPHOUS, FUMED, HYDROPHOBIC IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

TITANIUM DIOXIDE IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards	IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk
Australia Inventory of Chemical Substances (AICS)	International Agency for Research on Cancer (IARC) - Agents Classified by the IARC
GESAMP/EHS Composite List - GESAMP Hazard Profiles	Monographs
IMO IBC Code Chapter 17: Summary of minimum requirements	International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

National Inventory Status

National Inventory	Status		
Australia - AICS	Yes		
Canada - DSL	Yes		
Canada - NDSL	No (silica amorphous, fumed, hydrophobic; diatomaceous earth, flux-calcined; cristobalite)		
China - IECSC	Yes		
Europe - EINEC / ELINCS / NLP	Yes		
Japan - ENCS	No (silica amorphous, fumed, hydrophobic; diatomaceous earth, flux-calcined)		
Korea - KECI	Yes		
New Zealand - NZIoC	Yes		
Philippines - PICCS	Yes		
USA - TSCA	Yes		
Taiwan - TCSI	Yes		
Mexico - INSQ	No (silica amorphous, fumed, hydrophobic)		
Vietnam - NCI	Yes		
Russia - ARIPS	No (silica amorphous, fumed, hydrophobic)		
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)		

SECTION 16 OTHER INFORMATION

Revision Date	23/07/2019
Initial Date	28/07/2004

SDS Version Summary

Version	Issue Date	Sections Updated
5.1.1.1	20/11/2014	Supplier Information, Synonyms, Use
6.1.1.1	23/07/2019	Name

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit.

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

Chemwatch: 4993-61 Page 8 of 8 Issue Date: 23/07/2019 Version No: **6.1.1.1** Print Date: 25/09/2019

Dentsply Aquasil

LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.