		Page: 1
SAFETY DATA SHEET		Revision Date: 02/14/2019
		Print Date: 11/24/2020
		SDS Number: R0394062
Valvoline™ Mercon V Automatic Transmission Fluid ™ Trademark, Valvoline or its subsidiaries, registered in various countries 822345		Version: 1.7

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline™ Mercon V Automatic Transmission Fluid

™ Trademark, Valvoline or its subsidiaries, registered in various countries

Details of the supplier of the safety data sheet Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL (1-800-832-6825) SDS@valvoline.com	Emergency telephone number 1-800-VALVOLINE (1-800-825-8654) Regulatory Information Number 1-800-TEAMVAL (1-800-832-6825) Product Information 1-800-TEAMVAL (1-800-832-6825)
---	---

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Eye irritation : Category 2A

Skin sensitization : Category 1

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :  

Signal Word : Danger

Hazard Statements : May be fatal if swallowed and enters airways.
May cause an allergic skin reaction.
Causes serious eye irritation.

Precautionary Statements : **Prevention:**
Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.

SAFETY DATA SHEET

Revision Date: 02/14/2019

Print Date: 11/24/2020

SDS Number: R0394062

Version: 1.7

Valvoline™ Mercon V Automatic Transmission Fluid
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 822345

Wash skin thoroughly after handling.
 Contaminated work clothing must not be allowed out of the workplace.
 Wear protective gloves/ eye protection/ face protection.
Response:
 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
 IF ON SKIN: Wash with plenty of soap and water.
 IF IN EYES: Rinse cautiously with water for several minutes.
 Remove contact lenses, if present and easy to do. Continue rinsing.
 Do NOT induce vomiting.
 If skin irritation or rash occurs: Get medical advice/ attention.
 If eye irritation persists: Get medical advice/ attention.
 Wash contaminated clothing before reuse.
Storage:
 Store locked up.
Disposal:
 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	Not a hazardous substance or mixture.	>=30.00 - < 40.00
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	Asp. Tox. 1; H304	>=30.00 - < 40.00
POLYALKYLMETHACRYLATE		Eye Irrit. 2A; H319	>=10.00 - < 15.00
MINERAL OIL		Not a hazardous substance or mixture.	>=10.00 - < 15.00
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	Asp. Tox. 1; H304	>=1.50 - < 5.00
METHACRYLATE COPOLYMER		Eye Irrit. 2A; H319	>=1.00 - < 1.50
ALKYL METHACRYLATE		Skin Irrit. 2; H315	>=0.10 - < 0.50



SAFETY DATA SHEET

Revision Date: 02/14/2019

Print Date: 11/24/2020

SDS Number: R0394062

Version: 1.7

Valvoline™ Mercon V Automatic Transmission Fluid
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 822345

		Eye Irrit. 2A; H319	
		Skin Sens. 1; H317	
		STOT SE 3; H335	

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
 Show this safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.
- If inhaled : If breathed in, move person into fresh air.
 If unconscious, place in recovery position and seek medical
 advice.
 If symptoms persist, call a physician.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get
 medical attention.
 If on skin, rinse well with water.
 First aid is not normally required. However, it is
 recommended that exposed areas be cleaned by washing
 with soap and water.
 Wash contaminated clothing before re-use.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
 Remove contact lenses.
 Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.
 Never give anything by mouth to an unconscious person.
 If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : No symptoms known or expected.
 May be fatal if swallowed and enters airways.
 May cause an allergic skin reaction.
 Causes serious eye irritation.
- Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local
 circumstances and the surrounding environment.



SAFETY DATA SHEET

Revision Date: 02/14/2019

Print Date: 11/24/2020

SDS Number: R0394062

Version: 1.7

Valvoline™ Mercon V Automatic Transmission Fluid
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 822345

Water spray
 Foam
 Carbon dioxide (CO2)
 Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air and may travel along the ground and be ignited by heat, pilot lights, other flames and ignition sources at locations near the point of release.
 Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide
 Hydrocarbons
 nitrogen oxides (NOx)

Specific extinguishing methods :
 Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
 Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.
 Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
 Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

SAFETY DATA SHEET

Revision Date: 02/14/2019

Print Date: 11/24/2020

SDS Number: R0394062

Version: 1.7

Valvoline™ Mercon V Automatic Transmission Fluid
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 822345

Advice on safe handling : Do not breathe vapours/dust.
 Do not smoke.
 Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
 Container hazardous when empty.
 Avoid exposure - obtain special instructions before use.
 Avoid contact with skin and eyes.
 Smoking, eating and drinking should be prohibited in the application area.
 For personal protection see section 8.
 Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
		HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA
TWA	5 mg/m3 Inhalable fraction			ACGIH
TWA	5 mg/m3 Mist			OSHA P0
TWA	5 mg/m3 Mist			NIOSH REL
ST	10 mg/m3			NIOSH REL

SAFETY DATA SHEET

Revision Date: 02/14/2019

Print Date: 11/24/2020

SDS Number: R0394062

Version: 1.7

Valvoline™ Mercon V Automatic Transmission Fluid
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 822345

			Mist	
		PEL	5 mg/m3 particulate	CAL PEL
MINERAL OIL		TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection : Wear as appropriate:
 Impervious clothing
 Safety shoes
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.
 Discard gloves that show tears, pinholes, or signs of wear.
 Wear resistant gloves (consult your safety equipment supplier).

**SAFETY DATA SHEET**

Revision Date: 02/14/2019

Print Date: 11/24/2020

SDS Number: R0394062

Version: 1.7

Valvoline™ Mercon V Automatic Transmission Fluid
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
822345

Hygiene measures : Wash hands before breaks and at the end of workday.
When using do not eat or drink.
When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : red

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : 374 °F / 190 °C

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Self-ignition : No data available

Upper explosion limit / Upper flammability limit : No data available
No data available

Lower explosion limit / Lower flammability limit : No data available
No data available

Vapour pressure : 0.0133333 hPa (70.00 °F / 21.11 °C)
Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : No data available

Density : 0.858 g/cm³ (60.01 °F / 15.56 °C)

**SAFETY DATA SHEET**

Revision Date: 02/14/2019

Print Date: 11/24/2020

SDS Number: R0394062

Version: 1.7

Valvoline™ Mercon V Automatic Transmission Fluid
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
822345

Solubility(ies)
Water solubility : negligible
Solubility in other solvents : No data available
Partition coefficient: n-
octanol/water : No data available
Decomposition temperature : No data available
Viscosity
Viscosity, dynamic : No data available
Viscosity, kinematic : 7.4 mm²/s (212 °F / 100 °C)
Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.
Chemical stability : Stable under recommended storage conditions.
Possibility of hazardous
reactions : Product will not undergo hazardous polymerization.
Conditions to avoid : excessive heat
Incompatible materials : alkalis
Strong acids
Strong oxidizing agents
Hazardous decomposition
products : No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Acute oral toxicity : LD50 (Rat): > 15 g/kg

**SAFETY DATA SHEET**

Revision Date: 02/14/2019

Print Date: 11/24/2020

SDS Number: R0394062

Version: 1.7

Valvoline™ Mercon V Automatic Transmission Fluid
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
822345

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: Not classified as acutely toxic by inhalation
under GHS.
Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: No mortality observed at this dose.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation in susceptible persons.

Components:**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Assessment : Slight, transient irritation
Result : Slight, transient irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Species : Rabbit
Result : No skin irritation

POLYALKYLMETHACRYLATE:

Result : No skin irritation

MINERAL OIL:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

METHACRYLATE COPOLYMER:

Result : No skin irritation

ALKYL METHACRYLATE:

Assessment : Irritating to skin.
Result : Irritating to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

**SAFETY DATA SHEET**

Revision Date: 02/14/2019

Print Date: 11/24/2020

SDS Number: R0394062

Version: 1.7

Valvoline™ Mercon V Automatic Transmission Fluid
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
822345

Product:

Remarks : Vapours may cause irritation to the eyes, respiratory system
and the skin.
Causes serious eye irritation.

Components:**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Result : No eye irritation
Assessment : No eye irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Species : Rabbit
Result : No eye irritation

POLYALKYLMETHACRYLATE:

Result : Irritating to eyes.

MINERAL OIL:

Result : Slight, transient irritation
Assessment : Slight, transient irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result : Slight, transient irritation
Assessment : Slight, transient irritation

METHACRYLATE COPOLYMER:

Result : Irritating to eyes.

ALKYL METHACRYLATE:

Result : Irritating to eyes.
Assessment : Irritating to eyes.

Respiratory or skin sensitisation**Skin sensitisation**

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Product:

Remarks : May cause allergic skin reaction.

Components:**HYDROTREATED LIGHT PARAFFINIC DISTILLATE:**

Test Type : Buehler Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.

ALKYL METHACRYLATE:

Assessment : May cause sensitisation by skin contact.

**SAFETY DATA SHEET**

Revision Date: 02/14/2019

Print Date: 11/24/2020

SDS Number: R0394062

Version: 1.7

Valvoline™ Mercon V Automatic Transmission Fluid
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
822345

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Components:**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

MINERAL OIL:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation
Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

Components:**ALKYL METHACRYLATE:**

Assessment : May cause respiratory irritation.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Components:**DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

No aspiration toxicity classification

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

**SAFETY DATA SHEET**

Revision Date: 02/14/2019

Print Date: 11/24/2020

SDS Number: R0394062

Version: 1.7

Valvoline™ Mercon V Automatic Transmission Fluid
™ Trademark, Valvoline or its subsidiaries, registered in various
countries
822345

Further information**Product:**

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:**

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish : LL50 (Fish): > 100 mg/l
Exposure time: 96 hToxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l
Exposure time: 48 hToxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC (Fish): 10 mg/l

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Aquatic invertebrates): 10 mg/l

Ecotoxicology Assessment

Short-term (acute) aquatic hazard : Not classified based on available information.

Long-term (chronic) aquatic hazard : Not classified based on available information.

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 203
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l

SAFETY DATA SHEET

Revision Date: 02/14/2019

Print Date: 11/24/2020

SDS Number: R0394062

Version: 1.7

Valvoline™ Mercon V Automatic Transmission Fluid
 ™ Trademark, Valvoline or its subsidiaries, registered in various
 countries
 822345

- aquatic invertebrates Exposure time: 48 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 202
- Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
 End point: Growth inhibition
 Exposure time: 72 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 201
- Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >= 1,000 mg/l
 Exposure time: 14 d
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l
 Exposure time: 21 d
 Test substance: WAF
 Method: OECD Test Guideline 211
- ALKYL METHACRYLATE:
 Ecotoxicology Assessment
 Short-term (acute) aquatic hazard : Very toxic to aquatic life.
- Long-term (chronic) aquatic hazard : Very toxic to aquatic life with long lasting effects.

Persistence and degradability**Components:****HYDROTREATED LIGHT PARAFFINIC DISTILLATE:**

- Biodegradability : Result: Not readily biodegradable.
 Biodegradation: 2 - 4 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301B

No data available

Bioaccumulative potential**Components:****DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:**

- Partition coefficient: n-octanol/water : log Pow: Expected > 7

No data available

Mobility in soil**Components:**

No data available



SAFETY DATA SHEET

Revision Date: 02/14/2019

Print Date: 11/24/2020

SDS Number: R0394062

Version: 1.7

Valvoline™ Mercon V Automatic Transmission Fluid
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 822345

Other adverse effects

No data available

Product:

Additional ecological information : No data available

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Do not dispose of waste into sewer.
 Do not contaminate ponds, waterways or ditches with chemical or used container.
 Send to a licensed waste management company.
 Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
 Dispose of as unused product.
 Empty containers should be taken to an approved waste handling site for recycling or disposal.
 Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods



SAFETY DATA SHEET

Revision Date: 02/14/2019

Print Date: 11/24/2020

SDS Number: R0394062

Version: 1.7

Valvoline™ Mercon V Automatic Transmission Fluid
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 822345

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity


Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
XYLENE	1330-20-7	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Serious eye damage or eye irritation

		Page: 16
SAFETY DATA SHEET		Revision Date: 02/14/2019
		Print Date: 11/24/2020
		SDS Number: R0394062
Valvoline™ Mercon V Automatic Transmission Fluid ™ Trademark, Valvoline or its subsidiaries, registered in various countries 822345		Version: 1.7

Respiratory or skin sensitisation
Aspiration hazard

California Prop. 65

This product contains a chemical that is at or below California Propositions 65's "safe harbor level" for carcinogenicity as determined via a risk assessment. Therefore, the chemical is not required to be listed as a Prop 65 chemical on the SDS or label.

The components of this product are reported in the following inventories:

- DSL : All components of this product are on the Canadian DSL
- AICS : Not in compliance with the inventory
- ENCS : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : Not in compliance with the inventory
- TCSI : Not in compliance with the inventory
- TSCA : On TSCA Inventory

TSCA list

No substances are subject to TSCA 12(b) export notification requirements.

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 02/14/2019

NFPA:	HMIS III:
--------------	------------------

SAFETY DATA SHEET


Revision Date: 02/14/2019

Print Date: 11/24/2020

SDS Number: R0394062

Version: 1.7

Valvoline™ Mercon V Automatic Transmission Fluid
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 822345



NFPA Flammable and Combustible Liquids Classification
 Combustible Liquid Class IIIB

Full text of H-Statements

- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.


Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports
 The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

- ACGIH : American Conference of Industrial Hygienists
- BEI : Biological Exposure Index
- CAS : Chemical Abstracts Service (Division of the American Chemical Society).
- CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
- FG : Food grade
- GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
- H-statement : Hazard Statement

	Page: 18
SAFETY DATA SHEET	Revision Date: 02/14/2019
	Print Date: 11/24/2020
	SDS Number: R0394062
Valvoline™ Mercon V Automatic Transmission Fluid ™ Trademark, Valvoline or its subsidiaries, registered in various countries 822345	Version: 1.7

IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the “International Air Transport Association” (IATA).

ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the “International Civil Aviation Organization”
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
DOT : Department of Transportation
FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
HMIRC : Hazardous Materials Information Review Commission
HMIS : Hazardous Materials Identification System
NFPA : National Fire Protection Association
NIOSH : National Institute for Occupational Safety and Health
OSHA : Occupational Safety and Health Administration
PMRA : Health Canada Pest Management Regulatory Agency
RTK : Right to Know
WHMIS : Workplace Hazardous Materials Information System