## **HALLIBURTON**

## MATERIAL SAFETY DATA SHEET

Product Trade Name: BARACARB®-DF 50

Revision Date: 07-May-2014

## 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name: BARACARB®-DF 50

Synonyms: None Chemical Family: Mineral

Application: Bridging Agent

Manufacturer/Supplier Baroid Fluid Services

Product Service Line of Halliburton

P.O. Box 1675 Houston, TX 77251

Telephone: (281) 871-4000

Emergency Telephone: (281) 575-5000

Prepared By Chemical Compliance

Telephone: 1-580-251-4335

e-mail: fdunexchem@halliburton.com

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	CAS Number	PERCENT (w/w)	<b>ACGIH TLV-TWA</b>	OSHA PEL-TWA
Calcium carbonate	471-34-1	60 - 100%	10 mg/m <sup>3</sup>	15 mg/m <sup>3</sup>
Crystalline silica, quartz	14808-60-7	0.1 - 1%	TWA: 0.025 mg/m <sup>3</sup>	10 mg/m <sup>3</sup> _ %SiO2 + 2

More restrictive exposure limits may be enforced by some states, agencies, or other authorities.

## 3. HAZARDS IDENTIFICATION

Hazard Overview CAUTION! - ACUTE HEALTH HAZARD

May cause eye, skin, and respiratory irritation.

#### **DANGER! - CHRONIC HEALTH HAZARD**

Breathing crystalline silica can cause lung disease, including silicosis and lung cancer. Crystalline silica has also been associated with scleroderma and kidney disease.

This product contains quartz, cristobalite, and/or tridymite which may become airborne without a visible cloud. Avoid breathing dust. Avoid creating dusty conditions. Use only with adequate ventilation to keep exposures below recommended exposure limits. Wear a NIOSH certified, European Standard EN 149, AS/NZS 1715, or equivalent respirator when using this product. Review the Safety Data Sheet (SDS) for this product, which has been provided to your employer.

## 4. FIRST AID MEASURES

**Inhalation** If inhaled, remove from area to fresh air. Get medical attention if respiratory

irritation develops or if breathing becomes difficult.

**Skin** Wash with soap and water. Get medical attention if irritation persists.

Eyes In case of contact, immediately flush eyes with plenty of water for at least 15

minutes and get medical attention if irritation persists.

**Ingestion** Under normal conditions, first aid procedures are not required.

Notes to Physician Not Applicable

## 5. FIRE FIGHTING MEASURES

Flash Point/Range (F):

Flash Point/Range (C):

Flash Point Method:

Autoignition Temperature (F):

Autoignition Temperature (C):

Flammability Limits in Air - Lower (%):

Not Determined

Not Determined

Not Determined

Flammability Limits in Air - Lower (oz./ft3):

Flammability Limits in Air - Upper (%): Not Determined

Flammability Limits in Air - Upper (oz./ft3):

Fire Extinguishing Media All standard firefighting media.

Special Exposure Hazards Not applicable.

**Special Protective Equipment** 

for Fire-Fighters

Not applicable.

**NFPA Ratings:** Health 0, Flammability 0, Reactivity 0

Health 1\*, Flammability 0, Physical Hazard 0, PPE: E

## 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautionary** 

Measures

Use appropriate protective equipment. Avoid creating and breathing dust.

**Environmental Precautionary** 

**Measures** 

None known.

Procedure for Cleaning /

**Absorption** 

Collect using dustless method and hold for appropriate disposal. Consider possible toxic or fire hazards associated with contaminating substances and use appropriate methods for collection, storage and disposal.

## 7. HANDLING AND STORAGE

Handling Precautions This product contains quartz, cristobalite, and/or tridymite which may become

airborne without a visible cloud. Avoid breathing dust. Avoid creating dusty conditions. Use only with adequate ventilation to keep exposure below recommended exposure limits. Wear a NIOSH certified, European Standard En 149, or equivalent respirator when using this product. Material is slippery when wet. Avoid contact with eyes, skin, or clothing. Avoid creating or inhaling dust.

Storage Information Store away from acids. Store in a cool, dry location. Use good housekeeping in

storage and work areas to prevent accumulation of dust. Close container when not in use. Do not reuse empty container. Product has a shelf life of 60 months.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Engineering Controls**Use in a well ventilated area. Use approved industrial ventilation and local exhaust

as required to maintain exposures below applicable exposure limits.

Respiratory Protection Wear a NIOSH certified, European Standard EN 149 (FFP2/FFP3), AS/NZS 1715,

or equivalent respirator when using this product.

Hand Protection Normal work gloves.

**Skin Protection** Wear clothing appropriate for the work environment. Dusty clothing should be

laundered before reuse. Use precautionary measures to avoid creating dust when

removing or laundering clothing.

**Eye Protection** Wear safety glasses or goggles to protect against exposure.

Other Precautions None known.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Solid
Color: White to tan
Odor: Odorless
pH: 8-9
Specific Gravity @ 20 C (Water=1): 2.7

Density @ 20 C (lbs./gallon): Not Determined

Bulk Density @ 20 C (lbs/ft3): 168

**Boiling Point/Range (F):** Not Determined Boiling Point/Range (C): Not Determined Freezing Point/Range (F): Not Determined Freezing Point/Range (C): Not Determined Vapor Pressure @ 20 C (mmHg): Not Determined Vapor Density (Air=1): Not Determined **Percent Volatiles:** Not Determined Evaporation Rate (Butyl Acetate=1): Not Determined

Solubility in Water (g/100ml):

Solubility in Solvents (g/100ml):

VOCs (lbs./gallon):

Viscosity, Dynamic @ 20 C (centipoise):

Viscosity, Kinematic @ 20 C (centistokes):

Partition Coefficient/n-Octanol/Water:

Molecular Weight (g/mole):

Insoluble

Not Determined

Not Determined

Not Determined

10. STABILITY AND REACTIVITY

Stability Data: Stable

Hazardous Polymerization: Will Not Occur

Conditions to Avoid None anticipated

Incompatibility (Materials to

Avoid)

Strong acids.

**Hazardous Decomposition** 

**Products** 

Carbon monoxide and carbon dioxide. Amorphous silica may transform at

elevated temperatures to tridymite (870 C) or cristobalite (1470 C).

**Additional Guidelines** 

Not Applicable

## 11. TOXICOLOGICAL INFORMATION

**Principle Route of Exposure** 

Eye or skin contact, inhalation.

#### Sympotoms related to exposure

Acute Toxicity
Inhalation

Inhaled crystalline silica in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC, Group 1). There is sufficient evidence in experimental

animals for the carcinogenicity of tridymite (IARC, Group 2A).

Breathing silica dust may cause irritation of the nose, throat, and respiratory passages.

Breathing silica dust may not cause noticeable injury or illness even though permanent lung damage may be occurring. Inhalation of dust may also have serious chronic health effects

(See "Chronic Effects/Carcinogenicity" subsection below).

Eye Contact Skin Contact Ingestion May cause eye irritation May cause skin irritation.

None known

**Chronic Effects/Carcinogenicity** 

Silicosis: Excessive inhalation of respirable crystalline silica dust may cause a progressive, disabling, and sometimes-fatal lung disease called silicosis. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness, and reduced pulmonary function. This disease is exacerbated by smoking. Individuals with silicosis are predisposed to develop tuberculosis.

Cancer Status: The International Agency for Research on Cancer (IARC) has determined that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources can cause lung cancer in humans (Group 1 - carcinogenic to humans) and has determined that there is sufficient evidence in experimental animals for the carcinogenicity of tridymite (Group 2A - possible carcinogen to humans). Refer to IARC Monograph 68, Silica, Some Silicates and Organic Fibres (June 1997) in conjunction with the use of these minerals. The National Toxicology Program classifies respirable crystalline silica as "Known to be a human carcinogen". Refer to the 9th Report on Carcinogens (2000). The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica, quartz, as a suspected human carcinogen (A2).

There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of significant disease endpoints such as scleroderma (an immune system disorder manifested by scarring of the lungs, skin, and other internal organs) and kidney disease.

Toxicology data for the components

Substances	CAS Number	LD50 Oral	LD50 Dermal	LC50 Inhalation
Calcium carbonate	471-34-1	6450 mg/kg (Rat) > 2000 mg/kg (Rat)	> 2000 mg/kg (Rat)	> 3 mg/L (Rat) 4h
Crystalline silica, quartz	14808-60-7	> 5000 mg/kg (Rat)	No data available	No data available

## 12. ECOLOGICAL INFORMATION

#### **Ecotoxicological Information**

**Ecotoxicity Product** 

Acute Fish Toxicity: Not determined

Acute Crustaceans Toxicity: TLM96: >1,000,000 ppm (Mysidopsis bahia) SPP @ 178.5 ppb

Acute Algae Toxicity: Not determined

**Ecotoxicity Substance** 

Substances	CAS Number	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Toxicity to Invertebrates
Calcium carbonate	471-34-1	EC50(72h): > 14 mg/L (growth rate) (Desmodesmus subspicatus)	LC50(96h): > 100 mg/L (saturated solution) (Oncorhynchus mykiss)	EC50(3h): > 1000 mg/L (Activated sludge)	EC50(48h): > 100 mg/L (saturated solution) (Daphnia magna)
Crystalline silica, quartz	14808-60-7	No information available	LL0(96h): 10000 mg/L(Danio rerio) (similar substance)		LL50(24h): > 10000 mg/L (Daphnia magna) (similar substance)

12.2. Persistence and degradability

The methods for determining biodegradability are not applicable to inorganic substances.

Substances	CAS Number	Persistence and Degradability
Calcium carbonate	471-34-1	The methods for determining biodegradability are
		not applicable to inorganic substances.
Crystalline silica, quartz	14808-60-7	The methods for determining biodegradability are
		not applicable to inorganic substances.

## 12.3. Bioaccumulative potential

Does not bioaccumulate

Substances	CAS Number	Log Pow
Calcium carbonate	471-34-1	No information available
Crystalline silica, quartz	14808-60-7	No information available

#### 12.4. Mobility in soil

No information available

#### 12.5. Results of PBT and vPvB assessment

No information available.

Substances	PBT and vPvB assessment	
Crystalline silica, quartz	Not PBT/vPvB	

## 12.6. Other adverse effects

## 13. DISPOSAL CONSIDERATIONS

**Disposal Method** Bury in a licensed landfill according to federal, state, and local regulations.

**Contaminated Packaging** Follow all applicable national or local regulations.

## 14. TRANSPORT INFORMATION

**US DOT** 

UN Number: Not restricted.
UN Proper Shipping Name: Not restricted
Transport Hazard Class(es): Not applicable
Packing Group: Not applicable

**US DOT Bulk** 

DOT (Bulk) Not Applicable

Canadian TDG ul0

UN Number: Not restricted.
UN Proper Shipping Name: Not restricted

Transport Hazard Class(es): Not applicable Packing Group: Not applicable

IMDG/IMO

UN Number: Not restricted.
UN Proper Shipping Name: Not restricted
Transport Hazard Class(es): Not applicable
Packing Group: Not applicable

IATA/ICAO

UN Number: Not restricted.
UN Proper Shipping Name: Not restricted
Transport Hazard Class(es): Not applicable
Packing Group: Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable

Special Precautions for User: None

## 15. REGULATORY INFORMATION

**US Regulations** 

**US TSCA Inventory** All components listed on inventory or are exempt.

EPA SARA Title III Extremely

**Hazardous Substances** 

Not applicable

EPA SARA (311,312) Hazard

**Class** 

Acute Health Hazard Chronic Health Hazard

EPA SARA (313) Chemicals This product does not contain a toxic chemical for routine annual "Toxic Chemical

Release Reporting" under Section 313 (40 CFR 372).

EPA CERCLA/Superfund Reportable Spill Quantity Not applicable.

**EPA RCRA Hazardous Waste** 

Classification

If product becomes a waste, it does NOT meet the criteria of a hazardous waste

as defined by the US EPA.

**California Proposition 65** The California Proposition 65 regulations apply to this product.

MA Right-to-Know Law One or more components listed.

NJ Right-to-Know Law One or more components listed.

PA Right-to-Know Law One or more components listed.

Canadian Regulations

Canadian DSL Inventory All components listed on inventory or are exempt.

WHMIS Hazard Class D2A Very Toxic Materials

Crystalline silica

## 16. OTHER INFORMATION

# The following sections have been revised since the last issue of this SDS Not applicable

Additional information For additional information on the use of this product, contact your local Halliburton

representative.

For questions about the Safety Data Sheet for this or other Halliburton products,

contact Chemical Compliance at 1-580-251-4335.

**Disclaimer Statement** This information is furnished without warranty, expressed or implied, as to

accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the

sole responsibility of the user.

\*\*\*END OF MSDS\*\*\*