HALLIBURTON

SAFETY DATA SHEET

Product Trade Name: BARO-TROL® PLUS

Revision Date: 13-Jul-2015 Revision Number: 23

1. Identification

1.1. Product Identifier

Product Trade Name: BARO-TROL® PLUS

Synonyms: None
Chemical Family: Blend
Internal ID Code HM003562

1.2 Recommended use and restrictions on use Application:

Shale Inhibitor

Uses Advised Against No information available

1.3 Manufacturer's Name and Contact Details

Manufacturer/Supplier Baroid Fluid Services

Product Service Line of Halliburton

P.O. Box 1675 Houston, TX 77251

Telephone: (281) 871-4000

Emergency Telephone: (281) 575-5000

Prepared By Chemical Stewardship

Telephone: 1-580-251-4335

e-mail: fdunexchem@halliburton.com

1.4. Emergency telephone number

Emergency Telephone Number (281) 575-5000

2. Hazard(s) Identification

2.1 Classification in accordance with paragraph (d) of §1910.1200

Carcinogenicity	Category 1A - H350
Specific Target Organ Toxicity - (Repeated Exposure)	Category 1 - H372
Combustible dust	Combustible dust

2.2. Label Elements

Hazard Pictograms



Signal Word Danger

Hazard Statements H350 - May cause cancer

H372 - Causes damage to organs through prolonged or repeated exposure

May form combustible dust concentrations in air.

Precautionary Statements

Prevention P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood

P273 - Avoid release to the environment

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P260 - Do not breathe dust/fume/gas/mist/vapors/spray

P264 - Wash face, hands and any exposed skin thoroughly after handling

P270 - Do not eat, drink or smoke when using this product

Response P308 + P313 - IF exposed or concerned: Get medical advice/attention

P314 - Get medical attention/advice if you feel unwell

Storage P405 - Store locked up

Disposal P501 - Dispose of contents/container in accordance with

local/regional/national/international regulations

Contains

SubstancesCAS NumberCrystalline silica, quartz14808-60-7

2.3 Hazards not otherwise classified

None known

3. Composition/information on Ingredients

Substances	CAS Number	PERCENT (w/w)	GHS Classification - US
Crystalline silica, quartz	14808-60-7	1 - 5%	Carc. 1A (H350)
			STOT RE 1 (H372)

The exact percentage (concentration) of the composition has been withheld as proprietary.

4. First-Aid Measures

4.1. Description of first aid measures

Inhalation If inhaled, remove from area to fresh air. Get medical attention if respiratory

irritation develops or if breathing becomes difficult.

Eyes In case of contact, immediately flush eyes with plenty of water for at least 15

minutes and get medical attention if irritation persists.

Skin Wash with soap and water. Get medical attention if irritation persists.

Ingestion Do NOT induce vomiting. Give nothing by mouth. Obtain immediate medical

attention.

4.2 Most important symptoms/effects, acute and delayed

Breathing crystalline silica can cause lung disease, including silicosis and lung cancer. Crystalline silica has also been associated with scleroderma and kidney disease. Carcinogen. Prolonged or repeated exposure may cause damage to organs.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. Fire-fighting measures

5.1. Extinguishing media

Suitable Extinguishing Media

Water fog, carbon dioxide, foam, dry chemical.

Extinguishing media which must not be used for safety reasons

None known.

5.2 Specific hazards arising from the substance or mixture

Special Exposure Hazards

Decomposition in fire may produce harmful gases. Organic dust in the presence of an ignition source can be explosive in high concentrations. Good housekeeping practices are required to minimize this potential.

5.3 Special protective equipment and precautions for fire-fighters

Special Protective Equipment for Fire-Fighters

Full protective clothing and approved self-contained breathing apparatus required for fire fighting personnel.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use appropriate protective equipment. Avoid creating and breathing dust.

See Section 8 for additional information

6.2. Environmental precautions

Prevent from entering sewers, waterways, or low areas.

6.3. Methods and material for containment and cleaning up

Collect using dustless method and hold for appropriate disposal. Consider possible toxic or fire hazards associated with contaminating substances and use appropriate methods for collection, storage and disposal.

7. Handling and storage

7.1. Precautions for Safe Handling

Handling Precautions

Avoid contact with eyes, skin, or clothing. Avoid creating or inhaling dust.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Storage Information

Store away from oxidizers. Store in a cool, dry location. Product has a shelf life of 60 months.

8. Exposure Controls/Personal Protection

8.1 Occupational Exposure Limits

Substances	CAS Number	OSHA PEL-TWA	ACGIH TLV-TWA
Crystalline silica, quartz		TWA: 10 mg/m³ %SiO2 + 2	TWA: 0.025 mg/m ³

8.2 Appropriate engineering controls

Engineering ControlsUse approved industrial ventilation and local exhaust as required to maintain exposures below applicable exposure limits.

8.3 Individual protection measures, such as personal protective equipment

Personal Protective Equipment If engineering controls and work practices cannot prevent excessive exposures,

the selection and proper use of personal protective equipment should be

determined by an industrial hygienist or other qualified professional based on the

specific application of this product.

Respiratory Protection Wear a NIOSH certified, European Standard EN 149, AS/NZS 1715:2009,

AS/NZS 1715:2009, or equivalent respirator when product vapor or mist is

present.

Hand Protection Normal work gloves.

Skin Protection Wear clothing appropriate for the work environment. Dusty clothing should be

laundered before reuse. Use precautionary measures to avoid creating dust when

removing or laundering clothing.

Eve Protection Wear safety glasses or goggles to protect against exposure.

Other Precautions None known.

9. Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Physical State: Powder Color: Black to Brown

Odor: Asphalt Odor No information available

Threshold:

<u>Property</u> <u>Values</u>

Remarks/ - Method

pH: No data available Freezing Point/Range No data available Melting Point/Range No data available **Boiling Point/Range** No data available Flash Point No data available Flammability (solid, gas) No data available upper flammability limit No data available lower flammability limit No data available **Evaporation rate** No data available **Vapor Pressure** No data available **Vapor Density** No data available **Specific Gravity** 1.42

Water Solubility
Solubility Dispersible
No data available
Partition coefficient: n-octanol/water
Autoignition Temperature
Decomposition Temperature
Viscosity

1.42
Dispersible
No data available
No data available
No data available
No data available

Explosive PropertiesNo information available **Oxidizing Properties**No information available

9.2. Other information

VOC Content (%) No data available

10. Stability and Reactivity

10.1. Reactivity

Not expected to be reactive.

10.2. Chemical Stability

Stable

10.3. Possibility of Hazardous Reactions

Will Not Occur

10.4. Conditions to Avoid

None anticipated

10.5. Incompatible Materials

Strong oxidizers.

10.6. Hazardous Decomposition Products

Oxides of sulfur. Carbon monoxide and carbon dioxide. Toxic fumes. Amorphous silica may transform at elevated temperatures to tridymite (870 C) or cristobalite (1470 C).

11. Toxicological Information

11.1 Information on likely routes of exposure

Principle Route of Exposure Eye or skin contact, inhalation.

11.2 Symptoms related to the physical, chemical and toxicological characteristics

Acute Toxicity Inhalation

Inhaled crystalline silica in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC, Group 1). There is sufficient evidence in experimental animals for the carcinogenicity of tridymite (IARC, Group 2A).

Breathing silica dust may cause irritation of the nose, throat, and respiratory passages. Breathing silica dust may not cause noticeable iniury or illness even though permanent lung damage may be occurring. Inhalation of dust may also have serious chronic health effects (See "Chronic Effects/Carcinogenicity" subsection below).

Eye Contact Skin Contact Ingestion

May cause eye irritation. May cause skin irritation.

Irritation of the mouth, throat, and stomach. May cause abdominal pain, vomiting, nausea, and diarrhea.

Chronic Effects/Carcinogenicity Silicosis: Excessive inhalation of respirable crystalline silica dust may cause a progressive, disabling, and sometimes-fatal lung disease called silicosis. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness, and reduced pulmonary function. This disease is exacerbated by smoking. Individuals with silicosis are predisposed to develop tuberculosis.

> Cancer Status: The International Agency for Research on Cancer (IARC) has determined that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources can cause lung cancer in humans (Group 1 - carcinogenic to humans) and has determined that there is sufficient evidence in experimental animals for the carcinogenicity of tridymite (Group 2A - possible carcinogen to humans). Refer to IARC Monograph 68, Silica, Some Silicates and Organic Fibres (June 1997) in conjunction with the use of these minerals. The National Toxicology Program classifies respirable crystalline silica as "Known to be a human carcinogen". Refer to the 9th Report on Carcinogens (2000). The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica, quartz, as a suspected human carcinogen (A2).

> There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of significant disease endpoints such as scleroderma (an immune system disorder manifested by scarring of the lungs, skin, and other internal organs) and kidney disease.

11.3 Toxicity data

Toxicology data for the components

Toxicology data for t				
Substances	CAS Number	LD50 Oral	LD50 Dermal	LC50 Inhalation
Crystalline silica, quartz	14808-60-7	>15,000 mg/kg (Human)	No data available	No data available
Substances	CAS Number	Skin corrosion/irritation		
Crystalline silica, quartz	14808-60-7	Non-irritating to the skin		
	•	<u> </u>		
Substances	CAS Number	Eye damage/irritation		
Crystalline silica, quartz	14808-60-7	Mechanical irritation of the eyes is p	possible.	
Substances	CAS Number	Skin Sensitization		
Crystalline silica, quartz	14808-60-7	No information available.		
E .	1	T		
Substances	_	Respiratory Sensitization		
Crystalline silica, quartz	14808-60-7	No information available		
Substances	CAS Number	Mutagenic Effects		
Crystalline silica, quartz	14808-60-7	Not regarded as mutagenic.		
	T	T		
Substances				
Crystalline silica, quartz	14808-60-7	Contains crystalline silica which ma IARC and NTP have determined the crystalline silica with repeated respi substance is a threshold carcinoger lung injury.	ere is sufficient evidence in humar iratory exposure. Based on availab	ns of the carcinogenicity of ole scientific evidence, this
Substances	CAS Number	Poproductive toxicity		
Crystalline silica, quartz	14808-60-7	Reproductive toxicity No information available		
Orystalline Silica, quartz	114000 00 7	ive information available		
Substances	CAS Number	STOT - single exposure		
Crystalline silica, quartz	14808-60-7	No significant toxicity observed in a	nimal studies at concentration req	uiring classification.
Substances	CAS Number	STOT - repeated exposure		
	OAO Hallibel			
		Causes damage to organs through	prolonged or repeated exposure if	finhaled: (Lungs)
Crystalline silica, quartz	14808-60-7	Causes damage to organs through	prolonged or repeated exposure it	f inhaled: (Lungs)
	14808-60-7	Causes damage to organs through Aspiration hazard	prolonged or repeated exposure it	f inhaled: (Lungs)

12. Ecological Information

12.1. Toxicity **Ecotoxicity Effects**

<u>Product Ecotoxicity Data</u> No data available

Substance Ecotoxicity Data

Substance Ecotoxic	nty Data				
Substances	CAS Number	Toxicity to Algae	Toxicity to Fish	Toxicity to	Toxicity to Invertebrates
				Microorganisms	
Crystalline silica,	14808-60-7	No information available	LL0 (96h) 10,000 mg/L	No information available	LL50 (24h) > 10,000 mg/L
quartz			(Danio rerio) (similar		(Daphnia magna) (similar
			substance)		substance)

12.2. Persistence and degradability

Substances	CAS Number	Persistence and Degradability
Crystalline silica, quartz	14808-60-7	No information available

12.3. Bioaccumulative potential

Substances	CAS Number	Log Pow
Crystalline silica, quartz	14808-60-7	No information available

12.4. Mobility in soil

Substances	CAS Number	Mobility
Crystalline silica, quartz	14808-60-7	No information available

12.5 Other adverse effects

No information available

13. Disposal Considerations

13.1. Waste treatment methods

Disposal MethodBury in a licensed landfill according to federal, state, and local regulations.

Contaminated Packaging Follow all applicable national or local regulations.

14. Transport Information

US DOT

UN Number: Not restricted
UN Proper Shipping Name: Not restricted
Transport Hazard Class(es): Not applicable
Packing Group: Not applicable
Environmental Hazards: Not applicable

US DOT Bulk

DOT (Bulk) Not applicable

Canadian TDG

UN Number: Not restricted
UN Proper Shipping Name: Not restricted
Transport Hazard Class(es): Not applicable
Packing Group: Not applicable
Environmental Hazards: Not applicable

IMDG/IMO

UN Number:
UN Proper Shipping Name:
Transport Hazard Class(es):
Packing Group:
Not applicable
Not applicable
Not applicable
Not applicable

IATA/ICAO

UN Number:
UN Proper Shipping Name:
Transport Hazard Class(es):
Packing Group:
Environmental Hazards:
Not restricted
Not restricted
Not applicable
Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable

Special Precautions for User: None

15. Regulatory Information

US Regulations

US TSCA Inventory All components listed on inventory or are exempt.

EPA SARA Title III Extremely Hazardous Substances

Substances		EPA SARA Title III Extremely Hazardous Substances
Crystalline silica, quartz	14808-60-7	Not applicable

EPA SARA (311,312) Hazard Class

Acute Health Hazard Chronic Health Hazard

EPA SARA (313) Chemicals

Substances	CAS Number	Toxic Release Inventory (TRI) - Toxic Release Inventory	
		Group I	Group II
Crystalline silica, quartz	14808-60-7	Not applicable	Not applicable

EPA CERCLA/Superfund Reportable Spill Quantity

Substances	CAS Number	CERCLA RQ
Crystalline silica, quartz	14808-60-7	Not applicable

EPA RCRA Hazardous Waste Classification

If product becomes a waste, it does NOT meet the criteria of a hazardous waste as defined by the US EPA.

California Proposition 65 The California Proposition 65 regulations apply to this product.

MA Right-to-Know Law One or more components listed.

NJ Right-to-Know Law One or more components listed.

PA Right-to-Know Law One or more components listed.

Canadian Regulations

Canadian DSL Inventory All components listed on inventory or are exempt.

16. Other information

Preparation Information

Prepared By Chemical Stewardship

Telephone: 1-580-251-4335

e-mail: fdunexchem@halliburton.com

Revision Date: 13-Jul-2015

Reason for Revision Update to Format

SECTION:

2

Additional information

For additional information on the use of this product, contact your local Halliburton representative.

For questions about the Safety Data Sheet for this or other Halliburton products, contact Chemical Stewardship at 1-580-251-4335.

Key or legend to abbreviations and acronyms

bw - body weight

CAS - Chemical Abstracts Service

EC50 – Effective Concentration 50%

ErC50 – Effective Concentration growth rate 50%

LC50 – Lethal Concentration 50%

LD50 - Lethal Dose 50%

LL50 - Lethal Loading 50%

mg/kg - milligram/kilogram

mg/L - milligram/liter

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OEL - Occupational Exposure Limit

PEL – Permissible Exposure Limit

ppm – parts per million

STEL - Short Term Exposure Limit

TWA - Time-Weighted Average

UN - United Nations

h - hour

mg/m³ - milligram/cubic meter

mm - millimeter

mmHg - millimeter mercury

w/w - weight/weight

d - day

Key literature references and sources for data

www.ChemADVISOR.com/

Disclaimer Statement

This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

End of Safety Data Sheet