

MATERIAL SAFETY DATA SHEET

REVISION DATE: 04/19/2012 REVISION NUMBER: 2

DATE PRINTED: 04/19/2012 PREPARED BY: FH&S DEPARTMENT

1. CHEMICAL PRODUCT

PRODUCT NAME: BFW-410, Corrosion and Scale Inhibitor

PRODUCT CODE: 117625

NFPA/HMIS HAZARD CODES(minimal=0; slight=1; moderate=2; serious=3; severe=4)

Health:2/2Fire:0/0Reactivity:1/1Special/Protective Equipment:ALK/B

NAME OF THE Rochester Midland Corporation

MANUFACTURER: 155 Paragon Drive

Rochester, New York 14624

USA

Emergency Phone:

INFOTRAC: 1-800-535-5053 OUTSIDE US: 1-352-323-3500

2. HAZARDS IDENTIFICATION

EFFECTS FROM ACUTE EXPOSURE:

INGESTION: Severe burns to mucous membranes of mouth, throat and digestive tract. May cause allergic

reaction in sulfite sensitive individuals.

SKIN CONTACT: Causes moderate skin irritation. Prolonged contact causes severe burns which may not be

immediately painful or visible.

INHALATION: None in normal use. Inhalation of dust or mist may cause nose and respiratory irritation.

Possible tissue damage.

EYE CONTACT: Causes severe eye burns. May cause permanent eye damage. May cause blindness.

CHRONIC EFFECTS: Dermatitis.

EFFECTS/CARCINOGENICITY: None listed under OSHA, IARC, or NTP.

ROUTES OF ENTRY: Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation.

3. COMPOSITION/INFORMATION ON INGREDIENTS

PRODUCT COMPOSITION	%	ACGIH TLV	OSHA PELs
CAS#			
POTASSIUM HYDROXIDE 1310-58-3	8 max.	Not applicable	Not applicable
Sodium sulfite 7757-83-7	6 Max	Not applicable	Not applicable

4. FIRST AID MEASURES

INGESTION: DO NOT INDUCE VOMITING. Drink several glasses of water or milk. Never give anything by

mouth to an unconcious person. Get immediate medical attention.

SKIN: Flush with water for at least 15 minutes while removing all contaminated clothing and shoes.

Continue rinsing until "slippery" feeling is gone. Get medical attention if irritation or burns

develop.

INHALATION: Move person to fresh air. Aid breathing if necessary.

EYES: In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least

15 minutes and get medical attention immediately after flushing.

NOTES TO PHYSICIAN: None.

BFW-410, Corrosion and Scale Inhibitor

FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: (F): None (C): None

METHOD: None

FLAMMABLE LIMITS IN AIR

LOWER (%):

UPPER (%):

No data

No data

SENSITIVITY TO MECHANICAL IMPACT(Y/N): NO

SENSITIVITY TO STATIC DISCHARGE: Sensitivity to static discharge is not expected. SUITABLE EXTINGUISHING MEDIA: As for surrounding fire. Product will not burn.

FIRE FIGHTING PROCEDURES: None.

6. ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES:

SMALL SPILLS: Rinse down drain.

LARGE SPILLS: Dike to contain. Pick up with absorbant material. Put in suitable container for disposal. Flush

remainder with water.

PERSONAL PRECAUTIONS: Not applicable ENVIRONMENTAL PRECAUTIONS: Not applicable METHODS FOR CLEANING UP: Not applicable

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKENStore only in original container and keep closed. Avoid contact with skin and eyes.

IN HANDLING AND STORAGE:

OTHER PRECAUTIONS: Keep out of reach of children.

SPECIFIC USE(S): Not applicable.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

PROTECTIVE EQUIPMENT:



EXPOSURE CONTROLS: None known.

RESPIRATORY PROTECTION: Use an approved NIOSH full-face air supplied respirator if TLV/PEL's are exceeded or if over-

exposure is likely.

PROTECTIVE GLOVES: Nitrile, neoprene, or other appropriate gloves are recommended to minimize hand skin contact.

EYE PROTECTION: Goggles and face shield are recommended to minimize eye contact.

OTHER PERSONAL PROTECTION Appropriate protective clothing as needed to prevent skin contact. Eyewash fountains and safety showers must be easily accessible. It is the responsibility of the end user of this product

to determine level of PPE required that is consistent with safe use of this product.

(C) 100° C

VENTILATION: General mechanical and/or local exhaust as needed to meet exposure limits if mist in air.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Clear. Dark brown liquid. Mild odor.

BOILING POINT (F): 212° F

VAPOR PRESSURE: 15.7 mm Hg @ 22.2° C

VAPOR DENSITY (AIR=1): 0.625

SOLUBILITY IN WATER: Not determined

SPECIFIC GRAVITY: 1.200

VOC Content (%): Not determined EVAPORATION RATE: (BuAc = 1): 1.26

9. PHYSICAL AND CHEMICAL PROPERTIES

PH: 12.8 - 13.8

10. STABILITY AND REACTIVITY

STABILITY DATA: STABLE POLYMERIZATION: Will Not Occur.

HAZARDOUS DECOMPOSITION: If evaporated to dryness, as in a fire, may release: Soot. Carbon Monoxide. Carbon Dioxide.

Oxides of Sulfur.

INCOMPATIBILITY (MATERIALS TO

AVOID):

Do not mix with acidic materials. Neutralizes active ingredients. May release sulfur dioxide. Avoid contact with aluminum, zinc, other soft metals or galvanized metals. Reaction will

generate hydrogen gas. This gas is flammable and/or explosive in presence of ignition source.

CONDITIONS/HAZARDS TO AVOID: None.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY: Not Established EFFECTS OF CHRONIC EXPOSURE: Not established. OTHER TOXIC EFFECTS: Not established.

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL No data at this time

INFORMATION:

CHEMICAL FATE INFORMATION:

MOBILITY:

PERSISTENCE/DEGRADABILITY:

BIOACCUMULATIVE POTENTIAL:

OTHER ADVERSE EFFECTS:

No data at this time.

Not applicable.

Not applicable

Not applicable

13. DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS: Dispose in accordance with Federal, State and Local regulations.

14. TRANSPORT INFORMATION

Please refer to the Bill of Lading/Receiving documents for up to date shipping information.

15. REGULATORY INFORMATION

PRODUCT COMPOSITION CAS#	%	TSCA:	EINECS:	Canada DSL:	CA PROP 65:
POTASSIUM HYDROXIDE 1310-58-3	8 max.	Listed	Listed	Listed	Not Listed
Sodium sulfite 7757-83-7	6 Max	Listed	Listed	Listed	Not Listed

PRODUCT COMPOSITION CAS#	%	CERCLA:	SARA 302:	SARA 313:
POTASSIUM HYDROXIDE 1310-58-3	8 max.	1000 lb 454 kg	Not Listed	Not Listed
Sodium sulfite 7757-83-7	6 Max	Not Listed	Not Listed	Not Listed

BFW-410, Corrosion and Scale Inhibitor

PRODUCT COMPOSITION CAS#	%	Canada WHMIS:
POTASSIUM HYDROXIDE 1310-58-3	8 max.	Listed
Sodium sulfite 7757-83-7	6 Max	Listed

The following components of this material are included in the Massachusetts Substance List and are present at or above reportable levels.

PRODUCT COMPOSITION	%	MARTK:		
CAS#				
POTASSIUM HYDROXIDE	8 max.	Listed		
1310-58-3				

The following components of this material are included in the New Jersey Substance List and are present at or above reportable levels.

PRODUCT COMPOSITION CAS#	%	NJRTK:
POTASSIUM HYDROXIDE 1310-58-3	8 max.	Listed

The following components of this material are included in the Pennsylvania Substance List and are present at or above reportable levels.

10 7 0101				
PRODUCT COMPOSITION	%	PARTK:		
CAS#				
POTASSIUM HYDROXIDE	8 max.	Listed		
1310-58-3				

16. OTHER INFORMATION

This information was compiled from current, reliable sources and is believed to be correct. As data, and/or regulations change, and conditions of use and handling are beyond our control, no warranty, express or implied, is made as to completeness or continuing accuracy of this information.

*** END OF MSDS ***