

# SAFETY DATA SHEET

Issue Date 09-Jun-2015 Revision Date 09-Jun-2015 Version 1

#### 1. IDENTIFICATION

Product identifier

Product Name 790-11 HOT RUBBERIZED ASPHALT

Other means of identification

Product Code BH79011C Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Waterproofing Membrane Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

HENRY COMPANY

999 N. Sepulveda Blvd., Suite 800 El Segundo, CA 90245-2716 Company Contact: Technical Services Telephone Number: 800-486-1278

Web Site: www.henry.com www.ca.henry.com

Emergency telephone number

Emergency Telephone CHEMTREC: 800-424-9300

CHEMTREC: 703-527-3887 CANUTEC: 613-966-6666

## 2. HAZARDS IDENTIFICATION

## Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3

#### Label elements

## **Emergency Overview**

#### Warning

#### Hazard statements

Causes skin irritation Causes serious eye irritation May cause respiratory irritation



Appearance Black Physical state Solid Odor Sulfurous

#### **Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves/protective clothing/eye protection/face protection Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area

#### **Precautionary Statements - Response**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor/physician if you feel unwell

#### **Precautionary Statements - Storage**

Store in a well-ventilated place. Keep container tightly closed Store locked up

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

## Hazards not otherwise classified (HNOC)

Contact with product at elevated temperatures can result in thermal burns

#### Other Information

Respirable silica (quartz) is classified as carcinogenic by: IARC (Group 1 - human carcinogen); NTP (known carcinogen); and ACGIH (Group 2A - suspected human carcinogen). This product is in a form that makes exposure to respirable silica unlikely when it is applied as directed. IARC has classified occupational exposure to straight-run bitumen and their emissions during road paving as a carcinogen (category 2B - possibly carcinogenic to humans). Contact with hot product may cause thermal burns – consult SDS for additional first aid measures. Fumes from hot material can be unpleasant and may produce nausea, headaches and irritation of the upper respiratory tract. Substance may give off hydrogen sulfide (H2S) when heated which may collect in enclosed spaces. Exposure to H2S may result in respiratory tract irritation, headache, dizziness, nausea, gastrointestinal disturbances, coughing, a sensation of dryness and pain in the nose, throat, and chest, confusion and unconsciousness.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

## <u>Substance</u>

Chemical Name	CAS No.	Weight-%	Trade Secret
Asphalt, Petroleum (Residues)	64741-56-6	30 - 60	*
Calcium Carbonate	1317-65-3	30 - 60	*
Sulfur	7704-34-9	1 - 5	*
Silica, quartz	14808-60-7	0.1 - 1	*

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

## 4. FIRST AID MEASURES

#### Description of first aid measures

Eve contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

Consult a physician.

Skin contact Removal of solidified molten material from skin requires medical assistance. In case of burns,

immediately cool affected skin for as long as possible with cold water. For severe burns,

immediate medical attention is required.

Inhalation Remove to fresh air.

Ingestion Clean mouth with water and drink afterwards plenty of water.

#### Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

#### Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

#### 5. FIRE-FIGHTING MEASURES

#### Suitable extinguishing media

CO2, dry chemical, dry sand, alcohol-resistant foam.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

## Specific hazards arising from the chemical

No information available.

## Explosion data

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

## Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

## Personal precautions, protective equipment and emergency procedures

**Personal precautions** Wear protective gloves/protective clothing and eye/face protection. Ensure adequate

ventilation, especially in confined areas.

Environmental precautions

**Environmental precautions** Do not allow into any sewer, on the ground or into any body of water.

#### Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

## 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice.

## Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep containers tightly closed in a dry, cool and well-ventilated place.

Incompatible materials Strong oxidizing agents. Strong acids.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

**Exposure Guidelines** 

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Calcium Carbonate	-	TWA: 15 mg/m³ total dust	TWA: 10 mg/m³ total dust
1317-65-3		TWA: 5 mg/m³ respirable fraction	TWA: 5 mg/m <sup>3</sup> respirable dust
		(vacated) TWA: 15 mg/m <sup>3</sup> total dust	
		(vacated) TWA: 5 mg/m <sup>3</sup> respirable	
		fraction	
Silica, quartz	TWA: 0.025 mg/m <sup>3</sup> respirable	(vacated) TWA: 0.1 mg/m <sup>3</sup>	IDLH: 50 mg/m <sup>3</sup> respirable dust
14808-60-7	fraction	respirable dust	TWA: 0.05 mg/m <sup>3</sup> respirable dust
		: (30)/(%SiO2 + 2) mg/m <sup>3</sup> TWA	
		total dust	
		: (250)/(%SiO2 + 5) mppcf TWA	
		respirable fraction	
		: (10)/(%SiO2 + 2) mg/m <sup>3</sup> TWA	
		respirable fraction	

#### Appropriate engineering controls

**Engineering Controls** Showers

> Eyewash stations Ventilation systems.

## Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin and body protection Wear protective gloves and protective clothing.

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved Respiratory protection

> respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

**General Hygiene Considerations** Handle in accordance with good industrial hygiene and safety practice.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

Physical state Solid

Appearance Odor No information available Sulfurous

black Odor threshold No information available Color

Remarks • Method **Property** <u>Values</u>

pН No information available Melting point / freezing point No information available

BH79011C - 790-11 HOT RUBBERIZED ASPHALT

Cleveland Open Cup

Revision Date 09-Jun-2015

**Boiling point / boiling range**No information available

Flash point

No information available

> 291 °C / > 556 °F

Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density

No information available
No information available
No information available
No information available

Relative density 1.23 +/- 0.03 Water solubility Insoluble in water Solubility in other solvents No information available **Partition coefficient** No information available >290 °C / >550 °F **Autoignition temperature Decomposition temperature** No information available Kinematic viscosity No information available **Dynamic viscosity** No information available Not an explosive

Explosive properties

Oxidizing properties

Not an explosive Not applicable

**Other Information** 

Softening point
Molecular weight
VOC Content (%)
Density
Bulk density
No information available
No information available
No information available
No information available

## 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

## **Chemical stability**

Stable under recommended storage conditions.

## Possibility of Hazardous Reactions

None under normal processing.

**Hazardous polymerization** Hazardous polymerization does not occur.

#### **Conditions to avoid**

Extremes of temperature and direct sunlight.

Incompatible materials

Strong oxidizing agents. Strong acids.

## **Hazardous Decomposition Products**

Carbon monoxide. Carbon dioxide (CO2). Hydrogen sulfide.

#### 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Product Information No data available

**Inhalation** May cause irritation of respiratory tract.

**Eye contact** Irritating to eyes.

**Skin contact** Irritating to skin. Causes burns.

**Ingestion** No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Asphalt, Petroleum (Residues) 64741-56-6	= 4320 mg/kg (Rat)	> 2000 mg/kg ( Rabbit )	-
Sulfur 7704-34-9	> 3000 mg/kg (Rat)	> 2000 mg/kg ( Rabbit )	> 9.23 mg/L (Rat)4 h
Silica, quartz 14808-60-7	= 500 mg/kg (Rat)	-	-

#### Information on toxicological effects

**Symptoms** No information available.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available. Germ cell mutagenicity No information available.

Carcinogenicity This product contains one or more substances which are classified by IARC as carcinogenic

to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly carcinogenic

to humans (Group 2B).

· · · · · · · · · · · · · · · · · · ·				
Chemical Name	ACGIH	IARC	NTP	OSHA
Asphalt, Petroleum (Residues) 64741-56-6	-	Group 2B	-	X
Silica, quartz 14808-60-7	A2	Group 1	Known	Х

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity No information available. STOT - single exposure Respiratory system. STOT - repeated exposure No information available. **Aspiration hazard** No information available.

## Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document.

Oral LD50 9225 mg/kg **Dermal LD50** 4498 mg/kg

## 12. ECOLOGICAL INFORMATION

## **Ecotoxicity**

None known

## Persistence and degradability

No information available.

## Bioaccumulation

No information available.

Other adverse effects No information available

## 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

14. TRANSPORT INFORMATION

DOT Not regulated

TDG Not regulated

Not regulated MEX

ICAO (air) Not regulated

Not regulated IATA

IMDG Not regulated

RID Not regulated

ADR Not regulated

ADN Not regulated

## 15. REGULATORY INFORMATION

**International Inventories** 

**TSCA** Complies **DSL/NDSL** Complies **EINECS/ELINCS** Complies Does not comply **ENCS IECSC** Complies **KECL** Complies Complies

**PICCS AICS** Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

## US Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

#### SARA 311/312 Hazard Categories

Acute health hazard Yes **Chronic Health Hazard** No Fire hazard No Sudden release of pressure hazard No **Reactive Hazard** Nο

#### **CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

#### **CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

#### **US State Regulations**

## **California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65	
Silica, quartz - 14808-60-7	Carcinogen	

## U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Calcium Carbonate 1317-65-3	X	X	X
Sulfur 7704-34-9	X	X	X
Silica, quartz 14808-60-7	Х	X	X

## U.S. EPA Label Information

**EPA Pesticide Registration Number** Not applicable

## 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 1 Instability 0 Physical and Chemical Properties -

Hall Hall hazarda O. Flammakilli d. Bhariadharada O. Flammakilli d. Bhariadharada

HMIS Health hazards 2 Flammability 1 Physical hazards 0 Personal protection X

Issue Date 09-Jun-2015
Revision Date 09-Jun-2015
Revision Note

No information available

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**