

SAFETY DATA SHEET

M49011 - ANSI - EN



INDSPEC Chemical Corporation

A subsidiary of Occidental Petroleum Corporation

BINDEX® RESIN 73

SDS No.: M49011
Rev. Num. 02

SDS Revision Date: 18-Nov-2016

SECTION 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Company Identification:	INDSPEC Chemical Corporation Subsidiary of Occidental Petroleum Corporation 5005 LBJ Freeway P.O. Box 809050 Dallas, Texas 75380-9050
Manufacturing Address:	INDSPEC Chemical Corporation Subsidiary of Occidental Petroleum Corporation 133 Main Street Petrolia, Pennsylvania 16050 USA Information: (+1) 412-826-3666
24 Hour Emergency Telephone Number:	1-800-733-3665 or 1-972-404-3228 (U.S.); CHEMTREC (U.S.): 1-800-424-9300; CHEMTREC Contract No: CCN16186; CANUTEC (Canada): 1-613-996-6666 MEDICAL EMERGENCIES: 1-800-456-7566
To Request an SDS:	MSDS@oxy.com or 1-972-404-3245
Customer Service:	1-800-221-6514 or 1-972-404-3700
Product Identifier:	BINDEX® RESIN 73
Synonyms:	Resorcinol Homopolymer, Resorcinol-Formaldehyde Resin
Product Use:	Used in foundry or refractory applications
Uses Advised Against:	None identified
Chemical Family:	Resorcinol Homopolymer, Resorcinol-Formaldehyde Resin

BINDEX® RESIN 73

SDS No.: M49011

Supersedes Date: 2015-12-May

SDS Revision Date: 18-Nov-2016

Rev. Num.02

SECTION 2. HAZARDS IDENTIFICATION

OSHA REGULATORY STATUS: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

EMERGENCY OVERVIEW:

Color: Dark brown
Physical State: Liquid
Odor: Slight phenolic odor

Signal Word: **DANGER**

MAJOR HEALTH HAZARDS: CAUSES SERIOUS EYE DAMAGE. MAY BE HARMFUL IF SWALLOWED. CAUSES MILD SKIN IRRITATION. MAY CAUSE AN ALLERGIC SKIN REACTION.

AQUATIC TOXICITY: TOXIC TO AQUATIC LIFE.

PRECAUTIONARY STATEMENTS: Avoid breathing dust or mist. Wear protective gloves, protective clothing, eye, and face protection. Remove contaminated clothing and wash before reuse. Contaminated work clothing should not be allowed out of the workplace. Wash hands and affected skin thoroughly after handling. Avoid release to the environment.

ADDITIONAL HAZARD INFORMATION: Not for use or storage in or around home. Good hygiene and safety practices should be used when handling and working with this material. Good hygiene practices include but are not limited to: wearing suitable gloves and/or eye protection; washing hands and affected skin immediately after handling, before breaks, and at the end of the workday; regularly cleaning work area and clothing; etc.

GHS CLASSIFICATION:

GHS: CONTACT HAZARD - EYE:	Category 1 - Causes serious eye damage
GHS: SENSITIZATION HAZARD:	Skin Sensitizer Category 1 - May cause an allergic skin reaction

Unknown Acute Inhalation Toxicity:

There is no acute inhalation toxicity data available for this material. 100% of this product consists of ingredient(s) of unknown acute inhalation toxicity.

GHS SYMBOL: Exclamation mark, Corrosive

BINDEX® RESIN 73

SDS No.: M49011

Supersedes Date: 2015-12-May

SDS Revision Date: 18-Nov-2016

Rev. Num.02

GHS SIGNAL WORD: **DANGER****GHS HAZARD STATEMENTS:****GHS - Health Hazard Statement(s)**

- Causes serious eye damage
- May cause an allergic skin reaction

GHS - Precautionary Statement(s) - Prevention

- Wear eye protection/face protection
- Wear protective gloves and protective clothing
- Contaminated work clothing should not be allowed out of the workplace
- Avoid breathing dust or mist

GHS - Precautionary Statement(s) - Response

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- Immediately call a POISON CENTER or doctor/physician
- IF ON SKIN: Wash with plenty of soap and water
- If skin irritation or rash occurs: Get medical advice/attention
- Take off contaminated clothing and wash it before reuse

GHS - Precautionary Statement(s) - Storage

- There are no Precautionary-Storage phrases assigned

GHS - Precautionary Statement(s) - Disposal

- Dispose of contents and container in accordance with applicable local, regional, national, and/or international regulations

See Section 11: TOXICOLOGICAL INFORMATION

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**Synonyms:** Resorcinol Homopolymer, Resorcinol-Formaldehyde Resin

Component	Percent [%]	CAS Number
Resorcinol Homopolymer, Resorcinol	55-65	65876-95-1

BINDEX® RESIN 73

SDS No.: M49011

Supersedes Date: 2015-12-May

SDS Revision Date: 18-Nov-2016

Rev. Num.02

Formaldehyde Polymer		
Water	20-30	7732-18-5
Resorcinol	<15	108-46-3

SECTION 4. FIRST AID MEASURES

INHALATION: If inhaled and adverse effects occur, remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, contact poison control center or doctor/physician.

SKIN CONTACT: Wipe off excess chemical and flush contaminated areas with plenty of water. If skin irritation occurs: Get medical advice/ attention.

EYE CONTACT: If in eyes, immediately rinse eyes cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately contact a physician. Immediate and thorough decontamination of the eye is essential followed by ophthalmological assessment. Follow protocol for corrosive injury.

INGESTION: If swallowed, rinse mouth. Contact a Poison Center, or a doctor/physician, or get medical attention if you feel unwell.

Most Important Symptoms/Effects (Acute and Delayed):

Acute Symptoms/Effects: Listed below.

Inhalation (Breathing): Respiratory System Effects: Inhalation of this material may cause irritation, coughing.

Skin: Skin Irritation. Exposure of dust to skin may cause redness, mild irritation. Free resorcinol may penetrate the skin and cause systemic toxicity. This material contains less than 15% free resorcinol. May cause an allergic skin reaction.

Eye: Eye Irritation. Eye exposure may cause irritation and burns to the eyelids, conjunctivitis, corneal edema, and iritis.

Ingestion (Swallowing): Gastrointestinal System Effects: Exposure by ingestion may cause irritation, nausea, and vomiting. May cause local tissue damage to esophagus and stomach such as burning, inflammation. Free resorcinol is well absorbed by the gastrointestinal (GI) tract, and this route of exposure can lead to systemic effects such as unconsciousness, respiratory failure, seizures, leukocytosis and severe metabolic acidosis, and methemoglobinemia. Alterations in liver and kidney functions have been reported in severe poisonings. This material contains less than 15% free resorcinol.

Delayed Symptoms/Effects:

- No delayed / chronic effects have been identified

Interaction with Other Chemicals Which Enhance Toxicity: None known.

Medical Conditions Aggravated by Exposure: May aggravate preexisting conditions such as: eye disorders that decrease tear production or have reduced integrity of the eye; skin disorders that compromise the integrity of the skin; and respiratory conditions including asthma and other breathing disorders.

Protection of First-Aiders: Protect yourself by avoiding contact with this material. Avoid contact with skin and eyes. Use personal protective equipment. Refer to Section 8 for specific personal protective equipment recommendations.

BINDEX® RESIN 73

SDS No.: M49011

Supersedes Date: 2015-12-May

SDS Revision Date: 18-Nov-2016

Rev. Num.02

Do not ingest.

Notes to Physician: Treat symptomatically. There is no antidote. This material induces mild local irritation. For ingestion, consider evaluation of local mucosal irritation, and erosion.

SECTION 5. FIRE-FIGHTING MEASURES

Fire Hazard: Negligible fire hazard.

Explosive properties: Dust (powder) may form explosive mixture in air. Closed containers may explode or rupture when exposed to extreme heat (fire).

Extinguishing Media: Use dry chemical, carbon dioxide, foam, or water spray

Fire Fighting: Wear complete fire service protective equipment, including full-face MSHA/NIOSH approved self-contained breathing apparatus. Use water to cool fire-exposed container/structure/protect personnel.

Hazardous Combustion Products: Oxides of carbon (Carbon monoxide, Carbon dioxide)

Sensitivity to Mechanical Impact: Not sensitive.

Sensitivity to Static Discharge: Not sensitive.

Lower Flammability Level (air): Not applicable

Upper Flammability Level (air): Not applicable

Flash point: >100 °C (>212 °F)

Auto-ignition Temperature: Not applicable

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Keep unnecessary and unprotected personnel from entering the area. Stop leak if possible without personal risk. Stay upwind. Do not get in eyes. Do not breathe dust, fume, gas, mist, vapors, or spray. Avoid contact with skin and clothing. Wear appropriate personal protective equipment recommended in Section 8, Exposure Controls / Personal Protection, of the SDS.

Methods and Materials for Containment and Cleaning Up:

Contain spill. Use methods to minimize generation of dust. Shovel back into original dry container or waste receptacle. Flush area with water. Contain runoff from fire control and dilution water.

BINDEX® RESIN 73

SDS No.: M49011

Supersedes Date: 2015-12-May

SDS Revision Date: 18-Nov-2016

Rev. Num.02

Environmental Precautions:

Keep out of water supplies and sewers. Releases should be reported, if required, to appropriate regulatory agencies.

SECTION 7. HANDLING AND STORAGE

General: Not for use or storage in or around the home. Do not use until the manufacturer's precautions have been read/understood.

Precautions for Safe Handling:

Avoid prolonged or repeated breathing of dusts. Minimize generation of dust. Avoid contact with skin and eyes. Wash exposed skin thoroughly after contact and before eating, drinking, using tobacco products or restrooms. Observe good personal hygiene practices and recommended procedures. Wear personal protective equipment as described in Exposure Controls/Personal Protection (Section 8) of the SDS.

Safe Storage Conditions:

Keep container tightly closed and properly labeled. Store in a cool, well-ventilated area away from possible sources of ignition. Protect from physical damage. Keep containers closed when material is not in use. Keep away from food, drink and animal feed. Maintain good housekeeping. Keep separated from incompatible substances (see below or Section 10 of the Safety Data Sheet).

Incompatibilities/ Materials to Avoid:

Reaction with formaldehyde is mildly exothermic

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Regulatory Exposure Limit(s): This product does not contain any components that have regulatory occupational exposure limits (OEL's).

OEL: Occupational Exposure Limit; OSHA: United States Occupational Safety and Health Administration; PEL: Permissible Exposure Limit; TWA: Time Weighted Average; STEL: Short Term Exposure Limit

NON-REGULATORY EXPOSURE LIMIT(S): Listed below for the product components that have advisory (non-regulatory) occupational exposure limits (OEL's) established.

Component	ACGIH TWA	ACGIH STEL	ACGIH Ceiling	OSHA TWA (Vacated)	OSHA STEL (Vacated)	OSHA Ceiling (Vacated)
Resorcinol	10 ppm	20 ppm	-----	10 ppm 45 mg/m ³	20 ppm 90 mg/m ³	-----

- The Non-Regulatory United States Occupational Safety and Health Administration (OSHA) limits, if shown, are the Vacated 1989 PEL's (vacated by 58 FR 35338, June 30, 1993).

- The American Conference of Governmental Industrial Hygienists (ACGIH) is a voluntary organization of professional industrial hygiene personnel in government or educational institutions in the United States. The ACGIH develops and publishes recommended occupational exposure limits each year called Threshold Limit Values (TLVs) for hundreds of chemicals, physical agents, and biological exposure indices.

BINDEX® RESIN 73

SDS No.: M49011

Supersedes Date: 2015-12-May

SDS Revision Date: 18-Nov-2016

Rev. Num.02

Additional Advice:

1. Good hygiene and safety practices should be used when handling and working with this material
2. Good hygiene practices include but are not limited to: wearing suitable gloves and/or eye protection; washing hands and affected skin immediately after handling, before breaks, and at the end of the workday; regularly cleaning work area and clothing; etc.
3. Contaminated work clothing should not be allowed out of the workplace

ENGINEERING CONTROLS: Provide sufficient general/local exhaust ventilation in pattern/volume to control inhalation exposures below applicable exposure limits and to keep area dust levels below explosive dust concentrations.

PERSONAL PROTECTIVE EQUIPMENT:

Eye Protection: Wear safety glasses with side-shields. If eye contact is likely, wear chemical resistant safety goggles and/or face-shield when appropriate. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Skin and Body Protection: As a good hygiene practice, wear protective clothing to minimize skin contact such as standard industrial work clothes, coveralls, safety footwear. In dusty areas, wear necessary resistant protective apparel, including necessary head, hand, and foot protection. Contaminated clothing should be removed and laundered before reuse. Contaminated work clothing must not be allowed out of the workplace.

Hand Protection: As a good hygiene practice, wear appropriate chemical resistant gloves. Consult a glove supplier for assistance in selecting an appropriate chemical resistant glove.

Protective Material Types:

Butyl rubber, Natural rubber, Neoprene, Nitrile, Polyvinyl chloride (PVC), Tyvek®

Respiratory Protection: Not required under normal use conditions. A NIOSH/MSHA approved respirator with air purifying organic vapor cartridge/canister with particulate filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits, or when symptoms have been observed that are indicative of overexposure. The added protection of a full face-piece respirator is required when visible dusty conditions are encountered and eye irritation may occur. A respiratory protection program that meets 29 CFR 1910.134 must be followed whenever workplace conditions warrant use of a respirator.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Color:	Dark brown
Odor:	Slight phenolic odor
Odor Threshold [ppm]:	No data available.
Molecular Weight:	NA/Polymer
Chemical Family:	Resorcinol Homopolymer, Resorcinol-Formaldehyde Resin
Boiling Point/Range:	>100 °C (>212 °F)
Freezing Point/Range:	No data available.

BINDEX® RESIN 73

SDS No.: M49011

Supersedes Date: 2015-12-May

SDS Revision Date: 18-Nov-2016

Rev. Num.02

Melting Point/Range:	Not applicable to liquids
Vapor Pressure:	<1 mmHg
Vapor Density (air=1):	Not applicable
Relative Density/Specific Gravity (water=1):	1.24 @ 25 °C
Density:	No data available
Water Solubility:	Appreciable
pH:	4-5
VOC Content (%):	No data available
Evaporation Rate (ether=1):	No data available
Partition Coefficient (n-octanol/water):	No data available
Flash point:	>100 °C (>212 °F)
Flammability (solid, gas):	No data available
Lower Flammability Level (air):	Not applicable
Upper Flammability Level (air):	Not applicable
Auto-ignition Temperature:	Not applicable
Viscosity:	15 poise @ 23°C

SECTION 10. STABILITY AND REACTIVITY

Reactivity: Not reactive under normal temperatures and pressures. Reaction with formaldehyde is mildly exothermic.

Chemical Stability: Stable at normal temperatures and pressures.

Possibility of Hazardous Reactions: Closed containers may explode or rupture when exposed to extreme heat (fire).

Conditions to Avoid: (e.g., static discharge, shock, or vibration) -. Dust may form explosive mixture in air. Ground equipment in accordance with industry standards and best practices such as NFPA 77 [Recommended Practices on Static Electricity (2007)] and American Petroleum Institute (API) RP Recommended Practice 2003 [Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents (2008)].

Incompatibilities/ Materials to Avoid: Reaction with formaldehyde is mildly exothermic.

Hazardous Decomposition Products: Oxides of carbon (Carbon monoxide, Carbon dioxide)

Hazardous Polymerization: Will not occur.

SECTION 11. TOXICOLOGICAL INFORMATION

IRRITATION DATA: As listed below

Standard Draize (Eye):

Score - 57.0 @ 24, 59.0 @ 48, and 51.0 @ 72 hrs. (Rabbit)

BINDEX® RESIN 73

SDS No.: M49011

Supersedes Date: 2015-12-May

SDS Revision Date: 18-Nov-2016

Rev. Num.02

Standard Draize (Skin):

Score - 1.8 (Rabbit - 24 hrs.)

TOXICITY DATA:**PRODUCT TOXICITY DATA: BINDEX® RESIN 73****Note:** The test material for the toxicological studies was a structurally similar product (PENACOLITE® RESIN B-18-S).

<u>LD50 Oral:</u> 3100 mg/kg (Rat)	<u>LD50 Dermal:</u> >3980 mg/kg (Rabbit)	<u>LC50 Inhalation:</u> No data available
--	--	---

COMPONENT TOXICITY DATA:**Note:** The component toxicity data is populated by the LOLI database and may differ from the product toxicity data given.

Component	LD50 Oral:	LD50 Dermal:	LC50 Inhalation:
Resorcinol 108-46-3	202 mg/kg (Rat)	3360 mg/kg (Rabbit)	21.3 mg/L (1 hr-Rat)

POTENTIAL HEALTH EFFECTS:

Eye contact:	Direct contact with solid, dust, or solutions may cause severe irritation and burns to the eye lids, conjunctivitis, corneal edema, corneal burn.
Skin contact:	Direct contact or contact with dust or solutions may cause mild irritation and skin rash. Repeated contact may cause an allergic skin reaction.
Inhalation:	Inhalation of this material may cause irritation of upper and lower airways.
Ingestion:	Ingestion of this material may cause gastrointestinal irritation. May cause local tissue irritation to esophagus and stomach.
Chronic Effects:	None known.

SIGNS AND SYMPTOMS OF EXPOSURE:**Inhalation (Breathing):** Respiratory System Effects: Inhalation of this material may cause irritation, coughing.**Skin:** Skin Irritation. Exposure of dust to skin may cause redness, mild irritation. Free resorcinol may penetrate the skin and cause systemic toxicity. This material contains less than 15% free resorcinol. May cause an allergic skin reaction.**Eye:** Eye Irritation. Eye exposure may cause irritation and burns to the eyelids, conjunctivitis, corneal edema, and iritis.**Ingestion (Swallowing):** Gastrointestinal System Effects: Exposure by ingestion may cause irritation, nausea, and vomiting. May cause local tissue damage to esophagus and stomach such as burning, inflammation. Free resorcinol is well absorbed by the gastrointestinal (GI) tract, and this route of exposure can lead to systemic effects such as unconsciousness, respiratory failure, seizures, leukocytosis and severe metabolic acidosis, and methemoglobinemia. Alterations in liver and kidney functions have been reported in severe poisonings. This material contains less than 15% free resorcinol.

BINDEX® RESIN 73

SDS No.: M49011

Supersedes Date: 2015-12-May

SDS Revision Date: 18-Nov-2016

Rev. Num.02

TOXICITY:

The resorcinol-formaldehyde resin is irritating in contact with skin and mucus membranes. Resorcinol, in low concentrations, is commonly used in the pharmaceutical and cosmetic industries. Resorcinol has been reported to be less toxic than phenol or catechol by the ingestion or skin routes of exposure. Chemical analysis indicates that there is less than 50 ppm free formaldehyde present in this material.

CHRONIC TOXICITY:

Animal and human data have indicated that resorcinol may cause damage to the respiratory system. Animal and human data have indicated that resorcinol causes damage to the blood and central nervous system. This material contains less than 15% free resorcinol.

Interaction with Other Chemicals Which Enhance Toxicity: None known.

GHS HEALTH HAZARDS:

GHS: ACUTE TOXICITY - ORAL: Category 5 - May be harmful if swallowed.

GHS: CONTACT HAZARD - EYE: Category 1 - Causes serious eye damage

GHS: CONTACT HAZARD - SKIN: Category 3 - Causes mild skin irritation.

Skin Absorbent / Dermal Route? No.

GHS: SENSITIZATION HAZARD: Skin Sensitizer Category 1 - May cause an allergic skin reaction.

Carcinogenicity comment: Chemical analysis indicates that <50ppm free formaldehyde is present in product. No known ingredients which occur at greater than 0.1% are listed as a carcinogen in the IARC Monographs on the Evaluation of the Carcinogenic Risk of Chemicals to Humans, the NTP Annual Report on Carcinogens, or OSHA 29 CFR 1910 Subpart Z Toxic and Hazardous Substances (specifically regulated substances).

SECTION 12. ECOLOGICAL INFORMATION**Product Information:**

No data is available on the mixture itself.

ECOTOXICITY DATA:

<u>Component</u>	<u>Freshwater Fish</u>	<u>Invertebrate Toxicity:</u>	<u>Algae Toxicity:</u>	<u>Other Toxicity:</u>
Resorcinol Homopolymer, Resorcinol Formaldehyde Polymer	- Not Listed	- Not Listed	- No data available	- No data available
Resorcinol	- - 96 hr. LC50 Oncorhynchus mykiss: >100 mg/L (flow-through)	- 48 hr. LC50 Daphnia magna: 78 mg/L	- Algae-Scenedesmus: LD0 60 mg/L	- - Bacteria-E Coli: LD0 <1000 mg/L - Arthropoda-Daphnia:

BINDEX® RESIN 73

SDS No.: M49011

Supersedes Date: 2015-12-May

SDS Revision Date: 18-Nov-2016

Rev. Num.02

	- 96 hr. LC50 Pimephales promeias: 53.4 mg/L			LD0 0.8 mg/L
--	--	--	--	--------------

FATE AND TRANSPORT:**BIODEGRADATION:** No data available.**PERSISTENCE:** No data available.**BIOACCUMULATIVE POTENTIAL:** No data available.**MOBILITY IN SOIL:** No data available.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste from material:

Reuse or recycle if possible. Dispose of in accordance with federal, state and local regulations.

Container Management:

Dispose of container in accordance with applicable local, regional, national, and/or international regulations. Container rinsate must be disposed of in compliance with applicable regulations.

SECTION 14. TRANSPORT INFORMATION

IMPORTANT: The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.**LAND TRANSPORT****U.S. DOT 49 CFR 172.101:****Status:** Not Regulated.**CANADIAN TRANSPORTATION OF DANGEROUS GOODS:****Status:** Not Regulated.**MARITIME TRANSPORT (IMO / IMDG) :****Status - IMO / IMDG:** Not Regulated**AIR TRANSPORT (ICAO / IATA): :****Status - ICAO/IATA:** Not Regulated

BINDEX® RESIN 73

SDS No.: M49011

Supersedes Date: 2015-12-May

SDS Revision Date: 18-Nov-2016

Rev. Num.02

SECTION 15. REGULATORY INFORMATION**U.S. REGULATIONS****OSHA REGULATORY STATUS:**

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

CERCLA SECTIONS 102a/103 HAZARDOUS SUBSTANCES (40 CFR 302.4):

If a release is reportable under CERCLA section 103, notify the state emergency response commission and local emergency planning committee. In addition, notify the National Response Center at (800) 424-8802 or (202) 426-2675.

Component	CERCLA Reportable Quantities:
Resorcinol	5000 lb (final RQ)

SARA EHS Chemical (40 CFR 355.30)

Not regulated

EPCRA SECTIONS 311/312 HAZARD CATEGORIES (40 CFR 370.10):

Acute Health Hazard

EPCRA SECTION 313 (40 CFR 372.65):

Not regulated

OSHA PROCESS SAFETY (PSM) (29 CFR 1910.119):

Not regulated

NATIONAL INVENTORY STATUS

TSCA 12(b): This product is not subject to export notification.

Canadian Chemical Inventory: All components of this product are listed on either the DSL or the NDSL.

Component	DSL	NDSL
Resorcinol Homopolymer, Resorcinol Formaldehyde Polymer 65876-95-1	Listed	Not Listed
Resorcinol 108-46-3	Listed	Not Listed

STATE REGULATIONS**California Proposition 65:**

This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

BINDEX® RESIN 73

SDS No.: M49011

Supersedes Date: 2015-12-May

SDS Revision Date: 18-Nov-2016

Rev. Num.02

Component	California Proposition 65 Cancer WARNING:	California Proposition 65 CRT List - Male reproductive toxin:	California Proposition 65 CRT List - Female reproductive toxin:	Massachusetts Right to Know Hazardous Substance List	New Jersey Right to Know Hazardous Substance List	New Jersey Special Health Hazards Substance List
Resorcinol Homopolymer, Resorcinol Formaldehyde Polymer 65876-95-1	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Resorcinol 108-46-3	Not Listed	Not Listed	Not Listed	Listed	1634	Not Listed

Component	New Jersey - Environmental Hazardous Substance List	Pennsylvania Right to Know Hazardous Substance List	Pennsylvania Right to Know Special Hazardous Substances	Pennsylvania Right to Know Environmental Hazard List	Rhode Island Right to Know Hazardous Substance List
Resorcinol Homopolymer, Resorcinol Formaldehyde Polymer 65876-95-1	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Resorcinol 108-46-3	Not Listed	Listed	Not Listed	Present	Listed

CANADIAN REGULATIONS

• This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations

Component	Canadian Chemical Inventory:	NDSL:	WHMIS - Classifications of Substances:
Resorcinol Homopolymer, Resorcinol Formaldehyde Polymer	Listed		
Resorcinol	Listed Present (that participate in atmospheric photochemical reactions except those under item number 65 on the Toxic Substances List source)		D1B,D2B

SECTION 16. OTHER INFORMATION

Prepared by: OxyChem Corporate HESS - Product Stewardship

Rev. Date: 18-Nov-2016

Reason for Revision:

• Emergency Overview was revised: SEE SECTION 2

BINDEX® RESIN 73

SDS No.: M49011

Supersedes Date: 2015-12-May

SDS Revision Date: 18-Nov-2016

Rev. Num.02

-
- The Emergency Overview Signal word has been added or changed. SEE SECTION 2
 - Added Aquatic Toxicity Statements: SEE SECTION 2
 - Revised GHS Information: SEE SECTION 2
 - Updated First Aid Measures: SEE SECTION 4
 - Modified Exposure Limit information: SEE SECTION 8
 - Revised Exposure Controls/Personal Protection information: SEE SECTION 8
 - TOXICOLOGICAL INFORMATION (SECTION 11)
 - ECOLOGICAL INFORMATION (SECTION 12)
 - State Regulation changes: SEE SECTION 15
 - Removed NFPA/HMIS ratings from format: SEE SECTION 16

IMPORTANT:

The information presented herein, while not guaranteed, was prepared by technical personnel and is true and accurate to the best of our knowledge. NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTY OR GUARANTY OF ANY OTHER KIND, EXPRESS OR IMPLIED, IS MADE REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY OR OTHERWISE. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, storage, disposal and other factors that may involve other or additional legal, environmental, safety or performance considerations, and INDSPEC Chemical Corporation assumes no liability whatsoever for the use of or reliance upon this information. While our technical personnel will be happy to respond to questions, safe handling and use of the product remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patents or to violate any Federal, State, local or foreign laws.

OSHA Standard 29 CFR 1910.1200 requires that information be provided to employees regarding the hazards of chemicals by means of a hazard communication program including labeling, safety data sheets, training and access to written records. We request that you, and it is your legal duty to, make all information in this Safety Data Sheet available to your employees

End of Safety Data Sheet