

SAFETY DATA SHEET

1. Identification

Product identifier	BT214 GEL VANDALISM 482G		
Other means of identification			
Product code	1000020740		
Recommended use	CLEANER		
Recommended restrictions	None known.		
Manufacturer/Importer/Supplier/Distributor information			
Manufacturer			
Company name	K-G Spray-Pak Inc.		
Address	P.O. Box 89 8001 Keele Street Vaughan, Ontario L4K 1Y8 Canada		
Telephone	General Assistance	1-905-669-9855	
E-mail	aerosols@kgpackaging.com		
Emergency phone number	Emergency - US	1-866-836-8855	
	Emergency - Outside US	1-952-852-4046	
Supplier	Not available.		

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
Health hazards	Skin corrosion/irritation	Category 2
	Reproductive toxicity (the unborn child)	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2
	Aspiration hazard	Category 1

Label elements



Signal word	Danger
Hazard statement	Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.
Response	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF ON SKIN: Wash with plenty of water. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.

Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
Other hazards	None known.	
Supplemental information	None.	

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Toluene		108-88-3	36.88
Isobutane		75-28-5	16.96
Diacetone Alcohol		123-42-2	7.2
Xylene		1330-20-7	6.48
Isopropyl Alcohol		67-63-0	5.6
Propane		74-98-6	3.04
Ethyl Benzene		100-41-4	1.44
Sodium Nitrite		7632-00-0	0.161
Other components below reportable levels			22.239

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Water spray. Foam. Powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Avoid contact with eyes, skin, and clothing. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 2 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Type	Value
Diacetone Alcohol (CAS 123-42-2)	TWA	50 ppm
Ethyl Benzene (CAS 100-41-4)	TWA	20 ppm
Isobutane (CAS 75-28-5)	STEL	1000 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm
Xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value
Diacetone Alcohol (CAS 123-42-2)	TWA	238 mg/m3
		50 ppm
Ethyl Benzene (CAS 100-41-4)	STEL	543 mg/m3
		125 ppm
	TWA	434 mg/m3

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Type	Value
Isopropyl Alcohol (CAS 67-63-0)	STEL	100 ppm
		984 mg/m3
	TWA	400 ppm
		492 mg/m3
Propane (CAS 74-98-6)	TWA	200 ppm
		1000 ppm
Toluene (CAS 108-88-3)	TWA	188 mg/m3
		50 ppm
Xylene (CAS 1330-20-7)	STEL	651 mg/m3
		150 ppm
	TWA	434 mg/m3
		100 ppm

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value
Diacetone Alcohol (CAS 123-42-2)	TWA	50 ppm
Ethyl Benzene (CAS 100-41-4)	TWA	20 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm
	STEL	150 ppm
Xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value
Diacetone Alcohol (CAS 123-42-2)	TWA	50 ppm
Ethyl Benzene (CAS 100-41-4)	TWA	20 ppm
Isobutane (CAS 75-28-5)	STEL	1000 ppm
Isopropyl Alcohol (CAS 67-63-0)	STEL	400 ppm
	TWA	200 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm
	STEL	150 ppm
Xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value
Diacetone Alcohol (CAS 123-42-2)	STEL	360 mg/m3
	TWA	75 ppm
	TWA	240 mg/m3
		50 ppm
Ethyl Benzene (CAS 100-41-4)	STEL	125 ppm
	TWA	100 ppm
Isobutane (CAS 75-28-5)	TWA	800 ppm
	STEL	400 ppm
Isopropyl Alcohol (CAS 67-63-0)	TWA	200 ppm
	TWA	20 ppm
Toluene (CAS 108-88-3)	STEL	150 ppm
	TWA	100 ppm
Xylene (CAS 1330-20-7)	STEL	150 ppm
	TWA	100 ppm

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Type	Value
Diacetone Alcohol (CAS 123-42-2)	TWA	238 mg/m3
Ethyl Benzene (CAS 100-41-4)	STEL	50 ppm 543 mg/m3
	TWA	125 ppm 434 mg/m3
Isopropyl Alcohol (CAS 67-63-0)	STEL	100 ppm 1230 mg/m3
	TWA	500 ppm 983 mg/m3
Propane (CAS 74-98-6)	TWA	400 ppm 1800 mg/m3
Toluene (CAS 108-88-3)	TWA	1000 ppm 188 mg/m3
Xylene (CAS 1330-20-7)	STEL	50 ppm 651 mg/m3
	TWA	150 ppm 434 mg/m3 100 ppm

Biological limit values
ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Ethyl Benzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Isopropyl Alcohol (CAS 67-63-0)	40 mg/l	Acetone	Urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines
Canada - Alberta OELs: Skin designation

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

Canada - Quebec OELs: Skin designation

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

Canada - Saskatchewan OELs: Skin designation

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment
Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection
Hand protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Other

Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Gas.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
pH	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	185.73 °F (85.41 °C) estimated
Flash point	-99.4 °F (-73.0 °C) PROPELLANT estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)	1.4 % estimated
Flammability limit - upper (%)	8.3 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Specific gravity	0.821 estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Acids. Strong oxidizing agents. Nitrates. Halogens. Isocyanates. Fluorine. Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause drowsiness and dizziness. Headache. Nausea, vomiting.
Skin contact	Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

Symptoms related to the physical, chemical and toxicological characteristics

Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause redness and pain.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways. Narcotic effects.

Components	Species	Test Results
Diacetone Alcohol (CAS 123-42-2)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	14.5 ml/kg, 24 Hours
	Rat	> 1875 mg/kg, 24 Hours
		13500 mg/kg
Oral		
LD50	Rat	3002 mg/kg
Ethyl Benzene (CAS 100-41-4)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	17.8 ml/kg, 24 Hours
Inhalation		
LC50	Mouse	> 8000 ppm, 20 Minutes
	Rat	4000 ppm
Oral		
LD50	Rat	3500 mg/kg
Isobutane (CAS 75-28-5)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
Isopropyl Alcohol (CAS 67-63-0)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	16.4 ml/kg, 24 Hours
Inhalation		
LC50	Rat	> 10000 ppm, 6 Hours
Oral		
LD50	Rat	5.84 g/kg
Propane (CAS 74-98-6)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes

Components	Species	Test Results
	Rat	1355 mg/l 658 mg/l/4h
Sodium Nitrite (CAS 7632-00-0)		
<u>Acute</u>		
Oral		
LD50	Rat	180 mg/kg
Toluene (CAS 108-88-3)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 5000 mg/kg, 24 Hours
Inhalation		
LC50	Mouse	6405 - 7436 ppm, 6 Hours 5320 ppm, 8 Hours
	Rat	5879 - 6281 ppm, 6 Hours 25.7 mg/l, 4 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Xylene (CAS 1330-20-7)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 5000 ml/kg, 4 Hours 12126 mg/kg, 24 Hours
Inhalation		
LC50	Rat	5922 ppm, 4 Hours
Oral		
LD50	Mouse	5251 mg/kg
	Rat	3523 mg/kg 10 ml/kg

* Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Canada - Alberta OELs: Irritant

Diacetone Alcohol (CAS 123-42-2) Irritant

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Risk of cancer cannot be excluded with prolonged exposure.

ACGIH Carcinogens

Ethyl Benzene (CAS 100-41-4)	A3 Confirmed animal carcinogen with unknown relevance to humans.
Isopropyl Alcohol (CAS 67-63-0)	A4 Not classifiable as a human carcinogen.
Toluene (CAS 108-88-3)	A4 Not classifiable as a human carcinogen.
Xylene (CAS 1330-20-7)	A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

2-PROPANOL (CAS 67-63-0)	Not classifiable as a human carcinogen.
ETHYL BENZENE (CAS 100-41-4)	Confirmed animal carcinogen with unknown relevance to humans.
TOLUENE (CAS 108-88-3)	Not classifiable as a human carcinogen.
XYLENE (O, M AND P ISOMERS) (CAS 1330-20-7)	Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

Ethyl Benzene (CAS 100-41-4)

2B Possibly carcinogenic to humans.

Toluene (CAS 108-88-3)

3 Not classifiable as to carcinogenicity to humans.

Xylene (CAS 1330-20-7)

3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity

Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

Chronic effects

May cause damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.

12. Ecological information**Ecotoxicity** Toxic to aquatic life with long lasting effects.

Components		Species	Test Results
Diacetone Alcohol (CAS 123-42-2)			
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	420 mg/l, 96 hours
		Fish	420 mg/L, 96 Hours
Ethyl Benzene (CAS 100-41-4)			
Aquatic			
Algae	IC50	Algae	4.6 mg/L, 72 Hours
Crustacea	EC50	Daphnia	2.1 mg/L, 48 Hours
		Water flea (Daphnia magna)	1.37 - 4.4 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	7.5 - 11 mg/l, 96 hours
Isopropyl Alcohol (CAS 67-63-0)			
Aquatic			
Algae	IC50	Algae	1000.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	13299 mg/L, 48 Hours
Fish	LC50	Bluegill (Lepomis macrochirus)	> 1400 mg/l, 96 hours
Sodium Nitrite (CAS 7632-00-0)			
Aquatic			
Crustacea	EC50	Greasyback shrimp (Metapenaeus ensis)	16.14 - 26.61 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	0.15 - 0.25 mg/l, 96 hours
Toluene (CAS 108-88-3)			
Aquatic			
Algae	IC50	Algae	433.0001 mg/L, 72 Hours
Crustacea	EC50	Daphnia	7.645 mg/L, 48 Hours
		Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon,silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours
Xylene (CAS 1330-20-7)			
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	7.711 - 9.591 mg/l, 96 hours

* Estimates for product may be based on additional component data not shown.

Persistence and degradability

No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Diacetone Alcohol	-0.098
Ethyl Benzene	3.15
Isobutane	2.76
Isopropyl Alcohol	0.05
Propane	2.36
Toluene	2.73
Xylene	3.12 - 3.2

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations**Disposal instructions**

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information**TDG**

UN number	UN1950
UN proper shipping name	AEROSOLS, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not applicable.
Environmental hazards	Yes
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.
Environmental hazards	Yes
ERG Code	10L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	

Passenger and cargo aircraft	Allowed with restrictions.
-------------------------------------	----------------------------

Cargo aircraft only	Allowed with restrictions.
----------------------------	----------------------------

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not applicable.

Environmental hazards**Marine pollutant**

Yes

EmS


F-D, S-U

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.

**Transport in bulk according to
Annex II of MARPOL 73/78 and
the IBC Code**

Not applicable.

IATA; IMDG; TDG**Marine pollutant****General information**

IMDG Regulated Marine Pollutant.

15. Regulatory information**Canadian regulations****Controlled Drugs and Substances Act**

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Toluene (CAS 108-88-3)

Class B

International regulations**Stockholm Convention**

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories**Country(s) or region**

Australia

Inventory name

Australian Inventory of Chemical Substances (AICS)

On inventory (yes/no)*

Yes

Canada

Domestic Substances List (DSL)

Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information

Issue date	06-22-2016
Revision date	03-27-2017
Version #	02
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision information	Product and Company Identification: Alternate Trade Names