

Version number: 1

Revision number: 1

Replaces SDS: 2009-11-23

Issued: 2014-10-14

Not for sale in the USA

Section 1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1 Product identifier

Trade name BOC Mild Steel MIG Wire, MagMATE Mild Steel Mig Wire, ProFill 70S2 TIG Rod, ProFill Mild Steel TIG Rod

Article-no

Product/Article	Diameter(mm)	Packaging (kg)	Part Number
BOC Mild Steel MIG Wire	0.6	1	1061108
BOC Mild Steel MIG Wire	0.6	5	1061150
BOC Mild Steel MIG Wire	0.6	15	1061155
BOC Mild Steel MIG Wire	0.8	1	1081108
BOC Mild Steel MIG Wire	0.8	5	1081150
BOC Mild Steel MIG Wire	0.8	15	1081155
BOC Mild Steel MIG Wire	0.9	1	1091108
BOC Mild Steel MIG Wire	0.9	5	1091150
BOC Mild Steel MIG Wire	0.9	15	1091155
BOC Mild Steel MIG Wire	0.9	250	1091250
BOC Mild Steel MIG Wire	1.0	15	1101155
BOC Mild Steel MIG Wire	1.0	250	1101250
BOC Mild Steel MIG Wire	1.2	15	1121155
BOC Mild Steel MIG Wire	1.2	250	1121250
MagMATE Mild Steel Mig Wire	0.6	15	706B06-1
MagMATE Mild Steel Mig Wire	0.8	15	706B08-1
MagMATE Mild Steel Mig Wire	0.9	15	706B09-1
MagMATE Mild Steel Mig Wire	1.0	15	706B10-1
MagMATE Mild Steel Mig Wire	1.2	15	706B12-1
MagMATE Mild Steel Mig Wire	1.6	15	706B16-1
MagMATE Mild Steel Mig Wire	0.6	5	706B0506
MagMATE Mild Steel Mig Wire	0.8	5	706B0508
MagMATE Mild Steel Mig Wire	0.9	5	706B0509
MagMATE Mild Steel Mig Wire	0.9	250	706B09250
MagMATE Mild Steel Mig Wire	1.0	250	706B10250
MagMATE Mild Steel Mig Wire	1.2	250	706B12250
ProFill 70S2 TIG Rod	1.6	5	11605S2
ProFill 70S2 TIG Rod	2.4	5	12405S2
ProFill Mild Steel TIG Rod	1.6	5	11605S6
ProFill Mild Steel TIG Rod	2.4	5	12405S6

1.2 Relevant identified uses of the substance or mixture and uses advised against

Article type GMAW/GTAW Un-alloyed steel wire electrodes & Rods Classification: AWS SFA 5.18

Use Gas shielded Arc welding



Version number: 1

Revision number: 1

Replaces SDS: 2009-11-23

Issued: 2014-10-14

1.3 Details of the supplier of the safety data sheet

Supplier BOC Limited BOC Limited

Street address 10 Julius Avenue 970-988 Great South Road

North Ryde NSW 2113 Penrose, Auckland

Australia New Zealand

Telephone 131 262 0800 111 333

Fax 132 427 0800 229 923

Email <u>contact@boc.com</u> <u>customer.servicenz@boc.com</u>

1.4 Emergency telephone number

Available outside office hours Yes

Emergency phone number 1800 653 572 (Aus) or 0800 111 333 (NZ)

Other

Additional product information Web site: www.boc.com.au or www.boc.co.nz

Section 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

As shipped the product is:

Not Classified as Hazardous according to Australian, New Zealand and European regulations (refer Section 15 for references)

Not a Dangerous Good for Transport by road, rail, air or sea according to Australian, New Zealand, European, IMO, and IATA.

GHS Classification

Not Classified

2.3 Label Elements

Not Applicable

2.3 Other hazards

When the product is used in the welding process the most important hazards are:

Overexposure to fumes and gases from welding can be dangerous to health released from the welding process may release products that are classified as hazardous and can be dangerous to health. Refer to Section 16 for more information.

Watch out for splatter, hot metal and slag. It may cause skin burn and cause fire.

Arc rays can injure eyes and burn skin. Electric shock can kill. Avoid touching live electrical parts.

Section 3. COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substances



Version number: 1
Revision number: 1

Replaces SDS: 2009-11-23

Issued: 2014-10-14

3.2 Mixtur	es							
AWS Clas's	Fe %	C %	Mn %	Si %	Cu¹ %	Ti %	Zr %	AI %
CAS Number	7439-89-6	7440- 44-0	7439-96-5	7440-21-3	7440-50-8	7440- 32-6	7440- 67-7	7429-90-5
ER70S-2	>97	0.07	0.90 to 1.40	0.40 to 0.70	<0.5	0.05 to 0.15	0.02 to 0.12	0.05 to 0.15
ER70S-3	>97	0.06 to 0.15	0.90 to 1.40	0.45 to 0.70	<0.5			
ER70S-4	>97	0.07 to 0.15	1.00 to 1.50	0.65 to 0.85	<0.5			
ER70S-5	>97	0.07 to 0.19	0.90 to 1.40	0.30 to 0.60	<0.5			
ER70S-6	>96	0.07 to 0.15	1.40 to 1.85	0.80 to 1.15	<0.5			
ER70S-7	>96	0.07 to 0.15	1.50 to 2.00	0.50 to 0.80	<0.5			

Section 4. FIRST AND MEASURES

4.1 Description of first aid measures

Inhalation	IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms occur.
Skin contact	Burns should be treated by a doctor. Wash affected areas with running water/soap. Seek
	medical attention in event of irritation
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing. Burns from radiation, see doctor.
Ingestion	Contact a doctor if more than an insignificant amount has been swallowed.

4.2 Most important symptoms and effects, both acute and delayed

4.2 Most important symptoms and effects, both acute and delayed					
Inhalation	Welding can generate fumes, mists, dust, vapours and gases, including ozone. The				
	amounts and types of fumes produced vary greatly depending on the process involved and				
	the materials being used such as metals, solvents, flux, paint and plastics. The health				
	effects of exposure to fumes, dust, vapour and gases can vary. Effects can include irritation				
	of the upper respiratory tract (nose and throat), tightness in the chest, asphyxiation, asthma,				
	wheezing, metal fume fever, lung damage, bronchitis, cancer, pneumonia or emphysema.				



Version number: 1

Revision number: 1
Replaces SDS: 2009-11-23

Issued: 2014-10-14

4.3 Indication of any immediate medical attention and special treatment needed

Acute effects include irritation of the eyes, nose and throat, shortness of breath Some individuals may develop skin irritation.

Section 5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media Carbon dioxide (CO2), powder or diffuse jet of water. In case of major fire: Extinguish fire with diffuse jet of water or foam.

5.2 Special hazards arising from the substance or mixture

Avoid contact with strong acids or other substances which are corrosive to metals

5.3 Advice for fire fighters

Special protective equipment for Wear self contained breathing apparatus as in a fire welding rods may decompose on heating and produce hazardous decomposition products

Section 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

General ventilation and local fume extraction must be adequate to keep fume concentrations within safe limits. Use respiratory equipment when welding in a confined space. Wear protective clothing and eye protection appropriate to arc welding. Skin contact should be avoided to prevent possible allergic reactions.

6.2 Environmental precautions

Try to prevent the material from entering drains or water courses.

6.3 Methods and material for containment and cleaning up

Spills to be cleaned up immediately using dry clean up methods and avoid dust generation
Use appropriate PPE to prevent contact with skin
Ensure good hygiene practices following clean up

6.4 Reference to other sections

Personal protection see section 8 and for disposal see section 13. Environmental precautions, paragraph 12. See also section 7 Precautions for safe handling.



Version number: 1

Revision number: 1
Replaces SDS: 2009-11-23

Issued: 2014-10-14

Section 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Preventive handling precautions Ensure adequate ventilation for the welder and others. Use respiratory equipment when

welding in a confined space. Wear protective clothing and eye protection appropriate to arc

welding. Remove all flammable materials and liquids before welding.

General hygiene Wash hands before breaks and immediately after handling the product.

7.2 Conditions for safe storage, including any incompatibilities

Store welding consumables inside a room with low humidity. Do not store welding consumables directly on the ground or beside walls. Store away from chemical substances like acids which could cause chemical reactions.

7.3 Specific end use(s)

Welding process.

Section 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

Welding fume component	CAS No.	TWA ¹ (mg/m³)	STEL ¹ 15min TWA	Hazard Classification 67/548/EC	Hazard Classification (GHS) 1272/2008
Welding fumes (not otherwise classified)	-	5		R43	H351 Carc.2
Iron oxide fume (as Fe)	1309-37-1	5			
Manganese and its inorganic compounds (as Mn)	7439-96-5 and others	1	3	R20/R22	H332 Acute Tox.4
Copper Fume	7440-50-8	0.2			
Zinc oxide (fume)	1314-13-2	5	10		
Titanium dioxide (inspirable dust)	13463-67-7	10			
Silica, amorphous (Fume (thermally generated)(respirable dust) (g))	-	2			
Aluminium Inhalable Respirable dust	1344-28-1	10 4			
Zirconium compounds	7440-67-7	5	10		



Version number: 1
Revision number: 1

Replaces SDS: 2009-11-23

Issued: 2014-10-14

Nitrogen dioxide	10102-44-0	5.6	9.4	
Nitrogen monoxide	10102-43-9	31	0	
Ozone	10028-15-6	0,2 peak limitation		
Carbon dioxide	124-38-9	9000	54000	
Carbon monoxide	630-08-0	34		

Extracted from Safework Australia, Hazardous Substances Information System (HSIS) & Worksafe New Zealand Table of workplace exposure standards

8.2 Exposure controls

Environmental Exposure Controls - refer to Section 12 of this SDS

Technical precaution measures	General ventilation and local fume extraction must be adequate to keep fume
	concentrations within safe limits.

Eye / face protectionWorkers should always have their eyes, face and/or head protected whenever they are welding. For further information refer to: AS/NZS 1338: (series) Filters for eye protectors, AS/NZS 1338.1: Filters for eye protectors - Filters for protection against radiation

generated in welding and allied operations and AS/NZS 1336: Recommended practices for occupational eye protection and AS/NZS 1337: Eye protectors for industrial applications

Hand/Arm protection
Gloves should be fire resistant and protect exposed skin on the hands and wrists.
For further information refer to: AS/NZS 2161: (series) Occupational protective gloves.

Other skin protection Avoid clothing that has the potential to capture hot sparks and metals, for example in pockets or other folds. Clothing should be made of natural fibres.

For further information refer to: AS/NZS 4502: (series) Methods for evaluating clothing for protection against heat and fire. Foot protection should be non-slip and be heat and fire resistant. Avoid using foot protection that has the potential to capture hot sparks and metal debris, for example in laces or in open style shoes.

For further information refer to: AS/NZS 2210: (series) Occupational protective footwear and AS/NZS 2210.1: Safety, protective and occupational footwear - Guide to selection, care and use.

Respiratory protection

Respirators should be fitted for each person individually and if one is to be used by another operator, it must be disinfected and refitted before use. The tightness of all connections and the condition of the face piece, headbands and valves should be checked before each use. Air supplied respirators may be required in some situations, e.g. confined

For further information refer to: AS/NZS 1716: Respiratory protective devices and be selected in accordance with AS/NZS 1715: Selection, use and maintenance of respiratory protective equipment.

spaces.

6



Version number: 1

Revision number: 1

Replaces SDS: 2009-11-23 **Issued:** 2014-10-14

Section 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance, colour Generally grey or coppered coloured when coated

Appearance, physical state Metal wire or Rod

Auto-ignition temperature Not applicable

Auto-inflammability Not auto-flammable

Decomposition temperature Not applicable

Explosive properties Not applicable

Not explosive

Flammability (solid gas) Not applicable

Flash point Not applicable

Form Fast

Initial boiling point and boiling range Not applicable

Melting point / Freezing point Not applicable

Odour Odourless

Odour threshold Not applicable

Oxidising properties Not applicable

Partition coefficient: n-octanol / water Not applicable

pH value Not applicable

Relative density Not applicable

Solubility Not applicable

Solubility in water Insoluble

Upper / lower flammability or explosive Not applicable

limits

Vapour density Not applicable
Vapour pressure Not applicable
Viscosity Not applicable

9.2 Other information

Density 7.98g/cm³

Section 10. STABILITY AND REACTIVITY

10.1 Reactivity

Reactive with incompatible materials such as strong acids/corrosives



Version number: 1
Revision number: 1

Replaces SDS: 2009-11-23

Issued: 2014-10-14

10.2 Chemical stability

Stable at normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur

10.4 Conditions to avoid

None under normal conditions

10.5 Incompatible materials

Strong acids and metal corrosives

10.6 Hazardous decomposition products

Welding fumes and gases. Additional fume may arise from coatings and contaminants on the base material.

Welding fume component	CAS No.	Classification (67/548EEC)	CLP (1272/2	CLP (1272/2008)	
Aluminium oxide (Al)	1344-28-1	-	-	-	<0.1
Barium (Ba)	7440-39-3	-	-	-	<0.1
Bismuth oxide (Bi)	12640-40-3	-	-	-	<0.1
Calcium (Ca)	1305-78-8	-	-	-	<0.1 to 0.2
Cobalt oxide (Co)	1307-96-6	R22: Harmful if swallowed R43: May cause sensitisation by contact	Acute tox 4 (oral) Skin sens. 1	H302 H317	<0.1
Chromium III compounds (as Cr)	24613-89-6	R45: May cause cancer R35: Causes severe burns R43: May cause sensitisation by skin contact	Carc. 1B Skin Corr. 1A Skin Sens. 1	H350 H314 H317	<0.1
Copper oxide (Cu)	1317-38-0	-	-	-	0.3 to 1.1
Iron oxide (Fe)	1332-37-2	-	-	-	45.8 to 61.4
Potassium (K)	7440-09-7	R34: Causes burns	Skin Corr. 1B	H314	<0.1
Lithium (Li)	7439-93-2	R34: Causes burns	Skin Corr. 1B	H314	<0.1
Magnesium oxide (Mg)	1309-48-4	-	-	-	<0.1
Manganese (Mn)	7439-96-5	-	-	-	6.3 to 15.0



Version number: 1

Revision number: 1

Replaces SDS: 2009-11-23

Issued: 2014-10-14

Molybdenum (Mo)	7439-98-7	Molybdenum trioxide R36/37: Irritating to eyes and respiratory system R40: Limited evidence of carcinogenic effect	Molybdenum trioxide Carc. 2 Eye Irrit. 2 STOT SE 3	H351 H319 H335	<0.1
Sodium (Na)	7440-23-5	R34: Causes burns	Skin Corr. 1B	H314	<0.1
Nickel (Ni)	7440-02-0	R40: Limited evidence of carcinogenic effect R43: May cause sensitisation by skin contact R48/23: Toxic danger of serious damage to health by prolonged exposure through inhalation R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment	Carc. 2 Skin sens 1 STOT RE 1	H351 H317 H372	<0.1
Lead (Pb)	7439-92-1	-	-	-	<0.1
Silicon (Si)	7440-21-3	-	-	-	1.3 to 4.8
Titanium dioxide (Ti)	13463-67-7	-	-	-	<0.1
Vanadium (V)	7440-62-2	-	-	-	<0.1
Zinc (Zn)	7440-66-6	-	-	-	<0.1 to 0.7

The classification information above is related to the fume during use.

Approximate Fume analysis (electrode & clean base material):

Component	wt%
Calcium	0.1 to 0.2
Iron	45.8 t0 61.4
Manganese	6.3 to 15
Silicon	1.3 to 4.8
Zinc	0.1 to 0.7



Version number: 1

Revision number: 1

Replaces SDS: 2009-11-23

Issued: 2014-10-14

Section 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Conditions to avoid: none in the form supplied

When welding, fumes and gases generated can be dangerous to health.

Acute toxicology Welding operations may evolve fumes that may be irritating to the respiratory tract and harmful

if inhaled . Aspiration may cause pulmonary oedema and pneumonitis Short-term overexposure can cause dizziness, nausea and irritation of the nose, throat or eyes.

Irritation Manganese fumes – Eye (rabbit) 500 mg/24hr Mild

- Skin (rabbit) 500 mg/24 hr Mild

Corrosive effects Not available

Sensitisation May cause sensitisation by skin contact

Mutagenicity Not available

Carcinogenicity Welding fumes are possibly carcinogenic to humans and have been classified by the IARC as

Group 2B: Possibly Carcinogenic to Humans

Repeated dose toxicity Not available
Reproductive toxicity Not available

Section 12. ECOLOGICAL INFORMATION

12.1 Toxicity

The welding process can effect the environment if fume is released directly into the atmosphere. Residues from welding consumables could degrade and accumulate into soils and ground water.

12.2 Persistence and degradability

Not available

12.3 Bio accumulative potential

Not available

12.4 Mobility in Soil

Not available

12.5 Results of PBT and vPvB assessment

Not available



Version number: 1

Revision number: 1
Replaces SDS: 2009-11-23

Issued: 2014-10-14

12.6 Other adverse effects

Not available

Section 13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Disposal considerations

Recycle packing materials. Dispose of any product, residue or packing material according to national and local regulations. Spent ;fume extraction filters shall be disposed of as hazardous waste.



Version number: 1

Revision number: 1

Replaces SDS: 2009-11-23

Issued: 2014-10-14

Section 14. TRANSPORT INFORMATION

14.1 UN number

Not applicable

14.2 UN proper shipping name

Not applicable

14.3 Transport hazard class(es)

Not applicable

14.4 Packing group

Not applicable

14.5 Environmental hazards

Not applicable

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Other

Dangerous goods Not classified as a dangerous good for transport by air, land, or sea

Section 15. REGUATORY INFORMATION

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture.

EU reguations Dangerous Goods Regulations/2014 (IATA)

International Maritime Dangerous Goods/2012 (IMO)

Regulation (EC) No 1271/2008 [CLP]

Dangerous Substances Directive (67/548/EEC)

National regulations Model Work and Safety Regulations 2014 (Safework Australia)

Hazardous Substances [Classification] Regulations 2001 [New Zealand]

Australian Code for the transport of Dangerous Goods by Road and Rail Volume 7/2011

(NTC)



Version number: 1

Revision number: 1

Replaces SDS: 2009-11-23

Issued: 2014-10-14

Land Transport Rule 45001/1 (New Zealand)

Local laws and regulations should be carefully observed.

15.2 Chemical safety assessment

Not applicable

Section 16. OTHER INFORMATION

References to key literature and Regulation (EC) No 1907/2006 of the European Parliament and of the Council, (REACH).

data sources Regulation (EC) No 1272/2008 of the European Parliament and of the Council.

Safework Australia: Hazardous Substances Information System (HSIS)

Worksafe New Zealand: Table of workplace exposure standards

Annex VI CLP Regulation (EC) 1272/2008

Safework Australia: Code of Practice: Welding Processes/2012

Other

Manufacturer's notes Read this Safety Data Sheet carefully and become aware of hazards implied and the safety

information

Details of Hazards relating to As a result of intended normal use, decomposition products that are classified as Hazardous

fumes may be released.

GHS Classification Acute Toxicity – Inhalation (Hazard Category 4)

Sensitisation – Skin (Hazard Category 1)

Carcinogenicity (Hazard Category 2)

Hazard statement(s) H317 - May cause an allergic skin reaction

H332 - Harmful if inhaled

H351 - Suspected of causing cancer

Precautionary statements (s):

<u>Prevention</u>
P261 -Avoid breathing dust/fume/gas/mist/ vapours/spray

P271 - Use only outdoors or in a well-ventilated area.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P280 - Wear protective gloves

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P281 - Use personal protective equipment as required.

Response

P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P311 - Call a POISON CENTER or doctor/physician.

P312 - Call a POISON CENTER or doctor/physician if you feel unwell.

P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention.

P308 + P313 - IF exposed or concerned: Get medical advice/attention.

P302 + P352 -IF ON SKIN: Wash with plenty of soap and water.

P321 - Specific treatment (refer label)

P363 - Wash contaminated clothing before reuse.



Version number: 1

Revision number: 1

Replaces SDS: 2009-11-23

Issued: 2014-10-14

Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

Disposal

P501 - Dispose of contents/container in accordance with local, state and national regulations.

End of Document