

SAFETY DATA SHEET

Product Trade Name: BaraECD 4.2 Liquid Mud

Revision Date: 09-Jun-2015

Revision Number: 4

1. Identification

1.1. Product Identifier

Product Trade Name: BaraECD 4.2 Liquid Mud
Synonyms: None
Chemical Family: Blend
Internal ID Code HM008071

1.2 Recommended use and restrictions on use

Application: Mud System
Uses Advised Against No information available

1.3 Manufacturer's Name and Contact Details

Manufacturer/Supplier Baroid Fluid Services
Product Service Line of Halliburton
P.O. Box 1675
Houston, TX 77251
Telephone: (281) 871-4000
Emergency Telephone: (281) 575-5000

Prepared By Chemical Stewardship
Telephone: 1-580-251-4335
e-mail: fdunexchem@halliburton.com

1.4. Emergency telephone number

Emergency Telephone Number (281) 575-5000

2. Hazard(s) Identification

2.1 Classification in accordance with paragraph (d) of §1910.1200

2.2. Label Elements

Hazard Pictograms



Signal Word

Danger

Hazard Statements	H317 - May cause an allergic skin reaction H350 - May cause cancer by inhalation H372 - Causes damage to organs through prolonged or repeated exposure if inhaled
--------------------------	---

Precautionary Statements

Prevention	P201 - Obtain special instructions before use P260 - Do not breathe dust/fume/gas/mist/vapors/spray P270 - Do not eat, drink or smoke when using this product P272 - Contaminated work clothing should not be allowed out of the workplace
Response	P302 + P352 - IF ON SKIN: Wash with plenty of soap and water P308 + P313 - IF exposed or concerned: Get medical advice/attention P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention
Storage	None
Disposal	P501 - Dispose of contents/container to an approved incineration plant

Contains

Substances

Fatty acid, tall-oil, reaction product with diethylenetriamine, maleic anhydride, tetraethylenepentamine, and triethylenetetramine
Crystalline silica, quartz

CAS Number

68990-47-6

14808-60-7

2.3 Hazards not otherwise classified

None known

3. Composition/information on Ingredients

Substances	CAS Number	PERCENT (w/w)	GHS Classification - US
Fatty acid, tall-oil, reaction product with diethylenetriamine, maleic anhydride, tetraethylenepentamine, and triethylenetetramine	68990-47-6	1 - 5%	Skin Sens. 1 (H317)
Crystalline silica, quartz	14808-60-7	0.1 - 1%	Carc. 1A (H350) STOT RE 1 (H372)

The exact percentage (concentration) of the composition has been withheld as proprietary. The specific chemical identity of the composition has been withheld as proprietary.

4. First-Aid Measures

4.1. Description of first aid measures

Inhalation	If inhaled, move victim to fresh air and seek medical attention.
Eyes	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.
Skin	Wash with soap and water. Get medical attention if irritation persists. Remove contaminated clothing and launder before reuse.
Ingestion	Get medical attention! If vomiting occurs, keep head lower than hips to prevent aspiration.

4.2 Most important symptoms/effects, acute and delayed

No information available

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically.

5. Fire-fighting measures**5.1. Extinguishing media****Suitable Extinguishing Media**

Water fog, carbon dioxide, foam, dry chemical.

Extinguishing media which must not be used for safety reasons

None known.

5.2 Specific hazards arising from the substance or mixture**Special Exposure Hazards**

Use water spray to cool fire exposed surfaces. Closed containers may explode in fire. Decomposition in fire may produce toxic gases.

5.3 Special protective equipment and precautions for fire-fighters**Special Protective Equipment for Fire-Fighters**

Full protective clothing and approved self-contained breathing apparatus required for fire fighting personnel.

6. Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Use appropriate protective equipment. Wear self-contained breathing apparatus in enclosed areas.

See Section 8 for additional information

6.2. Environmental precautions

Prevent from entering sewers, waterways, or low areas.

6.3. Methods and material for containment and cleaning up

Isolate spill and stop leak where safe. Remove ignition sources and work with non-sparking tools. Contain spill with sand or other inert materials. Scoop up and remove.

7. Handling and storage**7.1. Precautions for Safe Handling****Handling Precautions**

Avoid contact with eyes, skin, or clothing. Avoid breathing vapors. Avoid breathing mist. Wash hands after use. Launder contaminated clothing before reuse. This product contains quartz, cristobalite, and/or tridymite which may become airborne without a visible cloud if this product becomes dry. Avoid breathing or creating dust. Use only with adequate ventilation to keep exposures below recommended exposure limits. Wear a NIOSH certified, European Standard EN 149, or equivalent respirator when using dried product. Material is slippery underfoot.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities**Storage Information**

Store away from oxidizers. Keep from heat, sparks, and open flames. Keep container closed when not in use. Product has a shelf life of 48 months.

8. Exposure Controls/Personal Protection

8.1 Occupational Exposure Limits

Substances	CAS Number	OSHA PEL-TWA	ACGIH TLV-TWA
Fatty acid, tall-oil, reaction product with diethylenetriamine, maleic anhydride, tetraethylenepentamine, and triethylenetetramine	68990-47-6	Not applicable	Not applicable
Crystalline silica, quartz	14808-60-7	TWA: 10 mg/m ³ %SiO ₂ + 2	TWA: 0.025 mg/m ³

8.2 Appropriate engineering controls**Engineering Controls**

Use approved industrial ventilation and local exhaust as required to maintain exposures below applicable exposure limits.

8.3 Individual protection measures, such as personal protective equipment**Personal Protective Equipment**

If engineering controls and work practices cannot prevent excessive exposures, the selection and proper use of personal protective equipment should be determined by an industrial hygienist or other qualified professional based on the specific application of this product.

Respiratory Protection

If engineering controls and work practices cannot keep exposure below occupational exposure limits or if exposure is unknown, wear a NIOSH certified, European Standard EN 149, AS/NZS 1715:2009, or equivalent respirator when using this product. Selection of and instruction on using all personal protective equipment, including respirators, should be performed by an Industrial Hygienist or other qualified professional.

Hand Protection

Impervious rubber gloves.

Skin Protection

Rubber apron.

Eye Protection

Chemical goggles; also wear a face shield if splashing hazard exists.

Other Precautions

Eyewash fountains and safety showers must be easily accessible.

9. Physical and Chemical Properties**9.1. Information on basic physical and chemical properties**

Physical State: Liquid

Color:

Light to dark yellow

Odor: Hydrocarbon

Odor

No information available

Threshold:

Property

Values

Remarks/ - Method

pH:

No data available

Freezing Point/Range

No data available

Melting Point/Range

No data available

Boiling Point/Range

148 °C / 300 °F

Flash Point

~ 137 °C / 279 °F PMCC

Flammability (solid, gas)

No data available

upper flammability limit

6

lower flammability limit

0.7

Evaporation rate

No data available

Vapor Pressure

No data available

Vapor Density

No data available

Specific Gravity

1.44

Water Solubility

Insoluble in water

Solubility in other solvents

No data available

Partition coefficient: n-octanol/water

No data available

Autoignition Temperature

257 °C / 495 °F

Decomposition Temperature	No data available
Viscosity	No data available
Explosive Properties	No information available
Oxidizing Properties	No information available

9.2. Other information

VOC Content (%)	No data available
------------------------	-------------------

10. Stability and Reactivity**10.1. Reactivity**

Not expected to be reactive.

10.2. Chemical Stability

Stable

10.3. Possibility of Hazardous Reactions

Will Not Occur

10.4. Conditions to Avoid

Keep away from heat, sparks and flame.

10.5. Incompatible Materials

Strong oxidizers.

10.6. Hazardous Decomposition Products

Oxides of nitrogen. Carbon monoxide and carbon dioxide.

11. Toxicological Information**11.1 Information on likely routes of exposure**

Principle Route of Exposure Eye or skin contact, inhalation.

11.2 Symptoms related to the physical, chemical and toxicological characteristics**Acute Toxicity****Inhalation**

Inhaled crystalline silica in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC, Group 1). There is sufficient evidence in experimental animals for the carcinogenicity of tridymite (IARC, Group 2A).

Breathing silica dust may cause irritation of the nose, throat, and respiratory passages. Breathing silica dust may not cause noticeable injury or illness even though permanent lung damage may be occurring. Inhalation of dust may also have serious chronic health effects (See "Chronic Effects/Carcinogenicity" subsection below).

Eye Contact

May cause eye irritation.

Skin Contact

May cause skin irritation. May cause an allergic skin reaction.

Ingestion

Aspiration into the lungs may cause chemical pneumonitis including coughing, difficulty breathing, wheezing, coughing up blood and pneumonia, which can be fatal.

Chronic Effects/Carcinogenicity Silicosis: Excessive inhalation of respirable crystalline silica dust may cause a progressive, disabling, and sometimes-fatal lung disease called silicosis. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness, and reduced pulmonary function. This disease is exacerbated by smoking. Individuals with silicosis are predisposed to develop tuberculosis.

Cancer Status: The International Agency for Research on Cancer (IARC) has determined that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources can cause lung cancer in humans (Group 1 - carcinogenic to humans) and has determined that there is sufficient evidence in experimental animals for the carcinogenicity of tridymite (Group 2A - possible carcinogen to humans). Refer to IARC Monograph 68, Silica, Some Silicates and Organic Fibres (June 1997) in conjunction with the use of these minerals. The National Toxicology Program classifies respirable crystalline silica as "Known to be a human carcinogen". Refer to the 9th Report on Carcinogens (2000). The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica, quartz, as a suspected human carcinogen (A2).

There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of significant disease endpoints such as scleroderma (an immune system disorder manifested by scarring of the lungs, skin, and other internal organs) and kidney disease.

11.3 Toxicity data

Toxicology data for the components

Substances	CAS Number	LD50 Oral	LD50 Dermal	LC50 Inhalation
Fatty acid, tall-oil, reaction product with diethylenetriamine, maleic anhydride, tetraethylenepentamine, and triethylenetetramine	68990-47-6	> 2020 mg/kg (Rat)	> 2000 mg/kg (Rat)	No data available
Crystalline silica, quartz	14808-60-7	>15,000 mg/kg (Human)	No data available	No data available

Substances	CAS Number	Skin corrosion/irritation
Fatty acid, tall-oil, reaction product with diethylenetriamine, maleic anhydride, tetraethylenepentamine, and triethylenetetramine	68990-47-6	Non-irritating to the skin
Crystalline silica, quartz	14808-60-7	Non-irritating to the skin

Substances	CAS Number	Eye damage/irritation
Fatty acid, tall-oil, reaction product with diethylenetriamine, maleic anhydride, tetraethylenepentamine, and triethylenetetramine	68990-47-6	Non-irritating to the eye
Crystalline silica, quartz	14808-60-7	Mechanical irritation of the eyes is possible.

Substances	CAS Number	Skin Sensitization
------------	------------	--------------------

Fatty acid, tall-oil, reaction product with diethylenetriamine, maleic anhydride, tetraethylenepentamine, and triethylenetetramine	68990-47-6	Skin sensitizer in guinea pig.
Crystalline silica, quartz	14808-60-7	No information available.

Substances	CAS Number	Respiratory Sensitization
Fatty acid, tall-oil, reaction product with diethylenetriamine, maleic anhydride, tetraethylenepentamine, and triethylenetetramine	68990-47-6	No information available
Crystalline silica, quartz	14808-60-7	No information available

Substances	CAS Number	Mutagenic Effects
Fatty acid, tall-oil, reaction product with diethylenetriamine, maleic anhydride, tetraethylenepentamine, and triethylenetetramine	68990-47-6	In vivo tests did not show mutagenic effects.
Crystalline silica, quartz	14808-60-7	Not regarded as mutagenic.

Substances	CAS Number	Carcinogenic Effects
Fatty acid, tall-oil, reaction product with diethylenetriamine, maleic anhydride, tetraethylenepentamine, and triethylenetetramine	68990-47-6	No information available.
Crystalline silica, quartz	14808-60-7	Contains crystalline silica which may cause silicosis, a delayed and progressive lung disease. The IARC and NTP have determined there is sufficient evidence in humans of the carcinogenicity of crystalline silica with repeated respiratory exposure. Based on available scientific evidence, this substance is a threshold carcinogen with a mode of action involving indirect genotoxicity secondary to lung injury.

Substances	CAS Number	Reproductive toxicity
Fatty acid, tall-oil, reaction product with diethylenetriamine, maleic anhydride, tetraethylenepentamine, and triethylenetetramine	68990-47-6	Animal testing did not show any effects on fertility.
Crystalline silica, quartz	14808-60-7	No information available

Substances	CAS Number	STOT - single exposure
Fatty acid, tall-oil, reaction product with diethylenetriamine, maleic anhydride, tetraethylenepentamine, and triethylenetetramine	68990-47-6	No information available
Crystalline silica, quartz	14808-60-7	No significant toxicity observed in animal studies at concentration requiring classification.

Substances	CAS Number	STOT - repeated exposure
Fatty acid, tall-oil, reaction product with diethylenetriamine, maleic anhydride, tetraethylenepentamine, and triethylenetetramine	68990-47-6	No data of sufficient quality are available.
Crystalline silica, quartz	14808-60-7	Causes damage to organs through prolonged or repeated exposure if inhaled: (Lungs)

Substances	CAS Number	Aspiration hazard
Fatty acid, tall-oil, reaction product with diethylenetriamine, maleic anhydride, tetraethylenepentamine, and triethylenetetramine	68990-47-6	Not applicable
Crystalline silica, quartz	14808-60-7	Not applicable

12. Ecological Information

12.1. Toxicity

Ecotoxicity Effects

Product Ecotoxicity Data

No data available

Substance Ecotoxicity Data

Substances	CAS Number	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Toxicity to Invertebrates
Fatty acid, tall-oil, reaction product with diethylenetriamine, maleic anhydride, tetraethylenepentamine, and triethylenetetramine	68990-47-6	EC50 (72h) > 100 mg/L (growth rate) (Pseudokirchnerella subcapitata)	LC50 (96h) > 100 mg/L (Danio rerio)	EC50 (3h) > 100 mg/L (Activated sludge) (respiration rate)	IC50 (48h) > 100 mg/L (Daphnia magna)
Crystalline silica, quartz	14808-60-7	No information available	LL0 (96h) 10,000 mg/L (Danio rerio) (similar substance)	No information available	LL50 (24h) > 10,000 mg/L (Daphnia magna) (similar substance)

12.2. Persistence and degradability

Substances	CAS Number	Persistence and Degradability
Fatty acid, tall-oil, reaction product with diethylenetriamine, maleic anhydride, tetraethylenepentamine, and triethylenetetramine	68990-47-6	Readily biodegradable (71% @ 28d)
Crystalline silica, quartz	14808-60-7	No information available

12.3. Bioaccumulative potential

Substances	CAS Number	Log Pow
Fatty acid, tall-oil, reaction product with diethylenetriamine, maleic anhydride, tetraethylenepentamine, and triethylenetetramine	68990-47-6	2.4
Crystalline silica, quartz	14808-60-7	No information available

12.4. Mobility in soil

Substances	CAS Number	Mobility
Fatty acid, tall-oil, reaction product with diethylenetriamine, maleic anhydride, tetraethylenepentamine, and triethylenetetramine	68990-47-6	No information available
Crystalline silica, quartz	14808-60-7	No information available

12.5 Other adverse effects

No information available

13. Disposal Considerations

13.1. Waste treatment methods

Disposal Method	Disposal should be made in accordance with federal, state, and local regulations.
Contaminated Packaging	Follow all applicable national or local regulations.

14. Transport Information

US DOT

UN Number:	Not restricted
UN Proper Shipping Name:	Not restricted
Transport Hazard Class(es):	Not applicable
Packing Group:	Not applicable
Environmental Hazards:	Not applicable

US DOT Bulk

DOT (Bulk)	Not applicable
-------------------	----------------

Canadian TDG

UN Number:	Not restricted
UN Proper Shipping Name:	Not restricted
Transport Hazard Class(es):	Not applicable
Packing Group:	Not applicable
Environmental Hazards:	Not applicable

IMDG/IMO

UN Number:	Not restricted
UN Proper Shipping Name:	Not restricted
Transport Hazard Class(es):	Not applicable
Packing Group:	Not applicable
Environmental Hazards:	Not applicable

IATA/ICAO

UN Number:	Not restricted
UN Proper Shipping Name:	Not restricted
Transport Hazard Class(es):	Not applicable
Packing Group:	Not applicable
Environmental Hazards:	Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable

Special Precautions for User: None

15. Regulatory Information

US Regulations

US TSCA Inventory	All components listed on inventory or are exempt.
EPA SARA Title III Extremely Hazardous Substances	Not applicable
EPA SARA (311,312) Hazard Class	Acute Health Hazard Chronic Health Hazard

EPA SARA (313) Chemicals	This product does not contain a toxic chemical for routine annual "Toxic Chemical Release Reporting" under Section 313 (40 CFR 372).
EPA CERCLA/Superfund Reportable Spill Quantity	Not applicable.
EPA RCRA Hazardous Waste Classification	If product becomes a waste, it does NOT meet the criteria of a hazardous waste as defined by the US EPA.
California Proposition 65	The California Proposition 65 regulations apply to this product.
MA Right-to-Know Law	One or more components listed.
NJ Right-to-Know Law	One or more components listed.
PA Right-to-Know Law	One or more components listed.

Canadian Regulations

Canadian DSL Inventory	Product contains one or more components not listed on the inventory.
-------------------------------	--

16. Other information

Preparation Information

Prepared By

Chemical Stewardship
Telephone: 1-580-251-4335
e-mail: fdunexchem@halliburton.com

Revision Date: 09-Jun-2015

Reason for Revision Not applicable

Additional information

For additional information on the use of this product, contact your local Halliburton representative.

For questions about the Safety Data Sheet for this or other Halliburton products, contact Chemical Stewardship at 1-580-251-4335.

Key or legend to abbreviations and acronyms

bw – body weight
CAS – Chemical Abstracts Service
EC50 – Effective Concentration 50%
ErC50 – Effective Concentration growth rate 50%
LC50 – Lethal Concentration 50%
LD50 – Lethal Dose 50%
LL50 – Lethal Loading 50%
mg/kg – milligram/kilogram
mg/L – milligram/liter
NIOSH – National Institute for Occupational Safety and Health
NTP – National Toxicology Program
OEL – Occupational Exposure Limit
PEL – Permissible Exposure Limit
ppm – parts per million
STEL – Short Term Exposure Limit
TWA – Time-Weighted Average
UN – United Nations
h - hour
mg/m³ - milligram/cubic meter
mm - millimeter
mmHg - millimeter mercury
w/w - weight/weight
d - day

Key literature references and sources for data

www.ChemADVISOR.com/

Disclaimer Statement

This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

End of Safety Data Sheet