HALLIBURTON

SAFETY DATA SHEET

Product Trade Name: BaraShield™-664

Revision Date: 07-Oct-2014 Revision Number: 4

1. Identification

1.1. Product Identifier

Product Trade Name: BaraShield™-664

Synonyms: None
Chemical Family: Blend
Internal ID Code HM007834

1.2 Recommended use and restrictions on use

Application:Loss Circulation MaterialUses Advised AgainstNo information available

1.3 Manufacturer's Name and Contact Details

Manufacturer/Supplier Baroid Fluid Services

Product Service Line of Halliburton

P.O. Box 1675 Houston, TX 77251

Telephone: (281) 871-4000

Emergency Telephone: (281) 575-5000

Prepared By Chemical Stewardship

Telephone: 1-580-251-4335

e-mail: fdunexchem@halliburton.com

1.4. Emergency telephone number

Emergency Telephone Number (281) 575-5000

2. Hazard(s) Identification

2.1 Classification in accordance with paragraph (d) of §1910.1200

Carcinogenicity Category 1A - H350

2.2. Label Elements

Hazard Pictograms



Signal Word Danger

Hazard Statements H350 - May cause cancer by inhalation

Precautionary Statements

Prevention P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood P280 - Wear protective gloves/protective clothing/eye protection/face protection

Response P308 + P313 - IF exposed or concerned: Get medical advice/attention

Storage P405 - Store locked up

Disposal P501 - Dispose of contents/container in accordance with

local/regional/national/international regulations

Contains

SubstancesCAS NumberCrystalline silica, quartz14808-60-7

2.3 Hazards not otherwise classified

None known

3. Composition/information on Ingredients

Substances	CAS Number	PERCENT (w/w)	GHS Classification - US
Crystalline silica, quartz	14808-60-7	0.1 - 1%	Carc. 1A (H350)
			STOT RE 1 (H372)

The exact percentage (concentration) of the composition has been withheld as proprietary.

4. First-Aid Measures

4.1. Description of first aid measures

Inhalation If inhaled, remove from area to fresh air. Get medical attention if respiratory

irritation develops or if breathing becomes difficult.

Eyes Immediately flush eyes with large amounts of water for at least 15 minutes. Get

immediate medical attention.

Skin Wash with soap and water. Get medical attention if irritation persists.

Ingestion Under normal conditions, first aid procedures are not required.

4.2 Most important symptoms/effects, acute and delayed

Breathing crystalline silica can cause lung disease, including silicosis and lung cancer. Crystalline silica has also been associated with scleroderma and kidney disease.

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. Fire-fighting measures

5.1. Extinguishing media

Suitable Extinguishing Media

All standard fire fighting media

Extinguishing media which must not be used for safety reasons

None known.

5.2 Specific hazards arising from the substance or mixture

Special Exposure Hazards

Not applicable.

5.3 Special protective equipment and precautions for fire-fighters

Special Protective Equipment for Fire-Fighters

Not applicable.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Use appropriate protective equipment. Avoid creating and breathing dust.

See Section 8 for additional information

6.2. Environmental precautions

None known.

6.3. Methods and material for containment and cleaning up

Collect using dustless method and hold for appropriate disposal. Consider possible toxic or fire hazards associated with contaminating substances and use appropriate methods for collection, storage and disposal.

7. Handling and storage

7.1. Precautions for Safe Handling

Handling Precautions

This product contains quartz, cristobalite, and/or tridymite which may become airborne without a visible cloud. Avoid breathing dust. Avoid creating dusty conditions. Use only with adequate ventilation to keep exposure below recommended exposure limits. Wear a NIOSH certified, European Standard En 149, or equivalent respirator when using this product. Material is slippery when wet. Avoid contact with eyes, skin, or clothing.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

7.2. Conditions for safe storage, including any incompatibilities

Storage Information

Store away from acids. Store in a cool, dry location. Use good housekeeping in storage and work areas to prevent accumulation of dust. Close container when not in use. Do not reuse empty container. Product has a shelf life of 36 months.

8. Exposure Controls/Personal Protection

8.1 Occupational Exposure Limits

Substances	CAS Number	OSHA PEL-TWA	ACGIH TLV-TWA
Crystalline silica, quartz		TWA: 10 mg/m³ %SiO2 + 2	TWA: 0.025 mg/m ³

8.2 Appropriate engineering controls

Engineering ControlsUse approved industrial ventilation and local exhaust as required to maintain

exposures below applicable exposure limits.

8.3 Individual protection measures, such as personal protective equipment

Personal Protective Equipment If engineering controls and work practices cannot prevent excessive exposures,

the selection and proper use of personal protective equipment should be

determined by an industrial hygienist or other qualified professional based on the

specific application of this product.

Respiratory Protection Wear a NIOSH certified, European Standard EN 149 (FFP2/FFP3), AS/NZS 1715,

or equivalent respirator when using this product.

Hand Protection Normal work gloves.

Skin Protection Wear clothing appropriate for the work environment. Dusty clothing should be

laundered before reuse. Use precautionary measures to avoid creating dust when

removing or laundering clothing.

Eye Protection Wear safety glasses or goggles to protect against exposure.

Other Precautions None known.

9. Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Physical State: Granules Color: Gray

Odor: Slight Odor No information available

Threshold:

<u>Property</u> <u>Values</u>

Remarks/ - Method

pH: 7

Freezing Point/Range No data available **Melting Point/Range** No data available **Boiling Point/Range** No data available **Flash Point** No data available No data available Flammability (solid, gas) upper flammability limit No data available lower flammability limit No data available **Evaporation rate** No data available **Vapor Pressure** No data available **Vapor Density** No data available

Specific Gravity 1.6 - 2.0

Water Solubility
Solubility in other solvents
Partition coefficient: n-octanol/water
Autoignition Temperature
Decomposition Temperature
Viscosity
Insoluble in water
No data available
No data available
No data available
No data available

Explosive PropertiesNo information available **Oxidizing Properties**No information available

9.2. Other information

VOC Content (%) No data available

10. Stability and Reactivity

10.1. Reactivity

Not expected to be reactive.

10.2. Chemical Stability

Stable

10.3. Possibility of Hazardous Reactions

Will Not Occur

10.4. Conditions to Avoid

None anticipated

10.5. Incompatible Materials

Strong acids.

10.6. Hazardous Decomposition Products

Amorphous silica may transform at elevated temperatures to tridymite (870 C) or cristobalite (1470 C). Carbon monoxide and carbon dioxide.

11. Toxicological Information

11.1 Information on likely routes of exposure

Principle Route of Exposure Eye or skin contact, inhalation.

11.2 Symptoms related to the physical, chemical and toxicological characteristics

Acute Toxicity Inhalation

Inhaled crystalline silica in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (IARC, Group 1). There is sufficient evidence in experimental animals for the carcinogenicity of tridymite (IARC, Group 2A).

Breathing silica dust may cause irritation of the nose, throat, and respiratory passages. Breathing silica dust may not cause noticeable injury or illness even though permanent lung damage may be occurring. Inhalation of dust may also have serious chronic health effects (See "Chronic Effects/Carcinogenicity" subsection below).

Eye Contact Skin Contact Ingestion

May cause mechanical irritation to eye. May cause mechanical skin irritation. None known.

Chronic Effects/Carcinogenicity Silicosis: Excessive inhalation of respirable crystalline silica dust may cause a progressive, disabling, and sometimes-fatal lung disease called silicosis. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness, and reduced pulmonary function. This disease is exacerbated by smoking. Individuals with silicosis are predisposed to develop tuberculosis.

> Cancer Status: The International Agency for Research on Cancer (IARC) has determined that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources can cause lung cancer in humans (Group 1 - carcinogenic to humans) and has determined that there is sufficient evidence in experimental animals for the carcinogenicity of tridymite (Group 2A - possible carcinogen to humans). Refer to IARC Monograph 68, Silica, Some Silicates and Organic Fibres (June 1997) in conjunction with the use of these minerals. The National Toxicology Program classifies respirable crystalline silica as "Known to be a human carcinogen". Refer to the 9th Report on Carcinogens (2000). The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica, quartz, as a suspected human carcinogen (A2).

> There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of significant disease endpoints such as scleroderma (an immune system disorder manifested by scarring of the lungs, skin, and other internal organs) and kidney disease.

11.3 Toxicity data

Toxicology data for the components

Substances	CAS Number	LD50 Oral	LD50 Dermal	LC50 Inhalation
Crystalline silica, quartz	14808-60-7	>15,000 mg/kg (Human)	No data available	No data available

Substances	CAS Number	Skin corrosion/irritation
Crystalline silica, quartz	14808-60-7	Non-irritating to the skin

Substances	CAS Number Eye damage/irritation

Crystalline silica, quartz	14808-60-7	Mechanical irritation of the eyes is possible.
Substances	CAS Number	Skin Sensitization
Crystalline silica, quartz	14808-60-7	No information available.
Substances	CAS Number	Respiratory Sensitization
Crystalline silica, quartz	14808-60-7	No information available
Substances	CAS Number	Mutagenic Effects
Crystalline silica, quartz	14808-60-7	Not regarded as mutagenic.
Substances	CAS Number	Carcinogenic Effects
Crystalline silica, quartz	14808-60-7	Contains crystalline silica which may cause silicosis, a delayed and progressive lung disease. The IARC and NTP have determined there is sufficient evidence in humans of the carcinogenicity of crystalline silica with repeated respiratory exposure. Based on available scientific evidence, this substance is a threshold carcinogen with a mode of action involving indirect genotoxicity secondary to lung injury.
Substances	CAS Number	Reproductive toxicity
Crystalline silica, quartz	14808-60-7	No information available
Substances	CAS Number	STOT - single exposure
Crystalline silica, quartz	14808-60-7	No significant toxicity observed in animal studies at concentration requiring classification.
Substances	CAS Number	STOT - repeated exposure
Crystalline silica, quartz	14808-60-7	Causes damage to organs through prolonged or repeated exposure if inhaled: (Lungs)
Substances		Aspiration hazard
Crystalline silica, quartz	14808-60-7	Not applicable

12. Ecological Information

12.1. Toxicity **Ecotoxicity Effects**

Product Ecotoxicity Data

No data available

Substance Ecotoxicity Data

Substances	CAS Number	Toxicity to Algae	Toxicity to Fish	Toxicity to	Toxicity to Invertebrates
				Microorganisms	
Crystalline silica, quartz	14808-60-7	No information available	LL0 (96h) 10,000 mg/L (Danio rerio) (similar substance)		LL50 (24h) > 10,000 mg/L (Daphnia magna) (similar substance)

12.2. Persistence and degradability
The methods for determining biodegradability are not applicable to inorganic substances.

Substances	CAS Number	Persistence and Degradability
Crystalline silica, quartz	14808-60-7	No information available

12.3. Bioaccumulative potential

Substances	CAS Number	Log Pow
Crystalline silica, quartz	14808-60-7	No information available

12.4. Mobility in soil

Substances	CAS Number	Mobility
Crystalline silica, quartz	14808-60-7	No information available

12.5 Other adverse effects

No information available

13. Disposal Considerations

13.1. Waste treatment methods

Disposal MethodBury in a licensed landfill according to federal, state, and local regulations.

Contaminated Packaging Follow all applicable national or local regulations.

14. Transport Information

US DOT

UN Number:
UN Proper Shipping Name:
Transport Hazard Class(es):
Packing Group:
Not applicable
Not applicable
Not applicable
Not applicable

US DOT Bulk

DOT (Bulk) Not applicable

Canadian TDG

UN Number:
UN Proper Shipping Name:
Transport Hazard Class(es):
Packing Group:
Not applicable
Not applicable
Not applicable
Not applicable

IMDG/IMO

UN Number:
UN Proper Shipping Name:
Transport Hazard Class(es):
Packing Group:
Not applicable
Not applicable
Not applicable
Not applicable

IATA/ICAO

UN Number:
UN Proper Shipping Name:
Transport Hazard Class(es):
Packing Group:
Not applicable
Not applicable
Not applicable
Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable

Special Precautions for User: None

15. Regulatory Information

US Regulations

US TSCA Inventory All components listed on inventory or are exempt.

EPA SARA Title III Extremely Hazardous Substances

El 71 O/11/71 Title III Extremely Tiazaraeae eabetarieee					
Substances	CAS Number	EPA SARA Title III Extremely Hazardous			
		Substances			
Crystalline silica, quartz	14808-60-7	Not applicable			

EPA SARA (311,312) Hazard Class

Acute Health Hazard Chronic Health Hazard

EPA SARA (313) Chemicals

Substances		Toxic Release Inventory (TRI) - Group I	Toxic Release Inventory (TRI) - Group II
Crystalline silica, quartz	14808-60-7	Not applicable	Not applicable

EPA CERCLA/Superfund Reportable Spill Quantity

Substances	ICAS Number	CERCLA RQ
Crystalline silica, quartz	14808-60-7	Not applicable

EPA RCRA Hazardous Waste Classification

If product becomes a waste, it does NOT meet the criteria of a hazardous waste as defined by the US EPA.

California Proposition 65 The California Proposition 65 regulations apply to this product.

MA Right-to-Know Law
One or more components listed.

NJ Right-to-Know Law
One or more components listed.

PA Right-to-Know Law One or more components listed.

Canadian Regulations

Canadian DSL Inventory All components listed on inventory or are exempt.

16. Other information

Preparation Information

Prepared By Chemical Stewardship

Telephone: 1-580-251-4335

e-mail: fdunexchem@halliburton.com

Revision Date: 07-Oct-2014

Reason for Revision SDS sections updated:

2

Additional information

For additional information on the use of this product, contact your local Halliburton representative.

For questions about the Safety Data Sheet for this or other Halliburton products, contact Chemical Stewardship at 1-580-251-4335.

Key or legend to abbreviations and acronyms

bw - body weight

CAS - Chemical Abstracts Service

EC50 – Effective Concentration 50%

ErC50 – Effective Concentration growth rate 50%

LC50 – Lethal Concentration 50%

LD50 - Lethal Dose 50%

LL50 - Lethal Loading 50%

mg/kg – milligram/kilogram

mg/L - milligram/liter

NIOSH - National Institute for Occupational Safety and Health

NTP – National Toxicology Program
OEL – Occupational Exposure Limit
PEL – Permissible Exposure Limit
ppm – parts per million
STEL – Short Term Exposure Limit
TWA – Time-Weighted Average
UN – United Nations
h - hour
mg/m³ - milligram/cubic meter
mm - millimeter
mmHg - millimeter mercury
w/w - weight/weight
d - day

Key literature references and sources for data

www.ChemADVISOR.com/

Disclaimer Statement

This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

End of Safety Data Sheet

Dama 0 / 0