

# Safety Data Sheet



## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Product Name:** PRO-SPEC FLEXI-SEAL SILICONE SEALANT  
BATHROOM & KITCHEN

**Recommended Use:** Silicone sealant for use on most common building materials.

**Supplier:** Selleys Australia, a division of DuluxGroup (Australia) Pty Ltd  
**ABN:** 67 000 049 427  
**Street Address:** 1 Gow Street,  
Padstow, NSW 2211  
Australia  
**Telephone Number:** +61 2 9781 8777  
**Facsimile:** +61 2 9781 8825  
**Emergency Telephone:** **1 800 033 111 (ALL HOURS)**

## 2. HAZARDS IDENTIFICATION

Based on available information, not classified as hazardous according to criteria of Safe Work Australia; NON-HAZARDOUS SUBSTANCE.

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

**Poisons Schedule:** None allocated.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Proportion	Risk Phrases
Distillates, petroleum, hydrotreated light	64742-47-8	10-<20%	R65
Methyltriacetoxy silane	4253-34-3	1-<3%	R14 R34
Ingredients determined not to be hazardous	-	to 100%	-

## 4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.

**Inhalation:**

Remove victim from area of exposure - avoid becoming a casualty. Seek medical advice if effects persist.

**Skin Contact:**

Wipe excess material from skin with a clean rag or paper towel (do NOT use solvent to clean skin). Remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice.

**Eye Contact:**

If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

**Ingestion:**

If swallowed, do NOT induce vomiting. Give a glass of water. Seek medical advice.

# Safety Data Sheet



## Medical attention and special treatment:

Treat symptomatically.

## 5. FIRE FIGHTING MEASURES

### Hazards from combustion products:

Combustible paste. On burning will emit toxic fumes, including those of acetic acid and oxides of carbon .

### Precautions for fire fighters and special protective equipment:

Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

### Suitable Extinguishing Media:

Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

## 6. ACCIDENTAL RELEASE MEASURES

### Emergency procedures:

If contamination of sewers or waterways has occurred advise local emergency services.

### Methods and materials for containment and clean up:

SMALL SPILLS: Wipe up with absorbent (clean rag or paper towels). Allow absorbent to dry before disposing with normal household garbage. Any residual material can be cleaned up with mineral turpentine or similar hydrocarbon solvent, or acetone based nail polish remover.

LARGE SPILLS: Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact. Avoid breathing in vapours. Work up wind or increase ventilation. Scrape up excess material before cure. Collect and seal in properly labelled containers or drums for disposal. Cured material can only be removed by cutting or abrasion.

## 7. HANDLING AND STORAGE

### Conditions for safe storage:

Store in a cool, dry, well ventilated place and out of direct sunlight. Keep containers closed when not in use - check regularly for leaks.

### Precautions for safe handling:

Keep out of reach of children. Avoid skin and eye contact and breathing in vapour.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Occupational Exposure Limits:** No value assigned for this specific material by the National Occupational Health and Safety Commission. However, Exposure Standard(s) for substance liberated during application and cure:

Acetic acid: 8hr TWA = 25 mg/m<sup>3</sup> (10 ppm), 15 min STEL = 37 mg/m<sup>3</sup> (15 ppm)

# Safety Data Sheet

**SELLEYS**

As published by the National Occupational Health and Safety Commission.

**TWA** - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

**STEL** (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight hour work day. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

## **Engineering controls:**

Use in well ventilated areas. Keep containers closed when not in use.

## **Personal Protective Equipment:**

The selection of PPE is dependant on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

Selleys Factory Safe Handling Code: Green



**MANUFACTURE, PACKAGING AND TRANSPORT:** Wear overalls, safety glasses and impervious gloves. Remove contact lenses before using sealant. Do not handle lenses until all sealant has been removed from fingertips, nails and cuticles. Always wash hands before smoking, eating, drinking or using the toilet. If risk of inhalation exists, wear organic vapour respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

**FOR CONSUMER USE:** Avoid contact with eyes and skin. No special personal protective equipment required. Wash hands after use.

## **9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Physical state:</b>	Paste
<b>Colour:</b>	White or Clear
<b>Odour:</b>	Acetic acid
<b>Solubility:</b>	Insoluble in water. Uncured material is soluble in organic solvents. No solvent known for cured sealant.
<b>Specific Gravity:</b>	0.992 @ 20°C
<b>Relative Vapour Density (air=1):</b>	Not available
<b>Vapour Pressure (20 °C):</b>	Not available
<b>Flash Point (°C):</b>	>100
<b>Flammability Limits (%):</b>	Not available
<b>Autoignition Temperature (°C):</b>	Not available
<b>% Volatile by Volume:</b>	Not available
<b>Solubility in water (g/L):</b>	Insoluble
<b>Melting Point/Range (°C):</b>	Not applicable
<b>Boiling Point/Range (°C):</b>	Not available

Product Name: PRO-SPEC FLEXI-SEAL SILICONE SEALANT

BATHROOM & KITCHEN

Substance No: 00000021339

Issued: 25/08/2011

Version: 2

# Safety Data Sheet



## 9. PHYSICAL AND CHEMICAL PROPERTIES

Decomposition Point (°C):	Not available
pH:	Not applicable
Viscosity:	Not available
Evaporation Rate:	Not available

## 10. STABILITY AND REACTIVITY

Chemical stability:	Stable under normal conditions of use.
Conditions to avoid:	Avoid contact with foodstuffs. Avoid exposure to moisture.
Incompatible materials:	Incompatible with oxidising agents.
Hazardous decomposition products:	Acetic acid. Oxides of carbon.
Hazardous reactions:	Reacts with water/moisture/humid air to form acetic acid.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Ingestion:	Swallowing may result in irritation to the mouth and throat. No adverse effects expected after swallowing cured (solvent free) sealant.
Eye contact:	May be an eye irritant.
Skin contact:	Contact with skin may result in irritation. Cured sealant (solvent free) is not expected to be a skin irritant.
Inhalation:	Breathing in vapour may produce respiratory irritation. Acetic acid is liberated during application and setting.
Long Term Effects:	No information available for the product.
Toxicological Data:	No LD50 data available for the product.

## 12. ECOLOGICAL INFORMATION

Ecotoxicity	Avoid contaminating waterways.
-------------	--------------------------------

## 13. DISPOSAL CONSIDERATIONS

Disposal methods:	Refer to Waste Management Authority. Normally suitable for disposal at approved land waste site.
-------------------	--

## 14. TRANSPORT INFORMATION

## 14. TRANSPORT INFORMATION

### Road and Rail Transport

Not classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; NON-DANGEROUS GOODS.

### Marine Transport

Not classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; NON-DANGEROUS GOODS.

### Air Transport

Not classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; NON-DANGEROUS GOODS.

## 15. REGULATORY INFORMATION

**Classification:** Based on available information, not classified as hazardous according to criteria of Safe Work Australia; NON-HAZARDOUS SUBSTANCE.

**Poisons Schedule:** None allocated.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

## 16. OTHER INFORMATION

For further copies of this sheet or other product information contact Selleys Customer Service.

Phone: 1300 555 205 (Australia wide)  
Fax: 1300 555 305 (Australia wide)  
Phone: 0800 735 539 (New Zealand)  
Fax: 0800 804 583 (New Zealand)

### Reason(s) for Issue:

5 Yearly Revised Primary SDS  
Alignment to HSNO requirements

This safety data sheet has been prepared by SDS Services.

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since DuluxGroup Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their DuluxGroup representative or DuluxGroup Limited at the contact details on page 1.

DuluxGroup Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.