## **Material Safety Data Sheet**

May be used to comply with OSHA's Hazard Communication Standard 29 CFR 1910.1200. Standard must be consulted for specific requirements U.S. Department of Labor

Occupation Safety and Health Administration

(Non-Mandatory Form)

Form Approved OMB No. 1218-0072

BEA-COOL SYN – H (160022)

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

	-			
Manufacture	ed For:			Emergency Telephone Number
Beaver R	esearch Com	pany		1-800-255-3924 (Chem-Tel)
Address (Number, Street, City, State, and ZIP Code)				Telephone Number For Information
3700 E. K	(ilgore Road,	Portage, MI 49002		269-382-0133
HMIS RATINGS:		Health:	0	Date Prepared
4=Severe	1=Slight	Flammability:	1	2/18/03
3=High	0=Minimal	Reactivity:	0	Signature of Preparer (optional)
2=Moderate	)	Special Protection:		

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical		ACGIH	Other Limits	%	
Identity; Common Name(s))	CAS No.	OSHA PEL	TLV	Recommended	(optional)
Triethanolamine	00102-71-6		N/E		10-20

Boiling Point	>212ºF	Specific Gravity (H2O =	1)	1.076
Vapor Pressure (mm Hg)	N/A °F	% Volatile by Volume		45-50 as water
Vapor Density (AIR = 1)	>1	Evaporation Rate (Butyl Acetate = 1)		<1
Solubility in Water		pH		
Complete				
Appearance and Odor				
Clear liquid, blue				
Section IV - Fire and Explosion	Hazard Data			
Flash Point (Method Used)		Flammable Limits	LEL	UEL
None		N/A		

Extinguishing Media

CO2, dry chemical, foam

Special Fire Fighting Procedures

The material as received will not support combustion, however its residues may. Therefore, precedures for an oil fire should be followed. Use self contained breathing apparatus. Use foam or dy chemical to extinguish fire. Water may be used ONLY to keep surrounding containers cool.

Unusual Fire and Explosion Hazards

Section V - Reactivity Data						
Stability	Unstable		Conditions to Avoid	Sources of ignition.		
	Stable	Х				
Incompatibility (Materials to Avoid)						
Strong oxidizing or reducing agents.						
Hazardous Decomposition or Byproducts						
Oxides of Carbon, Hydrogen and Nitrogen.						
Hazardous	May Occur		Conditions to			

Polymerization	Will Not Occur						
Section VI - Health Hazard Data							
Route(s) of Entry	: Inhala	ation?	Skin?	Ingestion?			
Health Hazards (	Acute and Chronic)						
term exposure on similar ma	<b>Skin</b> : Tests on similar materials indicate that no significant adverse health effects are expected to occur with short term exposure. <b>Eyes</b> : Tests on similar materials suggest that minimal irritation may occur on contact. <b>Ingestion</b> : Tests on similar materials indicate no significant adverse effects expected. Practically non-toxic. <b>Inhalation</b> : Test on similar materials indicate no acute effects are expected.						
Carcinogenicity:	NTP?		IARC Monographs?	OSHA Regulated?			
Signs and Sympt	Signs and Symptoms of Exposure						
Medical Condition	ns Generally Aggravated b	y Exposure					
Emergency and F	First Aid Procedure						
Eyes: Flush eyes immediately with water for at least 15 minutes or until irritation subsides. If irritation persists, consult a physician. Skin: Immediately remove soaked or contaminated cothing. Wash skin thoroughly with soap and water. Launder all contaminated clothing before reuse. If skin irritation or rash develops obtain medical assistance. Ingestion: Product is practically non-toxic. do not induce vomiting. Obtain emergency medical attention. Inhalation: Not likely to occur except as a mist. Move to fresh air and provide oxygen if necessary. Obtain emergency medical attention.							
		Safe Handling and Use					
Steps to be Taken in Case Material is Released or Spilled  Shut off ignition sources; absorb spillage with insert material. Contain spill and keep from entering waterways or sewers. Advise EPA/state agency if required. Use personal protective equipment. Shove, sweep or vacuum spill.							
Waste Disposal Method  Follow federal, state and local regulations. Not a RCRA hazardous waste if uncontaminated. If "used" RCRA criteria must be determined. Product may be amenable to sewer depending on local codes; if not permitted use a certified disposal service.							
Precautions to be Taken in Handling and Storage							
Keep away from flames, sparks or hot surfaces. Never use a torch to cut or weld on or near container. Empty containers can contain explosive vapors. NFPA Class IIIB storage.							
Other Precautions							
Section VIII - Control Measures							
Respiratory Prote	ection (Specify Type)						
Not required if adequate ventilation. If occupational exposure limits are exceeded wear NIOSH approved apparatus.							
Ventilation	Local Exhaust		Special				
	Mechanical(General)		Other				

The required it designate vertical entre expension at expension and exceeded the at the entre approved apparented						
Ventilation	Local Exhaust	Special				
	Mechanical(General)		Other			
Protective Gloves			Eye Protection			
•	aterials for gloves are polyvinyl chloride;	Glasses or goggles. Have suitable eye wash water				

Other Protective Clothing or Equipment

Avoid prolonged and/or repeated skin contact. If prolonged contact cannot be avoided, wear protective impervious gloves and clothing.

Work/Hygienic Practices

Wash thoroughly after handling. Do not use gasoline, solvents, kerosene, or harsh abrasive skin cleaners for washing exposed skin areas. Take a shower after work if general contact occurs. Remove soaked clothing and launder before reuse. Launder or discard contaminated shoes and leather gloves.