Material Safety Data Sheet for: BelleGlass HP Silane Primer

Kerr Italia SpA

MATERIAL SAFETY DATA SHEET

in accordance with communitary directive 2001/58/EC

Section I - Identification of Product and Company

Trade Product Name:	Preparation/Revision Date:
BelleGlass HP Silane Primer	12/03

Company Name: Kerr Corporation	Emergency phone: (+ 41)-91-61.00.639
Company Address: 1717 W.Collins Avenue Orange CA 92867 U.S.A.	Information phone: 00-800-41-050-505

Section II - Composition/Information on Ingredients

HAZARDOUS INGREDIENTS	%	SYMBOL	R	CAS N.	EINECS N.
Ethyl Alcohol	80-85	F	11	64-17-5	200-578-6
Organosilane Ester	15-20	N/A	N/A	N/A	N/A

Section III - Hazards Identification

HAZARD CLASSIFICATION Highly flammable	
--	--

Section IV - First Aid Measures

Treatment for eye contact: Flush with water for at least 15 minutes.

Treatment for skin contact: Wash thoroughly with soap and water. Use hand cream.

Treatment for inhalation (breathing): Move to fresh air. Restore breathing if necessary.

Treatment for ingestion (swallowing): Do not give liquids. If victim is unconscious, contact a physician.

Section V - Firefighting Measures

Suitable extinguishing media: Carbon dioxide, dry chemical, water spray.	
Forbidden extinguishing media: Not determined.	
Special firefighting measures: None.	
Unusual fire and explosion hazards: None.	
Special protection equipment: Sealed overall.	

Material Safety Data Sheet for: BelleGlass HP Silane Primer

Section VI - Accidental Release Measures

Personal Precautions: Follow recommended precautions listed in other sections.

Environmental Precautions: Material should not be allowed to drain to sewers.

Reclaiming Methods: Dilute with water, wipe with cloth and transfer to a suitable container for disposal.

Incinerate liquid in proper equipment.

Section VII - Handling and Storage

Handling Precautions: **Keep away from ignition sources.**

Precautions in case of Fire and Explosion: **Extinguish all ignition sources.**

Storage Conditions: Store in a cool, dry place away from ignition sources.

Suggested container(s): **The original containers provided by manufacturer.**

Indication for Combined Storage: **Avoid contact with strong oxidizing agent.**

Other Precautions: Material should not be allowed to drain to sewers. Use according to directions

Section VIII - Exposure controls/personal protection

Precautionary Measures	Ventilation Local Exhaust Ventilation: Recommended to keep exposure under 1000 ppm. Special Ventilation: None. Mechanical (General) Ventilation: Should be sufficient. Other Ventilation: Not applicable.
Limits	TWA: 1000 ppm; PEL: 1000 ppm
Respiratory Protection	Not needed.
Hands Protection	Latex gloves recommended.
Eyes Protection	Safety glasses with side shields.
Skin Protection	Handle in accordance with good personal hygiene and safety practices. These practices include avoiding unnecessary exposure to material.
Other Protective Equipments:	It is desiderable to use a lab coat.

Section IX - Physical and Chemical Properties

Boiling Point: 78,5°C (173°F) Vapor Pressure: 40 mm Hg		Melting Point: Not applicable Specific Gravity: ~ 0,85g/ml		
Evaporation Rate (n-butane= 1): Not established		Vapor Density (air=1): 1,59		
Solubility in Water: Soluble				
Appearance and Odor (Physical Form): Clear, colorless liquid with alcohol odor.			ol odor.	
Flash Point: 13°C (55°F)	Upper explosivity limit: 19		Lower explosivity limit: 4.3	

Material Safety Data Sheet for: BelleGlass HP Silane Primer

Section X - Stability and Reactivity

Stability: Stable if stored as directed.

Conditions to Avoid: Heat, sparks, open flames.

Incompatibility (Materials to Avoid): Strong oxidizing agents.

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide.

Hazardous Polymerization Products: Will not occur.

Section XI - Toxicological Information

Carcinogenicity/Teratogenicity: No.

Effects and Hazards of Overexposure (Acute and Chronic)

Effects and hazards of eye contact: May cause mild irritation.

Effects and hazards of skin contact: May cause mild irritation.

Effects and hazards of Inhalation (Breathing): May cause irritation of the throat.

Effects and hazards of Ingestion (Swallowing): May be poisonous by ingestion.

Effects for prolonged Exposure: Not applicable.

Section XII - Ecological Information

There is no specific information on the product. Use according to good working practices, avoiding release of the product into environment.

Environmental effects for Ethyl alcohol:

Aquatic toxicity: LC50 > 10000 mg/l (fish)

Section XIII - Disposal Considerations

May be absorbed with suitable material and transferred in container for disposal.

Section XIV - Transport Information

SEA TRANSP	SEA TRANSPORTATION							
IMCO Number			3219					
UN Number			1170					
Substance(s) de	termining ha	azard	Ethyl Alcohol					
AIR TRANSP	AIR TRANSPORTATION							
ICAO/IATA C	ass		3	3				
Substance(s) de	termining ha	azard	Ethyl Alcohol	Ethyl Alcohol				
TRANSPORTATION BY ROAD/RAILWAY								
RID/ADR 3	Item	3°	Hazard Identification	33	Substance	1170	Hazard	3
Class	Number	b	Number		Identification Number		Label	

Section XV - Regulatory Information

<u> </u>				
CLASSIFICATION IN ACCORDANCE WITH EEC DIRECTIVES				
HAZARD IDENTIFICATION SYMBOL	F			
R Sentences	R Sentences			
11	Highly flammable			
S Sentences				
7	Keep container tightly closed			
16	Keep away from sources of ignition - No smoking			
Ingredients determining the label	Ethyl Alcohol			

Section XVI - Other Information

Ethyl Alcohol	LC ₅₀ (inhalation mouse/4hrs)	$39g/m^3$
Ethyl Alcohol	LC ₅₀ (inhalation riouse/4iis) LC ₅₀ (inhalation rat/10hrs)	20000ppm
	LD _{Lo} (intraperitoneal dog)	3000mg/Kg
	LD ₅₀ (intraperitoneal guinea pig)	3414mg/Kg
	LD ₅₀ (intraperitoneal hamster)	5068mg/Kg
	LD ₅₀ (intraperitoneal mammal)	4300mg/Kg
	LD ₅₀ (intraperitoneal mouse)	933mg/Kg
	LD ₅₀ (intraperitoneal rat)	3750mg/Kg
	LD ₅₀ (intraperitoneal rabbit)	963mg/Kg
	LD _{Lo} (intravenous cat)	3945mg/Kg
	LD _{Lo} (intravenous chicken)	8216mg/Kg
	LD _{Lo} (intravenous dog)	1600mg/Kg
	LD ₅₀ (intravenous mouse)	1973mg/Kg
	LD ₅₀ (intravenous rat)	1440mg/Kg
	LD ₅₀ (intravenous rabbit)	2374mg/Kg
	LD _{Lo} (oral cat)	6000mg/Kg
	LD _{Lo} (oral child)	2000mg/Kg
	LD _{L0} (oral dog)	5500mg/Kg
	LD ₅₀ (oral guinea pig)	5560mg/Kg
	LD _{Lo} (oral human)	1400mg/Kg
	TD _{Lo} (oral man)	700mg/Kg
	TD _{L0} (oral man)	50mg/Kg
	TDLo (oral man)	1430mg/Kg
	LD ₅₀ (oral mouse)	7500mg/Kg
	LD ₅₀ (oral rat)	7060 mg/Kg
	LD50 (oral rabbit)	6300mg/Kg
	TD _{L₀} (oral woman)	6300mg/Kg
	LD _{Lo} (subcutaneous chicken)	5g/Kg
	LD _{Lo} (subcutaneous dog)	6000mg/Kg
	LD _{Lo} (subcutaneous frog)	7100mg/Kg
	LD _{Lo} (subcutaneous infant)	19440mg/Kg
	LD _{Lo} (subcutaneous mouse)	4g/Kg
	LD _{Lo} (subcutaneous pigeon)	5g/Kg
	LD _{Lo} (skin rabbit)	20g/Kg

CAUTION: PRODUCT FOR PROFESSIONAL USE

The information on this Safety Sheet is based on presently available data and to our best knowledge for the correct handling of the product under normal conditions. Any use of this product in any way not indicated on this Sheet or the use of this product together with any other process/procedure will be exclusively under the user's responsibility.