

Health	2
Flammability	4
Reactivity	0
Personal Protection	A

HMIS Ratings

BOWMAN DISTRIBUTION MATERIAL SAFETY DATA SHEET

Health	2
Flammability	4
Reactivity	0
Specific Hazard	

NFPA Ratings

SECTION I

PRODUCT NAME BELT DRESSING		BOWMAN PART NO. 21905, 21905-1 (page 1 of 2)
SUPPLIER Bowman Distribution, Barnes Group Inc.		EMERGENCY TELEPHONE NO. (216) 391-7200
ADDRESS 850 East 72nd Street, Cleveland, OH 44103		DATE 1/29/90
HAZARDOUS MATERIAL DESCRIPTION, PROPER SHIPPING NAME, HAZARD CLASS, HAZARD ID NO. (49 CFR 172.101) Consumer Commodity ORM-D UN-1954		
ADDITIONAL HAZARD CLASSES (as applicable) None		
CHEMICAL FAMILY Mixture	FORMULA TM-3234	

SECTION II - HAZARDOUS INGREDIENTS

CAS REGISTRY NUMBER	%W	%V	CHEMICAL NAME(S)	OSHA PEL	ACGIH TLV	STEL Other Limits	Listed as Carcinogen NTP, IARC or OSHA 1910(z) (specify)
110-54-3	81		Hexane	500	50	N.E.	No
Unknown	<5		Oil	N.E.	5mg/m ³ oil mist	N.E.	No
74-98-6	8		Propane/isobutane	1000	1000	asphyxiant	No
	>6		Non-Hazardous	N.A.	N.A.	N.A.	No

ALL CHEMICAL COMPOUNDS MARKED WITH AN ASTERISK () ARE TOXIC CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT (SARA) OF 1986 AND 40 CFR PART 372.

SECTION III - PHYSICAL DATA

BOILING POINT -40°F — 158°F _____ °C	SPECIFIC GRAVITY (H ₂ O = 1) 0.7		
VAPOR PRESSURE 45 @ 70 °F _____ °C _____ mm Hg <input checked="" type="checkbox"/> psi	PERCENT VOLATILE BY VOLUME (%) N.E.	PERCENT SOLID BY WEIGHT (%) N.E.	
VAPOR DENSITY (AIR = 1) Heavier than air 4.0	EVAPORATION RATE (= 1) Butyl Acetate <1		
SOLUBILITY IN WATER NIL	PH = N.A.		
APPEARANCE AND ODOR Clear/Solvent Odor	MATERIAL IS: Liquid & Gas		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT -40 °F _____ °C	method used T.C.C.	FLAMMABLE LIMITS	LEL 1.8	UEL 12.0
EXTINGUISHING MEDIA Use water fog, dry chemical or carbon dioxide.				
SPECIAL FIRE FIGHTING PROCEDURES Aerosol cans may rupture when heated.				
UNUSUAL FIRE AND EXPLOSION HAZARDS Heated cans may burst.				