

**Max 44 Total System Cleaner 55 Gal Drum**

Revision: 03/30/2016

Supersedes Revision: 04/30/2014

1. Product and Company Identification

Product Code: C4455

Product Name: Max 44 Total System Cleaner 55 Gal Drum

Company Name: CYCLO INDUSTRIES, INC. **Phone Number:**
902 SOUTH US HIGHWAY 1 (800)843-7813
JUPITER, FL 33477

Web site address: www.cyclo.com

Email address: ehs@cyclo.com

Emergency Contact: First Aid Emergency (800)752-7869
CHEMTREC (703) 527-3887 (800)424-9300

Information: First Aid Emergency (Outside U.S.) (312)906-6194

2. Hazards Identification**Flammable Liquids, Category 4****Acute Toxicity: Inhalation, Category 4****Acute Toxicity: Oral, Category 4****Acute Toxicity: Skin, Category 4****Skin Corrosion/Irritation, Category 3****Carcinogenicity, Category 2****Aspiration Toxicity, Category 1****GHS Signal Word:****Danger****GHS Hazard Phrases:**

H227: Combustible liquid.
H332: Harmful if inhaled.
H302: Harmful if swallowed.
H312: Harmful in contact with skin.
H316: Causes mild skin irritation.
H351: Suspected of causing cancer.
H304: May be fatal if swallowed and enters airways.
H412: Harmful to aquatic life with long lasting effects.

GHS Precaution Phrases:

P233: Keep container tightly closed.
P210: Keep away from heat/sparks/open flames/hot surfaces - No smoking.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P240: Ground/bond container and receiving equipment.
P241: Use explosion-proof electrical/ventilating/lighting equipment.
P243: Take precautionary measures against static discharge.
P242: Use only non-sparking tools.
P271: Use only outdoors or in a well-ventilated area.
P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
P264: Wash hands thoroughly after handling.
P270: Do not eat, drink or smoke when using this product.
P362+364: Take off contaminated clothing and wash it before reuse.
P201: Obtain special instructions before use.
P202: Do not handle until all safety precautions have been read and understood.
P281: Use personal protective equipment as required.
P273: Avoid release to the environment.

GHS Response Phrases:

P301+330+331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

**Max 44 Total System Cleaner 55 Gal Drum**

Revision: 03/30/2016

Supersedes Revision: 04/30/2014

P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

P363: Wash contaminated clothing before reuse.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P309+311: Call a POISON CENTER or doctor/physician if exposed or you feel unwell.

P403+235: Store in cool/well-ventilated place.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation.

GHS Storage and Disposal Phrases:**OSHA Regulatory Status:** This material is classified as hazardous under OSHA regulations.**Potential Health Effects** No data available.**(Acute and Chronic):****Medical Conditions Generally Aggravated By Exposure:** Irritation from skin exposure may aggravate existing open wounds, skin disorders, and dermatitis (rash).**3. Composition/Information on Ingredients**

CAS #	Hazardous Components (Chemical Name)	Concentration
91-20-3	Naphthalene	<=1.0 %
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	<=1.0 %
68476-30-2	Fuel oil, no. 2	>96.0 %
100-41-4	Ethylbenzene	<=1.0 %
1330-20-7	Xylene (mixed isomers)	<=1.0 %
NA	Polymer/amine	< 1.0 %

4. First Aid Measures**Emergency and First Aid Procedures:** If swallowed, do not induce vomiting. Aspiration of material due to vomiting can cause chemical pneumonitis which can be fatal. If conscious, give two glasses of water and get immediate medical attention to perform gastric lavage. If vomiting occurs naturally, the casualty should lean forward to reduce the risk of aspiration. If in eyes, rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately remove contaminated clothing. Launder contaminated clothing before reuse and discard shoes and other leather articles saturated with the material. If inhaled, remove exposed person to fresh air if adverse effects are observed. If breathing has stopped, apply artificial respiration. Call physician immediately if adverse reaction occurs.**Signs and Symptoms Of Exposure:** Eyes: Mild irritation.
Ingestion: nausea, vomiting, diarrhea and restlessness.
Skin: Irritation and dermatitis.
Inhalation: Headache, giddiness, vertigo and anesthetic stupor.



Max 44 Total System Cleaner 55 Gal Drum

Revision: 03/30/2016

Supersedes Revision: 04/30/2014

5. Fire Fighting Measures

Flash Pt:	63.00 C (145.4 F) Method Used: Pensky-Marten Closed Cup
Explosive Limits:	LEL: .7 at 32.0 F (0.0 C) UEL: 10 at 32.0 F (0.0 C)
Autoignition Pt:	>= 500.00 F (260.0 C)
Suitable Extinguishing Media:	Avoid using straight water streams. Water spray and foam (AFFF/ATC) must be applied carefully to avoid frothing and from as far a distance as possible. Recommended wearing self-contained breathing apparatus. Water may cause splattering. Material will float on water. Keep run-off water out of sewers and water sources.
Unsuitable Extinguishing Media:	Toxic fumes, gases or vapors may evolve on burning. Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Container may rupture on heating. Material does not have explosive properties.
Fire Fighting Instructions:	Use NIOSH/MSHA approved positive pressure self-contained breathing apparatus when in a confined area.
Flammable Properties and Hazards:	Flash Point = 146 +/- 1 F. (Pensky-Martens closed cup) Autoignition temperature = 489 F Flammable liquids in air - lower %: 0.7 Flammable limits in air - higher %: 5.0
Hazardous Combustion Products:	THIS PRODUCT IS CONSIDERED TO BE A COMBUSTIBLE LIQUID PER THE OSHA HAZARD COMMUNICATION STANDARD AND SHOULD BE KEPT AWAY FROM HEAT, FLAME AND SOURCES OF IGNITION. FOR ADDITIONAL FIRE RELATED INFORMATION, SEE NFPA 30 OR THE NORTH AMERICAN EMERGENCY RESPONSE GUIDE 128.

6. Accidental Release Measures

Steps To Be Taken In Case Material Is Released Or Spilled:	Keep public away. Isolate and evacuate the area. Shut off source is safe to do so. Eliminate all ignition sources. Personal Protective Equipment must be worn, see Personal Protection Section for PPE recommendations. Ventilate spill area. Prevent entry into sewers and waterways. If substance has entered waterway. Advise authorities. Pick up free liquid for recycle and/or disposal. Residual liquid can be absorbed on inert material like sand or soil. Check under Transportation and Labeling (DOT / CERCLA) and Other Regulatory Information Section (SARA) for hazardous substances to determine regulatory reporting requirements for spills.
---	---

7. Handling and Storage

Precautions To Be Taken in Handling:	Keep away from potential sources of ignition. Open container in a well ventilated area. Avoid breathing vapors. Keep containers closed when not in use. Do not discharge into drains or the environment. Dispose to an authorized waste collection point. Use appropriate containment to avoid environmental contamination. Wash thoroughly after handling. Empty containers retain material residue. Do not cut, weld, braze, solder, drill, grind or expose containers to heat, flame, spark or other sources of ignition. Keep out of the reach of children.
Precautions To Be Taken in Storing:	Do not store near potential sources of ignition. Store in well ventilated area. Equip bulk storage tanks with overflow protection such as high level alarms or secondary containment. Store drums in area with secondary containment. Storage area should be covered to prevent rain water from entering.

**Max 44 Total System Cleaner 55 Gal Drum**

Revision: 03/30/2016

Supersedes Revision: 04/30/2014

8. Exposure Controls/Personal Protection

CAS #	Partial Chemical Name	OSHA TWA	ACGIH TWA	Other Limits
91-20-3	Naphthalene	PEL: 10 ppm	TLV: 10 ppm STEL: 15 ppm	No data.
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	No data.	No data.	No data.
68476-30-2	Fuel oil, no. 2	PEL: 100 ppm	TLV: 100 mg/m3 STEL: 150 ppm	No data.
100-41-4	Ethylbenzene	PEL: 100 ppm	TLV: 100 ppm STEL: 125 ppm	No data.
1330-20-7	Xylene (mixed isomers)	PEL: 100 ppm	TLV: 100 ppm STEL: 150 ppm CEIL: 25 ppm	No data.
NA	Polymer/amine	No data.	No data.	No data.

Respiratory Equipment (Specify Type): Use NIOSH / MSHA approved full face respirator with an organic vapor cartridge if the recommended exposure limit is exceeded. Use self-contained breathing apparatus for entry into confined space, for other poorly ventilated areas and for large spill clean-up sites.

Eye Protection: Safety glasses or goggles.

Protective Gloves: Butyl rubber. Neoprene.

Other Protective Clothing: Long sleeve shirt is recommended. Wear either a chemical protective suit or apron when potential for contact with material exists. Use neoprene or nitrile rubber boots when necessary to avoid contaminating shoes. Do not wear rings, watches or similar apparel that could entrap the material and cause a burn.

Engineering Controls (Ventilation etc.): Use local exhaust ventilation to control mists or vapors. Additional ventilation or exhaust may be required to maintain air concentrations below recommended exposure limits.

9. Physical and Chemical Properties

Physical States: [] Gas [X] Liquid [] Solid

Appearance and Odor: Clear red liquid. Mild petroleum odor.

pH: No data.

Melting Point: No data.

Boiling Point: > 360.00 F (182.2 C) - 550.00 F (287.8 C)

Flash Pt: 63.00 C (145.4 F) Method Used: Pensky-Marten Closed Cup

Evaporation Rate: No data.

Flammability (solid, gas): No data available.

Explosive Limits: LEL: .7 at 32.0 F (0.0 C) UEL: 10 at 32.0 F (0.0 C)

Vapor Pressure (vs. Air or mm Hg): -1-10MM_HG - at 100F

Vapor Density (vs. Air = 1): -4 - 5

Specific Gravity (Water = 1): -0.827 - 0.847

Density: -6.88 - 7.08 LB/GA

Solubility in Water: No data.



Max 44 Total System Cleaner 55 Gal Drum

Revision: 03/30/2016

Supersedes Revision: 04/30/2014

Octanol/Water Partition Coefficient:	No data.
Percent Volatile:	0.0 % by weight.
VOC / Volume:	~ 10.0000
Autoignition Pt:	>= 500.00 F (260.0 C)
Decomposition Temperature:	No data.
Viscosity:	No data.

10. Stability and Reactivity

Stability:	Unstable [] Stable [X]
Conditions To Avoid - Instability:	The material is stable at 22 C, 760 mm pressure. Avoid high temperatures, open flames, sparks, welding, smoking and other ignition sources.
Incompatibility - Materials To Avoid:	Acids, oxidizing agents, halogens and halogenated compounds.
Hazardous Decomposition or Byproducts:	Smoke, carbon monoxide, carbon dioxide, aldehydes and other products of incomplete combustion. Under combustion conditions, oxides of the following elements will be formed: nitrogen.
Possibility of Hazardous Reactions:	Will occur [] Will not occur [X]
Conditions To Avoid - Hazardous Reactions:	No data available.

11. Toxicological Information

Toxicological Information:	<p>Oral Toxicity: The LD50 in rats is between 2000 mg/kg and 5000 mg/kg. Based on data from components or similar materials. Swallowing this material causes severe irritation and may cause burns of the mouth, esophagus and stomach, abdominal pain, nausea, vomiting and diarrhea. Ingestion may cause CNS depression.</p> <p>Eye Irritation: Corrosive to eyes. Based on data from components or similar materials.</p> <p>Skin Irritation: Corrosive to the skin. Based on data from components or similar material. Prolonged or repeated skin contact as from clothing wet with material may cause dermatitis. Symptoms may include redness, edema, drying, and cracking of the skin.</p> <p>Dermal Toxicity: The following estimated LD 50 is based on incomplete data on components. The LD50 in rabbits is > 2000 mg/Kg. Based on data from components or similar materials. Prolonged or widespread contact with this material could result in the absorption of potentially harmful amounts.</p> <p>Inhalation Toxicity: High concentrations may cause headaches, dizziness, nausea, stupor, and other central nervous system effects leading to visual impairment, difficulty breathing and convulsions.</p> <p>Respiratory Irritation: If material is misted or if vapors are generated from heating, exposure may cause irritation of mucous membranes and the upper respiratory tract. Based on data from components and similar materials.</p>
----------------------------	---



Max 44 Total System Cleaner 55 Gal Drum

Revision: 03/30/2016

Supersedes Revision: 04/30/2014

Exposure to a high concentration of vapor or mist is irritating to the respiratory tract.
Breathing of vapor or mist
may aggravate asthma and inflammatory or fibrotic pulmonary disease.

Dermal Sensitization: No data available to indicate product or components may be respiratory sensitizes.

CAS# 68476-30-2:

Other Studies:, TDLo, Skin, Species: Rabbit, 100.0 ML/KG, 12 D.

Results:

Skin and Appendages: Skin: After systemic exposure: Dermatitis, irritative.

Nutritional and Gross Metabolic: Weight loss or decreased weight gain.

Related to Chronic Data - death.

- "Toxicology of Petroleum Hydrocarbons, Proceedings of the Symposium, 1st, 1982,"
MacFarland, H.N., et al., eds., Washington, DC, American Petroleum Institute, 1983
Volume, Vol/p/yr: 1,1, 1983

Acute toxicity, LD50, Oral, Rat, 12.00 GM/KG.

Results:

Behavioral: Somnolence (general depressed activity).

- Advances in Modern Environmental Toxicology., Senate Press, Inc., P.O. Box 252,
Princeton Junction, NJ 08550, Vol/p/yr: 6,1, 1984

Acute toxicity, LD (Lethal dose), Skin, Species: Rabbit, > 5.000 GM/KG.

Results:

Behavioral: Tremor.

Behavioral: Convulsions or effect on seizure threshold.

- Advances in Modern Environmental Toxicology., Senate Press, Inc., P.O. Box 252,
Princeton Junction, NJ 08550, Vol/p/yr: 6,1, 1984

Tumorigenic Effects:, TDLo, Skin, Mouse, 243.0 GM/KG, 97 W.

Results:

Tumorigenic: Carcinogenic by RTECS criteria.

Skin and Appendages: Other: Tumors.

- Fundamental and Applied Toxicology., Academic Press, Inc., 1 E. First St., Duluth, MN
55802, Vol/p/yr: 9,297, 1987

Standard Draize Test, Skin, Species: Rabbit, 500.0 MG, 24 H, Moderate.

Results:

Brain and Coverings: Changes in surface EEG.

- "Toxicology of Petroleum Hydrocarbons, Proceedings of the Symposium, 1st, 1982,"
MacFarland, H.N., et al., eds., Washington, DC, American Petroleum Institute, 1983
Volume, Vol/p/yr: 1,1, 1983

Standard Draize Test, Eyes, Species: Rabbit, 100.0 MG, 30 S, Mild.

Results:

Behavioral: Somnolence (general depressed activity).

- "Toxicology of Petroleum Hydrocarbons, Proceedings of the Symposium, 1st, 1982,"
MacFarland, H.N., et al., eds., Washington, DC, American Petroleum Institute, 1983
Volume, Vol/p/yr: 1,1, 1983

**Chronic Toxicological
Effects:**

Chronic Toxicity: Repeated overexposure to petroleum naphtha can cause nervous
system damage. A 14-day
dermal toxicity study of 2-ethylhexanol in rats showed blood effects, decreased spleen

**Max 44 Total System Cleaner 55 Gal Drum**

Revision: 03/30/2016

Supersedes Revision: 04/30/2014

weight and decreased triglycerides. Repeated overexposure to naphthalene may cause destruction of red blood cells with anemia, fever, jaundice and kidney and liver damage. Repeated ingestion of 2-ethyhexanol may cause injury to the liver and kidneys.

Carcinogenicity: A two-year National Toxicology Program (NTP) study found an increased incidence of tumors of the nose in rats exposed to naphthalene by inhalation. In mice similarly exposed, increased incidence of alveolar / bronchiolar adenomas were observed. Naphthalene has been classified by the International Agency for Research on Cancer (IARC) as a possible human carcinogen (Group 2B) on the basis of sufficient evidence of carcinogenicity in experimental animals but inadequate evidence in exposed humans. This product is formulated with mineral oils which are considered to be severely refined and not considered to be carcinogenic under IARC. All of the oils in this product have been demonstrated to contain less than 3% extractables by the IP 346 test.

Mutagenicity: No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Reproductive Toxicity: No data available to indicate either product or components present at greater than .1% that may cause reproductive toxicity.

Tertaogenicity: No evidence of adverse effects were found in a developmental toxicity study of 2-ethyhexanol in rats. Doses up to 3 ml/kg applied to the skin during the most critical part of the gestation period produced evidence of toxicity to mothers, but no evidence of injury in the developing offspring. In a previous study, birth defects were observed by oral administration, an unlikely route of exposure in the workplace.

Exposure Limits: Contains mineral oil. Under conditions which may generate mists, observe the OSHA PEL of 5 mg. per cubic meter, ACGIH STEL of 10 mg per cubic meter.

CAS #	Hazardous Components (Chemical Name)	NTP	IARC	ACGIH	OSHA
91-20-3	Naphthalene	Possible	2B	A4	n.a.
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	n.a.	n.a.	n.a.	n.a.
68476-30-2	Fuel oil, no. 2	n.a.	2B	A3	n.a.
100-41-4	Ethylbenzene	n.a.	2B	A3	n.a.
1330-20-7	Xylene (mixed isomers)	n.a.	3	A4	n.a.
NA	Polymer/amine	n.a.	n.a.	n.a.	n.a.

**Max 44 Total System Cleaner 55 Gal Drum**

Revision: 03/30/2016

Supersedes Revision: 04/30/2014

12. Ecological Information**General Ecological Information:**

Product can cause fouling of shoreline and may be harmful to aquatic life in low concentrations. The 96 hour LL50 values for an accommodated fraction (WAF) of fuel oil ranged from 3.2 to 65 mg/l in fish and 2-210 mg/l in invertebrates, EL 50 values for inhibition of algae growth ranged from 1.8 to 2.9 mg/l for No. 2 fuel oil (the major component of this product) and from 10 to 78 mg/l for diesel fuel. This product does not concentrate or accumulate in the food chain. If released to soil and water, this product is expected to biodegrade under both aerobic and anaerobic conditions.

13. Disposal Considerations**Waste Disposal Method:**

Dispose of contents/container in accordance with local/regional/national/international regulation.

14. Transport Information**LAND TRANSPORT (US DOT):**

DOT Proper Shipping Name: Not Regulated

DOT Hazard Class:

UN/NA Number:

LAND TRANSPORT (European ADR/RID):

ADR/RID Shipping Name: Not-Restricted

UN Number:

Hazard Class:

MARINE TRANSPORT (IMDG/IMO):

IMDG/IMO Shipping Name: Non-Restricted

UN Number:

Hazard Class:

Packing Group:

IMDG MFAG Number:

Marine Pollutant: No

IMDG EMS Page:

AIR TRANSPORT (ICAO/IATA):

ICAO/IATA Shipping Name: Not-Restricted

15. Regulatory Information**EPA SARA (Superfund Amendments and Reauthorization Act of 1986) Lists**

CAS #	Hazardous Components (Chemical Name)	S. 302 (EHS)	S. 304 RQ	S. 313 (TRI)
91-20-3	Naphthalene	No	Yes 100 LB	Yes
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	No	No	No
68476-30-2	Fuel oil, no. 2	No	No	No
100-41-4	Ethylbenzene	No	Yes 1000 LB	Yes
1330-20-7	Xylene (mixed isomers)	No	Yes 100 LB	Yes
NA	Polymer/amine	No	No	No

CAS # Hazardous Components (Chemical Name)**Other US EPA or State Lists**

91-20-3	Naphthalene	CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes - Inventory, 4 Test, 8A PAIR; CA PROP.65: Yes; CA TAC, Title 8: TAC, Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: Part 5; NC TAP: Yes; NJ EHS: Yes - 1322; NY Part 597: Yes; PA HSL: Yes - E; SC TAP: Yes; WI Air: Yes
64742-94-5	Solvent naphtha (petroleum), Heavy arom.	CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes - Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS:



SAFETY DATA SHEET

Max 44 Total System Cleaner 55 Gal Drum

Revision: 03/30/2016

Supersedes Revision: 04/30/2014

68476-30-2 Fuel oil, no. 2

No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
CAA HAP,ODC: No; CWA NPDES: No; TSCA: Yes -
Inventory; CA PROP.65: No; CA TAC, Title 8: No; MA
Oil/HazMat: No; MI CMR, Part 5: No; NC TAP: No; NJ EHS:
No; NY Part 597: No; PA HSL: No; SC TAP: No; WI Air: No
CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes -
Inventory, 4 Test; CA PROP.65: Yes; CA TAC, Title 8: TAC,
Title 8; MA Oil/HazMat: Yes; MI CMR, Part 5: Part 5; NC TAP:
Yes; NJ EHS: Yes - 0851; NY Part 597: Yes; PA HSL: Yes -
E; SC TAP: Yes; WI Air: Yes

100-41-4 Ethylbenzene

CAA HAP,ODC: HAP; CWA NPDES: Yes; TSCA: Yes -
Inventory; CA PROP.65: No; CA TAC, Title 8: TAC, Title 8;
MA Oil/HazMat: Yes; MI CMR, Part 5: CMR, Part 5; NC TAP:
Yes; NJ EHS: Yes - 2014; NY Part 597: Yes; PA HSL: Yes -
E; SC TAP: Yes; WI Air: Yes

1330-20-7 Xylene (mixed isomers)

CAA HAP,ODC: No; CWA NPDES: No; TSCA: No; CA
PROP.65: No; CA TAC, Title 8: No; MA Oil/HazMat: No; MI
CMR, Part 5: No; NC TAP: No; NJ EHS: No; NY Part 597: No;
PA HSL: No; SC TAP: No; WI Air: No

NA Polymer/amine

CAS # Hazardous Components (Chemical Name)

International Regulatory Lists

91-20-3 Naphthalene

Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA:
Yes

64742-94-5 Solvent naphtha (petroleum), Heavy arom.

Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA:
Yes

68476-30-2 Fuel oil, no. 2

Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA:
Yes

100-41-4 Ethylbenzene

Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA:
116-01 (4)

1330-20-7 Xylene (mixed isomers)

Canadian DSL: Yes; Canadian NDSL: No; Taiwan TCSCA:
Yes


NA Polymer/amine

Canadian DSL: No; Canadian NDSL: No; Taiwan TCSCA: No

16. Other Information

Revision Date: 03/30/2016

Hazard Rating System:



Additional Information About This Product: No data available.

This Product:

Company Policy or

Disclaimer:

Cyclo Industries, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose. Cyclo Industries, Inc. makes no representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly, Cyclo Industries, Inc. will not be responsible for damages resulting from use of or reliance upon this information.