Product name: CADWELD® PLUS Page: 1/6

 Supersedes Date:
 2008-10-06
 Revision date:
 2011-03-02

 SDS-ID:
 CA(GB)/2.1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product name: CADWELD® PLUS

<u>Application:</u> Welding material <u>Container size:</u>

<u>Supplier:</u> ERICO Canada Inc.

P.O. Box 170 Mississauga, Ontario Canada L5M 2B8 Phone: 1-440-248-0100

Responsible for safety data sheet authoring:

SDS info@dhigroup.com

2. HAZARDS IDENTIFICATION

HMIS Ratings: Health: 1 Fire: 0 Physical Hazard: 0

Physical and Chemical

Hazards:

Improper use of the product or inadequate preparation of the conductors, moulds or

surroundings can result in aggressive reactions. Self-propagating high temperature reaction will occur if heated above ignition temperature. Generates molten metal in excess of 1370°C,

slag and dense, dusty smoke.

Human health: Harmful if swallowed. The molten product can cause serious burns. Inhalation of powder or

fumes may cause metal fume fever.

Exposure to reaction by-products: See section 8.

Environment: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

3. COMPOSITION/INFORMATION ON INGREDIENTS

The product contains: Copper, copper alloys., calcium fluoride.

tin (F20 and XF19)

aluminium-vanadium alloy (F33).

This material is a controlled product under Canadian WHMIS regulations.

The following substances shall be indicated according to legislation:

Dicopper oxide CAS-no. 1317-39-1 <80 %

Tin CAS-no. 7440-31-5 <10 %

CADWELD® PLUS Product name: Page: 2/6

Supersedes Date: 2008-10-06 Revision date: 2011-03-02

> SDS-ID: CA(GB)/2.1

4. FIRST-AID MEASURES

Molten product will cause skin burns and if in contact with eyes while in a molten state may cause serious damage. Burns (in contact with molten metal, slag or hot equipment): Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.

Inhalation of welding fumes: / Dust inhalation: Move into fresh air and keep at rest. In case of Inhalation:

persistent throat irritation or coughing: Seek medical attention and take along these

instructions.

Skin contact: Remove contaminated clothes and rinse skin thoroughly with water. If material is hot, treat for

thermal burns and get immediate medical attention.

Dust in the eyes: Do not rub eye. Immediately flush with plenty of water for up to 15 minutes. Eye contact:

Remove any contact lenses and open eyelids widely. If irritation persists: Seek medical

attention and bring these instructions.

Immediately rinse mouth and drink plenty of water. Keep person under observation. If person Ingestion:

becomes uncomfortable seek hospital and bring these instructions.

5. FIRE-FIGHTING MEASURES

Extinguish with dry sand and/or flood with large amounts of water. Extinguishing media:

Use fire-extinguishing media appropriate for surrounding materials.

Extinguishing media which are not suitable: Hand water buckets or hand storage pumps.

Molten metal contact with water can cause small pockets of superheated steam.

Specific hazards: During fire, health hazardous gases may be formed. Ignition temperature: > 950 °C

Ignition of large quantities of exothermic materials may result in large volumes of dense

smoke.

Protective equipment for

fire-fighters:

Selection of respiratory protection for fire fighting: follow the general fire precautions

indicated in the workplace.

6. **ACCIDENTAL RELEASE MEASURES**

Follow precautions for safe handling described in this safety data sheet. Avoid inhalation of Personal precautions:

dust. Do not breathe fumes. Avoid contact with skin and eyes. For personal protection, see

section 8.

Environmental

Precaution should be taken to prevent hot material and reaction byproducts from contact with combustible materials in surrounding areas. Avoid spreading dust or contaminated materials. precautions:

Avoid discharge to the aquatic environment. Contact local authorities in case of spillage to

drain/aquatic environment.

Methods for

cleaning up:

Sweep up spilled substance and remove to safe place. For waste disposal, see section 13.

Product name: CADWELD® PLUS Page: 3/6

Supersedes Date: 2008-10-06 Revision date: 2011-03-02

SDS-ID: CA(GB)/2.1

7. HANDLING AND STORAGE

Safe handling advice: Do not breathe fumes. Avoid contact with skin and eyes. Observe good chemical hygiene

practices. CADWELD PLUS integrated packages are designed for use in CADWELD equipment only. Use of improper or damaged equipment can lead to exposure to molten

metal and reaction byproducts.

<u>Technical measures:</u> Work practice should minimize risk of contact.

Technical precautions: Confined space: Local exhaust is recommended.

Technical measures for

safe storage:

Ensure that the container is undamaged and has a proper label.

Storage conditions: Store in closed original container in a dry place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering measures: Provide adequate ventilation. Observe occupational exposure limits and minimize the risk of

inhalation of dust and fumes.

Other provincial OEL's may apply.

Chemical name:	Exposure limits:	Type:	<u>Notes:</u>	References:
Copper dust and mists (as Cu)	1 mg/m³ 2 mg/m³	TWA STEL	- 15min	Al
Copper - Dusts and mists, as Cu	1 mg/m³	TWA	-	BC
Copper dust and mists (as copper)	1 mg/m³	TWA	-	On
Copper dust and mists (as copper)	1 mg/m³	TWA	-	Qu
Copper fume	0,2 mg/m³ 0,6 mg/m³	TWA STEL	- 15min	Al
Copper - Fume, as Cu	0,2 mg/m³	TWA	-	BC
Copper fume (as copper)	0,2 mg/m³	TWA	-	On
Copper fume (as copper)	0,2 mg/m³	TWA	-	Qu
Aluminum - Metal, total dust	10 mg/m³	TWA	-	BC
Aluminum - Metal, respirable dust	3 mg/m³	TWA	-	BC

<u>Personal protection:</u> Personal protection equipment should be chosen according to the the CEN standards and in

collaboration with the supplier of the personal protective equipment.

Use special welding equipment for protection of eyes, skin and respiratory system.

<u>Respiratory equipment:</u> Under normal conditions of use respiration protection should not be required.

When welding: In case of inadequate ventilation and work of long duration or on large surface areas in confined rooms. Use respiratory equipment with particle filter, type P2.

Hand protection: Protective gloves are recommended.

Eye protection: Wear goggles/face shield.

Hygiene measures: Wash hands after handling. Change contaminated clothing.

Product name: CADWELD® PLUS Page: 4/6

Supersedes Date: 2008-10-06 Revision date: 2011-03-02

SDS-ID: CA(GB)/2.1

9. PHYSICAL AND CHEMICAL PROPERTIES

Form: Granular grey - black Colour: Odor: Odorless not relevant pH: 1999°F Melting point: Boiling point: not available Flash point: 1749°F Vapor pressure: not available not available Vapour density:

Relative density: 5.5

Solubility: Insoluble in water

Other data: Ignition temperature: > 1742 °F

10. STABILITY AND REACTIVITY

Stability: Stable.

Not sensitive to vibrations, shock or impact and is not subject to spontaneous ignition.

Conditions/ Avoid exposure to temperatures above the flash point. (950 °C)

materials to avoid: Water, moisture.

Hazardous None under normal conditions. Polymerization will not occur

decomposition products:

11. TOXICOLOGICAL INFORMATION

<u>Inhalation:</u> Dust may irritate throat and respiratory system and cause coughing. Heating above the

melting point releases metallic oxides which may cause metal fume fever by inhalation. The

symptoms are shivering, fever, malaise and muscular pain.

Skin contact: Dust has an irritating effect on moist skin. Prolonged and/or repeated contact: May cause

eczema-like skin disorders (dermatitis).

The molten product can cause serious burns.

<u>Eye contact:</u> Particles/fumes in the eyes may cause discomfort/irritation.

Ingestion: Harmful if swallowed. LD50 (oral, rat): 490 mg/kg (Dicopper oxide CAS-no. 1317-39-1)

Specific effects: Frequent inhalation of dust over a long period of time increases the risk of developing lung

diseases. Copper oxide may by repeated or prolonged inhalation occasionally cause ulceration and perforation of the nasal septum. Long term exposure to copper containing

dusts may cause allergic dermatitis.

Product name: CADWELD® PLUS Page: 5/6

Supersedes Date: 2008-10-06 Revision date: 2011-03-02

SDS-ID: CA(GB)/2.1

12. ECOLOGICAL INFORMATION

Mobility: The product is not volatile but may be spread by dust-raising handling.

Degradability: The product solely consists of inorganic compounds which are not biodegradable.

Ecotoxicity: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

Dicopper oxide: EC50 (Daphnia magna, 48 hours): 0.51 mg/l

<u>Bioaccumulative</u>

potential:

No data available on bioaccumulation.

Other adverse effects: None known.

13. DISPOSAL CONSIDERATIONS

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

Reacted/Used Product - can be disposed of as a non-hazardous waste.

Unreacted, spilled product - should be cleaned up and disposed of as hazardous waste.

14. TRANSPORT INFORMATION

UN-number: 3077

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.

(Dicopper oxide)

Sea (IMDG):

 Class:
 9

 PG:
 III

 MP:
 Yes

 EmS:
 F-A , S-F

MFAG: 1

<u>Inland waterways:</u> To be handled locally.

Air (ICAO/IATA):

Class: 9 **PG:** III

TDG:

Class: Packing group: Primary risk label: Subsidiary risk label: -

Product name: CADWELD® PLUS Page: 6/6

Supersedes Date: 2008-10-06 Print date: 2011-03-02

SDS-ID: CA(GB)/2.1

15. REGULATORY INFORMATION

Workplace Hazardous Materials Information Systems (WHMIS): This product has been classified in accordance with the hazard criteria of the CPR (Controlled Product Regulations), and the MSDS contains all of the information required by the CPR.

TSCA: All chemicals included in the product are TSCA listed. DSL: All chemicals included in the product are DSL listed.

WHMIS Classification: Not controlled

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

Dicopper oxide CAS-no. 1317-39-1

Tin CAS-no. 7440-31-5

HMIS Ratings: Health: 1 Fire: 0 Physical Hazard: 0

State and local regulations may apply.

National regulation: Department of Justice. CPR – Controlled products Regulations. SOR/88-66, with amendments.

British Columbia: Occupational Exposure Limits for Chemical Substances, Occupational

Health and Safety Regulation 296/97, with amendments.

Quebec: Regulation respecting the quality of the work environment (R.R.Q. 1981, S-2.1, r.15),

with amendments.

Ontario: Control of Exposure to Biological or Chemical Agents R.R.O. 1990, Reg. 833, with

amendments.

Alberta Regulation 393/88 Occupational Health and Safety Act, Chemical Hazards Regulation,

with amendments..

Department of Justice. IDL - Ingredient Disclosure List. SOR/88-64, 31 December 1987, with

amendments.

16. OTHER INFORMATION

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions. The following sections contain revisions or new statements: 8

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.

Made by DHI - Centre for Environment and Toxicology, Agern Allé 5, DK-2970 Hørsholm, Denmark. www.dhigroup.com.