HALLIBURTON

MATERIAL SAFETY DATA SHEET

Product Trade Name: CAT-4 WINTER BLEND

Revision Date: 04-Jan-2011

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name: CAT-4 WINTER BLEND

Synonyms: None
Chemical Family: Amine
Application: Activator

Manufacturer/Supplier Halliburton Energy Services

P.O. Box 1431

Duncan, Oklahoma 73536-0431

Emergency Telephone: (281) 575-5000

Prepared By Chemical Compliance

Telephone: 1-580-251-4335

e-mail: fdunexchem@halliburton.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	CAS Number	PERCENT	ACGIH TLV-TWA	OSHA PEL-TWA
Methanol	67-56-1	30 - 60%	200 ppm (S)	200 ppm
Diethylenetriamine	111-40-0	10 - 30%	1 ppm (S)	Not applicable

3. HAZARDS IDENTIFICATION

Hazard Overview May cause eye, skin, and respiratory burns. May cause headache, dizziness, and

other central nervous system effects. May be fatal if swallowed. May cause blindness. May be absorbed through the skin. May cause allergic skin reaction.

Flammable.

4. FIRST AID MEASURES

Inhalation If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably

mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

Skin In case of contact, immediately flush skin with plenty of soap and water for at least 15

minutes. Get medical attention. Remove contaminated clothing and launder before

reuse. Destroy or properly dispose of contaminated shoes.

Eyes In case of contact, or suspected contact, immediately flush eyes with plenty of water

for at least 15 minutes and get medical attention immediately after flushing.

Ingestion Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek

medical attention. Never give anything by mouth to an unconscious person.

Notes to Physician Not Applicable

FIRE FIGHTING MEASURES

Flash Point/Range (F): 58 Flash Point/Range (C): 14.4 **Flash Point Method: PMCC Autoignition Temperature (F):** 743 **Autoignition Temperature (C):** 395 Flammability Limits in Air - Lower (%): 4.4 Flammability Limits in Air - Upper (%): 16.1

Fire Extinguishing Media Water fog, carbon dioxide, foam, dry chemical.

Special Exposure Hazards May be ignited by heat, sparks or flames. Use water spray to cool fire exposed

surfaces. Closed containers may explode in fire. Decomposition in fire may produce

toxic gases.

Fire-Fighters

Special Protective Equipment for Full protective clothing and approved self-contained breathing apparatus required for

fire fighting personnel.

NFPA Ratings: Health 2, Flammability 3, Reactivity 0 Health 2, Flammability 3, Reactivity 0 **HMIS Ratings:**

ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures Use appropriate protective equipment. Wear self-contained breathing apparatus in

enclosed areas.

Environmental Precautionary

Measures

Prevent from entering sewers, waterways, or low areas.

Procedure for Cleaning /

Absorption

Isolate spill and stop leak where safe. Remove ignition sources and work with nonsparking tools. Contain spill with sand or other inert materials. Scoop up and

remove.

HANDLING AND STORAGE

Avoid contact with eyes, skin, or clothing. Avoid breathing vapors. Launder **Handling Precautions**

contaminated clothing before reuse. Wash hands after use, Ground and bond

containers when transferring from one container to another.

Storage Information Store away from oxidizers. Store away from acids. Store in a cool well ventilated

area. Keep container closed when not in use. Product has a shelf life of 24 months.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls Use in a well ventilated area.

Respiratory Protection Organic vapor respirator.

Hand Protection Nitrile gloves.

Skin Protection Rubber apron.

Eye Protection Chemical goggles; also wear a face shield if splashing hazard exists.

Other Precautions Eyewash fountains and safety showers must be easily accessible.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:

Color:

Cdor:

Cdor:

Amine

pH:

8.5-9

Specific Gravity @ 20 C (Water=1): Not Determined Density @ 20 C (lbs./gallon): Not Determined Bulk Density @ 20 C (lbs/ft3): Not Determined **Boiling Point/Range (F):** Not Determined **Boiling Point/Range (C):** Not Determined Freezing Point/Range (F): Not Determined Freezing Point/Range (C): Not Determined Vapor Pressure @ 20 C (mmHg): Not Determined Vapor Density (Air=1): Not Determined **Percent Volatiles:** Not Determined **Evaporation Rate (Butyl Acetate=1):** Not Determined Solubility in Water (g/100ml): Miscible

Solubility in Water (g/100ml):

Solubility in Solvents (g/100ml):

VOCs (lbs./gallon):

Viscosity, Dynamic @ 20 C (centipoise):

Viscosity, Kinematic @ 20 C (centistrokes):

Partition Coefficient/n-Octanol/Water:

Mot Determined

Not Determined

Not Determined

Not Determined

10. STABILITY AND REACTIVITY

Stability Data: Stable

Hazardous Polymerization: Will Not Occur

Conditions to Avoid Keep away from heat, sparks and flame.

Incompatibility (Materials to

Avoid)

Strong oxidizers. Strong acids. Copper and copper alloys.

Hazardous Decomposition

Products

Ammonia. Oxides of nitrogen. Carbon monoxide and carbon dioxide.

Additional Guidelines Not Applicable

11. TOXICOLOGICAL INFORMATION

Principle Route of Exposure Eye or skin contact, inhalation.

Inhalation May cause respiratory irritation. May cause central nervous system depression

including headache, dizziness, drowsiness, incoordination, slowed reaction time,

slurred speech, giddiness and unconsciousness.

Skin ContactCauses severe burns. May be absorbed through the skin and produce effects similar

to those caused by inhalation and/or ingestion. May cause an allergic skin reaction.

Eye Contact May cause eye burns.

Ingestion May be fatal or cause blindness if swallowed. Causes burns of the mouth, throat and

stomach. May cause headache, dizziness, nausea, vomiting, gastrointestinal

irritation and central nervous system depression.

Aggravated Medical Conditions Skin disorders.

Chronic Effects/Carcinogenicity Prolonged or repeated exposure may cause eye, blood, lung, liver, kidney, heart,

central nervous system and spleen damage.

Other Information None known.

Toxicity Tests

Oral Toxicity: Not determined

Dermal Toxicity: Not determined

Inhalation Toxicity: Not determined

Primary Irritation Effect: Not determined

Carcinogenicity Not determined

Genotoxicity: Not determined

Reproductive /

Developmental Toxicity:

Not determined

12. ECOLOGICAL INFORMATION

Mobility (Water/Soil/Air) Not determined

Persistence/Degradability Not determined

Bio-accumulation Not determined

Ecotoxicological Information

Acute Fish Toxicity: Not determined Acute Crustaceans Toxicity: Not determined Acute Algae Toxicity: Not determined

Chemical Fate Information Not determined

Other Information Not applicable

13. DISPOSAL CONSIDERATIONS

Disposal Method Disposal should be made in accordance with federal, state, and local regulations.

Contaminated Packaging Follow all applicable national or local regulations.

14. TRANSPORT INFORMATION

Land Transportation

DOT

UN1230, Methanol Solution, 3, II, (14.4 C) NAERG 131

Canadian TDG

Methanol Solution, 3, UN1230, II, (14.4 C)

ADR

UN1230, Methanol Solution, 3, II

Air Transportation

ICAO/IATA

UN1230, Methanol Solution, 3, II

Sea Transportation

IMDG

UN1230, Methanol Solution, 3, II, (14.4 C) EmS F-E, S-D

Other Shipping Information

Labels: Flammable Liquid

REGULATORY INFORMATION

US Regulations

US TSCA Inventory All components listed on inventory or are exempt.

EPA SARA Title III Extremely Hazardous Substances

Not applicable

EPA SARA (311,312) Hazard

Class

Acute Health Hazard Chronic Health Hazard

Fire Hazard

EPA SARA (313) Chemicals

This product contains toxic chemical(s) listed below which is(are) subject to the reporting requirements of Section 313 of Title III of SARA and 40 CFR Part 372:

Methanol//67-56-1

EPA CERCLA/Superfund Reportable Spill Quantity

EPA Reportable Spill Quantity is 1319 Gallons based on Methanol (CAS: 67-56-1).

EPA RCRA Hazardous Waste Classification

If product becomes a waste, it does meet the criteria of a hazardous waste as defined by the US EPA, because of:

Ignitability D001

California Proposition 65

All components listed do not apply to the California Proposition 65 Regulation.

MA Right-to-Know Law

One or more components listed.

NJ Right-to-Know Law

One or more components listed.

PA Right-to-Know Law

One or more components listed.

Canadian Regulations

Canadian DSL Inventory

All components listed on inventory. **CAT-4 WINTER BLEND**

Page 5 of 6

WHMIS Hazard Class

B2 Flammable Liquids
D1A Very Toxic Materials
D2B Toxic Materials
E Corrosive Material

16. OTHER INFORMATION

The following sections have been revised since the last issue of this MSDS

Not applicable

Additional Information For additional information on the use of this product, contact your local Halliburton

representative.

For questions about the Material Safety Data Sheet for this or other Halliburton

products, contact Chemical Compliance at 1-580-251-4335.

Disclaimer StatementThis information is furnished without warranty, expressed or implied, as to accuracy

or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of

the user.

END OF MSDS