HALLIBURTON

MATERIAL SAFETY DATA SHEET

Product Trade Name: CAUSTIC SODA BEADS

Revision Date: 03-Jan-2012

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name: CAUSTIC SODA BEADS

Synonyms:NoneChemical Family:HydroxideApplication:pH Control

Manufacturer/Supplier Halliburton Energy Services

P.O. Box 1431

Duncan, Oklahoma 73536-0431 Emergency Telephone: (281) 575-5000

Prepared By Chemical Compliance

Telephone: 1-580-251-4335

e-mail: fdunexchem@halliburton.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	CAS Number	PERCENT (w/w)	ACGIH TLV-TWA	OSHA PEL-TWA
Sodium hydroxide	1310-73-2	60 - 100%	2 mg/m ³	2 mg/M3

3. HAZARDS IDENTIFICATION

Hazard Overview May cause eye, skin, and respiratory burns. May be harmful if swallowed.

4. FIRST AID MEASURES

Inhalation If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably

mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

Skin In case of contact, immediately flush skin with plenty of soap and water for at least

15 minutes. Get medical attention. Remove contaminated clothing and launder

before reuse. Destroy or properly dispose of contaminated shoes.

Eyes In case of contact, or suspected contact, immediately flush eyes with plenty of

water for at least 15 minutes and get medical attention immediately after flushing.

Ingestion Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek

medical attention. Never give anything by mouth to an unconscious person.

Notes to Physician Not Applicable

5. FIRE FIGHTING MEASURES

Flash Point/Range (F):

Flash Point/Range (C):

Flash Point Method:

Autoignition Temperature (F):

Autoignition Temperature (C):

Flammability Limits in Air - Lower (%):

Flammability Limits in Air - Upper (%):

Not Determined

Not Determined

Not Determined

Fire Extinguishing Media All standard firefighting media.

Special Exposure Hazards May form explosive mixtures with strong acids. Reaction with steel and certain

other metals generates flammable hydrogen gas.

Special Protective Equipment

for Fire-Fighters

Full protective clothing and approved self-contained breathing apparatus required

for fire fighting personnel.

NFPA Ratings: Health 3, Flammability 0, Reactivity 2

HMIS Ratings: Health 3, Flammability 0, Physical Hazard 2, PPE: Eos

6. ACCIDENTAL RELEASE MEASURES

Personal Precautionary

Measures

Use appropriate protective equipment. Avoid creating and breathing dust.

Environmental Precautionary

Measures

Prevent from entering sewers, waterways, or low areas.

Procedure for Cleaning /

Absorption

Neutralize to pH of 6-8. Scoop up and remove.

7. HANDLING AND STORAGE

Handling Precautions Avoid contact with eyes, skin, or clothing. Avoid creating or inhaling dust. Wash

hands after use. Launder contaminated clothing before reuse.

Storage Information Store away from acids. Store in a cool, dry location. Product has a shelf life of 24

months.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls

Use in a well ventilated area. Localized ventilation should be used to control dust

levels.

Respiratory Protection Dust/mist respirator. (N95, P2/P3)

Hand Protection Impervious rubber gloves.

Skin Protection Full protective chemical resistant clothing.

Eye Protection Chemical goggles; also wear a face shield if splashing hazard exists.

Other Precautions Eyewash fountains and safety showers must be easily accessible.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Solid

Color: White to off white

Odor: Odorless pH: 14
Specific Gravity @ 20 C (Water=1): 2.13

Density @ 20 C (lbs./gallon): Not Determined

Bulk Density @ 20 C (lbs/ft3):71.5Boiling Point/Range (F):2530Boiling Point/Range (C):1388Freezing Point/Range (F):604Freezing Point/Range (C):318

Vapor Pressure @ 20 C (mmHg):

Vapor Density (Air=1):

Not Determined

Not Determined

Percent Volatiles:

Evaporation Rate (Butyl Acetate=1): Not Determined

Solubility in Water (g/100ml): Soluble

Solubility in Solvents (g/100ml): Soluble in alcohols

VOCs (lbs./gallon):

Viscosity, Dynamic @ 20 C (centipoise):

Viscosity, Kinematic @ 20 C (centistokes):

Partition Coefficient/n-Octanol/Water:

Not Determined

Not Determined

Molecular Weight (g/mole): 40

10. STABILITY AND REACTIVITY

Stability Data: Stable

Hazardous Polymerization: Will Not Occur

Conditions to Avoid None anticipated

Incompatibility (Materials to

Avoid)

Strong acids. Halogenated compounds. Prolonged contact with aluminum, lead, or

zinc may liberate flammable hydrogen.

Hazardous Decomposition

Products

None known.

Additional Guidelines Not Applicable

11. TOXICOLOGICAL INFORMATION

Principle Route of Exposure Eye or skin contact, inhalation.

Sympotoms related to exposure

Acute Toxicity

Inhalation Causes severe respiratory burns. May cause chemical pneumonia.

Eye ContactCauses severe eye burns.Skin ContactCauses severe burns.

Ingestion Causes burns of the mouth, throat and stomach.

Chronic Effects/Carcinogenicity Prolonged, excessive exposure may cause erosion of the teeth.

Toxicology data for the components

Substances	CAS Number	LD50 Oral	LD50 Dermal	LC50 Inhalation
Oubstances				
Sodium hydroxide	1310-73-2	No data available	1350 mg/kg (Rabbit)	No data available

12. ECOLOGICAL INFORMATION

Ecotoxicological Information

Ecotoxicity Product

Acute Fish Toxicity: Not determined
Acute Crustaceans Toxicity: Not determined
Acute Algae Toxicity: Not determined

Ecotoxicity Substance

Substances	CAS Number	Toxicity to Algae	Toxicity to Fish	Toxicity to	Toxicity to Invertebrates
				Microorganisms	
Sodium hydroxide	1310-73-2	No information available	LC50: 45.4 mg/l	No information available	EC50(48 h): 40.4 mg/L
			(Oncorhynchus mykiss)		(Ceriodaphnia sp.)

12.2. Persistence and degradability

Substances	CAS Number	Persistence and Degradability
Sodium hydroxide	1310-73-2	The methods for determining biodegradability are
		not applicable to inorganic substances.

12.3. Bioaccumulative potential

Substances	CAS Number	Log Pow
Sodium hydroxide	1310-73-2	No information available

12.4. Mobility in soil

No information available

12.5. Results of PBT and vPvB assessment

No information available.

12.6. Other adverse effects

13. DISPOSAL CONSIDERATIONS

Disposal MethodDisposal should be made in accordance with federal, state, and local regulations.

Contaminated Packaging This bag may contain residue of a hazardous material. Some authorities may

regulate such containers as hazardous waste. Dispose of container according to

national or local regulations.

14. TRANSPORT INFORMATION

US DOT

UN Number: UN1823

UN Proper Shipping Name: Sodium Hydroxide, Solid

Transport Hazard Class(es): 8
Packing Group: ||

NAERG: NAERG 154

US DOT Bulk

DOT (Bulk) Not Applicable

Canadian TDG ul0

UN Number: UN1823

UN Proper Shipping Name: Sodium Hydroxide, Solid

Transport Hazard Class(es): 8
Packing Group: |

CAUSTIC SODA BEADS Page 4 of 6 IMDG/IMO

UN Number: UN1823

UN Proper Shipping Name: Sodium Hydroxide, Solid

Transport Hazard Class(es): 8
Packing Group: 8

EMS: EmS F-A, S-B

IATA/ICAO

UN Number: UN1823

UN Proper Shipping Name: Sodium Hydroxide, Solid

Transport Hazard Class(es): 8 Packing Group:

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable

Special Precautions for User: None

Labels: Corrosive

15. REGULATORY INFORMATION

US Regulations

US TSCA Inventory All components listed on inventory or are exempt.

EPA SARA Title III Extremely

Hazardous Substances

Not applicable

EPA SARA (311,312) Hazard

Class

Acute Health Hazard

EPA SARA (313) Chemicals This product contains toxic chemical(s) listed below which is(are) subject to the

reporting requirements of Section 313 of Title III of SARA and 40 CFR Part 372:

Sodium Hydroxide//1310-73-2

EPA CERCLA/Superfund

Reportable Spill Quantity

EPA Reportable Spill Quantity is 1000 Pounds based on Sodium hydroxide (CAS:

1310-73-2).

EPA RCRA Hazardous Waste

Classification

If product becomes a waste, it does NOT meet the criteria of a hazardous waste

as defined by the US EPA.

California Proposition 65 All components listed do not apply to the California Proposition 65 Regulation.

MA Right-to-Know Law One or more components listed.

NJ Right-to-Know Law One or more components listed.

PA Right-to-Know Law One or more components listed.

Canadian Regulations

Canadian DSL Inventory All components listed on inventory or are exempt.

WHMIS Hazard Class E Corrosive Material

16. OTHER INFORMATION

The following sections have been revised since the last issue of this SDS Not applicable

Additional information For additional information on the use of this product, contact your local Halliburton

representative.

For questions about the Safety Data Sheet for this or other Halliburton products,

contact Chemical Compliance at 1-580-251-4335.

Disclaimer Statement This information is furnished without warranty, expressed or implied, as to

accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the

sole responsibility of the user.

END OF MSDS