

# MATERIAL SAFETY DATA SHEET

CEG 2000 Epoxy - Part A

## Section 1: PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** CEG 2000 Epoxy - Part A  
**Product Use:** Epoxy grout.  
**Manufacturer/Supplier:** Custom Building Products  
13001 Seal Beach Blvd  
Seal Beach, CA 90740  
**Phone Number:** (562) 598-8808  
**Emergency Phone:** (562) 598-8808  
**Date of Preparation:** November 15, 2008

## Section 2: HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

WARNING

HARMFUL IF SWALLOWED. MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN IRRITATION.

**Potential Health Effects:** See Section 11 for more information.

**Likely Routes of Exposure:** Skin contact, eye contact, inhalation, and ingestion.

**Eye:** May cause eye irritation.

**Skin:** May cause skin irritation. May cause sensitisation by skin contact.

**Ingestion:** Harmful if swallowed. May cause stomach distress, nausea or vomiting.

**Inhalation:** May cause respiratory tract irritation.

**Chronic Effects:** Prolonged or repeated contact may dry skin and cause irritation.

**Signs and Symptoms:** Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Irritating to respiratory tract.

**Medical Conditions Aggravated By Exposure:** Asthma. Allergies.

**Target Organs:** Skin, eyes, gastrointestinal tract, respiratory system.

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**Potential Environmental Effects:** May cause long-term adverse effects in the aquatic environment. See Section 12 for more information.

## Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS #	Wt. %
Diethylenetriamine	111-40-0	30 - 60
Bisphenol A	80-05-7	30 - 60
Silica, amorphous, fumed	7631-86-9	1 - 5
Silica, crystalline, quartz	14808-60-7	10 - 30
Titanium dioxide	13463-67-7	0.1 - 1

## Section 4: FIRST AID MEASURES

**Eye Contact:** In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. Get medical attention immediately.

# MATERIAL SAFETY DATA SHEET

CEG 2000 Epoxy - Part A

**Skin Contact:** In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.

**Inhalation:** Remove person to fresh air. If symptoms persist, obtain medical attention.

**Ingestion:** If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Seek medical attention or call poison control.

**General Advice:** In case of accident or if you feel unwell, seek medical advice immediately (show the label or MSDS where possible).

**Note to Physicians:** Symptoms may not appear immediately.

## Section 5: FIRE FIGHTING MEASURES

**Flammability:** Not flammable by WHMIS/OSHA criteria.

**Means of Extinction:**

**Suitable Extinguishing Media:** Treat for surrounding material.

**Unsuitable Extinguishing Media:** Not available.

**Products of Combustion:** May include, and are not limited to: oxides of carbon, oxides of nitrogen, ammonia.

**Explosion Data:**

**Sensitivity to Mechanical Impact:** Not available.

**Sensitivity to Static Discharge:** Not available.

**Protection of Firefighters:** Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

## Section 6: ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental Precautions:** Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

**Methods for Containment:** Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

**Methods for Clean-Up:** Soak into absorbent material. Spills of this material are a slipping hazard. Thoroughly wash the area with water after a spill or leak. Allow gas to dissipate harmlessly into the atmosphere.

**Other Information:** Not available.

## Section 7: HANDLING AND STORAGE

**Handling:**

Avoid contact with skin and eyes. Do not swallow. Do not breathe gas/fumes/vapor/spray. Handle and open container with care. When using do not eat or drink. Wash hands before eating, drinking, or smoking.

**Storage:**

Keep out of the reach of children. Keep container tightly closed.

# MATERIAL SAFETY DATA SHEET

CEG 2000 Epoxy - Part A

## Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure Guidelines

Ingredient	Exposure Limits	
	OSHA-PEL	ACGIH-TLV
Diethylenetriamine	Not available.	1 ppm
Bisphenol A	Not available.	Not available.
Silica, amorphous, fumed	80 mg/m <sup>3</sup> /%SiO <sub>2</sub>	10 mg/m <sup>3</sup>
Silica, crystalline, quartz	((10 mg/m <sup>3</sup> )/(%SiO <sub>2</sub> +2) TWA (resp)); ((30 mg/m <sup>3</sup> )/(%SiO <sub>2</sub> +2) TWA (total)); ((250)/(%SiO <sub>2</sub> +5) mppcf TWA (resp))	0.025 mg/m <sup>3</sup>
Titanium dioxide	15 mg/m <sup>3</sup> (total)	10 mg/m <sup>3</sup>

**Engineering Controls:** Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

### Personal Protective Equipment:

**Eye/Face Protection:** Wear eye/face protection.

**Hand Protection:** Wear suitable gloves.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** In case of insufficient ventilation, wear suitable respiratory equipment.

**General Hygiene Considerations:** Handle according to established industrial hygiene and safety practices.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Not available.
<b>Color:</b>	Not available.
<b>Odour:</b>	Characteristic.
<b>Odour Threshold:</b>	Not available.
<b>Physical State:</b>	Liquid.
<b>pH:</b>	11
<b>Viscosity:</b>	Not available.
<b>Freezing Point:</b>	Not available.
<b>Boiling Point:</b>	~ 200 °C (~ 392 °F)
<b>Flash Point:</b>	~ 112 °C (~ 233.6 °F)
<b>Evaporation Rate:</b>	Not available.
<b>Lower Flammability Limit:</b>	Not available.
<b>Upper Flammability Limit:</b>	Not available.
<b>Vapor Pressure:</b>	< 1 mm Hg @ 20 C
<b>Vapor Density:</b>	Not available.
<b>Specific Gravity:</b>	1.2
<b>Solubility in Water:</b>	Partial.
<b>Coefficient of Water/Oil Distribution:</b>	Not available.
<b>Auto-ignition Temperature:</b>	Not available.

# MATERIAL SAFETY DATA SHEET

CEG 2000 Epoxy - Part A

**Percent Volatile, wt. %:** Not available.

**VOC content, wt. %:** Not available.

## Section 10: STABILITY AND REACTIVITY

**Stability:** Stable under normal storage conditions.

**Conditions of Reactivity:** Heat. Incompatible materials.

**Incompatible Materials:** Acids. Oxidizers. Nitrates.

**Hazardous Decomposition Products:** May include, and are not limited to: oxides of carbon, oxides of nitrogen, ammonia.

**Possibility of Hazardous Reactions:** No dangerous reaction known under conditions of normal use.

## Section 11: TOXICOLOGY INFORMATION

### EFFECTS OF ACUTE EXPOSURE

#### Component Analysis

Ingredient	LD <sub>50</sub> (oral)	LC <sub>50</sub>
Diethylenetriamine	1080 mg/kg, rat	Not available.
Bisphenol A	3250 mg/kg, rat	Not available.
Silica, amorphous, fumed	Not available.	Not available.
Silica, crystalline, quartz	500 mg/kg, rat	Not available.
Titanium dioxide	Not available.	Not available.

**Eye:** May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

**Skin:** May cause skin irritation. May cause sensitisation by skin contact. Symptoms may include redness, drying, defatting and cracking of the skin.

**Ingestion:** Harmful if swallowed. May cause stomach distress, nausea or vomiting.

**Inhalation:** May cause respiratory tract irritation.

### EFFECTS OF CHRONIC EXPOSURE

**Target Organs:** Not available.

**Chronic Effects:** Hazardous by WHMIS/OSHA criteria.

**Carcinogenicity:** Hazardous by WHMIS/OSHA criteria.

Ingredient	Chemical Listed as Carcinogen or Potential Carcinogen *
Diethylenetriamine	Not listed.
Bisphenol A	Not listed.
Silica, amorphous, fumed	I-3, N-1, CP65
Silica, crystalline, quartz	G-A2, I-1, N-1, CP65
Titanium dioxide	I-2B

\* See Section 15 for more information.

**Mutagenicity:** Not hazardous by WHMIS/OSHA criteria.

**Reproductive Effects:** Hazardous by WHMIS/OSHA criteria.

**Developmental Effects:**

**Teratogenicity:** Not hazardous by WHMIS/OSHA criteria.

# MATERIAL SAFETY DATA SHEET

CEG 2000 Epoxy - Part A

**Embryotoxicity:** Not hazardous by WHMIS/OSHA criteria.

**Respiratory Sensitization:** Not hazardous by WHMIS/OSHA criteria.

**Skin Sensitization:** Hazardous by WHMIS/OSHA criteria.

**Toxicologically Synergistic Materials:** Not available.

## Section 12: ECOLOGICAL INFORMATION

**Ecotoxicity:** May cause long-term adverse effects in the aquatic environment.

**Persistence / Degradability:** Not available.

**Bioaccumulation / Accumulation:** Not available.

**Mobility in Environment:** Not available.

## Section 13: DISPOSAL CONSIDERATIONS

### Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

## Section 14: TRANSPORTATION INFORMATION

### DOT Classification

Not regulated

### TDG Classification

Not regulated

## Section 15: REGULATORY INFORMATION

### Federal Regulations

**Canadian:** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

**US:** MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200).

### SARA Title III

#### Ingredient

	<b>Section 302 (EHS) TPQ (lbs.)</b>	<b>Section 304 EHS RQ (lbs.)</b>	<b>CERCLA RQ (lbs.)</b>	<b>Section 313</b>
Diethylenetriamine	Not listed.	Not listed.	Not listed.	Not listed.
Bisphenol A	Not listed.	Not listed.	Not listed.	313
Silica, amorphous, fumed	Not listed.	Not listed.	Not listed.	Not listed.
Silica, crystalline, quartz	Not listed.	Not listed.	Not listed.	Not listed.
Titanium dioxide	Not listed.	Not listed.	Not listed.	Not listed.

### State Regulations

#### California Proposition 65:

This product contains chemicals known to the state of California to cause cancer.

# MATERIAL SAFETY DATA SHEET

CEG 2000 Epoxy - Part A

## Global Inventories

Ingredient	Canada DSL/NDSL	USA TSCA
Diethylenetriamine	DSL	Yes.
Bisphenol A	DSL	Yes.
Silica, amorphous, fumed	DSL	Yes.
Silica, crystalline, quartz	DSL	Yes.
Titanium dioxide	DSL	Yes.

## HMIS - Hazardous Materials Identification System

Health - 2      Flammability - 0      Physical Hazard - 0      PPE - B

## NFPA - National Fire Protection Association:

Health - 2      Fire - 0      Reactivity - 0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme

## WHMIS Classification(s):

- Class D2A - Carcinogenicity
- Class D2A - Reproductive Toxicity
- Class D2A - Chronic Toxic Effects
- Class D2B - Skin Sensitization
- Class D2B - Eye Irritant

## WHMIS Hazard Symbols:



## SOURCE AGENCY CARCINOGEN CLASSIFICATIONS:

**OSHA (O)** Occupational Safety and Health Administration.

**ACGIH (G)** American Conference of Governmental Industrial Hygienists.

- A1 - Confirmed human carcinogen.
- A2 - Suspected human carcinogen.
- A3 - Animal carcinogen.
- A4 - Not classifiable as a human carcinogen.
- A5 - Not suspected as a human carcinogen.

**IARC (I)** International Agency for Research on Cancer.

- 1 - The agent (mixture) is carcinogenic to humans.
- 2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.
- 2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.
- 3 - The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.
- 4 - The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

**NTP (N)** National Toxicology Program.

- 1 - Known to be carcinogens.
- 2 - Reasonably anticipated to be carcinogens.

# MATERIAL SAFETY DATA SHEET

CEG 2000 Epoxy - Part A

## Section 16: OTHER INFORMATION

**Disclaimer:**

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

**Expiry Date:** November 15, 2011

**Version #:** 1.0

**Prepared by:** Nexreg Compliance Inc.  
Phone: (519) 488-5126  
[www.nexreg.com](http://www.nexreg.com)