# **HALLIBURTON**

# **MATERIAL SAFETY DATA SHEET**

Product Trade Name: CEM-TROL 381

Revision Date: 04-Jan-2011

# 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name: CEM-TROL 381

Synonyms: None Chemical Family: Blend

**Application:** Cement Additive

Manufacturer/Supplier Baroid Fluid Services

Product Service Line of Halliburton

P.O. Box 1675 Houston, TX 77251

Telephone: (281) 871-4000

Emergency Telephone: (281) 575-5000

Prepared By Chemical Compliance

Telephone: 1-580-251-4335

e-mail: fdunexchem@halliburton.com

# 2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	CAS Number	PERCENT	ACGIH TLV-TWA	OSHA PEL-TWA
Hematite	1317-60-8	10 - 30%	Not applicable	Not applicable
Crystalline silica, tridymite	15468-32-3	0 - 1%	0.05 mg/m <sup>3</sup>	1/2 x 10 mg/m <sup>3</sup> %SiO2 + 2
Crystalline silica, cristobalite	14464-46-1	0 - 1%	0.025 mg/m <sup>3</sup>	1/2 x <u>10 mg/m³</u> %SiO2 + 2
Modified bentonite		30 - 60%	Not applicable	Not applicable
Crystalline silica, quartz	14808-60-7	2-6	0.025 mg/m <sup>3</sup>	10 mg/m <sup>3</sup> %SiO2 + 2

More restrictive exposure limits may be enforced by some states, agencies, or other authorities.

#### 3. HAZARDS IDENTIFICATION

Hazard Overview CAUTION! - ACUTE HEALTH HAZARD

May cause eye, skin, and respiratory irritation.

DANGER! - CHRONIC HEALTH HAZARD

Breathing crystalline silica can cause lung disease, including silicosis and lung cancer. Crystalline silica has also been associated with scleroderma and kidney disease.

This product contains quartz, cristobalite, and/or tridymite which may become airborne without a visible cloud. Avoid breathing dust. Avoid creating dusty conditions. Use only with adequate ventilation to keep exposures below recommended exposure limits. Wear a NIOSH certified, European Standard EN 149, or equivalent respirator when using this product. Review the Material Safety Data Sheet (MSDS) for this product, which has been provided to your employer.

#### 4. FIRST AID MEASURES

**Inhalation** If inhaled, remove from area to fresh air. Get medical attention if respiratory irritation

develops or if breathing becomes difficult.

**Skin** Wash with soap and water. Get medical attention if irritation persists.

Eyes In case of contact, immediately flush eyes with plenty of water for at least 15 minutes

and get medical attention if irritation persists.

**Ingestion** Under normal conditions, first aid procedures are not required.

Notes to Physician Not Applicable

#### 5. FIRE FIGHTING MEASURES

Flash Point/Range (F):

Flash Point/Range (C):

Flash Point Method:

Autoignition Temperature (F):

Flammability Limits in Air - Lower (%):

Flammability Limits in Air - Upper (%):

Not Determined

Not Determined

Not Determined

Not Determined

Not Determined

Fire Extinguishing Media All standard firefighting media.

Special Exposure Hazards Organic dust in the presence of an ignition source can be explosive in high

concentrations. Good housekeeping practices are required to minimize this

potential.

Special Protective Equipment for Not applicable.

Fire-Fighters

NFPA Ratings: Health 1, Flammability 1, Reactivity 0
HMIS Ratings: Health 1\*, Flammability 1, Physical Hazard 0

#### 6. ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures Use appropriate protective equipment. Avoid creating and breathing dust.

**Environmental Precautionary** 

Measures

None known.

Procedure for Cleaning / **Absorption** 

Collect using dustless method and hold for appropriate disposal. Consider possible toxic or fire hazards associated with contaminating substances and use appropriate methods for collection, storage and disposal.

# HANDLING AND STORAGE

**Handling Precautions** This product contains quartz, cristobalite, and/or tridymite which may become

> airborne without a visible cloud. Avoid breathing dust. Avoid creating dusty conditions. Use only with adequate ventilation to keep exposure below

recommended exposure limits. Wear a NIOSH certified, European Standard En 149,

or equivalent respirator when using this product. Material is slippery when wet.

**Storage Information** Do not reuse empty container. Store in a cool, dry location. Use good housekeeping

in storage and work areas to prevent accumulation of dust. Close container when

not in use. Product has a shelf life of 36 months.

# **EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Engineering Controls** Use approved industrial ventilation and local exhaust as required to maintain

exposures below applicable exposure limits listed in Section 2.

Wear a NIOSH certified, European Standard EN 149, or equivalent respirator when **Respiratory Protection** 

using this product.

**Hand Protection** Normal work gloves.

Wear clothing appropriate for the work environment. Dusty clothing should be Skin Protection

laundered before reuse. Use precautionary measures to avoid creating dust when

removing or laundering clothing.

**Eye Protection** Wear safety glasses or goggles to protect against exposure.

**Other Precautions** None known.

# PHYSICAL AND CHEMICAL PROPERTIES

Powder **Physical State:** 

Color: White to gray

Odor: Mild 11.8 (1%) pH:

Specific Gravity @ 20 C (Water=1): 2.5

Density @ 20 C (lbs./gallon): Not Determined

Bulk Density @ 20 C (lbs/ft3): 49 - 67

**Boiling Point/Range (F):** Not Determined **Boiling Point/Range (C):** Not Determined Freezing Point/Range (F): Not Determined Freezing Point/Range (C): Not Determined Vapor Pressure @ 20 C (mmHg): Not Determined Vapor Density (Air=1): Not Determined **Percent Volatiles:** Not Determined **Evaporation Rate (Butyl Acetate=1):** Not Determined

Solubility in Water (g/100ml): Insoluble

Solubility in Solvents (g/100ml): Not Determined VOCs (lbs./gallon): Not Determined Viscosity, Dynamic @ 20 C (centipoise): Not Determined Viscosity, Kinematic @ 20 C (centistrokes): Not Determined Partition Coefficient/n-Octanol/Water: Not Determined

> CEM-TROL 381 Page 3 of 7

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Molecular Weight (g/mole): Not Determined

# 10. STABILITY AND REACTIVITY

Stability Data: Stable

Hazardous Polymerization: Will Not Occur

Conditions to Avoid None anticipated

Incompatibility (Materials to

Avoid)

Hydrofluoric acid. Strong oxidizers.

**Hazardous Decomposition** 

**Products** 

Amorphous silica may transform at elevated temperatures to tridymite (870 C) or

cristobalite (1470 C). Carbon monoxide. Carbon dioxide. Oxides of sulfur.

Additional Guidelines Not Applicable

# 11. TOXICOLOGICAL INFORMATION

**Principle Route of Exposure** Eye or skin contact, inhalation.

**Inhalation** Inhaled crystalline silica in the form of quartz or cristobalite from occupational

sources is carcinogenic to humans (IARC, Group 1). There is sufficient evidence in

experimental animals for the carcinogenicity of tridymite (IARC, Group 2A).

Breathing silica dust may cause irritation of the nose, throat, and respiratory passages. Breathing silica dust may not cause noticeable injury or illness even though permanent lung damage may be occurring. Inhalation of dust may also have serious chronic health effects (See "Chronic Effects/Carcinogenicity" subsection

below).

**Skin Contact** May cause skin irritation.

**Eye Contact** May cause eye irritation.

**Ingestion** Irritation of the mouth, throat, and stomach.

bronchitis, or subject to eye irritation, should not be exposed to quartz dust.

#### **Chronic Effects/Carcinogenicity**

Cancer Status: The International Agency for Research on Cancer (IARC) has determined that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources can cause lung cancer in humans (Group 1 - carcinogenic to humans) and has determined that there is sufficient evidence in experimental animals for the carcinogenicity of tridymite (Group 2A - possible carcinogen to humans). Refer to IARC Monograph 68, Silica, Some Silicates and Organic Fibres (June 1997) in conjunction with the use of these minerals. The National Toxicology Program classifies respirable crystalline silica as "Known to be a human carcinogen". Refer to the 9th Report on Carcinogens (2000). The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica, quartz, as a suspected human carcinogen (A2).

There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of significant disease endpoints such as scleroderma (an immune system disorder manifested by scarring of the lungs, skin, and other internal organs) and kidney disease.

Silicosis: Excessive inhalation of respirable crystalline silica dust may cause a progressive, disabling, and sometimes-fatal lung disease called silicosis. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness, and reduced pulmonary function. This disease is exacerbated by smoking. Individuals with silicosis are predisposed to develop tuberculosis.

#### **Other Information**

For further information consult "Adverse Effects of Crystalline Silica Exposure" published by the American Thoracic Society Medical Section of the American Lung Association, American Journal of Respiratory and Critical Care Medicine, Volume 155, pages 761-768 (1997).

#### **Toxicity Tests**

Oral Toxicity: LD50: > 5000 mg/kg (Rat)

Dermal Toxicity: Not determined
Inhalation Toxicity: Not determined
Primary Irritation Effect: Not determined

Carcinogenicity Refer to IARC Monograph 68, Silica, Some Silicates and Organic Fibres (June

1997).

Genotoxicity: Not determined

Reproductive / Developmental Toxicity:

Not determined

# 12. ECOLOGICAL INFORMATION

Mobility (Water/Soil/Air) Not determined

Persistence/Degradability Not determined

Bio-accumulation Not determined

# **Ecotoxicological Information**

Acute Fish Toxicity: Not determined Acute Crustaceans Toxicity: Not determined

**Acute Algae Toxicity:** Not determined **Chemical Fate Information** Not determined Other Information Not applicable

#### **DISPOSAL CONSIDERATIONS**

Bury in a licensed landfill according to federal, state, and local regulations. **Disposal Method** 

**Contaminated Packaging** Follow all applicable national or local regulations.

# TRANSPORT INFORMATION

# **Land Transportation**

DOT

Not restricted

**Canadian TDG** 

Not restricted

**ADR** 

Not restricted

# **Air Transportation**

ICAO/IATA

Not restricted

# Sea Transportation

Not restricted

# **Other Shipping Information**

Labels: None

#### REGULATORY INFORMATION

# **US Regulations**

**US TSCA Inventory** All components listed on inventory or are exempt.

**EPA SARA Title III Extremely** 

**Hazardous Substances** 

Not applicable

**EPA SARA (311,312) Hazard** 

Class

Acute Health Hazard Chronic Health Hazard

**EPA SARA (313) Chemicals** 

This product does not contain a toxic chemical for routine annual "Toxic Chemical

Release Reporting" under Section 313 (40 CFR 372).

**EPA CERCLA/Superfund** Reportable Spill Quantity Not applicable.

**EPA RCRA Hazardous Waste** 

Classification

If product becomes a waste, it does NOT meet the criteria of a hazardous waste as

defined by the US EPA.

**California Proposition 65** The California Proposition 65 regulations apply to this product.

MA Right-to-Know Law One or more components listed.

**NJ Right-to-Know Law**One or more components listed.

PA Right-to-Know Law One or more components listed.

**Canadian Regulations** 

Canadian DSL Inventory All components listed on inventory.

WHMIS Hazard Class D2A Very Toxic Materials

Crystalline silica

# 16. OTHER INFORMATION

# The following sections have been revised since the last issue of this MSDS

Not applicable

**Additional Information** For additional information on the use of this product, contact your local Halliburton

representative.

For questions about the Material Safety Data Sheet for this or other Halliburton

products, contact Chemical Compliance at 1-580-251-4335.

**Disclaimer Statement** This information is furnished without warranty, expressed or implied, as to accuracy

or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of

the user.

\*\*\*END OF MSDS\*\*\*