SAFETY DATA SHEET



Date of issue/Date of revision 17 August 2016

Version 5.01

Section 1. Identification

Product name : COLOR BANK COL R ROJO EXTERIOR

Product code : 19A0670309
Other means of : Not available.

identification

Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Product use : Consumer applications.

Use of the substance/

mixture

: Pigment paste

Uses advised against : Not applicable.

Manufacturer : Comercial Mexicana de Pinturas S.A. de C.V.

Marcos Achar Lobatón, No. 6

Tepexpan, Acolman de Nezahualcóyotl

Estado de México CP. 55885 Tel. 01 (55)1669-1400 (México)

Emergency telephone

number

: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) 01-800-00-21-400 (Mexico)

Customer Service /

Technical Phone Number : 01-(55) 1669-3400 (México)

Section 2. Hazards identification

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

: ACUTE TOXICITY (oral) - Category 4

SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (Respiratory tract

irritation) - Category 3

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (kidneys) -

Category 2

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 34.5%

GHS label elements

United States Page: 1/13

Date of issue 17 August 2016

Version 5.01

Product name COLOR BANK COL R ROJO EXTERIOR

Section 2. Hazards identification

Hazard pictograms





Signal word : Warning

Hazard statements : Harmful if swallowed.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure. (kidneys)

Precautionary statements

General : Read label before use. Keep out of reach of children. If medical advice is needed,

have product container or label at hand.

Prevention: Use only outdoors or in a well-ventilated area. Do not breathe vapor. Do not eat, drink

or smoke when using this product. Wash hands thoroughly after handling.

Response : Get medical attention if you feel unwell. IF INHALED: Remove person to fresh air and

keep comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF SWALLOWED: Call a POISON CENTER or physician if you feel unwell. Rinse

mouth.

Storage : Store locked up.

Disposal : Dispose of contents and container in accordance with all local, regional, national and

international regulations.

Supplemental label

elements

: Avoid contact with skin and clothing. Wash thoroughly after handling. Emits toxic fumes

when heated.

Hazards not otherwise

classified

: Prolonged or repeated contact may dry skin and cause irritation.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Product name : COLOR BANK COL R ROJO EXTERIOR

| Ingredient name | % | CAS number |
|---|--|---|
| Talc , not containing asbestiform fibres 2,2' -oxybisethanol ethanediol Cyclohexanamine, N,N-dimethyl-, compd. with α-isotridecyl-ω-hydroxypoly(oxy-1,2-ethanediyl) phosphate | ≥20 - ≤50 ≥20 - ≤50 ≥10 - ≤20 ≥1.0 - ≤5.0 | 14807-96-6 111-46-6 107-21-1 164383-18-0 |

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

United States Page: 2/13

Product name COLOR BANK COL R ROJO EXTERIOR

Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessary first aid measures

Eye contact: Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids

apart for at least 10 minutes and seek immediate medical advice.

Inhalation : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained

personnel.

Skin contact : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water

or use recognized skin cleanser. Do NOT use solvents or thinners.

Ingestion : If swallowed, seek medical advice immediately and show this container or label. Keep

person warm and at rest. Do NOT induce vomiting.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact: No known significant effects or critical hazards.

Inhalation : May cause respiratory irritation.

Skin contact: Defatting to the skin. May cause skin dryness and irritation.

Ingestion: Harmful if swallowed.

Over-exposure signs/symptoms

Eve contact: No specific data.

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact: Adverse symptoms may include the following:

irritation dryness cracking

Ingestion: No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed.

The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments: No specific treatment.

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. If it is

suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to

give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

United States Page: 3/13

Date of issue 17 August 2016

Version 5.01

Product name COLOR BANK COL R ROJO EXTERIOR

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon dioxide

carbon monoxide nitrogen oxides phosphorus oxides halogenated compounds metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

United States Page: 4/13

Product name COLOR BANK COL R ROJO EXTERIOR

Section 6. Accidental release measures

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Special precautions

: If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits | | | |
|--|--|--|--|--|
| Talc , not containing asbestiform fibres | ACGIH TLV (United States, 3/2015). | | | |
| - | TWA: 2 mg/m³ 8 hours. Form: Respirable | | | |
| | fraction | | | |
| | OSHA PEL Z3 (United States, 2/2013). | | | |
| | TWA: 20 mppcf 8 hours. Form: not | | | |
| | containing asbestos | | | |
| 2,2' -oxybisethanol | IPEL (PPG). | | | |
| | TWA: 10 mg/m³ | | | |
| ethanediol | ACGIH TLV (United States, 3/2015). | | | |
| | United States Page: 5/13 | | | |

Date of issue 17 August 2016 Version 5.01

Product name COLOR BANK COL R ROJO EXTERIOR

Section 8. Exposure controls/personal protection

Cyclohexanamine, N,N-dimethyl-, compd. with α-isotridecyl-ωhydroxypoly(oxy-1,2-ethanediyl) phosphate

C: 100 mg/m³ Form: Aerosol

None.

Key to abbreviations

= Acceptable Maximum Peak S = Potential skin absorption ACGIH = American Conference of Governmental Industrial Hygienists. SR = Respiratory sensitization С = Ceiling Limit SS = Skin sensitization

F STEL = Short term Exposure limit values = Fume

IPEL = Internal Permissible Exposure Limit TD = Total dust OSHA Occupational Safety and Health Administration. TLV = Threshold Limit Value R = Respirable TWA = Time Weighted Average

= OSHA 29 CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances 7

Consult local authorities for acceptable exposure limits.

procedures

Recommended monitoring: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection Skin protection

: Safety glasses with side shields.

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Gloves

: For prolonged or repeated handling, use the following type of gloves:

Recommended: nitrile rubber, Chloroprene, PVC

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

> **United States** Page: 6/13

Product name COLOR BANK COL R ROJO EXTERIOR

Section 8. Exposure controls/personal protection

Other skin protection : Appropriate footwear and any additional skin protection measures should be selected

based on the task being performed and the risks involved and should be approved by a

specialist before handling this product.

Respirator selection must be based on known or anticipated exposure levels, the **Respiratory protection**

hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate. certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying

with an approved standard if a risk assessment indicates this is necessary.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid.

Color Not available. Odor : Not available. Not available. Odor threshold pH Not available. **Melting point** : Not available. **Boiling point** : >37.78°C (>100°F)

Flash point : Closed cup: Not applicable. [Product does not sustain combustion.]

Auto-ignition temperature : Not available. **Decomposition temperature** : Not available. Flammability (solid, gas) : Not available. Lower and upper explosive

(flammable) limits

: Not available.

Evaporation rate : Not available. Vapor pressure : Not available. Vapor density : Not available.

Relative density : 1.29 : 10.77 Density (lbs/gal)

Solubility : Soluble in the following materials: cold water.

Partition coefficient: n-

octanol/water

: Not available.

Viscosity : Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)

Volatility : 75% (v/v), 58.32% (w/w)

% Solid. (w/w) : 41.68

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

United States Page: 7/13

Product name COLOR BANK COL R ROJO EXTERIOR

Section 10. Stability and reactivity

Conditions to avoid : When exposed to high temperatures may produce hazardous decomposition products.

Refer to protective measures listed in sections 7 and 8.

Incompatible materials : Keep away from the following materials to prevent strong exothermic reactions:

oxidizing agents, strong alkalis, strong acids.

Hazardous decomposition products

: Decomposition products may include the following materials: carbon monoxide, carbon

dioxide, smoke, oxides of nitrogen.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|---|--------------------------|---------------|----------------------------|----------|
| 2,2' -oxybisethanol | LD50 Dermal LD50 Oral | Rabbit Rat | 11890 mg/kg 12000 mg/kg | - |
| ethanediol | LD50 Dermal LD50 Oral | Rabbit | 9.53 g/kg 4700 mg/kg | - |
| Cyclohexanamine, N,N-dimethyl-, compd. with α- | LD50 Oral | | >2500 mg/kg | _ |
| isotridecyl-ω-hydroxypoly(oxy- 1,2-ethanediyl) phosphate | | | | |

Conclusion/Summary: There are no data available on the mixture itself.

Irritation/Corrosion

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Eyes : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Sensitization

Conclusion/Summary

Skin : There are no data available on the mixture itself.

Respiratory : There are no data available on the mixture itself.

Mutagenicity

Conclusion/Summary: There are no data available on the mixture itself.

Carcinogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Reproductive toxicity

Conclusion/Summary: There are no data available on the mixture itself.

Teratogenicity

Conclusion/Summary: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

United States Page: 8/13

Product name COLOR BANK COL R ROJO EXTERIOR

Section 11. Toxicological information

| Name | Category |
|--|------------|
| Talc , not containing asbestiform fibres | Category 3 |

Specific target organ toxicity (repeated exposure)

| Name | Category | |
|--------------------------------|--------------------------|--|
| 2,2' -oxybisethanol ethanediol | Category 2 Category 2 | |

Target organs

: Contains material which may cause damage to the following organs: kidneys, lungs, liver, cardiovascular system, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

Aspiration hazard

Not available.

Information on the likely routes of exposure

Potential acute health effects

Eye contact : No known significant effects or critical hazards.

Inhalation : May cause respiratory irritation.

Skin contact : Defatting to the skin. May cause skin dryness and irritation.

: Harmful if swallowed. Ingestion

Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact : Adverse symptoms may include the following:

> irritation dryness cracking

Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Conclusion/Summary : There are no data available on the mixture itself. If splashed in the eyes, the liquid may

cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral,

inhalation and dermal routes of exposure and eye contact.

Short term exposure

Potential immediate

: There are no data available on the mixture itself.

Potential delayed effects

: There are no data available on the mixture itself.

Long term exposure

: There are no data available on the mixture itself. Potential immediate

effects

effects

Potential delayed effects : There are no data available on the mixture itself.

Potential chronic health effects

United States Page: 9/13

Product name COLOR BANK COL R ROJO EXTERIOR

Section 11. Toxicological information

General : May cause damage to organs through prolonged or repeated exposure. Prolonged or

repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.

Carcinogenicity: No known significant effects or critical hazards.

Mutagenicity: No known significant effects or critical hazards.

Teratogenicity: No known significant effects or critical hazards.

Developmental effects: No known significant effects or critical hazards.

Fertility effects: No known significant effects or critical hazards.

No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

| Route | ATE value |
|-------|-------------|
| Oral | 885.4 mg/kg |

Section 12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|---|-------------------|---------|----------|
| Cyclohexanamine, N,N-dimethyl-, compd. with α-isotridecyl-ω-hydroxypoly(oxy-1,2-ethanediyl) phosphate | LC50 1 to 10 mg/l | Fish | 96 hours |

Persistence and degradability

Not available.

Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|--------------------------------|----------------|-----|------------|
| 2,2' -oxybisethanol ethanediol | -1.47 -1.36 | - | low low |

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a

United States Page: 10/13

Date of issue 17 August 2016

Version 5.01

Product name COLOR BANK COL R ROJO EXTERIOR

Section 13. Disposal considerations

safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information

| | DOT | IMDG | IATA |
|------------------------------|--|-----------------|-----------------|
| UN number | UN3082 | Not regulated. | Not regulated. |
| UN proper shipping name | ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ethanediol) | - | - |
| Transport hazard class (es) | 9 | - | - |
| Packing group | III | - | - |
| Environmental hazards | No. | No. | No. |
| Marine pollutant substances | Not applicable. | Not applicable. | Not applicable. |
| Product RQ (lbs) | 34288.8 | Not applicable. | Not applicable. |
| RQ substances | (ethanediol) | Not applicable. | Not applicable. |

Additional information

DOT

: The classification of the product is due solely to the presence of one or more US DOT-listed 'Hazardous substances' that are subject to reportable quantity requirements and only applies to shipments of packages greater than, or equal to, the product reportable quantity. Package sizes less than the product reportable quantity are not regulated as hazardous materials.

IMDG : None identified. **IATA** : None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

> **United States** Page: 11/13

Date of issue 17 August 2016

Version 5.01

Product name COLOR BANK COL R ROJO EXTERIOR

Section 15. Regulatory information

United States

United States inventory (TSCA 8b): All components are listed or exempted.

United States - TSCA 5(a)2 - Final significant new use rules:

Cyclohexanamine, N,N-dimethyl-, compd. with α-isotridecyl-ω-hydroxypoly(Listed P-96-1176

oxy-1,2-ethanediyl) phosphate

SARA 302/304

SARA 304 RQ : Not applicable.

Composition/information on ingredients

No products were found.

SARA 311/312

Classification : Immediate (acute) health hazard

Delayed (chronic) health hazard

Composition/information on ingredients

| Name | Fire hazard | Sudden release of pressure | Reactive | Immediate (acute) health hazard | Delayed (chronic) health hazard |
|---|----------------|----------------------------------|----------|--|--|
| Falc , not containing asbestiform fibres 2,2' -oxybisethanol ethanediol Cyclohexanamine, N,N-dimethyl-, compd. with α-isotridecyl-ω-hydroxypoly(oxy-1,2-ethanediyl) phosphate | No. | No. | No. | Yes. | No. |
| | No. | No. | No. | Yes. | Yes. |
| | No. | No. | No. | Yes. | Yes. |
| | No. | No. | No. | Yes. | No. |

SARA 313

Chemical name

CAS number Concentration

Supplier notification : ethanediol

107-21-1 10 - 30

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health: 2 * Flammability: 0 Physical hazards: 0

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)

Health: 2 Flammability: 0 Instability: 0

United States Page: 12/13

Product name COLOR BANK COL R ROJO EXTERIOR

Section 16. Other information

Date of previous issue : 6/14/2016

Organization that prepared the MSDS

: EHS

Key to abbreviations

: ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

United States Page: 13/13