HALLIBURTON

MATERIAL SAFETY DATA SHEET

Product Trade Name: CORE GUN LOAD ASSEMBLY LOW TEMP

Revision Date: 03-Jan-2013

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name: CORE GUN LOAD ASSEMBLY LOW TEMP

Synonyms: LOAD ASSEMBLY, CORE GUN, LOW TEMP, 400 CRTG - 100004188

LOAD ASSEMBLY, CORE GUN, LOW TEMP, 450 CRTG - 100004189 LOAD ASSEMBLY, CORE GUN, LOW TEMP, 500 CRTG - 100004190 LOAD ASSEMBLY, CORE GUN, LOW TEMP, 550 CRTG - 100142074 LOAD ASSEMBLY, CORE GUN, LOW TEMP, 600 CRTG - 100142075

Chemical Family: Explosive

Application: Explosive Charge

Manufacturer/Supplier Halliburton Energy Services

P.O. Box 1431

Duncan, Oklahoma 73536-0431

Emergency Telephone: (281) 575-5000

Prepared By Chemical Compliance

Telephone: 1-580-251-4335

e-mail: fdunexchem@halliburton.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	CAS Number	PERCENT	ACGIH TLV-TWA	OSHA PEL-TWA
Nitroglycerin	55-63-0	2 - 40%	0.05 ppm	0.2 ppm
Nitrocellulose	9004-70-0	60 - 98%	Not applicable	Not applicable

3. HAZARDS IDENTIFICATION

Hazard Overview Explosive. May cause eye, skin, and respiratory irritation. May cause headache,

dizziness, and other central nervous system effects. May be harmful if swallowed.

4. FIRST AID MEASURES

Inhalation If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably

mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

Skin Wash with soap and water. Get medical attention if irritation persists.

Eyes In case of contact, or suspected contact, immediately flush eyes with plenty of water

for at least 15 minutes and get medical attention immediately after flushing.

Ingestion Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek

medical attention. Never give anything by mouth to an unconscious person.

Notes to Physician Treat symptomatically.

5. FIRE FIGHTING MEASURES

Flash Point/Range (F):

Flash Point/Range (C):

Flash Point Method:

Autoignition Temperature (F):

Flammability Limits in Air - Lower (%):

Flammability Limits in Air - Upper (%):

Not Determined

Not Determined

Not Determined

Not Determined

Not Determined

Fire Extinguishing Media None. Do NOT fight fire. Isolate area and evacuate personnel to a safe area. Guard

against intruders. Allow fire to burn itself out.

Special Exposure Hazards May detonate with impact or on heating. May explode and throw fragments 1 mile or

more in fire. Evacuate all persons, including emergency responders.

Special Protective Equipment for Not applicable.

Fire-Fighters

NFPA Ratings: Health 1, Flammability 3, Reactivity 4
HMIS Ratings: Health 1, Flammability 3, Reactivity 4

6. ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures Use appropriate protective equipment. Use only competent persons for cleanup.

Environmental Precautionary

Measures

Prevent from entering sewers, waterways, or low areas.

Procedure for Cleaning /

Absorption

Isolate area and remove sources of friction, impact, heat, low level electrical current,

and RF energy. Remove ignition sources and work with non-sparking tools.

7. HANDLING AND STORAGE

Handling Precautions Avoid contact with eyes, skin, or clothing. Do NOT consume food, drink, or tobacco

in contaminated areas. Wash hands after use. Launder contaminated clothing before

reuse.

Storage Information Store only in ATF approved magazines. Keep away from friction, impact, and heat.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls Use in a well ventilated area.

Respiratory Protection Dust/mist respirator. (N95, P2/P3)

Hand Protection Cloth gloves.

Skin Protection Cotton coveralls, undergarments, and socks. Conductive soled shoes.

Eye Protection Wear safety glasses or goggles to protect against exposure.

Other Precautions None known.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:SolidColor:MetallicOdor:Odorless

PHYSICAL AND CHEMICAL PROPERTIES

pH: Not Determined Specific Gravity @ 20 C (Water=1): Not Determined Density @ 20 C (lbs./gallon): Not Determined Bulk Density @ 20 C (lbs/ft3): Not Determined **Boiling Point/Range (F):** Not Determined **Boiling Point/Range (C):** Not Determined Freezing Point/Range (F): Not Determined Freezing Point/Range (C): Not Determined Vapor Pressure @ 20 C (mmHg): Not Determined Vapor Density (Air=1): Not Determined **Percent Volatiles:** Not Determined **Evaporation Rate (Butyl Acetate=1):** Not Determined Solubility in Water (q/100ml): Insoluble Solubility in Solvents (g/100ml): Not Determined Not Determined VOCs (lbs./gallon): Viscosity, Dynamic @ 20 C (centipoise): Not Determined Viscosity, Kinematic @ 20 C (centistokes): Not Determined Partition Coefficient/n-Octanol/Water: Not Determined Molecular Weight (g/mole): Not Determined

10. STABILITY AND REACTIVITY

Stable **Stability Data:**

Hazardous Polymerization: Will Not Occur

Conditions to Avoid May detonate with friction, impact, heat, and low level electrical current.

Incompatibility (Materials to

Avoid)

Strong acids. Strong alkalis.

Hazardous Decomposition

Products

Shrapnel. Oxides of nitrogen. Metal oxides. Carbon monoxide and carbon dioxide.

Additional Guidelines Not Applicable

TOXICOLOGICAL INFORMATION 11.

Principle Route of Exposure Eye or skin contact, inhalation. Product does not present exposures health hazards

during normal handling and use. However, this product is an explosive material and uncontrolled detonation may cause severe physical injury including death. All explosives are dangerous and must be handles carefully and used following

approved safety procedures under the direction of competent, experience persons in

accordance with all applicable regulations and ordinances.

Inhalation May cause effects to the blood and blood system. May cause central nervous system

depression including headache, dizziness, drowsiness, incoordination, slowed

reaction time, slurred speech, giddiness and unconsciousness.

May cause damage to the nervous, urinary, and reproductive systems. Nitrogen

oxides generated during use are irritating to the respiratory system.

Skin Contact May be absorbed through the skin and contribute to the symptoms listed under

ingestion. Nitrogen oxides generated during use are skin irritants.

Eye Contact May cause eye irritation.

Ingestion May cause abdominal pain, vomiting, nausea, and diarrhea.

Aggravated Medical Conditions None known. Chronic Effects/Carcinogenicity Prolonged or repeated exposure may cause blood forming system, nervous, urinary

tract and reproductive system damage. Prolonged or repeated exposure may cause

embryo and fetus toxicity.

Other Information None known.

Toxicity Tests

Oral Toxicity: Not determined

Dermal Toxicity: Not determined

Inhalation Toxicity: Not determined

Primary Irritation Effect: Not determined

Carcinogenicity Not determined

Genotoxicity: Not determined

Reproductive /

Not determined

Developmental Toxicity:

12. ECOLOGICAL INFORMATION

Mobility (Water/Soil/Air) Not determined

Persistence/Degradability Not applicable

Bio-accumulation Not determined

Ecotoxicological Information

Acute Fish Toxicity: Not determined Acute Crustaceans Toxicity: Not determined Acute Algae Toxicity: Not determined

Chemical Fate Information Not determined

Other Information Not applicable

13. DISPOSAL CONSIDERATIONS

Disposal Method Disposal should be made in accordance with federal, state, and local regulations.

Contaminated Packaging Do NOT reuse container. Store only in ATF approved magazines.

14. TRANSPORT INFORMATION

Land Transportation

DOT

UN0278, Cartridges, Oil Well, 1.4C, II EX-1985070019 EX-1985070020 EX-1985070021 EX-1985070022 EX-1985070023 NAERG 114

Canadian TDG

Cartridges, Oil Well, 1.4C, UN0278, II

EX-1985070019 EX-1985070020 EX-1985070021 EX-1985070022 EX-1985070023

ADR

UN0278, Cartridges, Oil Well, 1.4C, II

EX-1985070019 EX-1985070020 EX-1985070021 EX-1985070022 EX-1985070023

Air Transportation

ICAO/IATA

UN0278, Cartridges, Oil Well, 1.4C, II

EX-1985070019 EX-1985070020 EX-1985070021 EX-1985070022 EX-1985070023

Sea Transportation

IMDG

UN0278, Cartridges, Oil Well, 1.4C, II EX-1985070019 EX-1985070020 EX-1985070021 EX-1985070022 EX-1985070023 EmS F-B, S-X

Other Transportation Information

Labels: Explosive 1.4C

15. REGULATORY INFORMATION

US Regulations

US TSCA Inventory Product contains one or more components not listed on the inventory.

EPA SARA Title III Extremely

Hazardous Substances

Not applicable

EPA SARA (311,312) Hazard

Class

Sudden Release of Pressure Hazard

Acute Health Hazard

Fire Hazard

EPA SARA (313) Chemicals

This product does not contain a toxic chemical for routine annual "Toxic Chemical

Release Reporting" under Section 313 (40 CFR 372).

EPA CERCLA/Superfund Reportable Spill Quantity

Not applicable.

EPA RCRA Hazardous Waste

Classification

If product becomes a waste, it does meet the criteria of a hazardous waste as

defined by the US EPA, because of:

Reactivity D003

California Proposition 65 All components listed do not apply to the California Proposition 65 Regulation.

MA Right-to-Know Law Does not apply.

NJ Right-to-Know Law Does not apply.

PA Right-to-Know Law Does not apply.

CORE GUN LOAD ASSEMBLY LOW TEMP Page 5 of 6

Canadian Regulations

Canadian DSL Inventory Product contains one or more components not listed on the inventory.

WHMIS Hazard Class F Dangerously Reactive Material

D2B Toxic Material Causing Other Toxic Effects

16. OTHER INFORMATION

The following sections have been revised since the last issue of this MSDS

Not applicable

Additional Information For additional information on the use of this product, contact your local Halliburton

representative.

For questions about the Material Safety Data Sheet for this or other Halliburton

products, contact Chemical Compliance at 1-580-251-4335.

Disclaimer Statement This information is furnished without warranty, expressed or implied, as to accuracy

or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of

the user.

END OF MSDS