

MATERIAL SAFETY DATA SHEET**I - PRODUCT IDENTIFICATION****COMPANY NAME:** Crosstex International**ADDRESS:** 10 Rannick Rd.
Hauppauge, NY 11788**TEL. NO.:** (631) 582-6777**EMERGENCY:** Infotrac: 1-800-535-5053**PRODUCT NAME:** Tartar, Light Stain & Permanent Cement Remover**PRODUCT NO(S):** JEZTS**Synonyms:** Sulfamic Acid Solution**II - HAZARDOUS INGREDIENTS OF MIXTURES**

MATERIAL:	CAS #	Hazard	% By Wt.	TLV	PEL
Sulfamic Acid	5329-14-6	Corrosive	15%	-----	-----

III - PHYSICAL DATA

ND = Not Determined

Vapor Pressure, mm Hg: ND**Evaporation Rate (ether = 1):** ND**Solubility in H₂O:** Very soluble**Boiling Point:** 214°F**Specific Gravity (H₂O = 1):** 1.09 g/ml**Vapor Density (Air = 1):** ND**% Volatile by volume:** 86%**pH:** 0.5 - 0.9**Appearance:** Clear liquid**Odor:** Sweet**IV - FIRE AND EXPLOSION****Flash Point:** 210°F TCC**Flammable Limits:** Not determined**Extinguishing Media:** CO₂, Dry Chemical**Special Fire Fighting Procedures:** Firefighters should be equipped with self-contained breathing apparatus to protect against potentially toxic and irritation fumes.**Unusual Fire and Explosion Hazards:** None**V - REACTIVITY DATA****Stability:** Unstable ☐
Stable ☒**Conditions to Avoid:** None**Incompatibility:** (Materials to Avoid) Contact with strong alkaline materials.**Hazardous Decomposition Products:** None**Hazardous Polymerization:** May Occur ☐
Will Not Occur ☒**Conditions to Avoid:** None

Tartar, Light Stain & Permanent Cement Remover

VI - HEALTH HAZARDS

OSHA Permissible Exposure Limit: None

ACGIH Threshold Exposure Limit: None

Other Exposure Limit Used: None

A. Acute Overexposure: Skin irritation or burns

B. Chronic, Other: Not known

Medical Conditions Generally Aggravated by Exposure: None known

Primary Route(s) of Exposure: Eye and skin contact; accidental ingestion

Hygienic Practices: Do not place in unlabeled container

Chemical Listed as Carcinogen or Potential Carcinogen: Not listed with NTP, IARC or OSHA as a suspect carcinogen.

VII - EMERGENCY AND FIRST AID PROCEDURES

Skin: Immediately flush skin with plenty of water and soap.

Ingestion: If swallowed seek medical advice immediately.

Eyes: Immediately flush eyes with plenty of water for at least 15 minutes. Obtain medical attention if irritation continues.

VIII - SPILL OR LEAK PROCEDURES

Spill Management: Treat as acid spill. Use absorbent to collect material.

Waste Disposal Methods: This material is corrosive. Dispose of in accordance with Local, State and Federal regulations.

IX - PROTECTION INFORMATION / CONTROL MEASURES

Respiratory: None

Eye Protection: Safety glasses

Gloves: Latex gloves; non-impervious

Other Clothing and Equipment: None

Ventilation: None

X - SPECIAL PRECAUTIONS

Precautions to be Taken in Handling and Storing: Keep away from heat.

XI - ADDITIONAL INFORMATION

Oral LD₅₀ for Sulfamic Acid is 3160mg/kg; Rabbit dermal 500mg/24 hr. produced severe irritation.

Date: May 13, 2013

Supersedes MSDS Dated: None

We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and these opinions and the conditions of use of the product are not within the control of Darby Dental Supply, it is the users obligation to determine the conditions of safe use of the product.
--