		Page: 1
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 2/14/2017
		SDS Number: R0405608
Car Brite™ LASER BRITE™ Mild Lotion Polish & Protectant CBO1A048-03		Version: 1.1

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Car Brite™ LASER BRITE™
Mild Lotion Polish & Protectant

Recommended use of the chemical and restrictions on use

Use of the Substance/Mixture : Personal care
Metal polish

Details of the supplier of the safety data sheet Niteo Products, LLC P.O. Box 191629 Dallas TX 75219 United States of America	Emergency telephone number CHEMTREC DIRECT 1-800-424-9300 Product Information 1-844-696-4836
--	---

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Reproductive toxicity : Category 2

GHS Label element


Hazard pictograms :



Signal Word : Warning

Hazard Statements : Flammable liquid and vapor.
Suspected of damaging fertility or the unborn child.

Precautionary Statements : If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Read label before use.

		Page: 2
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 2/14/2017
		SDS Number: R0405608
Car Brite™ LASER BRITE™ Mild Lotion Polish & Protectant		Version: 1.1
CBO1A048-03		

Prevention:

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep container tightly closed.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ ventilating/ lighting/ equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF exposed or concerned: Get medical advice/ attention.
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

Store in a well-ventilated place. Keep cool.
Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards


None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture
Chemical nature : Aspiration hazard
Chemical nature : Defatter

Hazardous components


Chemical Name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	Flam. Liq. 3; H226 STOT SE 3; H336 Asp. Tox. 1; H304	14.02
GLYCERIN	56-81-5	Not a hazardous	2.00

		Page: 3
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 2/14/2017
		SDS Number: R0405608
Car Brite™ LASER BRITE™ Mild Lotion Polish & Protectant CBO1A048-03		Version: 1.1

		substance or mixture.	
ALKOXY-TERMINATED AMINOALKYL-FUNCTIONAL SILOXANE	67923-07-3	Eye Irrit. 2A; H319	1.00
OCTAMETHYLCYCLOTETRASIL OXANE	556-67-2	Flam. Liq. 3; H226 Repr. 2; H361	0.10

SECTION 4. FIRST AID MEASURES

General advice	: Move out of dangerous area. Call a POISON CENTRE or doctor/physician if exposed or you feel unwell. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: If breathed in, move person into fresh air. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: If on skin, rinse well with water. First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water. If on clothes, remove clothes.
In case of eye contact	: Flush eyes with water as a precaution. Remove contact lenses. Protect unharmed eye. If eye irritation persists, consult a specialist.
If swallowed	: Obtain medical attention. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material.

		Page: 4
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 2/14/2017
		SDS Number: R0405608
Car Brite™ LASER BRITE™ Mild Lotion Polish & Protectant CBO1A048-03		Version: 1.1


Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
 stomach or intestinal upset (nausea, vomiting, diarrhea)
 irritation (nose, throat, airways)
 Lung irritation
 confusion
 irregular heartbeat
 Convulsions
 Suspected of damaging fertility or the unborn child.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
 Water spray
 Foam
 Alcohol-resistant foam
 Carbon dioxide (CO₂)
 Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.
 Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
 Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide
 Hydrocarbons
 aluminum oxides
 silicon oxides
 formaldehyde
 Aldehydes
 nitrogen oxides (NO_x)
- Specific extinguishing methods :

 Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
 Use a water spray to cool fully closed containers.

		Page: 5
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 2/14/2017
		SDS Number: R0405608
Car Brite™ LASER BRITE™ Mild Lotion Polish & Protectant		Version: 1.1
CBO1A048-03		


Special protective equipment : In the event of fire, wear self-contained breathing apparatus. for firefighters

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | |
|---|--|
| Personal precautions, protective equipment and emergency procedures | : Evacuate personnel to safe areas.
Remove all sources of ignition.
Ensure adequate ventilation.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. |
| Environmental precautions | : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities. |
| Methods and materials for containment and cleaning up | : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). |
| Other information | : Comply with all applicable federal, state, and local regulations.
Suppress (knock down) gases/vapours/mists with a water spray jet. |

SECTION 7. HANDLING AND STORAGE

- | | |
|-----------------------------|--|
| Advice on safe handling | : Open drum carefully as content may be under pressure.
Avoid formation of aerosol.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Container hazardous when empty.
Take precautionary measures against static discharges.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations. |
| Conditions for safe storage | : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions. |

		Page: 6
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 2/14/2017
		SDS Number: R0405608
Car Brite™ LASER BRITE™ Mild Lotion Polish & Protectant		Version: 1.1
CBO1A048-03		

No smoking.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	TWA	200 mg/m3 Non-aerosol (as total hydrocarbon vapor)	ACGIH
		REL	100 mg/m3	NIOSH/GUID E
GLYCERIN	56-81-5	PEL	15 mg/m3 Total dust.	OSHA_TRA NS
		PEL	5 mg/m3 Respirable fraction.	OSHA_TRA NS

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment


Respiratory protection : A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

Hand protection
Remarks

: The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

		Page: 7
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 2/14/2017
		SDS Number: R0405608
Car Brite™ LASER BRITE™ Mild Lotion Polish & Protectant CBO1A048-03		Version: 1.1

Skin and body protection : Wear as appropriate:
 impervious clothing
 Safety shoes
 Flame-resistant clothing
 Choose body protection according to the amount and concentration of the dangerous substance at the work place.
 Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Colour : off-white

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : 32 °F / 0 °C
 No data available

Boiling point/boiling range : 149 °F / 65 °C
 (1,013.333333 hPa)
 Calculated Phase Transition Liquid/Gas

Flash point : 109.9 °F / 43.3 °C
 Method: Pensky Martens closed cup

Evaporation rate : 0.36

Flammability (solid, gas) :
 No data available


Flammability (liquids) : Static Accumulating liquid

Flammability (liquids) :
 Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : 23.3333333 hPa (20 °C)
 Calculated Vapor Pressure

Relative vapour density : 4.9

		Page: 8
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 2/14/2017
		SDS Number: R0405608
Car Brite™ LASER BRITE™ Mild Lotion Polish & Protectant		Version: 1.1
CBO1A048-03		

Relative density : No data available

Density : 0.9916 g/cm3

Solubility(ies)

Water solubility : soluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 10,000 mm2/s (40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Vapours may form explosive mixture with air.


Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong bases
Strong oxidizing agents
strong reducing agents

Hazardous decomposition products

acrolein
Aldehydes
carbon dioxide and carbon monoxide
formaldehyde
Hydrocarbons
silicon oxides

SECTION 11. TOXICOLOGICAL INFORMATION

		Page: 9
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 2/14/2017
		SDS Number: R0405608
Car Brite™ LASER BRITE™ Mild Lotion Polish & Protectant CBO1A048-03		Version: 1.1

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC 50 (Rat, male and female): > 5.28 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD 50 (Rabbit): > 2,000 mg/kg
Assessment: No adverse effect has been observed in acute dermal toxicity tests.

GLYCERIN:

Acute oral toxicity : LD 50 (Rat): 12,600 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC 50 (Rat): > 570 mg/m³
Exposure time: 1 h
Assessment: Not classified as acutely toxic by inhalation under GHS.

Acute dermal toxicity : LD 50 (Rabbit): > 10 g/kg

OCTAMETHYLCYCLOTETRASILOXANE:

Acute oral toxicity : LD 50 (Rat): > 4,800 mg/kg
Assessment: Not classified as acutely toxic by ingestion under GHS.

Acute inhalation toxicity : LC50 (Rat): 36 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist


Acute dermal toxicity : LD50 (Rabbit): > 2,400 mg/kg
Assessment: Not classified as acutely toxic by dermal absorption under GHS.
Remarks: No mortality observed at this dose.

Skin corrosion/irritation

Not classified based on available information.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

		Page: 10
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 2/14/2017
		SDS Number: R0405608
Car Brite™ LASER BRITE™ Mild Lotion Polish & Protectant CBO1A048-03		Version: 1.1

Components:

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Result: Mildly irritating to skin

GLYCERIN:

Result: Not irritating to skin

ALKOXY-TERMINATED AMINOALKYL-FUNCTIONAL SILOXANE:

Result: Not irritating to skin

OCTAMETHYLCYCLOTETRASILOXANE:

Species: Rabbit

Result: Not irritating to skin

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Result: Mildly irritating to eyes

GLYCERIN:

Result: Mildly irritating to eyes

ALKOXY-TERMINATED AMINOALKYL-FUNCTIONAL SILOXANE:

Result: Irritating to eyes

OCTAMETHYLCYCLOTETRASILOXANE:

Species: Rabbit

Result: Slightly irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

OCTAMETHYLCYCLOTETRASILOXANE:

Test Type: Maximisation Test (GPMT)

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Components:


OCTAMETHYLCYCLOTETRASILOXANE:

Genotoxicity in vitro : Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

		Page: 11
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 2/14/2017
		SDS Number: R0405608
Car Brite™ LASER BRITE™ Mild Lotion Polish & Protectant CBO1A048-03		Version: 1.1

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Components:

OCTAMETHYLCYCLOTETRAISILOXANE:

Reproductive toxicity - : Some evidence of adverse effects on sexual function and
Assessment fertility, based on animal experiments.

STOT - single exposure

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration toxicity classification

Components:

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Solvents may degrease the skin.

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP


No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

GLYCERIN:

Toxicity to fish : LC 50 (Goldfish (Carassius auratus)): > 5,000 mg/l

		Page: 12
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 2/14/2017
		SDS Number: R0405608
Car Brite™ LASER BRITE™ Mild Lotion Polish & Protectant CBO1A048-03		Version: 1.1

Exposure time: 24 h
Method: Static
Remarks: Mortality

Toxicity to daphnia and other aquatic invertebrates : LC 50 (Water flea (Daphnia magna)): > 10,000 mg/l
Exposure time: 24 h
Method: Static
Remarks: Mortality

OCTAMETHYLCYCLOTETRASILOXANE:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 0.022 mg/l
Exposure time: 96 h
Test Type: flow-through test
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : NOEC (Daphnia magna (Water flea)): >= 0.015 mg/l
Exposure time: 48 h
Test Type: flow-through test
Remarks: No toxicity at the limit of solubility

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 0.022 mg/l
End point: Growth inhibition
Exposure time: 96 h
Remarks: No toxicity at the limit of solubility

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): >= 0.0044 mg/l
Exposure time: 93 d
Test Type: flow-through test
Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia (water flea)): 0.0079 mg/l
Exposure time: 21 d
Test Type: flow-through test
Remarks: No toxicity at the limit of solubility

Ecotoxicology Assessment
Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.


Persistence and degradability

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT:

Biodegradability : Result: Inherently biodegradable
Biodegradation: 58.6 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

OCTAMETHYLCYCLOTETRASILOXANE:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 3.7 %
Exposure time: 29 d
Method: OECD Test Guideline 310

		Page: 13
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 2/14/2017
		SDS Number: R0405608
Car Brite™ LASER BRITE™ Mild Lotion Polish & Protectant CBO1A048-03		Version: 1.1

Bioaccumulative potential

GLYCERIN:

Partition coefficient: n-octanol/water : log Pow: -1.76

OCTAMETHYLCYCLOTETRASILOXANE:

Bioaccumulation : Species: Fathead minnow (Pimephales promelas)
Bioconcentration factor (BCF): 14,261
Exposure time: 28 d
Concentration: 0.00016 mg/l
Method: Flow through

Partition coefficient: n-octanol/water : log Pow: 6.488 (25 °C)
Method: OECD Test Guideline 123

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods


General advice : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

		Page: 14
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 2/14/2017
		SDS Number: R0405608
Car Brite™ LASER BRITE™ Mild Lotion Polish & Protectant		Version: 1.1
CBO1A048-03		

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

UN	1993	FLAMMABLE LIQUID, N.O.S. (ALIPHATIC PETROLEUM DISTILLATES)	3	III
----	------	---	---	-----

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO


UN	1993	Flammable liquid, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES)	3	III
----	------	---	---	-----

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

UN	1993	Flammable liquid, n.o.s. (ALIPHATIC PETROLEUM DISTILLATES)	3	III
----	------	---	---	-----

MX_DG

UN	1993	LIQUIDO INFLAMABLE, N.E.P. (ALIPHATIC PETROLEUM DISTILLATES)	3	III
----	------	---	---	-----

		Page: 15
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 2/14/2017
		SDS Number: R0405608
Car Brite™ LASER BRITE™ Mild Lotion Polish & Protectant CBO1A048-03		Version: 1.1

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Fire Hazard
Chronic Health Hazard

SARA 313 Component(s) : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Pennsylvania Right To Know

WATER	7732-18-5	70.00 - 90.00 %
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	10.00 - 20.00 %
ALUMINUM SILICATE CALCINED	66402-68-4	5.00 - 10.00 %
GLYCERIN	56-81-5	1.00 - 5.00 %

New Jersey Right To Know


WATER	7732-18-5	70.00 - 90.00 %
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT	64742-47-8	10.00 - 20.00 %
ALUMINUM SILICATE CALCINED	66402-68-4	5.00 - 10.00 %
DIMETHYL SILICONES AND SILOXANES	63148-62-9	1.00 - 5.00 %
GLYCERIN	56-81-5	1.00 - 5.00 %

California Prop 65 Proposition 65 warnings are not required for this product based on the results of a risk assessment.

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL.

		Page: 16
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 2/14/2017
		SDS Number: R0405608
Car Brite™ LASER BRITE™ Mild Lotion Polish & Protectant CBO1A048-03		Version: 1.1

AICS : On the inventory, or in compliance with the inventory
 ENCS : Not in compliance with the inventory
 KECI : On the inventory, or in compliance with the inventory
 PICCS : On the inventory, or in compliance with the inventory
 IECSC : On the inventory, or in compliance with the inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information


Revision Date: 07/31/2015

NFPA:	HMIS III:						
<p>Flammability</p>  <p>Health</p> <p>Instability</p> <p>Special hazard.</p>	<table border="1"> <tr> <td>HEALTH</td><td>1</td></tr> <tr> <td>FLAMMABILITY</td><td>2</td></tr> <tr> <td>PHYSICAL HAZARD</td><td>0</td></tr> </table> <p> 0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic </p>	HEALTH	1	FLAMMABILITY	2	PHYSICAL HAZARD	0
HEALTH	1						
FLAMMABILITY	2						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class II

Full text of H-Statements referred to under sections 2 and 3.

		Page: 17
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 2/14/2017
		SDS Number: R0405608
Car Brite™ LASER BRITE™ Mild Lotion Polish & Protectant		Version: 1.1
CBO1A048-03		

H226	Flammable liquid and vapor.
H304	May be fatal if swallowed and enters airways.
H313	May be harmful in contact with skin.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H361f	Suspected of damaging fertility.

Sources of key data used to compile the Safety Data Sheet

Internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

Cefic, the European Chemical Industry Council.

ESIS European Chemical Substances Information System

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Niteo's Environmental Health and Safety Department (1-844-696-4836).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx

N.O.S.: Not Otherwise Specified

OECD : Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit

P-Statement : Precautionary Statement


PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment

STEL : Short-term exposure limit

STOT : Specific Target Organ Toxicity

TLV : Threshold Limit Value

		Page: 18
SAFETY DATA SHEET		Revision Date: 07/31/2015
		Print Date: 2/14/2017
		SDS Number: R0405608
Car Brite™ LASER BRITE™ Mild Lotion Polish & Protectant CBO1A048-03		Version: 1.1

TWA : Time-weighted average

vPvB : Very Persistent and Very Bioaccumulative

WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act

DOT : Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act

HMIRC : Hazardous Materials Information Review Commission

HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System