SAFETY DATA SHEET Castrol

Section 1. Identification

Product name	Castrol TranSynd 668
SDS #	470369
Code	470369-US65
Relevant identified uses of	the substance or mixture and uses advised against
Product use	Automatic transmission fluid. For specific application advice see appropriate Technical Data Sheet or consult our company representative.
Supplier	BP Lubricants USA Inc. 1500 Valley Road Wayne, NJ 07470 Telephone: 1-888-CASTROL
	1 (800) 447-8735
INFORMATION:	Outside the US: +1 703-527-3887 (CHEMTREC)
EMERGENCY SPILL INFORMATION:	1 (800) 424-9300 CHEMTREC (USA)

Section 2. Hazards identification

OSHA/HCS status	This material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	Not classified.
GHS label elements	
Signal word	No signal word.
Hazard statements	No known significant effects or critical hazards.
Precautionary statements	
Prevention	Not applicable.
Response	Not applicable.
Storage	Not applicable.
Disposal	Not applicable.
Hazards not otherwise classified	Defatting to the skin.

Section 3. Composition/information on ingredients

Substance/mixture

Highly refined base oil (IP 346 DMSO extract < 3%). Proprietary performance additives.

Mixture

Section 3. Composition/information on ingredients

5		
Ingredient name	%	CAS number
Distillates (petroleum), hydrotreated light paraffinic	≥25 - ≤50	64742-55-8
Distillates (petroleum), hydrotreated heavy paraffinic	≥25 - ≤50	64742-54-7
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	≤3	72623-87-1
Distillates (petroleum), solvent-dewaxed heavy paraffinic	≤3	64742-65-0
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	≤3	72623-86-0
Distillates (petroleum), solvent-refined heavy paraffinic	≤3	64741-88-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures Eye contact In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention. Skin contact Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention if symptoms occur. Inhalation If inhaled, remove to fresh air. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. Get medical attention if symptoms occur. Ingestion Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur. **Protection of first-aiders** No action shall be taken involving any personal risk or without suitable training.

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	Treatment should in general be symptomatic and directed to relieving any effects. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
Specific treatments	No specific treatment.

Section 5. Fire-fighting measures

Extinguishing media		
Suitable extinguishing media	In case of fire, use foam, dry chemical or ca	rbon dioxide extinguisher or spray.
Unsuitable extinguishing media	Do not use water jet.	
Specific hazards arising from the chemical	In a fire or if heated, a pressure increase wil	l occur and the container may burst.
Hazardous combustion products	Combustion products may include the follow carbon oxides (CO, CO ₂) (carbon monoxide, nitrogen oxides (NO, NO ₂ etc.)	0
Special protective actions for fire-fighters	0,11	nal risk or without suitable training. Promptly om the vicinity of the incident if there is a fire.
Product name Castrol Trans	ynd 668 Product c	ode 470369-US65 Page: 2/10
Version 2.02 Date of issue	12/19/2023. Format US	Language ENGLISH

Section 5. Fire-fighting measures

Special protective equipment for fire-fighters

Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Section 6. Accidental release measures

Personal precautions, protectiv	ve equipment and emergency procedures
For non-emergency personnel	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.
For emergency responders	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non- emergency personnel".
Environmental precautions	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for con	tainment and cleaning up
Small spill	Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling **Protective measures** Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is Advice on general handled, stored and processed. Wash thoroughly after handling. Remove contaminated occupational hygiene clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures. Store in accordance with local regulations. Store in original container protected from Conditions for safe storage, direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials including any (see Section 10) and food and drink. Keep container tightly closed and sealed until incompatibilities ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. Not suitable Prolonged exposure to elevated temperature

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Distillates (petroleum), hydrotreated light paraffinic

OSHA PEL (United States). [Oil mist, mineral]

TWA: 5 mg/m³ 8 hours. Issued/Revised: 6/1993

ACGIH TLV (United States). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m³ 8 hours. Issued/Revised:

11/2009 Form: Inhalable fraction

Distillates (petroleum), hydrotreated heavy paraffinic

OSHA PEL (United States). [Oil mist, mineral]

Product name Castrol TranSynd 668	Product code	470369-US65 Pag	e: 3/10
Version 2.02 Date of issue 12/19/2023.	Format US	Language ENC	SLISH

Section 8. Exposure controls/personal protection

	TWA: 5 mg/m ³ 8 hours. Issued/Revised: 6/1993 ACGIH TLV (United States). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m ³ 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	None.
Distillates (petroleum), solvent-dewaxed heavy paraffinic	OSHA PEL (United States). [Oil mist, mineral] TWA: 5 mg/m ³ 8 hours. Issued/Revised: 6/1993 ACGIH TLV (United States). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m ³ 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	OSHA PEL (United States). [Oil mist, mineral] TWA: 5 mg/m ³ 8 hours. Issued/Revised: 6/1993 ACGIH TLV (United States). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m ³ 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction
Distillates (petroleum), solvent-refined heavy paraffinic	OSHA PEL (United States). [Oil mist, mineral] TWA: 5 mg/m ³ 8 hours. Issued/Revised: 6/1993 ACGIH TLV (United States). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m ³ 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction

Biological exposure indices

No exposure indices known.

Version 2.02 Date of issue 12/19/2023.

Appropriate engineering controls	considered after other forms of co suitably evaluated. Personal prot standards, be suitable for use, be Your supplier of personal protecti selection and appropriate standard organisation for standards. Provide exhaust ventilation or oth concentrations below their respect The final choice of protective equ	posures are adequately controlled. Personal protective equipment should only be asidered after other forms of control measures (e.g. engineering controls) have been tably evaluated. Personal protective equipment should conform to appropriate indards, be suitable for use, be kept in good condition and properly maintained. ar supplier of personal protective equipment should be consulted for advice on ection and appropriate standards. For further information contact your national anisation for standards. wide exhaust ventilation or other engineering controls to keep the relevant airborne incentrations below their respective occupational exposure limits. e final choice of protective equipment will depend upon a risk assessment. It is portant to ensure that all items of personal protective equipment are compatible. issions from ventilation or work process equipment should be checked to ensure they nply with the requirements of environmental protection legislation. In some cases,		
Environmental exposure controls		environmental prot ering modifications	ection legislation. In to the process equi	n some cases,
Individual protection measures				
Hygiene measures	Wash hands, forearms and face t eating, smoking and using the law techniques should be used to ren contaminated clothing before reus are close to the workstation locat	vatory and at the e nove potentially co sing. Ensure that	nd of the working pentities in the second seco	eriod. Appropriate . Wash
Eye/face protection	Safety glasses with side shields.			
Product name Castrol TranSy	nd 668	Product code	470369-US65	Page: 4/10

Format US

Language ENGLISH

Section 8. Exposure controls/personal protection

Skin protection	
Hand protection	Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.
Body protection	Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.
Other skin protection	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment. The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state	Liquid.			
Color	Red.			
Odor	Not available.			
Odor threshold	Not available.			
рН	Not applicable.			
Melting point/freezing point	Not available.			
Boiling point, initial boiling point, and boiling range	Not available.			
Flash point Pour point	Open cup: >210°C (≯ -51 °C	>410°F) [Cl	eveland]
Evaporation rate	Not available.			
Flammability	Not applicable. Base	d on - Phys	sical stat	te
Lower and upper explosion limit/flammability limit	Not available.			
Vapor pressure		Vapor	Pressu	re at 20°C
	Ingredient name	mm Ha	kPa	Method

	Vapor Pressure at 20°C			Vapor pressure at 50°C		
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
Distillates (petroleum), hydrotreated light paraffinic	<0.08	<0.011	ASTM D 5191			
Distillates (petroleum), hydrotreated heavy paraffinic	<0.08	<0.011	ASTM D 5191			
Lubricating oils (petroleum), C20-50,	<0.08	<0.011	ASTM D 5191			

Product nameCastrol TranSynd 668Version 2.02Date of issue 12/19/2023.

Product code

Section 9. Physical	and	l chemica	l pro	pertie	S			
	hydro base	otreated neutral oil- d						
		lates (petroleum), ent-dewaxed heavy finic	<0.08	<0.011	ASTM D 5191			
	(petro	cating oils bleum), C15-30, btreated neutral oil- d	<0.08	<0.011	ASTM D 5191			
Relative vapor density	Not a	Not available.						
Density	<1000 kg/m³ (<1 g/cm³) at 15°C							
Solubility(ies)								
Media		Result						
water		Not soluble						
Partition coefficient: n- octanol/water	Not a	Not applicable.						
Auto-ignition temperature	Not a	available.						
Decomposition temperature	Not available.							
Viscosity	Kinematic: 33 mm²/s (Kinematic: 6.5 to 7.5 r				i cSt) at 100°C			
Particle characteristics								
Median particle size	Not a	Not applicable.						

Section 10. Stability and reactivity

Reactivity	No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.	
Chemical stability	The product is stable.	
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur. Under normal conditions of storage and use, hazardous polymerization will not occur.	
Conditions to avoid	Avoid all possible sources of ignition (spark or flame).	
Incompatible materials	Reactive or incompatible with the following materials: oxidizing materials.	
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.	

Section 11. Toxicological information

Information on toxicological effects

Aspiration hazard				
Name		Result		
Distillates (petroleum), hydrotreated light paraffinic Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based		ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1 ASPIRATION HAZARD - Category 1		
Information on the likely routes of exposure	Routes of entry anticipated: Dermal, In	halation, Eyes.		
Potential acute health effects Eye contact	No known significant effects or critical	hazards.		

Skin contact No known significant effects or critical hazards.

Product name Castrol TranSynd 668	Product code	470369-US65	Page: 6/10
Version 2.02 Date of issue 12/19/2023.	Format US	Language	ENGLISH

Inhalation	Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
Ingestion	No known significant effects or critical hazards.
Symptoms related to the phys	sical, chemical and toxicological characteristics
Eye contact	No specific data.
Skin contact	Adverse symptoms may include the following: irritation dryness cracking
Inhalation	May be harmful by inhalation if exposure to vapor, mists or fumes resulting from thermal decomposition products occurs.
Ingestion	No specific data.
Delayed and immediate effect Short term exposure	s and also chronic effects from short and long term exposure
Potential immediate effects	Not available.
Potential delayed effects	Not available.
Long term exposure	
Potential immediate effects	Not available.
Potential delayed effects	Not available.
Potential chronic health effe	<u>cts</u>
General	No known significant effects or critical hazards.
Carcinogenicity	No known significant effects or critical hazards.
Mutagenicity	No known significant effects or critical hazards.
Teratogenicity	No known significant effects or critical hazards.
	No known significant effects or critical hazards.
Developmental effects	No known significant effects of childar hazards.

Numerical measures of toxicity

Acute toxicity estimates Not available.

Section 12. Ecological information

Toxicity

No testing has been performed by the manufacturer.

Persistence and degradability

Not expected to be rapidly degradable.

Bioaccumulative potential

This product is not expected to bioaccumulate through food chains in the environment.

Mobility in soil

Not available.

Soil/water partition coefficient (K_{oc}) Mobility

Not available.

Spillages may penetrate the soil causing ground water contamination.

Product name Castrol TranSynd 668	Product code	470369-US65 Page: 7/10
Version 2.02 Date of issue 12/19/2023.	Format US	Language ENGLISH

Section 12. Ecological information

Other adverse effects

No known significant effects or critical hazards.

Other ecological information

No known significant effects of childa hazards.

Spills may form a film on water surfaces causing physical damage to organisms. Oxygen transfer could also be impaired.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Transport hazard class(es)	-	-	-	-
Packing group	-	-	-	-
Environmental hazards	No.	No.	No.	No.
Additional information	-	-	-	-

Special precautions for user Not available.

Transport in bulk according Not available. to IMO instruments

Version 2.02 Date of issue 12/19/2023.

Section 15. Regulatory information

U.S. Federal regulations United States inventory All components are active or exempted. (TSCA 8b) SARA 302/304 **Composition/information on ingredients** No products were found. SARA 311/312 Classification Not applicable. **SARA 313** Form R - Reporting This product does not contain any hazardous ingredients at or above regulated thresholds. requirements **Supplier notification** This product does not contain any hazardous ingredients at or above regulated thresholds. State regulations Product name **Product code** 470369-US65 Castrol TranSynd 668 Page: 8/10

Format US

Language ENGLISH

Section 15. Regulatory information

Massachusetts	The following components are listed: MINERAL OIL, PETROLEUM DISTILLATES, HYDROTREATED LIGHT PARAFFINIC; OIL MIST, MINERAL; OIL MIST, MINERAL; OIL MIST, MINERAL; OIL MIST, MINERAL; OIL MIST, MINERAL
New Jersey	The following components are listed: MINERAL OIL (UNTREATED and MILDLY TREATED); Amines, polyethylenepoly-, reaction products with succinic anhydride polyisobutenyl derivs., borated
Pennsylvania	The following components are listed: Amines, polyethylenepoly-, reaction products with succinic anhydride polyisobutenyl derivs., borated
O allfamate Duran OF	

California Prop. 65

▲ WARNING: This product can expose you to chemicals including Benzene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including sulfur dioxide, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Other regulations

History

Australia inventory (AIIC)	All components are listed or exempted.
Canada inventory	All components are listed or exempted.
China inventory (IECSC)	All components are listed or exempted.
Japan inventory (CSCL)	All components are listed or exempted.
Korea inventory (KECI)	All components are listed or exempted.
Philippines inventory (PICCS)	All components are listed or exempted.
Taiwan Chemical Substances Inventory (TCSI)	All components are listed or exempted.
REACH Status	For the REACH status of this product please consult your company contact, as identified in Section 1.

Section 16. Other information

National Fire Protection Association (U.S.A.)



Date of issue/Date of revision	12/19/2023.
Date of previous issue	11/10/2023.
Prepared by	Product Stewardship
Key to abbreviations	 ACGIH = American Conference of Industrial Hygienists ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor CAS Number = Chemical Abstracts Service Registry Number GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) OEL = Occupational Exposure Limit SDS = Safety Data Sheet STEL = Short term exposure limit TWA = Time weighted average UN = United Nations UN Number = United Nations Number, a four digit number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods. Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64742-54-7, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7,

Product name Castrol TranSynd 668	Product code	470369-US65 Page: 9/10
Version 2.02 Date of issue 12/19/2023.	Format US	Language ENGLISH

Section 16. Other information

64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.