

Safety Data Sheet



Cleaner Fluid - Aerosol

Section 1 – Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product Code(s)

- Cleaner Fluid - Aerosol

Product Description

- 16-483
- Clear flammable liquid in aerosol form with a hydrocarbon odor.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified use(s)

- Cleaning compound.

Uses advised against

- No data available

1.3 Details of the supplier of the safety data sheet

Manufacturer

- Patch Rubber Company
100 Patch Rubber Road
Weldon, NC 27890
United States
sales@patchrubber.com

Telephone

Technical

- (252)-536-2574

Responsible Party - EU

- Christian Gimenez
Intertek Analytical Services France

Telephone

Technical

- 33 (0) 6 07 11 22 15

1.4 Emergency telephone number

Emergency

- 800-424-9300 - Chemtrec

Section 2 - Hazards Identification

EU/EEC

According to EU Directive 1272/2008 (CLP)/REACH 1907/2006 [amended by 453/2010]

According to EU Directive 67/548/EEC (DSD) or 1999/45/EC (DPD)

2.1 Classification of the substance or mixture

CLP/REACH

- Extremely Flammable Aerosol – Category 1 - H222
- Skin Irritant – Category 2 - H315
- Aspiration Toxicity – Category 1 - H304
- Specific Target Organ Toxicity Single Exposure – Category 3 - H336
- Chronic Hazard to Aquatic Environment – Category 1 - H410
- Acute Hazard to Aquatic Environment – Category 1 - H400

DSD/DPD

- F+ – Extremely Flammable – R12

- Xi – Irritant – R38
- Xn– Harmful – R65, R67
- N – Dangerous for the environment - R50/53

2.2 Label elements

CLP/REACH

DANGER



Hazard statements

- H222 – Extremely flammable aerosol.
- H315 – Causes skin irritation.
- H336 – May cause drowsiness or dizziness.
- H304 – May be fatal if swallowed and enters airways.
- H410 – Very toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

- P102 – Keep out of reach of children
- P210 – Keep away from heat/sparks/open flames/hot surfaces-No smoking.
- P211 – Do not spray on an open flame or other ignition source.
- P273 – Avoid releases to the environment.
- P251– Pressurized container: Do not pierce or burn, even after use.
- P280 – Wear protective gloves/protective clothing/eye protection/face protection

Response

- P301+P310 – IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P331 – Do NOT induce vomiting.

Storage/Disposal

- P501 – Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

DSD/DPD



Risk phrases

- R12 – Extremely flammable
- R38 – Irritating to skin
- R65 – Harmful: may cause lung damage if swallowed.
- R67 – Vapors may cause drowsiness and dizziness
- R50/53 – Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases

- S2 – Keep out of reach of children
- S9 – Keep container in a well-ventilated place
- S16 – Keep away from sources of ignition – No smoking
- S29 – Do not empty into drains
- S33 – take precautionary measures against static discharges
- S60 – This material and its container must be disposed of as hazardous waste
- S62 – Avoid releases to the environment. Refer to special instructions/safety data sheet
- S62 – If swallowed, do not induce vomiting: Seek medical advice immediately and show this container or label

2.3 Other hazards

- The components of this material contain less than 0.1% Benzene therefore the carcinogen and mutagen classifications of the components do not apply to the material.
- According to EU Directive 1272/2008 (CLP) this product is considered hazardous.
- This product is considered dangerous according to the European Directive 1999/45/EC.
- This material does not meet the criteria for PBT and vPvB.

UN GHS

According to United Nations - Third Revised Edition

2.1 Classification of the substance or mixture

- Extremely Flammable Aerosol – Category 1 - H222
- Skin Irritant – Category 2 - H315
- Aspiration Toxicity – Category 1 - H304
- Specific Target Organ Toxicity Single Exposure – Category 3 - H336

2.2 Label elements

- **DANGER**



Hazard statements

- H222 – Extremely Flammable Aerosol
- H315 – Causes skin irritation
- H336 – May cause drowsiness or dizziness
- H304 – May be fatal if swallowed and enters airways.

Precautionary statements

Prevention

- P102 – Keep out of reach of children
- P210 – Keep away from heat/sparks/open flames/hot surfaces-No smoking.
- P211 – Do not spray on an open flame or other ignition source.
- P251 – Pressurized container: Do not pierce or burn, even after use.
- P280 – Wear protective gloves/protective clothing/eye protection/face protection

Response

- P301+P310 – IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P331 – Do NOT induce vomiting.

Storage/Disposal

- P501 – Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

2.3 Other hazards

- According to the Globally Harmonized Standard for Classification and Labeling (GHS) this product is considered hazardous.

United States (US)

According to OSHA 29 CFR 1910.1200 HCS – Hazard Communication Standard

2.1 Classification of the substance or mixture

- Flammable Liquid, Flammable/Combustible - Class IB
- Irritant
- Central nervous system depressant (CNS)

2.2 Label elements

- Not Applicable

2.3 Other hazards

- Under United States Regulations (29 CFR 1900.1200 - Hazard Communication Standard), this product is considered hazardous.

Canada

According to WHMIS – Workplace Hazardous Material Information System

2.1 Classification of the substance or mixture

- Class B - Flammable and Combustible Materials - Division 5
- Class D - Poisonous and Infectious Materials - Division 2 - Subdivision B

2.2 Label elements



2.3 Other hazards

- In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

2.4 Other hazard rating systems

NFPA



Section 3 - Composition/Information on Ingredients

3.1 Substances

- Material does not meet the criteria of a Substance in accordance with Regulation (EC) No 1272/2008.

3.2 Mixtures

Chemical Name	Identifiers	%(wt)	LD50/LC50	Classifications According to Regulation/Directive	Comments
Heptane	CAS: 142-82-5 Index: 601-008-00-2 EINECS: 205-563-8 UN: UN1206	30% to 50%	Inhalation-Rat LC50 · 103 g/m ³ 4 Hour(s)	DSD/DPD: F; R11 Xi; R38 N; R50 R53 Xn; R65 R67; Note C; EU CLP: Flammable Liquid 2 - H225; Skin Irritant 2 - H315; Aspiration Toxicity 1 - H304; Specific Target Organ Toxicity Single Exposure 3 - H336; Chronic Hazard to Aquatic Environment 1 - H410; Acute Hazard to Aquatic Environment 1 - H400; Note C;	*
Solvent naphtha (petroleum), light aliph.	CAS: 64742-89-8 Index: 649-267-00-0 EINECS: 265-151-9	30% to 50%	NDA	DSD/DPD: Carc. Cat. 2; R46; Muta. Cat. 2; R46; Xn; R65; Notes: H, P; EU CLP: Carc. 1B - H350; Muta. 1B - H340; Asp. Tox. 1 - H304; Notes: H, P;	*
Isobutane	CAS: 75-28-5 Index: 601-004-00-0 EINECS: 200-857-2	0% to 25%	Inhalation Rat LC50 · 658000 mg/m ³ 4 Hour(s)	DSD/DPD: F+; R12 EU CLP: Flam. Gas 1 - H220; Press Gas	**
Propane	CAS: 74-98-6 Index: 601-003-00-5 EINECS: 200-827-9	0% to 25%	NDA	DSD/DPD: F+; R12 EU CLP: Flam. Gas 1 - H220; Press Gas	**

Key to abbreviations

* = This product may be composed, in whole or in part, of the above refinery streams.

** = Refers to a mixture of Isobutane and Propane.

Section 4 - First Aid Measures

4.1 Description of first aid measures

- | | |
|------------|---|
| Inhalation | <ul style="list-style-type: none"> Move victim to fresh air. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. |
| Skin | <ul style="list-style-type: none"> In case of contact with substance, immediately flush skin with running water for at least 20 minutes. Wash skin with soap and water. Take off contaminated clothing and wash before reuse. If skin irritation occurs: Get medical advice/attention. |
| Eye | <ul style="list-style-type: none"> IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. |
| Ingestion | <ul style="list-style-type: none"> Do NOT induce vomiting. If person is drowsy or unconscious and vomiting, place on the left side with head down. Seek medical attention. |

4.2 Most important symptoms and effects, both acute and delayed

- May cause skin irritation. Inhalation of vapors or fumes will cause central nervous system effects with symptoms of dizziness, drowsiness, lethargy, coma and death. Material aspirated into the lungs will cause lung damage, chemical pneumonitis, pulmonary edema or death.

4.3 Indication of any immediate medical attention and special treatment needed

- | | |
|--------------------|---|
| Notes to Physician | <ul style="list-style-type: none"> Material if aspirated into the lungs may cause chemical pneumonitis. Treat appropriately. |
|--------------------|---|

4.4 Other information

- Call 911 or emergency medical service. Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Keep victim warm and quiet.

Section 5 - Firefighting Measures

5.1 Extinguishing media

- | | |
|------------------------------|--|
| Suitable Extinguishing Media | <ul style="list-style-type: none"> Carbon dioxide (CO₂), water fog, dry chemical or chemical foam. |
|------------------------------|--|

Unsuitable Extinguishing Media
Firefighting Procedures

- Avoid the use of streaming water, as this may spread the fire.
- Move containers from fire area if you can do it without risk. Use water spray to cool containers exposed to fire.

5.2 Special hazards arising from the substance or mixture

Unusual Fire and Explosion Hazards

- **HIGHLY FLAMMABLE:** Will be easily ignited by heat, sparks or flames. Containers may explode when heated. Extremely flammable liquid and vapor. Vapors may form explosive mixtures with air. Vapor explosion hazard indoors, outdoors or in sewers. Vapors may travel to source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Hazardous Combustion Products

- Smoke, soot, fumes or vapors, oxides of carbon.

5.3 Advice for firefighters

- Structural firefighters' protective clothing will only provide limited protection. Wear positive pressure self-contained breathing apparatus (SCBA).

Section 6 - Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Precautions

- Wear appropriate protective equipment including respiratory protection as conditions warrant. Do not touch or walk through spilled material. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

Emergency Procedures

- As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area) Keep out of low areas. Keep unauthorized personnel away. Stay upwind. Ventilate closed spaces before entering.

6.2 Environmental precautions

- Prevent entry into waterways, sewers, basements or confined areas.

6.3 Methods and material for containment and cleaning up

Containment/Clean-up Measures

- Stop leak if you can do it without risk. All equipment used when handling the product must be grounded. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers. Use clean non-sparking tools to collect absorbed material. A vapor suppressing foam may be used to reduce vapors. LARGE SPILLS: Dike far ahead of liquid spill for later disposal.

6.4 Reference to other sections

- See Sections 8 and 13.

Section 7 - Handling and Storage

7.1 Precautions for safe handling

Handling

- Keep away from heat and ignition sources – No Smoking. Product can accumulate static charge by flow or agitation. Bond and ground equipment when transferring from one vessel to another. Empty containers retain product residue and may be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat, flame, sparks or other ignition sources. They may explode and cause injury or death. Use only with adequate ventilation. Do not enter confined spaces such tanks or pits without following proper entry procedures.

7.2 Conditions for safe storage, including any incompatibilities

Storage

- Store in a cool/low -temperature, well ventilated place away from heat and ignition sources. Keep container closed when not in use. Keep away from incompatible materials.

Incompatible Materials or Ignition Sources

- Keep away from heat, ignition sources oxidizers and strong acids.

7.3 Specific end use(s)

- See Section 1.2 – Relevant identified use(s)

Section 8 - Exposure Controls/Personal Protection

8.1 Control parameters

Engineering Measures/Controls

- Adequate ventilation systems as needed to control concentrations of airborne contaminants below applicable exposure limit values.

Exposure Limits/Guidelines						
	Result	ACGIH	Canada Ontario	Canada Quebec	France	Italy
Propane (74-98-6)	TWAs	1000 ppm TWA	1000 ppm TWAEV	1000 ppm TWAEV; 1800 mg/m3 TWAEV	Not established	Not established
Isobutane (75-28-5)	TWAs	1000 ppm TWA	Not established	Not established	Not established	Not established
Heptane (142-82-5)	TWAs	400 ppm TWA	400 ppm TWAEV; 1635 mg/m3 TWAEV	400 ppm TWAEV; 1640 mg/m3 TWAEV	400 ppm VME (restrictive limit); 1668 mg/m3 VME (restrictive limit)	500 ppm TWA; 2085 mg/m3 TWA
	STELs	500 ppm STEL	500 ppm STEV; 2045 mg/m3 STEV	500 ppm STEV; 2050 mg/m3 STEV	500 ppm VLCT (restrictive limit); 2085 mg/m3 VLCT (restrictive limit)	Not established

Exposure Limits/Guidelines(Con't.)			
	Result	NIOSH	OSHA
Propane (74-98-6)	TWAs	1000 ppm TWA; 1800 mg/m3 TWA	1000 ppm TWA; 1800 mg/m3 TWA
Isobutane (75-28-5)	TWAs	800 ppm TWA; 1900 mg/m3 TWA	Not established
Heptane (142-82-5)	TWAs	85 ppm TWA; 350 mg/m3 TWA	500 ppm TWA; 2000 mg/m3 TWA
	Ceilings	440 ppm Ceiling (15 min); 1800 mg/m3 Ceiling (15 min)	Not established

Exposure Control Notations

Italy

- Naphtha (petroleum), hydrotreated light (64742-49-0):**Carcinogens:Category 2 Carcinogen**
- Isobutane (75-28-5):**Carcinogens:Category 1 Carcinogen** (containing $\geq 0.1\%$ butadiene)
- Light aliphatic solvent naphtha (64742-89-8):**Carcinogens:Category 2 Carcinogen**

Exposure Limits Supplemental

ACGIH

- Isobutane (75-28-5):**TLV Basis - Critical Effects:**cardiac sensitization; CNS impairment
- Heptane (142-82-5):**TLV Basis - Critical Effects:**CNS impairment; upper respiratory tract irritation
- Propane (74-98-6):**TLV Basis - Critical Effects:**cardiac sensitization; CNS impairment

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene

VLCT = Valeurs limites d'exposition à court terme is the short-term exposure limit based on 15-minute exposure.

VME = Valeur Moyenne d'Exposition is the maximum permissible concentration for a work day

NIOSH = National Institute of Occupational Safety and Health

MSHA = Mine Safety and Health Administration

STEL = Short Term Exposure Limits are based on 15-minute exposures

STEV = Short Term Exposure Value

TWAEV = Time-Weighted Average Exposure Value

8.2 Exposure controls

Personal Protective Equipment

Pictograms



Respiratory

- In case of insufficient ventilation, wear suitable respiratory equipment. Follow the OSHA respirator regulations found in 29 CFR 1910.134. Use a NIOSH/MSHA approved respirator if exposure limits are exceeded or symptoms are experienced. If ventilation is not sufficient to effectively prevent buildup of dust, appropriate European Standard EN141 and/or EN405 approved respiratory equipment must be provided.

Eye/Face

- Wear safety goggles.

Hands

- Wear protective gloves -neoprene, butyl or nitrile rubber with cuffs.

Skin/Body

- Where extensive dermal exposure may be expected, either a chemical suit or chemical apron will be needed.

General Industrial Hygiene Considerations

- Handle in accordance with good industrial hygiene and safety practice. Wash

thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Safety shower and eye wash should be available close to work areas.

Section 9 - Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Physical Form:	Aerosol	Appearance/Description:	Clear flammable liquid in aerosol form with a hydrocarbon odor.
Color:	Clear	Odor:	Hydrocarbon
Taste:	No data available	Particulate Type:	No data available
Particulate Size:	No data available	Aerosol Type:	No data available
Odor Threshold:	No data available	Boiling Point:	195 to 210 F(90.5556 to 98.8889 C)
Melting Point:	No data available	Decomposition Temperature:	No data available
Heat of Decomposition:	No data available	pH:	No data available
Specific Gravity/Relative Density:	= 0.696 Water=1	Density:	= 5.797 lbs/gal
Bulk Density:	No data available	Water Solubility:	Negligible
Solvent Solubility:	No data available	Viscosity:	= 0.83 Centistoke (cSt, cS) or mm ² /sec @ 100 F(37.7778 C)
Vapor Pressure:	= 45 mmHg (torr) @ 20 C(68 F)	Vapor Density:	= 3.5 Air=1
Evaporation Rate:	= 2.8 n-Butyl Acetate = 1	VOC (Wt.):	No data available
VOC (Vol.):	No data available	Volatiles (Wt.):	No data available
Volatiles (Vol.):	No data available	Flash Point:	15 F(-9.4444 C)
Flash Point Test Type:	No data available	UEL:	6.7 %
LEL:	1 %	Heat of Combustion (ΔH _c):	No data available
Autoignition:	475 F(246.1111 C)	Self-Accelerating Decomposition Temperature (SADT):	No data available
Burning Time:	No data available	Flame Duration:	No data available
Flame Height:	No data available	Flame Extension:	> 18
Ignition Distance:	No data available	Half-Life:	No data available

Octanol/Water Partition coefficient:	2.1 to 5 log Kow	Coefficient of water/oil distribution:	No data available
Bioaccumulation Factor:	No data available	Bioconcentration Factor:	No data available
Biochemical Oxygen Demand BOD/BOD5:	No data available	Chemical Oxygen Demand:	No data available
Persistence:	No data available	Degradation:	No data available

9.2 Other Information

- No data available

Section 10 - Stability and Reactivity

10.1 Reactivity

- Not reactive

10.2 Chemical stability

- Stable under normal temperatures and pressures.

10.3 Possibility of hazardous reactions

- Hazardous polymerization will not occur.

10.4 Condition to avoid

- High temperatures, sparks, open flames and live electrical circuits.

10.5 Incompatible materials

- Oxidizing agents, strong acids.

10.6 Hazardous decomposition products

- In case of fire oxides of carbon, hydrocarbons, fumes or vapors, soot and smoke may be produced.

Section 11 - Toxicological Information

11.1 Information on toxicological effects

Component Name	Concentration	CAS	Data
Heptane	30% TO 50%	142-82-5	Acute Toxicity: ; ihl-rat LC50:103 gm/m3/4H; ihl-hmn TCLo:1000 ppm/6M; ihl-rat TCLo:420 mg/m3/12H/2W-I
Isobutane	0% TO 25%	75-28-5	Acute Toxicity: ; ihl-rat LC50:57 pph/15M

Key to abbreviations

- LC = Lethal Concentration
TC = Toxic Concentration

GHS Properties	Classification
Acute toxicity - oral	EU/CLP: Classification criteria not met UN GHS: Classification criteria not met
Acute toxicity - dermal	EU/CLP: Classification criteria not met UN GHS: Classification criteria not met
Acute toxicity - inhalation	EU/CLP: Classification criteria not met UN GHS: Classification criteria not met
Skin corrosion/Irritation	EU/CLP: Category 2 UN GHS: Category 2
Serious eye damage/Irritation	EU/CLP: Classification criteria not met UN GHS: Classification criteria not met
Skin sensitization	EU/CLP: Classification criteria not met UN GHS: Classification criteria not met

Respiratory sensitization	EU/CLP: Data lacking UN GHS: Classification criteria not met
Aspiration hazard	EU/CLP: Category 1 UN GHS: Category 1
Carcinogenicity	EU/CLP: Classification criteria not met UN GHS: Classification criteria not met
Germ cell mutagenicity	EU/CLP: Classification criteria not met UN GHS: Classification criteria not met
Toxicity for reproduction/ fertility	EU/CLP: Classification criteria not met UN GHS: Classification criteria not met
Toxicity for reproduction / developmental	EU/CLP: Classification criteria not met UN GHS: Classification criteria not met
Effects on Lactation	EU/CLP: Classification criteria not met UN GHS: Classification criteria not met
STOT-SE	EU/CLP: Category 3 – Narcotic Effects UN GHS: Category 3 – Narcotic Effects
STOT-RE	EU/CLP: Classification criteria not met UN GHS: Classification criteria not met

Target Organs**Route(s) of entry/exposure****Potential Health Effects****Inhalation****Acute (Immediate)**

- Central Nervous System (CNS)
- Inhalation, Skin, Eye, Ingestion
- High aerosol concentrations can cause irritation. May affect the central nervous system. Symptoms may include dizziness, drowsiness, lethargy, coma and death. Intentional concentration and inhalation of heptane vapors may lead to nervous system damage.
- No data available.

Chronic (Delayed)**Skin****Acute (Immediate)**

- Causes skin irritation. Direct skin contact with heptane may cause pain, burning, and itching.
- Repeated and prolonged exposure may cause dermatitis.

Chronic (Delayed)**Eye****Acute (Immediate)**

- Causes eye irritation.

Chronic (Delayed)

- No data available.

Ingestion**Acute (Immediate)**

- Material may be aspirated into lungs during ingestion and/or subsequent vomiting. Aspiration of this material will cause severe lung injury, chemical pneumonitis, pulmonary edema or death.
- No data available.

Chronic (Delayed)**Carcinogenic Effects**

- No effects expected.

Mutagenic Effects

- No effects expected.

Reproductive Effects

- No effects expected.

Section 12 - Ecological Information

Component Name	Concentration	CAS	Data
Heptane	0% TO 100%	142-82-5	Fish: 96 Hour(s) LC50 Fish 375 mg/L

12.1 Toxicity

- No data available.

12.2 Persistence and degradability

- No data available.

12.3 Bioaccumulative potential

- No data available.

12.4 Mobility in soil

- No data available.

12.5 Results of PBT and vPvB assessment

- No chemical safety report required.

12.6 Other adverse effects

Ecological Fate

- No data available.

12.7 Other Information

- No data is available on the adverse effects of this material on the environment. This product will normally float on water and components will evaporate rapidly. Heptane may be harmful to aquatic organisms and may cause long term adverse effects in the aquatic environment.

Section 13 - Disposal Considerations

13.1 Waste treatment methods

Product waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Packaging waste

- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Section 14 - Transport Information

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	NDA	Consumer commodity	ORM-D	NDA	NDA
TDG	UN1950	AEROSOLS, flammable	2.1	NDA	NDA
IMO/IMDG	UN1950	AEROSOLS	2.1	NDA	NDA
ADN	UN1950	AEROSOLS, flammable	2.1	NDA	NDA
ADR/RID	UN1950	Aerosols, flammable	2.1	NDA	NDA
IATA/ICAO	UN1950	Aerosols, flammable	2.1	NDA	NDA

14.6 Special precautions for user

- No data available

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

▪ No data available

Key to abbreviations

DOT = United States - Department of Transportation
 TDG = Canada - Transport of Dangerous Goods
 IMO/IMDG = International Maritime Transport
 ADN = Europe Transport of Dangerous Goods by Road/Inland Waterway

IATA = International Air Transport Association
 ICAO = International Civil Aviation Organization
 ADR = Europe Transport of Dangerous Goods by Road/Inland Waterway
 RID = Europe Transport of Dangerous Goods by Railways

Section 15 - Regulatory Information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Hazard Classifications ▪ Acute, Chronic, Fire, Pressure(Sudden Release of)

State Right To Know

Component	CAS	MA	NJ	PA
Heptane	142-82-5	Yes	Yes	Yes
Light aliphatic solvent naphtha	64742-89-8	No	No	No
Isobutane	75-28-5	Yes	Yes	Yes
Propane	74-98-6	Yes	Yes	Yes

Inventory

Component	CAS	Canada DSL	Canada NDSL	EU EINECS	EU ELNICS	TSCA
Heptane	142-82-5	Yes	No	Yes	No	Yes
Light aliphatic solvent naphtha	64742-89-8	Yes	No	Yes	No	Yes
Isobutane	75-28-5	Yes	No	Yes	No	Yes
Propane	74-98-6	Yes	No	Yes	No	Yes

Canada

Labor

Canada - WHMIS - Ingredient Disclosure List

▪ Isobutane	75-28-5	0% TO 25%	Not Listed
▪ Heptane	142-82-5	30% TO 50%	1 %
▪ Propane	74-98-6	0% TO 25%	Not Listed
▪ Light aliphatic solvent naphtha	64742-89-8	30% TO 50%	Not Listed

Environment

Canada - CEPA - Priority Substances List

▪ Isobutane	75-28-5	0% TO 25%	Not Listed
▪ Heptane	142-82-5	30% TO 50%	Not Listed
▪ Propane	74-98-6	0% TO 25%	Not Listed
▪ Light aliphatic solvent naphtha	64742-89-8	30% TO 50%	Not Listed

Europe

Other

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Classification

▪ Isobutane	75-28-5	0% TO 25%	F+; R12
▪ Heptane	142-82-5	30% TO 50%	F; R11 Xi; R38 N; R50 R53 Xn; R65 R67
▪ Propane	74-98-6	0% TO 25%	F+; R12
▪ Light aliphatic solvent naphtha	64742-89-8	30% TO 50%	Carc.Cat.2; R45 Muta.Cat.2; R46 Xn; R65

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Concentration Limits

▪ Isobutane	75-28-5	0% TO 25%	Not Listed
▪ Heptane	142-82-5	30% TO 50%	Not Listed
▪ Propane	74-98-6	0% TO 25%	Not Listed
▪ Light aliphatic solvent naphtha	64742-89-8	30% TO 50%	Not Listed

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Labelling

▪ Isobutane	75-28-5	0% TO 25%	F+ R:12 S:(2)-9-16
▪ Heptane	142-82-5	30% TO 50%	F Xn N R:11-38-65-67-50/53 S:(2)-9-16-29-33-60-61-62
▪ Propane	74-98-6	0% TO 25%	F+ R:12 S:(2)-9-16
▪ Light aliphatic solvent naphtha	64742-89-8	30% TO 50%	T R:45-46-65 S:53-45

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Notes - Substances and Preparations

▪ Isobutane	75-28-5	0% TO 25%	C
▪ Heptane	142-82-5	30% TO 50%	C
▪ Propane	74-98-6	0% TO 25%	Not Listed
▪ Light aliphatic solvent naphtha	64742-89-8	30% TO 50%	H, P

EU - CLP (1272/2008) - Annex VI - Table 3.2 - Safety Phrases

▪ Isobutane	75-28-5	0% TO 25%	S:(2)-9-16
▪ Heptane	142-82-5	30% TO 50%	S:(2)-9-16-29-33-60-61-62
▪ Propane	74-98-6	0% TO 25%	S:(2)-9-16
▪ Light aliphatic solvent naphtha	64742-89-8	30% TO 50%	S:53-45

United States

Labor

U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals

▪ Isobutane	75-28-5	0% TO 25%	Not Listed
▪ Heptane	142-82-5	30% TO 50%	Not Listed
▪ Propane	74-98-6	0% TO 25%	Not Listed
▪ Light aliphatic solvent naphtha	64742-89-8	30% TO 50%	Not Listed

U.S. - OSHA - Specifically Regulated Chemicals

▪ Isobutane	75-28-5	0% TO 25%	Not Listed
▪ Heptane	142-82-5	30% TO 50%	Not Listed
▪ Propane	74-98-6	0% TO 25%	Not Listed

▪ Light aliphatic solvent naphtha	64742-89-8	30% TO 50%	Not Listed
-----------------------------------	------------	---------------	------------

Environment**U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants**

▪ Isobutane	75-28-5	0% TO 25%	Not Listed
▪ Heptane	142-82-5	30% TO 50%	Not Listed
▪ Propane	74-98-6	0% TO 25%	Not Listed
▪ Light aliphatic solvent naphtha	64742-89-8	30% TO 50%	Not Listed

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

▪ Isobutane	75-28-5	0% TO 25%	Not Listed
▪ Heptane	142-82-5	30% TO 50%	Not Listed
▪ Propane	74-98-6	0% TO 25%	Not Listed
▪ Light aliphatic solvent naphtha	64742-89-8	30% TO 50%	Not Listed

U.S. - CERCLA/SARA - Radionuclides and Their Reportable Quantities

▪ Isobutane	75-28-5	0% TO 25%	Not Listed
▪ Heptane	142-82-5	30% TO 50%	Not Listed
▪ Propane	74-98-6	0% TO 25%	Not Listed
▪ Light aliphatic solvent naphtha	64742-89-8	30% TO 50%	Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs

▪ Isobutane	75-28-5	0% TO 25%	Not Listed
▪ Heptane	142-82-5	30% TO 50%	Not Listed
▪ Propane	74-98-6	0% TO 25%	Not Listed
▪ Light aliphatic solvent naphtha	64742-89-8	30% TO 50%	Not Listed

U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs

▪ Isobutane	75-28-5	0% TO 25%	Not Listed
▪ Heptane	142-82-5	30% TO 50%	Not Listed
▪ Propane	74-98-6	0% TO 25%	Not Listed
▪ Light aliphatic solvent naphtha	64742-89-8	30% TO 50%	Not Listed

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

▪ Isobutane	75-28-5	0% TO 25%	Not Listed
▪ Heptane	142-82-5	30% TO 50%	Not Listed
▪ Propane	74-98-6	0% TO 25%	Not Listed
▪ Light aliphatic solvent naphtha	64742-89-8	30% TO 50%	Not Listed

U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing

▪ Isobutane	75-28-5	0% TO 25%	Not Listed
▪ Heptane	142-82-5	30% TO 50%	Not Listed
▪ Propane	74-98-6	0% TO 25%	Not Listed

▪ Light aliphatic solvent naphtha	64742-89-8	30% TO 50%	Not Listed
-----------------------------------	------------	---------------	------------

United States - California**Environment****U.S. - California - Proposition 65 - Carcinogens List**

▪ Isobutane	75-28-5	0% TO 25%	Not Listed
▪ Heptane	142-82-5	30% TO 50%	Not Listed
▪ Propane	74-98-6	0% TO 25%	Not Listed
▪ Light aliphatic solvent naphtha	64742-89-8	30% TO 50%	Not Listed

U.S. - California - Proposition 65 - Developmental Toxicity

▪ Isobutane	75-28-5	0% TO 25%	Not Listed
▪ Heptane	142-82-5	30% TO 50%	Not Listed
▪ Propane	74-98-6	0% TO 25%	Not Listed
▪ Light aliphatic solvent naphtha	64742-89-8	30% TO 50%	Not Listed

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

▪ Isobutane	75-28-5	0% TO 25%	Not Listed
▪ Heptane	142-82-5	30% TO 50%	Not Listed
▪ Propane	74-98-6	0% TO 25%	Not Listed
▪ Light aliphatic solvent naphtha	64742-89-8	30% TO 50%	Not Listed

U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL)

▪ Isobutane	75-28-5	0% TO 25%	Not Listed
▪ Heptane	142-82-5	30% TO 50%	Not Listed
▪ Propane	74-98-6	0% TO 25%	Not Listed
▪ Light aliphatic solvent naphtha	64742-89-8	30% TO 50%	Not Listed

U.S. - California - Proposition 65 - Reproductive Toxicity - Female

▪ Isobutane	75-28-5	0% TO 25%	Not Listed
▪ Heptane	142-82-5	30% TO 50%	Not Listed
▪ Propane	74-98-6	0% TO 25%	Not Listed
▪ Light aliphatic solvent naphtha	64742-89-8	30% TO 50%	Not Listed

U.S. - California - Proposition 65 - Reproductive Toxicity - Male

▪ Isobutane	75-28-5	0% TO 25%	Not Listed
▪ Heptane	142-82-5	30% TO 50%	Not Listed
▪ Propane	74-98-6	0% TO 25%	Not Listed
▪ Light aliphatic solvent naphtha	64742-89-8	30% TO 50%	Not Listed

United States - Massachusetts**United States - New Jersey****United States - Pennsylvania**

Labor**U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List**

▪ Isobutane	75-28-5	0% TO 25%	Not Listed
▪ Heptane	142-82-5	30% TO 50%	Not Listed
▪ Propane	74-98-6	0% TO 25%	Not Listed
▪ Light aliphatic solvent naphtha	64742-89-8	30% TO 50%	Not Listed

U.S. - Pennsylvania - RTK (Right to Know) - Special Hazardous Substances

▪ Isobutane	75-28-5	0% TO 25%	Not Listed
▪ Heptane	142-82-5	30% TO 50%	Not Listed
▪ Propane	74-98-6	0% TO 25%	Not Listed
▪ Light aliphatic solvent naphtha	64742-89-8	30% TO 50%	Not Listed

United States - Rhode Island**Labor****U.S. - Rhode Island - Hazardous Substance List**

▪ Isobutane	75-28-5	0% TO 25%	Not Listed
▪ Heptane	142-82-5	30% TO 50%	Toxic; Flammable
▪ Propane	74-98-6	0% TO 25%	Toxic; Flammable
▪ Light aliphatic solvent naphtha	64742-89-8	30% TO 50%	Not Listed

Section 16 - Other Information**Phrases****Last Revision Date****Preparation Date****Disclaimer/Statement of Liability**

- Refer to Section 2
- 17/10/2011
- 17/10/2011
- The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstance of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.

Key to abbreviations

CAS = Chemical Abstract Services
EINECS = European Inventory of Existing Chemical Substances
LD = Lethal Dose
LC = Lethal Concentration
NDA = No data available

DSD = Dangerous Substances Directive (EU Directive 67/548/EEC)
DPD = Dangerous Preparations Directive (EU Directive 1999/45/EC)
EU CLP = EU Directive 1272/2008
UN GHS = United Nations Globally Harmonized System of Classification and Labelling of Chemicals