## MATERIAL SAFETY DATA SHEET

# SECTION 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

LUBRIPLATE Lubricants Co. 129 Lockwood St.

Newark, NJ 07105

Emergency Telephone Number: 1-800-255-3924-CHEM-TEL (24 hour) Telephone Number for information: 1-973-589-9150

**SUBSTANCE: LUBRIPLATE® Clearplex-1** 

TRADE NAMES/SYNONYMS:

**NSF H-1 REGISTRATION NUMBER:** 140575

**PRODUCT USE:** Petroleum lubricating grease

**CREATION DATE:** 07/18/2008 **REVISION DATE:** 09/08/2009

## SECTION 2 COMPOSITION/INFORMATION ON INGREDIENTS

**COMPONENT:** White mineral oil

**CAS NUMBER:** 8042-47-5

**EC NUMBER (EINECS):** 232-455-8

PERCENTAGE: 75-80

**COMPONENT:** Polybutene **CAS NUMBER:** 9003-29-6

**EC NUMBER (EINECS):** 500-004-7

PERCENTAGE: 10-15

**COMPONENT:** Fatty acids **CAS NUMBER:** 68440-15-3

**EC NUMBER (EINECS):** 270-438-7

**PERCENTAGE: 2-5** 

**COMPONENT:** Oxoaluminum acylate

**CAS NUMBER:** 151911-66-9

EC NUMBER (EINECS): not assigned

**PERCENTAGE:** 5-10

**COMPONENT:** Benzoic acid **CAS NUMBER:** 65-85-0

**EC NUMBER (EINECS):** 200-618-2

PERCENTAGE: 0-2

**Special Protection: See Section 8** 

**COMPONENT:** Triphenyl phosphorothionate

**CAS NUMBER:** 597-82-0

**EC NUMBER (EINECS): 209-909-9** 

**PERCENTAGE:** 0-1

**COMPONENT:** Benzenepropanoic acid

**CAS NUMBER:** 41484-35-9

**EC NUMBER (EINECS): 255-392-8** 

**PERCENTAGE:** 0-1

**COMPONENT:** Silicon dioxide **CAS NUMBER:** 112945-52-5

EC NUMBER (EINECS): not assigned

PERCENTAGE: 0-1

**COMPONENT:** Sodium benzoate

**CAS NUMBER:** 532-32-1

**EC NUMBER (EINECS): 208-534-8** 

**PERCENTAGE:** 0-1

**NOTE:** The IP 346 value of the mineral oil is less than 3%

#### SECTION 3 HAZARDS IDENTIFICATION

#### POTENTIAL HEALTH EFFECTS:

**INHALATION:** 

**SHORT TERM EXPOSURE:** Irritation **LONG TERM EXPOSURE:** Lung damage

**SKIN CONTACT:** 

**SHORT TERM EXPOSURE:** Irritation

**LONG TERM EXPOSURE:** Irritation, skin disorders

**EYE CONTACT:** 

**SHORT TERM EXPOSURE:** Irritation

**LONG TERM EXPOSURE:** No information available

**INGESTION:** 

**SHORT TERM EXPOSURE:** Diarrhea, difficulty breathing

LONG TERM EXPOSURE: no information on significant adverse effects

## **HAZARDOUS MATERIAL IDENTIFICATION SYSTEM (HMIS):**

Health – 1

Flammability – 1

Reactivity -0

## Not a Controlled Product under (WHMIS) – Canada

## SECTION 4 FIRST AID MEASURES

**INHALATION:** Vapor pressure is very low and inhalation at room temperature is not a problem. If overcome by vapor from hot product, immediately remove from exposure and call a physician.

**SKIN CONTACT:** Remove any contaminated clothing and wash with soap and warm water. If injected by high pressure under skin, regardless of the appearance or its size, contact a physician IMMEDIATELY. Delay may cause loss of affected part of the body.

**EYE CONTACT:** Flush with clear water for 15 minutes or until irritation subsides. If irritation persists, consult a physician.

**INGESTION:** If ingested, call a physician immediately. Do not induce vomiting.

#### SECTION 5 FIRE FIGHTING MEASURES

FIRE AND EXPLOSION HAZARDS: Slight fire hazard

**EXTINGUISHING MEDIA:** Foam, Dry Chemical, Carbon Dioxide or Water Spray (Fog)

**SPECIAL FIRE FIGHTING PROCEDURES:** Cool exposed containers with water. Use air-supplied breathing equipment for enclosed or confined spaces.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Do not store or mix with strong oxidants. Empty containers retain residue. Do not cut, drill, grind, or weld, as they may explode.

## SECTION 6 ACCIDENTAL RELEASE MEASURES

**OCCUPATIONAL RELEASE:** Scrape up grease, wash remainder with suitable petroleum solvent or add absorbent. Keep petroleum products out of sewers and water courses. Advise authorities if product has entered or may enter sewers and water courses.

#### SECTION 7 HANDLING AND STORAGE

**STORAGE:** Keep containers closed when not in use. Do not handle of store near heat, sparks, flame, or strong oxidants.

#### SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

## **EXPOSURE LIMITS:**

**OIL MIST IN AIR (Not Encountered in Normal Usage):** 

5 mg/m<sup>3</sup> UK OES TWA 10mg/m<sup>3</sup> UK OES STEL

**VENTILATION:** Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

**EYE PROTECTION:** Wear splash resistant safety goggles. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

**CLOTHING:** Wear appropriate chemical resistant clothing.

**GLOVES:** Wear appropriate chemical resistant (nitrile) gloves.

**RESPIRATOR:** Consider the need for appropriate protective equipment, such as self-contained breathing apparatus, adequate masks and filters.

#### SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: semi-solid

APPEARANCE: smooth
COLOUR: translucent
PHYSICAL FORM: grease
ODOR: slight mineral oil odor
BOILING POINT: >288°C

**FREEZING POINT:** Not available **FLASH POINT:** 238°C (COC)

**LOWER FLAMMABLE LIMIT:** 0.9% by volume **UPPER FLAMMABLE LIMIT:** 7.0% by volume

**AUTO IGNITION:** not available **VAPOUR PRESSURE:** <0.01 **VAPOR DENSITY (air=1):** >5

SPECIFIC GRAVITY (water=1): 0.98

**DENSITY:** not available

WATER SOLUBILITY: negligible

**pH:** not available

**VOLATILITY:** not available

**ODOR THRESHOLD:** not available

**EVAPORATION RATE** (Butyl acetate = 1): <0.01

VISCOSITY: not available

**COEFFICIENT OF WATER/OIL DISTRIBUTION:** not available

#### SECTION 10 STABILITY AND REACTIVITY

**REACTIVITY:** Stable at normal temperatures and pressures

**CONDITIONS TO AVOID:** Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials.

**INCOMPATIBLES:** Oxidising materials, chlorine

#### HAZARDOUS DECOMPOSITION:

Thermal decomposition products or combustion: oxides of carbon, oxides of sulphur

**POLYMERISATION:** Will not polymerise.

## SECTION 11 TOXICOLOGICAL INFORMATION

## White mineral oil:

**TOXICITY DATA:** 

Greater than 5,000 mg/kg oral-rat LD50

## **Polybutene:**

## **TOXICITY DATA:**

Greater than 34,600 mg/kg oral-rat LD50

## **Fatty acids:**

## **TOXICITY DATA:**

No data available

## **Oxoaluminum acylate:**

## **TOXICITY DATA:**

No data available

#### Benzoic acid:

## **TOXICITY DATA:**

No data available

## **Triphenyl phosphorothionate:**

## **TOXICITY DATA:**

Greater than 10,000 mg/kg oral-rat LD50

## Benzenepropanoic acid:

## **TOXICITY DATA:**

Greater than 5,000 mg/kg LD50 oral-rat

#### Silicon dioxide:

#### **TOXICITY DATA:**

Greater than 5,000 mg/kg oral-rat LD50

## **Sodium benzoate:**

## **TOXICITY DATA:**

4,100 mg/kg oral-rat LD50

## SECTION 12 ECOLOGICAL INFORMATION

Not available

## SECTION 13 DISPOSAL CONSIDERATIONS

Dispose in accordance with all applicable regulations

## SECTION 14 TRANSPORT INFORMATION

**LAND TRANSPORT ADR:** No classification assigned.

**LAND TRANSPORT RID:** No classification assigned.

AIR TRANSPORT IATA: No classification assigned.

**AIR TRANSPORT ICAO:** No classification assigned.

MARITIME TRANSPORT IMDG: No classification assigned.

SECTION 15 REGULATORY INFORMATION

EUROPEAN REGULATIONS:

EC CLASSIFICATION (CALCULATED): N

SECTION 16 OTHER INFORMATION

The above information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of LUBRIPLATE Lubricants Company. The data on these sheets relates only to the specific material designated herein. LUBRIPLATE Lubricants Company assumes no legal responsibility for use or reliance upon this data.