

SAFETY DATA SHEET

1. Identification of the substance/mixture and of the company

1.1 Product identifier

Product Name:
Type HP™ Cleaner/Degreaser Aerosol

Product ID numbers: HPY-12

1.2 Relevant identified uses of the mixture and uses advised against

Identified uses: Electrical cleaning

List of advices against: Not applicable.

1.3 Details of the supplier of the safety data sheet

Supplier/Manufacturer:

American Polywater Corporation
11222 - 60th Street North
Stillwater, MN 55082 USA
Tel: 1-651-430-2270
Email: sds@polywater.com

Polywater Europe BV
Zuidhaven 9-11 Unit B2
4761 CR Zevenbergen
Netherlands
Tel: +31 (0)10 2330578
Email: sds@polywater.com

1.4 Emergency telephone numbers

INFOTRAC 1-352-323-3500 (USA)

2. Hazards Identification

2.1 Classification of the substance or mixture

Classification according to OSHA 29 CFR 1910.1200 and Regulation (EC) No 1272/2008.

Skin Sens 1 H317

Flam Aerosol 2 H223, H229

2.2 Label elements

This product is intended for consumer use and is labeled according to CPSC guidelines and not to GHS guidelines listed below. It is safe for consumers and other users under normal and reasonably foreseeable use. The SDS contains valuable information for industrial workplace conditions.

Contains: Hydrocarbon Solvent, Citrus Terpenes



Pictograms:

Signal word: Warning

Hazard Statements:

H223 Flammable aerosol
H229 Pressurized container, may burst if heated
H317 May cause an allergic skin reaction

Precautionary Statements:

P210 Keep away from flames and hot surfaces. No smoking.
P251 Do not pierce or burn, even after use.
P280 Wear protective gloves.
P302 + P352 IF ON SKIN: Wash with plenty of water.
P333 + P313 If skin irritation or rash occurs: Get medical advice.

P403 + P235 Store in a well-ventilated place. Keep cool.
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P501 Dispose of contents/container in accordance with local and national regulations.

Notes: Aspiration classification not applied due to the physical form of the product.

2.3 Other hazards: No information available.

3. Composition/Information on Ingredients

<u>Component</u>	<u>CAS #</u>	<u>EC #</u>	<u>Wt. %</u>	<u>GHS/CLP Classification</u>
Petroleum distillates, hydrotreated light	64742-47-8	265-149-8	< 100	Asp. Tox. 1 H304; EUH066 Skin Irrit. 3 H316; Flam Liq 4 H227
d-Limonene	5989-27-5	227-813-5	< 10	Flam Liq 3, H226 Skin Irrit 2, H315 Skin Sens 1, H317 Aquatic Chronic 1, H410
Carbon Dioxide	124-38-9	204-6969-9	< 5	Aquatic Acute 1, H400

4. First Aid Measures

4.1 Description of first aid measures

Eye Contact: If eye irritation from exposure to vapors develops, move to fresh air. Flush eyes with clean water. If irritation persists, seek medical attention. For direct eye contact, flush with large quantity of water for 15 minutes. Seek medical attention.

Skin Contact: Remove contaminated clothing; flush skin thoroughly with water. If irritation occurs, seek medical attention.

Inhalation (Breathing): If irritation of nose or throat develops, move to fresh air. If irritation persists, seek medical attention. If breathing is difficult, provide oxygen. If not breathing, give artificial respiration. Seek immediate medical attention.

Ingestion (Swallowing): Do not induce vomiting or give anything by mouth. If victim is drowsy or unconscious, place on the left side with head down. Do not leave victim unattended. Seek medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 for more information.

4.3 Indication of immediate medical attention and special treatment needed.

Aspiration hazard. If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. This route not expected in aerosol package.

5. Firefighting Measures

5.1 Extinguishing media:

Carbon dioxide, water fog, dry chemical or foam.

5.2 Special hazards arising from the substance or mixture

Hazardous decomposition and by-products:

Burning generates CO, CO₂ and smoke. Smoke may be acrid and fumes irritating.

5.3 Advice for firefighters

Wear full protective clothing, including self-contained, positive pressure or pressure-demand breathing apparatus. Sealed container can build up pressure when exposed to high heat. Use water spray to cool fire exposed containers. Aerosol cans can build up pressure and explode when exposed to temperatures greater than 122°F (50°C).

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures:

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Use only non-sparking tools to clean up the spill. For a spill in a confined space, provide mechanical ventilation to disperse or exhaust vapors. For emergency responders: use respiratory protection: half-face or full-face respirator with filter(s) for organic vapor for spills in a confined space. Work gloves that are resistant to aromatic hydrocarbons are recommended. Chemical goggles are recommended if splashes or contact with eyes is possible. For small spills: normal antistatic work clothes are usually adequate.

6.2 Environmental precautions:

Avoid release to the environment. Dike the spill to prevent entry into waterways, sewers, basements or confined areas.

6.3 Methods materials for containment and cleaning up:

Absorb spill with sand or absorbents. Collect as much of the spilled material as possible using non-sparking tools and transfer to a container. Seal the container. Remember, adding an absorbent material does not change the toxicity or flammability hazard.

6.4 Reference to other sections:

Refer to Sections 4, 5, 8, and 13 for more information.

7. Handling and Storage**7.1 Precautions for safe handling**

Keep away from heat/sparks/open flames/hot surfaces. No smoking. Avoid breathing vapors or spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse. For industrial or professional use only.

7.2 Conditions for safe storage, including incompatibilities

Do not expose container to direct sunlight or temperatures above 122°F (50°C). Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store away from acids and oxidizing agents.

7.3 Specific end uses

See technical data sheet on this product for further information.

8. Exposure Controls / Personal Protection**8.1 Control parameters****Exposure limits and recommendations:**

Component Name	Limit	Standard	Source/Note
Petroleum distillates, hydrotreated light	100 ppm	ACGIH TWA	United States
Petroleum distillates, hydrotreated light	500 ppm	OSHA TWA	United States
Petroleum distillates, hydrotreated light	1200 mg/m ³	RCP* TWA	ACGIH, Manufacturer
d-Limonene	110 mg/m ³	DFG** OEL	Germany

*reciprocal calculation procedure for total hydrocarbons

**deutsche forschungsgemeinschaft, German Research Foundation

8.2 Exposure controls**Respiratory protection:**

Normal ventilation is adequate. If exposure exceeds recommended limits, respirator protection is recommended. Use a respirator or gas mask with cartridges for organic vapors (NIOSH or CE approved) with particulate pre-filter, P100 or AP2.

Protective gloves:

For repeated or prolonged skin contact, the use of impermeable gloves is recommended to prevent drying and possible irritation.

Suggested Material: Nitrile Rubber

Suggested Thickness: For short term contact (<15 minutes), splashes use 0.2 mm. For full contact use 0.4 mm

Exact break-through time has not been determined. Guidance is based on similar chemistry/material.

Maximum wearing time should be determined based on 50 % of the penetration time determined by EN

374 part III.

Eye protection:

Safety glasses recommended.

Other protective equipment:

It is suggested that a source of clean water be available in work area for flushing eyes and skin. Impervious clothing should be worn as needed.

9. Physical and Chemical**9.1 Information of basic physical and chemical properties**

Appearance:	Clear, colorless liquid with a very light citrus scent in aerosol package.
Odor threshold:	Not available
pH:	Does not apply
Freezing point:	<-58°F (<-50°C)
Boiling point:	365°F (185°C) Initial
Flash point:	>140°F (>60.5°C), Closed Cup (PMCC)
Evaporation rate:	<0.1 (n-butyl acetate = 1)
Flammability (solid, gas):	Not applicable to liquids
Upper/lower flammability or explosive limits:	LEL = 0.7% UEL = 6.1%-7.0%
Vapor pressure:	<1 mm Hg < 134 Pa @ 20°C
Vapor density (Air = 1):	> 1.0
Specific gravity (H₂O = 1):	0.79
Solubility in water:	Nil
Partition coefficient: n-octanol/water:	Not available
Auto-ignition temperature:	Not available
Decomposition temperature:	Not available
Viscosity:	Not available.

9.2 Other Information

Volatiles (Weight %):	100%
VOC Content:	790 g/l

10. Stability and Reactivity**10.1 Reactivity:**

See remaining headings in Section 10.

10.2 Chemical stability:

Stable

10.3 Possibility of hazardous reactions:

None known.

10.4 Conditions to avoid:

Avoid heat, flame, and sparks.

10.5 Incompatible materials :

Strong oxidizing agents.

10.6 Hazardous decomposition products:

Carbon dioxide, carbon monoxide.

11. Toxicological Information

11.1 Information on toxicological effects:**Acute toxicity****Eye contact:**

Direct eye contact may cause eye irritation. This irritation is minimal and expected to be transient.

Skin contact:

Prolonged or repeated skin exposure can remove oils, causing redness, drying and cracking. Persons with pre-existing skin disorders may be more susceptible to skin irritation from this material.

Irritation and Sensitization Potential:

Product may be irritating to skin and eyes. It is not a sensitizer.

Inhalation (Breathing):

Concentrated petroleum solvent vapors may cause irritation of the nose and throat. Prolonged exposure to excessively high vapor concentrations can result in central nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue). Persons with impaired lung function may experience additional breathing difficulties due to the irritant properties of this material.

Ingestion:

Ingestion of large quantities may cause irritation of the digestive tract, nervous system depression (e.g., drowsiness, dizziness, loss of coordination, and fatigue).

Toxicity to Animals:

Petroleum distillates,
hydrotreated light:

LD₅₀ (oral rat) >5000 mg/kg

LD₅₀ (dermal rabbit) >2000 mg/kg

LC₅₀ (inhl rat) >4.3mg/L, 4 hours

d-Limonene:

LD₅₀ (oral rat) >5000 mg/kg

LD₅₀ (dermal rabbit) 5000 mg/kg

RD₅₀ 1000 ppm

Aspiration hazard

May be fatal if swallowed and enters airways. Not expected with aerosol package.

Chronic Exposure:

Reproductive Toxicity: Not available.

Mutagenicity: Not available.

Teratogenicity: Not available.

Specific Target Organ Toxicity (STOT) No end point data.

Toxicologically Synergistic Products: Not available.

Carcinogenic Status: This substance has not been identified as a carcinogen or probable carcinogen by NTP, IARC, or OSHA, nor have any of its components.

12. Ecological Information**12.1 Toxicity:**

Ecotoxicity: No information available.

Aquatic Toxicity: No information available.

12.2 Persistence and degradability: Expected to be biodegradable.

12.3 Bioaccumulation potential: No information available

12.4 Mobility in soil: No information available.

12.5 Results of PBT and vPvB Assessment: This product is not, nor does it contain a substance that is a PBT or vPvB.

12.6 Other adverse effects: None known.

13. Disposal Considerations

Dispose of product in accordance with National and Local Regulations.

14. Transport Information

UN Number: 1950
UN Proper shipping name: AEROSOLS, Flammable, less than 1 liter each, Class 2.1, LTD QTY
Transport hazard class(es): Class 9
Packing group: Not Applicable
Environmental hazards: None known
Special precautions: None known
TDG: Not Regulated
ICAO/IATA-DGR: Consumer Commodity, ID 8000, Class 9, LTD QTY
 UN 1950, AEROSOLS, Flammable, less than 1 liter each, Class 2.1, LTD QTY
IMDG: QTY

15. Regulatory Information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****USA Federal and State**

All components are listed on the TSCA inventory.

Hazard Categories for SARA Section 311/312 Reporting	<u>Acute</u> No	<u>Chronic</u> No	<u>Fire</u> Yes	<u>Pressure</u> No	<u>Reactive</u> No
---	---------------------------	-----------------------------	---------------------------	------------------------------	------------------------------

<u>Components</u>	CERCLA/SARA Sec 302 <u>Hazardous Substance RQ</u>	<u>EHS TPQ</u>	SARA Sec. 313 <u>Toxic Release</u>
--------------------------	--	-----------------------	---

Components are not affected by these Superfund regulations.

NFPA Ratings: Health: 1
 Fire: 2
 Reactivity: 0

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel during spill, fire or similar emergencies. Hazard ratings are based on physical and toxic properties of combustion or decomposition.

European Union

All components are listed on the European Inventory of Existing Chemical Substances (EINECS). Product complies with the communication requirements of REACH Regulation (EC) No. 1907/2006. It does not contain Substances of Very High Concern (SVHC).

Canada

All components are listed on the DSL inventory.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

WHMIS Classification: B3

Australia

All components are listed on the AICS.

Hazardous according to criteria of NOHSC Australia. Product classified as harmful (Xn).

15.2 Chemical Safety Assessment

No chemical safety assessment has been carried out for the mixture by the supplier.

16. Other Information**Abbreviations and acronyms:**

OSHA = Occupational Safety and Health Administration

CLP = Classification, Labeling and Packaging Regulation

STOT = Specific Target Organ Toxicity

LD₅₀ = Median Lethal Dose

DNEL = Derived No Effect Level

ACGIH = American Conference of Governmental Industrial Hygienists

TSCA = Toxic Substances Control Act (USA)

DSL = Domestic Substances List (Canada)

AICS = Australian Inventory of Chemical Substances

Revision Date: January 2, 2015

Revision Number: 5

Supersedes: September 23, 2014

Other: Not Applicable

Indication of Changes: Section 1, 2, 3, 8, 15, 16 updated. Hazard and precautionary codes adjusted, additional information on exposure limits. Addition of acronyms and other formatting changes.
Updated in accordance with the provisions of OSHA 1910.1200 App D and REACH Annex II (EU No 453/2010). (GHS format)

The information and recommendations contained herein are believed to be reliable. However, the supplier makes no warranties, express or implied, concerning the use of this product. The buyer must determine conditions of safe usage and assumes all risk and liability in handling this product.