

MATERIAL SAFETY DATA SHEET

Product Trade Name: DCA-22001

Revision Date: 09-Dec-2013

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name: DCA-22001
Synonyms: None
Chemical Family: Blend
Application: Cleaner

Manufacturer/Supplier Halliburton Energy Services
P.O. Box 1431
Duncan, Oklahoma 73536-0431
Emergency Telephone: (281) 575-5000

Prepared By Chemical Compliance
Telephone: 1-580-251-4335
e-mail: fdunexchem@halliburton.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	CAS Number	PERCENT (w/w)	ACGIH TLV-TWA	OSHA PEL-TWA
Isopropanol	67-63-0	10 - 30%	TWA: 200 ppm STEL: 400 ppm	400 ppm

3. HAZARDS IDENTIFICATION

Hazard Overview May cause eye, skin, and respiratory irritation. May cause headache, dizziness, and other central nervous system effects. May be harmful if swallowed.
Flammable.

4. FIRST AID MEASURES

Inhalation If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

Skin In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes. Get medical attention. Remove contaminated clothing and launder before reuse.

Eyes In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.

Ingestion Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

Notes to Physician Not Applicable

5. FIRE FIGHTING MEASURES

Flash Point/Range (F):	77
Flash Point/Range (C):	25
Flash Point Method:	PMCC
Autoignition Temperature (F):	Not Determined
Autoignition Temperature (C):	Not Determined
Flammability Limits in Air - Lower (%):	Not Determined
Flammability Limits in Air - Upper (%):	Not Determined

Fire Extinguishing Media Water fog, carbon dioxide, foam, dry chemical.

Special Exposure Hazards May be ignited by heat, sparks or flames. Use water spray to cool fire exposed surfaces. Closed containers may explode in fire. Decomposition in fire may produce toxic gases.

Special Protective Equipment for Fire-Fighters Full protective clothing and approved self-contained breathing apparatus required for fire fighting personnel.

NFPA Ratings: Health 2, Flammability 3, Reactivity 0
HMIS Ratings: Health 2, Flammability 3, Reactivity 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures Use appropriate protective equipment. Wear self-contained breathing apparatus in enclosed areas.

Environmental Precautionary Measures Prevent from entering sewers, waterways, or low areas.

Procedure for Cleaning / Absorption Isolate spill and stop leak where safe. Remove ignition sources and work with non-sparking tools. Contain spill with sand or other inert materials. Scoop up and remove.

7. HANDLING AND STORAGE

Handling Precautions Avoid contact with eyes, skin, or clothing. Avoid breathing vapors.

Storage Information Store away from oxidizers. Keep from heat, sparks, and open flames. Keep container closed when not in use. Store between 40.5 F (4.7 C) and 120.5 F (49 C). Product has a shelf life of 24 months.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls Use in a well ventilated area. Local exhaust ventilation should be used in areas without good cross ventilation.

Respiratory Protection Organic vapor respirator.

Hand Protection Impervious rubber gloves.

Skin Protection Rubber apron.

Eye Protection Chemical goggles; also wear a face shield if splashing hazard exists.

Other Precautions

Eyewash fountains and safety showers must be easily accessible.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Color:	Colorless to Amber
Odor:	Alcohol
pH:	6.5 - 7.5
Specific Gravity @ 20 C (Water=1):	0.96
Density @ 20 C (lbs./gallon):	8.01
Bulk Density @ 20 C (lbs/ft3):	Not Determined
Boiling Point/Range (F):	176
Boiling Point/Range (C):	80
Freezing Point/Range (F):	Not Determined
Freezing Point/Range (C):	Not Determined
Vapor Pressure @ 20 C (mmHg):	33
Vapor Density (Air=1):	Not Determined
Percent Volatiles:	58-60
Evaporation Rate (Butyl Acetate=1):	Not Determined
Solubility in Water (g/100ml):	Miscible
Solubility in Solvents (g/100ml):	Not Determined
VOCs (lbs./gallon):	Not Determined
Viscosity, Dynamic @ 20 C (centipoise):	Not Determined
Viscosity, Kinematic @ 20 C (centistokes):	Not Determined
Partition Coefficient/n-Octanol/Water:	Not Determined
Molecular Weight (g/mole):	Not Determined

10. STABILITY AND REACTIVITY

Stability Data:	Stable
Hazardous Polymerization:	Will Not Occur
Conditions to Avoid	Keep away from heat, sparks and flame.
Incompatibility (Materials to Avoid)	Strong oxidizers.
Hazardous Decomposition Products	Carbon monoxide and carbon dioxide.
Additional Guidelines	Not Applicable

11. TOXICOLOGICAL INFORMATION

Principle Route of Exposure	Eye or skin contact, inhalation.
-----------------------------	----------------------------------

Symptoms related to exposure**Acute Toxicity****Inhalation**

May cause respiratory irritation. May cause central nervous system depression including headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness.

Eye Contact

May cause eye irritation.

Skin Contact

May cause skin irritation.

Ingestion

Irritation of the mouth, throat, and stomach. May cause abdominal pain, vomiting, nausea, and diarrhea. May cause headache, dizziness, nausea, vomiting, gastrointestinal irritation and central nervous system depression.

Chronic Effects/Carcinogenicity

Repeated overexposure may cause liver and kidney effects. May contain ethylene oxide in the headspace of the drum. Ethylene oxide is a cancer and reproductive hazard.

Toxicology data for the components

Substances	CAS Number	LD50 Oral	LD50 Dermal	LC50 Inhalation
Isopropanol	67-63-0	4396 mg/kg (Rat) 3600 mg/kg (mouse)	12800 mg/kg (Rat) 12870 mg/kg (Rabbit)	72.6 mg/L (Rat) 4 h

12. ECOLOGICAL INFORMATION**Ecotoxicological Information****Ecotoxicity Product**

Acute Fish Toxicity:	Not determined
Acute Crustaceans Toxicity:	Not determined
Acute Algae Toxicity:	Not determined

Ecotoxicity Substance

Substances	CAS Number	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Isopropanol	67-63-0	EC50: > 1000 mg/l(Desmodesmus subspicatus)	LC50: 9640 mg/l (Pimephales promelas)	No information available	EC50: 13299 mg/l (Daphnia magna)

12.2 Persistence and degradability

No information available

12.3 Bioaccumulative potential

No information available

12.4 Mobility in soil

No information available

12.5 Results of PBT and vPvB assessment

No information available.

12.6 Other adverse effects**13. DISPOSAL CONSIDERATIONS****Disposal Method**

Disposal should be made in accordance with federal, state, and local regulations. Incineration recommended in approved incinerator according to federal, state, and local regulations.

Contaminated Packaging

Follow all applicable national or local regulations.

14. TRANSPORT INFORMATION**Land Transportation****DOT**

UN1993, Flammable Liquid, N.O.S. (Contains Isopropanol) , 3 , III , (25 C)
NAERG 128

Canadian TDG

Flammable Liquid, N.O.S. (Contains Isopropanol) , 3 , UN1993 , III , (25 C)

ADR

UN1993, Flammable Liquid, N.O.S (Contains Isopropanol) , 3 , III

Air Transportation**ICAO/IATA**

UN1993, Flammable Liquid, N.O.S , 3 , III (Contains Isopropanol)

Sea Transportation**IMDG**

UN1993, Flammable Liquid, N.O.S (Contains Isopropanol) , 3 , III , (25 C)
EmS F-E, S-E

Other Transportation Information

Labels: Flammable Liquid

15. REGULATORY INFORMATION

US Regulations

US TSCA Inventory	All components listed on inventory or are exempt.
EPA SARA Title III Extremely Hazardous Substances	Not applicable
EPA SARA (311,312) Hazard Class	Acute Health Hazard Chronic Health Hazard Fire Hazard
EPA SARA (313) Chemicals	This product contains toxic chemical(s) listed below which is(are) subject to the reporting requirements of Section 313 of Title III of SARA and 40 CFR Part 372: Isopropanol//67-63-0
EPA CERCLA/Superfund Reportable Spill Quantity	Not applicable.
EPA RCRA Hazardous Waste Classification	If product becomes a waste, it does meet the criteria of a hazardous waste as defined by the US EPA, because of: Ignitability D001
California Proposition 65	All components listed do not apply to the California Proposition 65 Regulation.
MA Right-to-Know Law	One or more components listed.
NJ Right-to-Know Law	One or more components listed.

PA Right-to-Know Law One or more components listed.

Canadian Regulations

Canadian DSL Inventory All components listed on inventory or are exempt.

WHMIS Hazard Class B2 Flammable Liquids
D2B Toxic Materials

16. OTHER INFORMATION

The following sections have been revised since the last issue of this SDS

Not applicable

Additional Information For additional information on the use of this product, contact your local Halliburton representative.

For questions about the Safety Data Sheet for this or other Halliburton products, contact Chemical Compliance at 1-580-251-4335.

Disclaimer Statement This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

*****END OF MSDS*****