

MATERIAL SAFETY DATA SHEET

Product Trade Name: DCA-32003

Revision Date: 09-Dec-2013

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name: DCA-32003
Synonyms: None
Chemical Family: Alcohol Surfactant Blend
Application: Wetting Agent

Manufacturer/Supplier: Halliburton Energy Services, Inc.
P.O. Box 1431
Duncan, Oklahoma 73536-0431
Emergency Telephone: (281) 575-5000

Prepared By: Chemical Compliance
Telephone: 1-580-251-4335
e-mail: fdunexchem@halliburton.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	CAS Number	PERCENT (w/w)	ACGIH TLV-TWA	OSHA PEL-TWA
Alkylbenzene sulfonate, compd. with 2-propanamine	Proprietary	5 - 10%	Not applicable	Not applicable
Alkylbenzene sulfonate, compd. with triethanolamine	Proprietary	5 - 10%	Not applicable	Not applicable
Methanol	67-56-1	60 - 100%	TWA: 200 ppm STEL: 250 ppm	200 ppm

3. HAZARDS IDENTIFICATION

Hazard Overview May cause eye, skin, and respiratory irritation. May cause headache, dizziness, and other central nervous system effects. May be harmful if swallowed. May cause blindness. May be absorbed through the skin. Repeated overexposure may cause liver and kidney effects. Flammable.

4. FIRST AID MEASURES

Inhalation If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

Skin In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes. Get medical attention. Remove contaminated clothing and launder before reuse.

Eyes In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.

Ingestion	Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.
Notes to Physician	The administration of ethanol after ingestion of this compound acts to counter the adverse effects of this material on the liver.

5. FIRE FIGHTING MEASURES

Flash Point/Range (F):	62
Flash Point/Range (C):	16.7
Flash Point Method:	PMCC
Autoignition Temperature (F):	Not Determined
Autoignition Temperature (C):	Not Determined
Flammability Limits in Air - Lower (%):	Not Determined
Flammability Limits in Air - Upper (%):	Not Determined

Fire Extinguishing Media Carbon Dioxide, Dry Chemicals, Foam.

Special Exposure Hazards May be ignited by heat, sparks or flames. Use water spray to cool fire exposed surfaces. Closed containers may explode in fire. Decomposition in fire may produce toxic gases. Runoff to sewer may cause fire or explosion hazard.

Special Protective Equipment for Fire-Fighters Full protective clothing and approved self-contained breathing apparatus required for fire fighting personnel.

NFPA Ratings: Health 2, Flammability 3, Reactivity 0
HMIS Ratings: Health 2, Flammability 3, Physical Hazard 0 , PPE: X

6. ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures Use appropriate protective equipment. Wear self-contained breathing apparatus in enclosed areas.

Environmental Precautionary Measures Prevent from entering sewers, waterways, or low areas.

Procedure for Cleaning / Absorption Isolate spill and stop leak where safe. Remove ignition sources and work with non-sparking tools. Contain spill with sand or other inert materials. Scoop up and remove.

7. HANDLING AND STORAGE

Handling Precautions Wash hands after use. Launder contaminated clothing before reuse. Ground and bond containers when transferring from one container to another. Avoid contact with eyes, skin, or clothing. Avoid breathing vapors. Avoid breathing mist.

Storage Information Store away from oxidizers. Keep from heat, sparks, and open flames. Keep container closed when not in use. Product has a shelf life of 12 months.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls Use in a well ventilated area. Local exhaust ventilation should be used in areas without good cross ventilation.

Respiratory Protection	If engineering controls and work practices cannot keep exposure below occupational exposure limits or if exposure is unknown, wear a NIOSH certified, European Standard EN 149, or equivalent respirator when using this product. Selection of and instruction on using all personal protective equipment, including respirators, should be performed by an Industrial Hygienist or other qualified professional. Positive pressure self-contained breathing apparatus if methanol is released.
Hand Protection	Impervious rubber gloves.
Skin Protection	Rubber apron.
Eye Protection	Chemical goggles; also wear a face shield if splashing hazard exists.
Other Precautions	Eyewash fountains and safety showers must be easily accessible.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Color:	Colorless to amber or brown
Odor:	Alcohol
pH:	5.87 - 7.17
Specific Gravity @ 20 C (Water=1):	0.8661 - 0.8921
Density @ 20 C (lbs./gallon):	7.22 - 7.44
Bulk Density @ 20 C (lbs/ft3):	Not Determined
Boiling Point/Range (F):	Not Determined
Boiling Point/Range (C):	Not Determined
Freezing Point/Range (F):	0
Freezing Point/Range (C):	-17.8
Vapor Pressure @ 20 C (mmHg):	Not Determined
Vapor Density (Air=1):	Not Determined
Percent Volatiles:	Not Determined
Evaporation Rate (Butyl Acetate=1):	Not Determined
Solubility in Water (g/100ml):	Soluble
Solubility in Solvents (g/100ml):	Not Determined
VOCs (lbs./gallon):	Not Determined
Viscosity, Dynamic @ 20 C (centipoise):	Not Determined
Viscosity, Kinematic @ 20 C (centistokes):	Not Determined
Partition Coefficient/n-Octanol/Water:	Not Determined
Molecular Weight (g/mole):	Not Determined

10. STABILITY AND REACTIVITY

Stability Data:	Stable
Hazardous Polymerization:	Will Not Occur
Conditions to Avoid	Keep away from heat, sparks and flame.
Incompatibility (Materials to Avoid)	Strong oxidizers. Strong alkalis.
Hazardous Decomposition Products	Carbon monoxide and carbon dioxide. Oxides of sulfur.
Additional Guidelines	Not Applicable

11. TOXICOLOGICAL INFORMATION

Principle Route of Exposure Eye or skin contact, inhalation.

Symptoms related to exposure

Acute Toxicity

Inhalation

May cause respiratory irritation. May cause central nervous system depression including headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness.

Eye Contact

May cause severe eye irritation.

Skin Contact

May cause skin irritation. May be absorbed through the skin and contribute to the symptoms listed under ingestion. May cause skin defatting with prolonged exposure.

Ingestion

May be fatal or cause blindness if swallowed. May cause headache, dizziness, nausea, vomiting, gastrointestinal irritation and central nervous system depression.

Chronic Effects/Carcinogenicity

Prolonged or repeated exposure may cause eye, blood, lung, liver, kidney, heart, central nervous system and spleen damage.

Toxicology data for the components

Substances	CAS Number	LD50 Oral	LD50 Dermal	LC50 Inhalation
Alkylbenzene sulfonate, compd. with 2-propanamine	Proprietary	No data available	No data available	No data available
Alkylbenzene sulfonate, compd. with triethanolamine	Proprietary	No data available	No data available	No data available
Methanol	67-56-1	> 1187 - 2769 mg/kg (Rat) 3000 mg/kg (Monkey) 300 mg/kg (Human)	15800 mg/kg (Rabbit) 393 mg/kg (Primate)	87.5 mg/L (Rat) 4h 128.2 mg/L (Rat) 4h 83.2 mg/L (Rat) 4 h 64000 ppm (Rat) 4 h 10 mg/L (Human)

12. ECOLOGICAL INFORMATION

Ecotoxicological Information

Ecotoxicity Product

Acute Fish Toxicity: Not determined

Acute Crustaceans Toxicity: Not determined

Acute Algae Toxicity: Not determined

Ecotoxicity Substance

Substances	CAS Number	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Alkylbenzene sulfonate, compd. with 2-propanamine	Proprietary	No information available	No information available	No information available	No information available
Alkylbenzene sulfonate, compd. with triethanolamine	Proprietary	No information available	No information available	No information available	No information available
Methanol	67-56-1	EC50(96h): ca. 22000 mg/L (Pseudokirchnerella subcapitata, Growth rate)	LC50: 28200 mg/l (Pimephales promelas) LC50(96h): 12700 – 15400 mg/L (Lepomis macrochirus)	IC50(3h): > 1000 mg/L (Activated sludge)	EC50(96h): 18260 mg/L (Daphnia magna) NOEC(21d): 122 mg/L (Daphnia magna, Reproduction)

12.2 Persistence and degradability

No information available

12.3 Bioaccumulative potential

No information available

Substances	Log Pow
Methanol	-0.77 BCF 1.0 – 4.5 (Cyprinus carpio) BCF < 10 (Leuciscus idus melanotus)

12.4 Mobility in soil

No information available

12.5 Results of PBT and vPvB assessment

No information available.

12.6 Other adverse effects

13. DISPOSAL CONSIDERATIONS

Disposal Method Disposal should be made in accordance with federal, state, and local regulations.

Contaminated Packaging Follow all applicable national or local regulations.

14. TRANSPORT INFORMATION

Land Transportation

DOT

UN1993, Flammable Liquid, N.O.S. (Contains Methanol) , 3 , II , (16.7 C)
NAERG 128

Canadian TDG

Flammable Liquid, N.O.S. (Contains Methanol) , 3 , UN1993 , II , (16.7 C)

ADR

UN1993, Flammable Liquid, N.O.S (Contains Methanol) , 3 , II

Air Transportation

ICAO/IATA

UN1993, Flammable Liquid, N.O.S , 3 , II (Contains Methanol)

Sea Transportation

IMDG

UN1993, Flammable Liquid, N.O.S (Contains Methanol) , 3 , II , (16.7 C)
EmS F-E, S-E

Other Transportation Information

Labels: Flammable Liquid

15. REGULATORY INFORMATION

US Regulations

US TSCA Inventory	All components listed on inventory or are exempt.
EPA SARA Title III Extremely Hazardous Substances	Not applicable
EPA SARA (311,312) Hazard Class	Acute Health Hazard Fire Hazard
EPA SARA (313) Chemicals	This product contains toxic chemical(s) listed below which is(are) subject to the reporting requirements of Section 313 of Title III of SARA and 40 CFR Part 372: Methanol//67-56-1
EPA CERCLA/Superfund Reportable Spill Quantity	EPA Reportable Spill Quantity is 1088 Gallons based on Methanol (CAS: 67-56-1).
EPA RCRA Hazardous Waste Classification	If product becomes a waste, it does meet the criteria of a hazardous waste as defined by the US EPA, because of: Ignitability D001
California Proposition 65	All components listed do not apply to the California Proposition 65 Regulation.
MA Right-to-Know Law	One or more components listed.
NJ Right-to-Know Law	One or more components listed.
PA Right-to-Know Law	One or more components listed.

Canadian Regulations

Canadian DSL Inventory	All components listed on inventory or are exempt.
WHMIS Hazard Class	D1B Toxic Materials D2A Very Toxic Materials D2B Toxic Materials B2 Flammable Liquids

16. OTHER INFORMATION

The following sections have been revised since the last issue of this SDS

Not applicable

Additional Information	For additional information on the use of this product, contact your local Halliburton representative. For questions about the Safety Data Sheet for this or other Halliburton products, contact Chemical Compliance at 1-580-251-4335.
Disclaimer Statement	This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

*****END OF MSDS*****