SAFETY DATA SHEET



Date of issue/Date of revision 1 May 2016 Version 3

Section 1. Identification		
Product name	: DFT258C DEFT WATERBASED POLYURETHANE	
Product code	: 00411526	
Other means of identification	: Not available.	
Product type	: Liquid.	
Relevant identified uses of	the substance or mixture and uses advised against	
Product use	: Industrial applications, Used by spraying.	
Use of the substance/ mixture	: Coating.	
Uses advised against	: Not applicable.	
Manufacturer	: PPG Industries, Inc. One PPG Place Pittsburgh, PA 15272	
Emergency telephone number	: (412) 434-4515 (U.S.) (514) 645-1320 (Canada) 01-800-00-21-400 (Mexico)	
Technical Phone Number	\cdot 1 800 441 9695 (8:00 am to 5:00 pm EST)	

Technical Phone Number : 1-800-441-9695 (8:00 am to 5:00 pm EST)

Section 2. Hazards identification

OSHA/HCS status	 This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A TOXIC TO REPRODUCTION (Unborn child) - Category 1B SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2 Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 29.3%
GHS label elements Hazard pictograms	

Signal word

: Danger

Substance/mixture

Product name

Product name DFT258C DEFT WATERBASED POLYURETHANE

Section 2. Hazards identification

Hazard statements	: Causes serious eye irritation.
	Causes skin irritation.
	May damage the unborn child.
	May cause damage to organs through prolonged or repeated exposure.
Precautionary statements	
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Do not breathe vapor. Wash hands thoroughly after handling
Response	: Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attentior
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	: Avoid contact with skin and clothing. Wash thoroughly after handling. Emits toxic fumes when heated.
Hazards not otherwise classified	: Prolonged or repeated contact may dry skin and cause irritation.

Section 3. Composition/information on ingredients

: Mixture

: DFT258C DEFT WATERBASED POLYURETHANE

Ingredient name	%	CAS number
M-methyl-2-pyrrolidone	≥1.0 - ≤5.0	872-50-4
triethylamine	≥1.0 - <3.0	121-44-8
ω-[3-[3-(2H-benzotriazol-2-yl) derivatives	<1.0	104810-47-1
α-[3-[3-(2H-benzotriazol-2-yl) derivatives	<1.0	104810-48-2
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	<1.0	41556-26-7
methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate	<1.0	82919-37-7

SUB codes represent substances without registered CAS Numbers.

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Product name DFT258C DEFT WATERBASED POLYURETHANE

Section 4. First aid measures

If ingestion, irritation, any type of overexposure or symptoms of overexposure occur during or persists after use of this product, contact a POISON CONTROL CENTER, EMERGENCY ROOM OR PHYSICIAN immediately; have Safety Data Sheet information available. Never give anything by mouth to an unconscious or convulsing person.

Description of necessar	
Eye contact	 Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	 Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Ingestion	: If swallowed, seek medical advice immediately and show this container or label. Keep person warm and at rest. Do NOT induce vomiting.
Most important sympto	ms/effects, acute and delayed
Potential acute health	<u>effects</u>
Eye contact	: Causes serious eye irritation.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: Causes skin irritation. Defatting to the skin.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/s	<u>ymptoms</u>
Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: irritation redness dryness cracking reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Indication of immediate	medical attention and special treatment needed, if necessary
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

Date of issue 1 May 2016

Product name DFT258C DEFT WATERBASED POLYURETHANE

Section 4. First aid measures

Protection of first-aiders
 No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Product name DFT258C DEFT WATERBASED POLYURETHANE

Section 6. Accidental release measures

Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling	
Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Special precautions	: If this material is part of a multiple component system, read the Safety Data Sheet(s) for the other component or components before blending as the resulting mixture may have the hazards of all of its parts.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Product name DFT258C DEFT WATERBASED POLYURETHANE

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

osure limits
. (PPG). Absorbed through skin.
A: 10 ppm
IH TLV (United States, 3/2015).
orbed through skin.
EL: 1 ppm 15 minutes.
A: 0.5 ppm 8 hours.
A PEL (United States, 2/2013).
A: 100 mg/m³ 8 hours.
A: 25 ppm 8 hours.
9.
9.
9.
9.

A	 Acceptable Maximum Peak 	S	 Potential skin absorption
ACGIH	 American Conference of Governmental Industrial Hygienists. 	SR	 Respiratory sensitization
С	= Ceiling Limit	SS	 Skin sensitization
F	= Fume	STEL	 Short term Exposure limit values
IPEL	Internal Permissible Exposure Limit	TD	= Total dust
OSHA	 Occupational Safety and Health Administration. 	TLV	= Threshold Limit Value
R	= Respirable	TWA	= Time Weighted Average
Z	= OSHA 29 CFR 1910.1200 Subpart Z - Toxic and Hazardous Substances		

Consult local authorities for acceptable exposure limits.

Recommended monitoring : procedures	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
Appropriate engineering : controls	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
Environmental exposure : controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection measures	
Hygiene measures :	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection : Skin protection	Chemical splash goggles.

Product name DFT258C DEFT WATERBASED POLYURETHANE

Section 8. Exposure controls/personal protection

Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Gloves	: butyl rubber
Body protection	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
Restrictions on use	: Persons with a history of asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used.

Section 9. Physical and chemical properties

Appearance

		United States	Page: 7/13
Viscosity	1	Kinematic (40°C (104°F)): >0.21 cm²/s (>21 cSt)	
Partition coefficient: n- octanol/water	:	Not available.	
Solubility		Soluble in the following materials: cold water.	
Density(lbs / gal)	1	8.43	
Relative density	1	1.01	
Vapor density	1	Not available.	
Vapor pressure	1	Not available.	
Evaporation rate	1	Not available.	
Lower and upper explosive (flammable) limits	:	Lower: 0.09% Upper: 0.09%	
Flammability (solid, gas)	:	Not available.	
Decomposition temperature	1	Not available.	
Auto-ignition temperature	1	Not available.	
Flash point	1	Closed cup: 113.33°C (236°F) [Product does not sustain combustion.]	
Boiling point	1	>37.78°C (>100°F)	
Melting point	:	Not available.	
рН	1	Not available.	
Odor threshold		Not available.	
Odor		Characteristic.	
Color		Not available.	
Physical state	1	Liquid.	

Product code 00411526	Date of issue 1 May 2016 Version 3			
Product name DFT258C DEFT WATERBASED POLYURETHANE				
Section 9. Physic	al and chemical properties			
Volatility	: 70% (v/v), 68.685% (w/w)			
% Solid. (w/w)	: 31.315			
Section 10. Stabil	ity and reactivity			
Reactivity	: No specific test data related to reactivity available for this product or its ingredients.			
Chemical stability	: The product is stable.			
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.			
Conditions to avoid	: When exposed to high temperatures may produce hazardous decomposition products. Refer to protective measures listed in sections 7 and 8.			
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions: oxidizing agents, strong alkalis, strong acids.			
Hazardous decomposition products	: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.			

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
N-methyl-2-pyrrolidone	LC50 Inhalation Dusts and mists	Rat	>5100 mg/m ³	4 hours
	LD50 Dermal	Rabbit	8 g/kg	-
	LD50 Oral	Rat	3.914 g/kg	-
triethylamine	LC50 Inhalation Vapor	Mouse	1027 ppm	4 hours
-	LC50 Inhalation Vapor	Rat	0.42 mg/l	1 hours
	LD50 Oral	Rat	460 mg/kg	-
α-[3-[3-(2H-benzotriazol-2-yl) derivatives	LC50 Inhalation Vapor	Rat	5800 mg/m ³	4 hours
bis(1,2,2,6,6-pentamethyl- 4-piperidyl) sebacate	LD50 Oral	Rat	3.125 g/kg	-
methyl 1,2,2,6,6-pentamethyl- 4-piperidyl sebacate	LD50 Oral	Rat	3.125 g/kg	-
Conclusion/Summary	: There are no data available on the	ne mixture itself.		·
Irritation/Corrosion				
Conclusion/Summary				
Skin	: There are no data available on the	ne mixture itself.		

Respiratory

Eyes

- There are no data available on the mixture itself.There are no data available on the mixture itself.
- Sensitization
- **Conclusion/Summary**

Date of issue 1 May 2016

Version 3

Category 3 Category 3 Category 3

Product name DFT258C DEFT WATERBASED POLYURETHANE

Section 11. Toxicological information

	5
Skin	: There are no data available on the mixture itself.
Respiratory	: There are no data available on the mixture itself.
<u>Mutagenicity</u>	
Conclusion/Summary	: There are no data available on the mixture itself.
Carcinogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Reproductive toxicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Teratogenicity	
Conclusion/Summary	: There are no data available on the mixture itself.
Specific target organ toxici	t <u>y (single exposure)</u>
Name	
N-methyl-2-pyrrolidone triethylamine	
Specific target organ toxici	ty (repeated exposure)

Name	Category
N-methyl-2-pyrrolidone	Category 2

Target organs

: Contains material which causes damage to the following organs: skin.

Contains material which may cause damage to the following organs: kidneys, the reproductive system, liver, heart, spleen, cardiovascular system, upper respiratory tract, adrenal, bone marrow, central nervous system (CNS), eye, lens or cornea.

Aspiration hazard

Not available.

Information on the likely routes of exposure

Potential acute health effects

Eye contact	1	Causes serious eye irritation.
Inhalation	1	No known significant effects or critical hazards.
Skin contact	1	Causes skin irritation. Defatting to the skin.
Ingestion	1	No known significant effects or critical hazards.
Over-exposure signs/sympto	on	<u>15</u>
Eye contact	:	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	:	Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Inhalation (dusts and mists)

87.02 mg/l

Product name DFT258C DEFT WATERBASED POLYURETHANE

Section 11. Toxicological information

Skin contact	: Adverse symptoms may include the following:
Skin contact	irritation
	redness
	dryness
	cracking
	reduced fetal weight
	increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following:
ingestion	reduced fetal weight
	increase in fetal deaths
	skeletal malformations
Delayed and immediate effe	cts and also chronic effects from short and long term exposure
Conclusion/Summary	: There are no data available on the mixture itself. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.
<u>Short term exposure</u>	
Potential immediate	: There are no data available on the mixture itself.
effects	
Potential delayed effects	: There are no data available on the mixture itself.
<u>Long term exposure</u>	
Potential immediate effects	: There are no data available on the mixture itself.
Potential delayed effects	: There are no data available on the mixture itself.
Potential chronic health effe	<u>ects</u>
General	: May cause damage to organs through prolonged or repeated exposure. Prolonged or
	repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: May damage the unborn child.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Numerical measures of toxic	<u>ity</u>
Acute toxicity estimates	
Route	ATE value
Øral	19298.1 mg/kg
Dermal	63815.8 mg/kg
Inhalation (gases)	261064.6 ppm
Inhalation (vapors)	638.2 mg/l
uppolotion (duoto and misto)	

Product name DFT258C DEFT WATERBASED POLYURETHANE

Section 12. Ecological information

Toxicity

Not available.

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
N-methyl-2-pyrrolidone	-	-	Readily

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
M-methyl-2-pyrrolidone	-0.38	3.16	low
triethylamine	1.45	4.9	low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees. Section 6. Accidental release measures

14. Transport information

	DOT	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
	•	Uni	ited States Page: 11/13

Product code 0041152	6	Date of issue 1 N	lay 2016	Version 3	
Product name DFT258C DEFT WATERBASED POLYURETHANE					
14. Transport in	formation				
Environmental hazards	No.	No.	No.		
Marine pollutant substances	Not applicable.	Not applicable.	Not a	oplicable.	

DOT	: None identified.
IMDG	: None identified.
ΙΑΤΑ	: None identified.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

United States

United States inventory (TSCA 8b) : All components are listed or exempted.

SARA 302/304

SARA 304 RQ : Not applicable.

Composition/information on ingredients

No products were found.

SARA 311/312

Classification

: Immediate (acute) health hazard Delayed (chronic) health hazard

Composition/information on ingredients

Name	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
M-methyl-2-pyrrolidone	No.	No.	No.	Yes.	Yes.
triethylamine	Yes.	No.	No.	Yes.	No.
ω-[3-[3-(2H-benzotriazol-2-yl) derivatives	No.	No.	No.	Yes.	No.
α-[3-[3-(2H-benzotriazol-2-yl) derivatives	No.	No.	No.	Yes.	No.
bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	No.	No.	No.	Yes.	No.
methyl 1,2,2,6,6-pentamethyl- 4-piperidyl sebacate	No.	No.	No.	Yes.	No.

<u>SARA 313</u>

Supplier notification

Chemical name
 M-methyl-2-pyrrolidone triethylamine

Concentration 1 - 5

0.5 - 1.5

United States Page: 12/13

Version 3

Product name DFT258C DEFT WATERBASED POLYURETHANE

Section 15. Regulatory information

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

Additional environmental information is contained on the Environmental Data Sheet for this product, which can be obtained from your PPG representative.

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Section 16. Other information

Hazardous Material Information System (U.S.A.)

Health : 3 * Flammability : 1 Physical hazards : 0 (*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)

Health : 3 Flamma Date of previous issue Organization that prepared the MSDS	ability : 1 Instability : 0 : 8/18/2015 : EHS
Key to abbreviations	 ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations

Indicates information that has changed from previously issued version.

Disclaimer

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.