

 Product name:
 DP-LUBRICANT PURPLE
 Page:
 1/10

 Revision Date:
 2014-09-24
 Print date:
 2014-09-24

 Document No.:
 M0147
 SDS-ID:
 AU-EN/10.0

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier

Product name: DP-LUBRICANT PURPLE

Cat. No. 40700059, 40700060, 40700061

Container size: 1, 5, 10 l

Relevant identified uses of the substance or mixture and uses advised against

<u>Application:</u> For materialographic preparation

Details of the supplier of the safety data sheet

Supplier: Struers Australia

27 Mayneview Street Milton QLD 4064, Australia

Responsible for safety data Responsible for safety data sheet authoring: DHI

sheet authoring: Any questions to the contents of this safety data sheet should be sent to:

Lisbeth.Mygind@struers.dk

Emergency telephone number

Emergency telephone: +61 7 3512 9600

(Only during office hours)

 Product name:
 DP-LUBRICANT PURPLE
 Page:
 2/10

 Revision Date:
 2014-09-24
 Print date:
 2014-09-24

 Document No.:
 M0147
 SDS-ID:
 AU-EN/10.0

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

This product is classified as hazardous according to criteria of NOHSC:

HAZARDOUS SUBSTANCES. DANGEROUS GOODS

67/548/EEC / 1999/45/EC: F;R11

GHS: Flam. Liq. 2;H225 - Eye Irrit. 2;H319 (*)

Label elements

(*)



Danger

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P280 Wear protective gloves, eye and face protection.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local regulations.

Other hazards

PBT/vPvB: Not relevant.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

The product contains: organic solvents and pigments.

67/548/EEC:

<u>%:</u>	CAS-No.:	EC No.:	REACH Reg. No:	<u>Chemical name:</u>	Hazard classification:	Notes:
70-85	64-17-5	200-578-6	-	Ethanol	F;R11	
5-<10	67-63-0	200-661-7	01-2119457558- 25-xxxx	Propan-2-ol	F;R11 Xi;R36 R67	
5-15	57-55-6	200-338-0	-	Propylene glycol	-	
<0.1	81457-64-9	279-766-5	-	Blue dye	-	
<0.1	130-22-3	204-981-8	-	Red dye (C. I. Acid Red 211)	-	

 Product name:
 DP-LUBRICANT PURPLE
 Page:
 3/10

 Revision Date:
 2014-09-24
 Print date:
 2014-09-24

 Document No.:
 M0147
 SDS-ID:
 AU-EN/10.0

GHS:

<u>%:</u>	CAS-No.:	EC No.:	REACH Reg. No:	<u>Chemical name:</u>	Hazard classification:	Notes:
70-85	64-17-5	200-578-6	-	Ethanol	Flam. Liq. 2;H225 Eye Irrit. 2;H319	
5-<10	67-63-0	200-661-7	01-2119457558- 25-xxxx	Propan-2-ol	Flam. Liq. 2;H225 Eye Irrit. 2;H319 STOT SE 3;H336	
5-15	57-55-6	200-338-0	-	Propylene glycol	-	
<0.1	81457-64-9	279-766-5	-	Blue dye	-	
<0.1	130-22-3	204-981-8	_	Red dye (C. I. Acid Red 211)	_	

References: The full text for all R-phrases and hazard statements are displayed in section 16.

SECTION 4: FIRST AID MEASURES

Description of first aid measures

Burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.

<u>Inhalation:</u> Move into fresh air and keep at rest.

Skin contact: Remove contaminated clothes and rinse skin thoroughly with water.

Eye contact: Immediately flush with plenty of water for up to 15 minutes. Remove any contact

lenses and open eyelids widely. If irritation persists: Seek medical attention and

bring these instructions.

Immediately rinse mouth and drink plenty of water. Keep person under

observation. If person becomes uncomfortable seek hospital and bring these

instructions.

Most important symptoms and effects, both acute and delayed

Symptoms/effects: See section 11 for more detailed information on health effects and symptoms.

Indication of any immediate medical attention and special treatment needed

Medical attention/treatments: Not known.

 Product name:
 DP-LUBRICANT PURPLE
 Page:
 4/10

 Revision Date:
 2014-09-24
 Print date:
 2014-09-24

 Document No.:
 M0147
 SDS-ID:
 AU-EN/10.0

SECTION 5: FIREFIGHTING MEASURES

Extinguishing media

Extinguishing media: Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

Cool containers exposed to heat with water spray and remove container, if no

risk is involved.

Special hazards arising from the substance or mixture

Specific hazards: The product is highly flammable, and explosive vapours/air mixtures may be

formed even at normal room temperatures. Vapours may be ignited by a spark, a

hot surface or an ember.

Advice for firefighters

Protective equipment for

Use air-supplied respirator during fire fighting.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

<u>Personal precautions:</u> Do not smoke or use open fire, or other sources of ignition. Avoid inhalation of

vapours and contact with skin and eyes.

Environmental precautions

Environmental

Do not discharge into drains, water courses or onto the ground.

precautions:

fire-fighters:

Methods and material for containment and cleaning up

Spill Cleanup Methods: Large quantities of concentrate should not be discharged into the drain but

removed with absorbing material. Do not use sawdust or other combustible

material.

Reference to other sections

References: For personal protection, see section 8. For waste disposal, see section 13.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Safe handling advice: Avoid inhalation of vapours and contact with skin and eyes. Observe good

chemical hygiene practices. Take precautionary measures against static

discharges.

<u>Technical measures:</u> Do not smoke or use open fire or other sources of ignition.

<u>Technical precautions:</u> Local exhaust is recommended.

Conditions for safe storage, including any incompatibilities

<u>Technical measures for safe</u> Follow rules for flammable liquids.

storage:

Storage conditions: Store in a cool and well-ventilated place. Avoid contact with oxidising agents.

Specific end use(s)

Specific use(s): Not relevant.

 Product name:
 DP-LUBRICANT PURPLE
 Page:
 5/10

 Revision Date:
 2014-09-24
 Print date:
 2014-09-24

 Document No.:
 M0147
 SDS-ID:
 AU-EN/10.0

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Occupational exposure limits:

CAS-No.:	Chemical name:	<u>As:</u>	<u>Exposur</u>	re limits:	Type:	Notes:	References:
67-63-0	Isopropyl alcohol	-	400 ppm	983 mg/m3	TWA	-	NOHSC
		-	500 ppm	1230 mg/m3	STEL	15min	
57-55-6	Propane-1,2-diol (total, vapour & particulates)	-	150 ppm	474 mg/m3	TWA	-	NOHSC
57-55-6	Propane-1,2-diol (particulates only)	-		10 mg/m3	TWA	-	NOHSC
64-17-5	Ethyl alcohol	-	1000 ppm	1880 mg/m3	TWA	-	NOHSC

Exposure controls

Engineering measures: Provide adequate ventilation. Observe Occupational Exposure Limits and

minimise the risk of inhalation of vapours.

<u>Personal protection:</u> Personal protection equipment should be chosen according to the CEN

standards and in discussion with the supplier of the personal protective

equipment.

Respiratory equipment: In case of inadequate ventilation and work of brief duration, use suitable

respiratory equipment. Use respiratory equipment with gas filter, type A2.

<u>Hand protection:</u> Wear protective gloves. Nitrile gloves are recommended, but be aware that the

liquid may penetrate the gloves. Frequent change is advisable. The most suitable glove must be chosen in consultation with the gloves supplier, who

can inform about the breakthrough time of the glove material.

Eve protection: Wear goggles/face shield. (*)

Skin protection: No special precautions.

Environmental Exposure

Controls:

Not available.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance: purple liquid

Odour: odour of alcohol

pH: Not relevant.

Boiling point: Not available.

Flash point: 13°C

Explosion limits: 3,2-19 %

Relative density: 0,81

Solubility: Miscible with water.

Other information

Other data: Volatile Organic Compound (VOC): 720 g/l (calculated)

 Product name:
 DP-LUBRICANT PURPLE
 Page:
 6/10

 Revision Date:
 2014-09-24
 Print date:
 2014-09-24

 Document No.:
 M0147
 SDS-ID:
 AU-EN/10.0

SECTION 10: STABILITY AND REACTIVITY

Reactivity

Reactivity: None known.

Chemical stability

Stability: Stable under normal temperature conditions.

Possibility of hazardous reactions

Hazardous Reactions: None known.

Conditions to avoid

Conditions/materials to avoid: Direct sunlight. Heating. Oxidizing agents.

Incompatible materials

<u>Incompatible materials:</u> None known.

Hazardous decomposition products

<u>Hazardous decomposition</u> None in particular.

products:

SECTION 11: TOXICOLOGICAL INFORMATION

Information on toxicological effects

In case of insufficient ventilation, extensive use may cause the damage described below.

Inhalation: Small quantities: Vapours may irritate throat and respiratory system and cause

coughing.

Large quantities: Vapours may irritate throat and respiratory system and cause

headache, dizziness and dullness.

Skin contact: Prolonged contact may cause redness, irritation and dry skin. Contains 2

-propanol which may penetrate the skin.

<u>Eye contact:</u> Causes serious eye irritation. (*)
<u>Ingestion:</u> May irritate and cause malaise.

Specific effects: Frequent inhalation of even small concentrations may cause irritability, fatigue

and memory failure and eventually permanent damage to the nervous system,

including the brain.

Carcinogenicity:

National Toxicology Program (NTP): No.

I.A.R.C. Monographs: No.

Product name:DP-LUBRICANT PURPLEPage:7/10Revision Date:2014-09-24Print date:2014-09-24Document No.:M0147SDS-ID:AU-EN/10.0

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

<u>Ecotoxicity:</u> The product is not expected to be hazardous to the environment.

Persistence and degradability

<u>Degradability:</u> The product is 80% biodegradable.

Bioaccumulative potential

Bioaccumulative potential: No data available on bioaccumulation.

Mobility in soil

Mobility: No data available.

Results of PBT and vPvB assessment

PBT/vPvB: Not relevant.

Other adverse effects

Other adverse effects: None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Dispose of waste and residues in accordance with local authority requirements. Waste is classified as hazardous waste.

Waste from residues: EWC-code: 16 09 08

Product name:DP-LUBRICANT PURPLEPage:8/10Revision Date:2014-09-24Print date:2014-09-24Document No.:M0147SDS-ID:AU-EN/10.0

SECTION 14: TRANSPORT INFORMATION

UN number

<u>UN-No:</u> 1993

UN proper shipping name

Proper Shipping Name: FLAMMABLE LIQUID, N.O.S (Ethanol, Isopropylalcohol Mixture)

Additional IMDG information:

EmS: F-E , S-E MFAG: 1

Transport hazard class(es)

Class: 3

Packing group

PG:

Environmental hazards

Marine pollutant: No. Environmentally Hazardous No.

substance:

Special precautions for user

Special precautions: None known.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

<u>Transport in bulk:</u> Not relevant.

 Product name:
 DP-LUBRICANT PURPLE
 Page:
 9/10

 Revision Date:
 2014-09-24
 Print date:
 2014-09-24

 Document No.:
 M0147
 SDS-ID:
 AU-EN/10.0

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Special provisions: AICS: Listed.

National regulation: Work Health and Safety Regulations 2011

National model Code of Practice for the Labelling of Workplace Hazardous

Chemicals (2011)

National model Code of Practice for the Preparation of Safety Data Sheets for

Hazardous Chemicals (2011).

National Exposure Standard [NOHSC:1003(1995)].

National Standard: Approved criteria for classifying hazardous substances

[NOHSC:1008(2004)]. 3rd Edition.

The Industrial Chemicals (Notification and Assessment) Act 1989

(Commonwealth), including listing on the Australian Inventory of Chemical

Substances (AICS).

Commission Decision 2000/532/EC as amended by Decision 2001/118/EC establishing a list of wastes and hazardous waste pursuant to Council Directive 75/442/EEC on waste and Directive 91/689/EEC on hazardous waste with

amendments.

Chemical Safety Assessment

CSA status: Not relevant.

 Product name:
 DP-LUBRICANT PURPLE
 Page:
 10/10

 Revision Date:
 2014-09-24
 Print date:
 2014-09-24

 Document No.:
 M0147
 SDS-ID:
 AU-EN/10.0

SECTION 16: OTHER INFORMATION

The user must be instructed in the proper work procedure and be familiar with the contents of these instructions.

The following sections contain revisions or new statements: 2, 8, 11.

The (*) indicates the changes made with respect to the previous version.

Approved by DHI.

Allan Vorup

Additional information: Classification according to Regulation (EC) No. 1272/2008:

Calculation method.

Wording of R-phrases and

H-statements:

R11 Highly flammable.
R36 Irritating to eyes.

R67 Vapours may cause drowsiness and dizziness.

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

The information on this data sheet represents our current data and is reliable provided that the product is used under the prescribed conditions and in accordance with the application specified on the packaging and/or in the technical guidance literature. Any other use of the product which involves using the product in combination with any other product or any other process is the responsibility of the user.

Made by DHI - Environment and Toxicology, Agern Allé 5, DK-2970 Hørsholm, Denmark. www.dhigroup.com.