

MATERIAL SAFETY DATA SHEET

Product Trade Name: DRILFOAM®

Revision Date: 16-Jan-2014

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name: DRILFOAM®
Synonyms: None
Chemical Family: Blend
Application: Foaming Agent

Manufacturer/Supplier Baroid Fluid Services
Product Service Line of Halliburton
P.O. Box 1675
Houston, TX 77251
Telephone: (281) 871-4000
Emergency Telephone: (281) 575-5000

Prepared By Chemical Compliance
Telephone: 1-580-251-4335
e-mail: fdunexchem@halliburton.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	CAS Number	PERCENT (w/w)	ACGIH TLV-TWA	OSHA PEL-TWA
Ethanol	64-17-5	5 - 10%	STEL: 1000 ppm	1000 ppm
Isopropanol	67-63-0	5 - 10%	TWA: 200 ppm STEL: 400 ppm	400 ppm

3. HAZARDS IDENTIFICATION

Hazard Overview May cause eye, skin, and respiratory irritation. May cause headache, dizziness, and other central nervous system effects. May be absorbed through the skin. May be harmful if swallowed. Repeated overexposure may cause liver and kidney effects. Flammable.

4. FIRST AID MEASURES

Inhalation If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

Skin In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes. Get medical attention. Remove contaminated clothing and launder before reuse.

Eyes In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.

Ingestion	Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.
Notes to Physician	Not Applicable

5. FIRE FIGHTING MEASURES

Flash Point/Range (F):	74
Flash Point/Range (C):	23
Flash Point Method:	PMCC
Autoignition Temperature (F):	750
Autoignition Temperature (C):	398
Flammability Limits in Air - Lower (%):	2
Flammability Limits in Air - Upper (%):	12

Fire Extinguishing Media Water fog, carbon dioxide, foam, dry chemical.

Special Exposure Hazards May be ignited by heat, sparks or flames. Use water spray to cool fire exposed surfaces. Closed containers may explode in fire. Decomposition in fire may produce toxic gases.

Special Protective Equipment for Fire-Fighters Full protective clothing and approved self-contained breathing apparatus required for fire fighting personnel.

NFPA Ratings: Health 1, Flammability 3, Reactivity 0
HMIS Ratings: Health 1, Flammability 3, Reactivity 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures Use appropriate protective equipment.

Environmental Precautionary Measures Prevent from entering sewers, waterways, or low areas.

Procedure for Cleaning / Absorption Isolate spill and stop leak where safe. Remove ignition sources and work with non-sparking tools. Contain spill with sand or other inert materials. Scoop up and remove.

7. HANDLING AND STORAGE

Handling Precautions Avoid contact with eyes, skin, or clothing. Avoid breathing vapors. Wash hands after use. Launder contaminated clothing before reuse. Ground and bond containers when transferring from one container to another.

Storage Information Store away from oxidizers. Keep from heat, sparks, and open flames. Keep container closed when not in use. Product has a shelf life of 24 months.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls Use in a well ventilated area. Local exhaust ventilation should be used in areas without good cross ventilation.

Respiratory Protection Organic vapor respirator.

Hand Protection Impervious rubber gloves.

Skin Protection	Rubber apron.
Eye Protection	Chemical goggles; also wear a face shield if splashing hazard exists.
Other Precautions	Eyewash fountains and safety showers must be easily accessible.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Color:	Light yellow
Odor:	Alcohol
pH:	7.3-7.8
Specific Gravity @ 20 C (Water=1):	1.02
Density @ 20 C (lbs./gallon):	8.52
Bulk Density @ 20 C (lbs/ft3):	Not Determined
Boiling Point/Range (F):	Not Determined
Boiling Point/Range (C):	Not Determined
Freezing Point/Range (F):	Not Determined
Freezing Point/Range (C):	Not Determined
Vapor Pressure @ 20 C (mmHg):	Not Determined
Vapor Density (Air=1):	Not Determined
Percent Volatiles:	Not Determined
Evaporation Rate (Butyl Acetate=1):	Not Determined
Solubility in Water (g/100ml):	Soluble
Solubility in Solvents (g/100ml):	Not Determined
VOCs (lbs./gallon):	Not Determined
Viscosity, Dynamic @ 20 C (centipoise):	192
Viscosity, Kinematic @ 20 C (centistokes):	Not Determined
Partition Coefficient/n-Octanol/Water:	Not Determined
Molecular Weight (g/mole):	Not Determined

10. STABILITY AND REACTIVITY

Stability Data:	Stable
Hazardous Polymerization:	Will Not Occur
Conditions to Avoid	Keep away from heat, sparks and flame.
Incompatibility (Materials to Avoid)	Strong oxidizers. Strong alkalis.
Hazardous Decomposition Products	Oxides of sulfur. Oxides of nitrogen. Ammonia. Carbon monoxide and carbon dioxide.
Additional Guidelines	Not Applicable

11. TOXICOLOGICAL INFORMATION

Principle Route of Exposure	Eye or skin contact, inhalation.
------------------------------------	----------------------------------

Symptoms related to exposure

Acute Toxicity

Inhalation

May cause respiratory irritation. May cause central nervous system depression including headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness.

Eye Contact	May cause eye irritation.
Skin Contact	May cause skin irritation. May be absorbed through the skin and produce effects similar to those caused by inhalation and/or ingestion.
Ingestion	Irritation of the mouth, throat, and stomach. May cause central nervous system depression including headache, dizziness, drowsiness, muscular weakness, incoordination, slowed reaction time, fatigue blurred vision, slurred speech, giddiness, tremors and convulsions. May cause kidney damage.

Chronic Effects/Carcinogenicity Repeated overexposure may cause liver and kidney effects.

Toxicology data for the components

Substances	CAS Number	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethanol	64-17-5	7060 mg/kg (Rat)	No data available	124.7 mg/L (Rat) 4 h
Isopropanol	67-63-0	4396 mg/kg (Rat) 5840 mg/kg (Rat) 3600 mg/kg (Mouse)	12800 mg/kg (Rat) 12870 mg/kg (Rabbit) 16.4 mL/kg (Rabbit)	72.6 mg/L (Rat) 4h >1000 ppm(24.6 mg/L) (Rat)

12. ECOLOGICAL INFORMATION

Ecotoxicological Information

Ecotoxicity Product

Acute Fish Toxicity:	Not determined
Acute Crustaceans Toxicity:	Not determined
Acute Algae Toxicity:	Not determined

Ecotoxicity Substance

Substances	CAS Number	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Ethanol	64-17-5	No information available	LC50: > 100 mg/L (Pimephales promelas)	No information available	LC50: 9268 - 14221 mg/L (Daphnia magna)
Isopropanol	67-63-0	EC50: > 1000 mg/l(Desmodesmus subspicatus) EC50(7d): 1800 mg/L (mean extinction value) (Scenedesmus quadricauda)	LC50: 9640 mg/l (Pimephales promelas)	TT(16h): 1050 mg/L (Pseudomonas putida)	EC50: 13299 mg/l (Daphnia magna) EC50(24h): > 10000 mg/L (Daphnia magna)

12.2 Persistence and degradability

No information available

Substances	Persistence and Degradability
Isopropanol	Readily biodegradable

12.3 Bioaccumulative potential

No information available

Substances	Log Pow
Ethanol	-0.32
Isopropanol	0.05

12.4 Mobility in soil

No information available

12.5 Results of PBT and vPvB assessment

No information available.

12.6 Other adverse effects

13. DISPOSAL CONSIDERATIONS

Disposal Method	Disposal should be made in accordance with federal, state, and local regulations.
Contaminated Packaging	Follow all applicable national or local regulations.

14. TRANSPORT INFORMATION

Land Transportation

DOT

UN1993, Flammable Liquid, N.O.S. (Contains Ethanol, Isopropanol) , 3 , III , (23.3 C)
NAERG 128

Not Restricted when shipped in containers less than 119 gallons as authorized by 49 CFR 173.150(e)(1) and 49 CFR 173.150(f)(2).

Canadian TDG

Flammable Liquid, N.O.S. (Contains Ethanol, Isopropanol) , 3 , UN1993 , III , (23.3 C)

ADR

UN1993, Flammable Liquid, N.O.S (Contains Ethanol, Isopropanol) , 3 , III

Air Transportation

ICAO/IATA

UN1993, Flammable Liquid, N.O.S , 3 , III (Contains Ethanol, Isopropanol)

Sea Transportation

IMDG

UN1993, Flammable Liquid, N.O.S (Contains Ethanol, Isopropanol) , 3 , III , (23.3 C)
EmS F-E, S-E

Other Transportation Information

Labels: Flammable Liquid

15. REGULATORY INFORMATION

US Regulations

US TSCA Inventory All components listed on inventory or are exempt.

EPA SARA Title III Extremely Hazardous Substances Not applicable

EPA SARA (311,312) Hazard Class Acute Health Hazard
Chronic Health Hazard
Fire Hazard

EPA SARA (313) Chemicals	This product contains toxic chemical(s) listed below which is(are) subject to the reporting requirements of Section 313 of Title III of SARA and 40 CFR Part 372: Isopropanol//67-63-0
EPA CERCLA/Superfund Reportable Spill Quantity	Not applicable.
EPA RCRA Hazardous Waste Classification	If product becomes a waste, it does meet the criteria of a hazardous waste as defined by the US EPA, because of: Ignitability D001
California Proposition 65	The California Proposition 65 regulations apply to this product.
MA Right-to-Know Law	One or more components listed.
NJ Right-to-Know Law	One or more components listed.
PA Right-to-Know Law	One or more components listed.
Canadian Regulations	
Canadian DSL Inventory	All components listed on inventory or are exempt.
WHMIS Hazard Class	B2 Flammable Liquids D2B Toxic Materials

16. OTHER INFORMATION

The following sections have been revised since the last issue of this SDS

Not applicable

Additional Information	For additional information on the use of this product, contact your local Halliburton representative. For questions about the Safety Data Sheet for this or other Halliburton products, contact Chemical Compliance at 1-580-251-4335.
Disclaimer Statement	This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

*****END OF MSDS*****