

SAFETY DATA SHEET

M31867 - ANSI - EN



Occidental Chemical Corporation

A subsidiary of Occidental Petroleum Corporation



DRY CAUSTIC POTASH (ALL GRADES)

SDS No.: M31867

SDS Revision Date: 04-Mar-2016

SECTION 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Company Identification:	Occidental Chemical Corporation 5005 LBJ Freeway P.O. Box 809050 Dallas, TX 75380-9050 1-800-752-5151
24 Hour Emergency Telephone Number:	1-800-733-3665 or 1-972-404-3228 (U.S.); CHEMTREC (outside U.S.): +1 703-527-3887; +(56)-25814934 (Chile); 4001-204937 (China); 800-968-793 (Hong Kong); +(61)-290372994 (Australia); CHEMTREC Contract No: CCN 16186
To Request an SDS:	MSDS@oxy.com or 1-972-404-3245
Customer Service:	1-800-752-5151 or 1-972-404-3700
Product Identifier:	DRY CAUSTIC POTASH (ALL GRADES)
Trade Name:	Caustic Potash-Crystal; Caustic Potash-Flake; Caustic Potash-Flake 90%; Dry Caustic Potash (Off Spec)
Synonyms:	Potassium hydroxide, KOH Dry, Caustic Potash-Anhydrous
Product Use:	Manufacture of substances, Formulation, Glass Production, Cleaner, Process cleaner, Petroleum Industry, Food processing, Fertilizer, Chemical Intermediate, Coatings and paints, fillers, putties, thinners, Washing and cleaning products, Electrical batteries and accumulators, Extraction agents, pH adjustment, Neutralization agent, Precipitants, Flocculants
Uses Advised Against:	None identified

DRY CAUSTIC POTASH (ALL GRADES)

SDS No.: M31867

SDS Revision Date: 04-Mar-2016

SECTION 2. HAZARDS IDENTIFICATION

OSHA REGULATORY STATUS: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

EMERGENCY OVERVIEW:

Color: White, Off-white
Physical State: Solid
Odor: Odorless

Signal Word: **DANGER**

MAJOR HEALTH HAZARDS: CORROSIVE. CAUSES SERIOUS EYE DAMAGE. CAUSES SEVERE SKIN BURNS. HARMFUL IF SWALLOWED.

PHYSICAL HAZARDS: MAY BE CORROSIVE TO METALS. Mixing with water, acid or incompatible materials may cause splattering and release of heat. Do not store in aluminum container or use aluminum fittings or transfer lines, as flammable hydrogen gas may be generated.

ECOLOGICAL HAZARDS: This material has exhibited moderate toxicity to aquatic organisms.

PRECAUTIONARY STATEMENTS: Wear protective gloves, protective clothing, eye, and face protection. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling. Do not breathe dust. Do not ingest. Do not eat, drink, or smoke when using this product. Keep container tightly closed. Use only with adequate ventilation.

ADDITIONAL HAZARD INFORMATION: Toxicity may be delayed, and may not be readily visible. Significant exposures must be referred for medical attention immediately. There is no specific antidote.

GHS CLASSIFICATION:

GHS: PHYSICAL HAZARDS:	Corrosive to Metals Mixing with water may cause splattering and release of heat
GHS: CONTACT HAZARD - SKIN:	Category 1B - Causes severe skin burns and eye damage.
GHS: CONTACT HAZARD - EYE:	Category 1 - Causes serious eye damage
GHS: ACUTE TOXICITY - ORAL:	Category 4 - Harmful if swallowed.
GHS: CARCINOGENICITY:	Not classified as a carcinogen per GHS criteria. This product is not classified as a carcinogen by NTP, IARC or OSHA.
GHS: HAZARDOUS TO AQUATIC ENVIRONMENT - ACUTE HAZARD:	Category 3 - Harmful to aquatic life

DRY CAUSTIC POTASH (ALL GRADES)

SDS No.: M31867

SDS Revision Date: 04-Mar-2016

UNKNOWN ACUTE TOXICITY: A percentage of this product consists of ingredient(s) of unknown acute toxicity.

Unknown Acute Dermal Toxicity:

There is no acute dermal toxicity data available for this material. 100% of this product consists of ingredient(s) of unknown acute dermal toxicity.

Unknown Acute Inhalation Toxicity:

There is no acute inhalation toxicity data available for this material. 100% of this product consists of ingredient(s) of unknown acute inhalation toxicity.

GHS SYMBOL: Corrosive, Exclamation mark



GHS SIGNAL WORD: DANGER

GHS HAZARD STATEMENTS:

GHS - Physical Hazard Statement(s)

- May be corrosive to metals

GHS - Health Hazard Statement(s)

- Causes serious eye damage
- Causes severe skin burns and eye damage
- Harmful if swallowed

GHS - Precautionary Statement(s) - Prevention

- Wear protective gloves/protective clothing/eye protection/face protection
- Wash thoroughly after handling
- Do not breathe dust, fume, gas, mist, vapors, or spray
- Do not eat, drink or smoke when using this product
- Keep only in original container

GHS - Precautionary Statement(s) - Response

- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower
- Wash contaminated clothing before reuse
- IF INHALED: Remove person to fresh air and keep comfortable for breathing
- Immediately call a POISON CENTER or doctor/physician
- IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
- IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
- Specific treatment (see First Aid information on product label and/or Section 4 of the SDS)
- Absorb spillage to prevent material damage

DRY CAUSTIC POTASH (ALL GRADES)

SDS No.: M31867

SDS Revision Date: 04-Mar-2016

GHS - Precautionary Statement(s) - Storage

- Store in corrosive resistant and NON-ALUMINUM container with a resistant inner liner (NOTE: flammable hydrogen gas may be generated if aluminum container and/or aluminum fittings are used)
- Store locked up

GHS - Precautionary Statement(s) - Disposal

- Dispose of contents and container in accordance with applicable local, regional, national, and/or international regulations

Hazards Not Otherwise Classified (HNOC)

None identified

See Section 11: TOXICOLOGICAL INFORMATION

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**Synonyms:** Potassium hydroxide, KOH Dry, Caustic Potash-Anhydrous

Component	Percent [%]	CAS Number
Potassium hydroxide	84.0 - 92.0	1310-58-3
Water	8.0 - 16.0	7732-18-5

SECTION 4. FIRST AID MEASURES

INHALATION: If inhalation of dust occurs and adverse effects result, remove to uncontaminated area. Evaluate ABC's (is Airway constricted, is Breathing occurring, and is blood Circulating) and treat symptomatically. GET MEDICAL ATTENTION IMMEDIATELY.

SKIN CONTACT: Immediately flush contaminated areas with water. Remove contaminated clothing, jewelry and shoes. Wash contaminated areas with large amounts of water. GET MEDICAL ATTENTION IMMEDIATELY. Thoroughly clean and dry contaminated clothing before reuse. Discard contaminated leather goods.

EYE CONTACT: Immediately flush contaminated eyes with a directed stream of water for as long as possible. Remove contact lenses, if present, then continue rinsing. GET MEDICAL ATTENTION IMMEDIATELY.

INGESTION: If swallowed, do not induce vomiting. For definite or probable ingestion, do not administer oral fluids. If vomiting occurs spontaneously, keep airway clear. Monitor airway. Volume resuscitation (IV fluids) and circulatory support (CPR) may be required. Never give anything by mouth to an unconscious or convulsive person. GET MEDICAL ATTENTION IMMEDIATELY.

Most Important Symptoms/Effects (Acute and Delayed) Corrosive. This material may be corrosive to any tissue it comes in contact with. It can cause serious burns and extensive tissue destruction resulting in: liquefaction, necrosis, and/or perforation.

DRY CAUSTIC POTASH (ALL GRADES)

SDS No.: M31867

SDS Revision Date: 04-Mar-2016

Acute Symptoms/Effects: Listed below.

Inhalation (Breathing): Respiratory System Effects: Exposure to airborne material may cause irritation, redness of upper and lower airways, coughing, laryngeal spasm and edema, shortness of breath, bronchio-constriction, and possible pulmonary edema. Severe and permanent scarring may occur. Aspiration of this material may cause the same conditions.

Skin: Skin Corrosion: When skin is exposed to solid product with moisture, may cause redness, itching, irritation, swelling, burns (first, second, or third degree), liquefaction of skin, and damage to underlying tissues (deep and painful wounds).

Eye: Serious Eye Damage. Eye exposures may cause eye lid burns, conjunctivitis, corneal edema, corneal burn, corneal perforation, damage to internal contents of the eye, permanent visual defects, and blindness and/or loss of the eye.

Ingestion (Swallowing): Gastrointestinal System Effects: Exposure by ingestion may cause irritation, swelling, and perforation of upper and lower gastrointestinal tissues. Permanent scarring may occur.

Delayed Symptoms/Effects:

- Repeated or prolonged exposures to skin that cause irritation may cause a chronic dermatitis

Medical Conditions Aggravated by Exposure: Corrosive. May aggravate pre-existing eye, skin, and respiratory conditions (including asthma and other breathing disorders).

Protection of First-Aiders: Protect yourself by avoiding contact with this material. Use personal protective equipment. Refer to Section 8 for specific personal protective equipment recommendations. Avoid contact with skin and eyes. Do not ingest. Do not breathe dust. At minimum, treating personnel should utilize PPE sufficient for prevention of bloodborne pathogen transmission.

Notes to Physician: Medical observation and assessment is recommended for all ingestions, all eye exposures, and symptomatic inhalation and dermal exposures. For symptomatic ingestion, do not administer oral fluids and consider investigation by endoscopy, X-ray, or CT scan. Esophageal perforation, airway compromise, hypotension, and shock are possible. For prolonged exposures and significant exposures, consider delayed injury to exposed tissues. There is no antidote. Treatment is supportive care. Follow normal parameters for airway, breathing, and circulation. Surgical intervention may be required.

SECTION 5. FIRE-FIGHTING MEASURES

Fire Hazard: Non-combustible, substance itself does not burn but may decompose upon heating to produce corrosive and/or toxic fumes. May react with chemically reactive metals such as aluminum, zinc, magnesium, copper, etc. to release hydrogen gas which can form explosive mixtures in air.

Extinguishing Media: Use extinguishing agents appropriate for surrounding fire. Use water spray to keep containers cool. Avoid direct contact of this product with water as this can cause an exothermic reaction.

Fire Fighting: Move container from fire area if it can be done without risk. Cool containers with water. Wear NIOSH approved positive-pressure self-contained breathing apparatus operated in pressure demand mode. Avoid contact with skin and eyes. Avoid inhalation of material or combustion by-products.

Hazardous Combustion Products:

No information available

DRY CAUSTIC POTASH (ALL GRADES)

SDS No.: M31867

SDS Revision Date: 04-Mar-2016

Sensitivity to Mechanical Impact: Not sensitive.

Sensitivity to Static Discharge: Not sensitive.

Lower Flammability Level (air): Not flammable

Upper Flammability Level (air): Not flammable

Flash point: Not flammable

Auto-ignition Temperature: Not determined

GHS: PHYSICAL HAZARDS:

- Corrosive to Metals
 - Mixing with water may cause splattering and release of heat
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions:

Avoid contact with skin, eyes and clothing. Do not breathe vapors, fumes or mist. Wear appropriate personal protective equipment recommended in Section 8, Exposure Controls / Personal Protection, of the SDS.

Methods and Materials for Containment and Cleaning Up:

Shovel dry material into suitable container. Recycle or dispose according to regulations.

Environmental Precautions:

Keep out of water supplies and sewers. This material is alkaline and may raise the pH of surface waters with low buffering capacity. Releases should be reported, if required, to appropriate agencies.

SECTION 7. HANDLING AND STORAGE

Precautions for Safe Handling:

Avoid breathing dust. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling. When mixing, slowly add to water to minimize heat generation and spattering.

Safe Storage Conditions:

Store and handle in accordance with all current regulations and standards. Keep container tightly closed and properly labeled. Store in a cool, dry, well ventilated area. Do not store in aluminum container or use aluminum fittings or transfer lines, as flammable hydrogen gas may be generated. Keep separated from incompatible substances (see below or Section 10 of the Safety Data Sheet).

Incompatibilities/ Materials to Avoid:

Acids, halogenated compounds, and prolonged contact with aluminum, brass, bronze, copper, lead, tin, zinc or other alkali sensitive metals or alloys, water

DRY CAUSTIC POTASH (ALL GRADES)

SDS No.: M31867

SDS Revision Date: 04-Mar-2016

GHS: PHYSICAL HAZARDS:

- Corrosive to Metals
- Mixing with water may cause splattering and release of heat

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Regulatory Exposure Limit(s): None. This product does not contain any components that have non-regulatory occupational exposure limits (OEL's).

OEL: Occupational Exposure Limit; OSHA: United States Occupational Safety and Health Administration; PEL: Permissible Exposure Limit; TWA: Time Weighted Average; STEL: Short Term Exposure Limit

NON-REGULATORY EXPOSURE LIMIT(S): Listed below for the product components that have non-regulatory occupational exposure limits (OEL's).

Component	ACGIH TWA	ACGIH STEL	ACGIH Ceiling	OSHA TWA (Vacated)	OSHA STEL (Vacated)	OSHA Ceiling (Vacated)
Potassium hydroxide	-----	-----	2 mg/m ³	-----	-----	2 mg/m ³

- The Non-Regulatory United States Occupational Safety and Health Administration (OSHA) limits, if shown, are the Vacated 1989 PEL's (vacated by 58 FR 35338, June 30, 1993).

- The American Conference of Governmental Industrial Hygienists (ACGIH) is a voluntary organization of professional industrial hygiene personnel in government or educational institutions in the United States. The ACGIH develops and publishes recommended occupational exposure limits each year called Threshold Limit Values (TLVs) for hundreds of chemicals, physical agents, and biological exposure indices.

Component	OXY REL 8 hr TWA	OXY REL STEL	OXY REL Ceiling
Potassium hydroxide 1310-58-3 (84.0 - 92.0)			2 mg/m ³

ENGINEERING CONTROLS: Provide local exhaust ventilation where dust or mist may be generated. Ensure compliance with applicable exposure limits.

PERSONAL PROTECTIVE EQUIPMENT:

Eye Protection: Wear chemical safety goggles with a face-shield to protect against eye and skin contact when appropriate. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Skin and Body Protection: Wear protective clothing to minimize skin contact. When potential for contact with wet material exists, wear Tychem® or similar chemical protective suit. When potential for contact with dry material exists, wear disposable coveralls suitable for dust exposure, such as Tyvek®. Always place pants legs over boots. Thoroughly clean and dry contaminated clothing before reuse. Discard contaminated leather goods.

Hand Protection: Wear chemical protective gloves. Consult a glove supplier for assistance in selecting an appropriate chemical resistant glove.

DRY CAUSTIC POTASH (ALL GRADES)

SDS No.: M31867

SDS Revision Date: 04-Mar-2016

Protective Material Types:

Butyl rubber, Natural rubber, Nitrile, Polyvinyl chloride (PVC), Tychem®, Tyvek®

Respiratory Protection: A NIOSH approved respirator with N95 dust/mist filter (1/2 facepiece) or N100 dust/mist filter (full facepiece) cartridges may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits, or when symptoms have been observed that are indicative of overexposure. If eye irritation occurs, a full face style mask should be used. A respiratory protection program that meets 29 CFR 1910.134 must be followed whenever workplace conditions warrant use of a respirator.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Solid
Color:	White, Off-white
Odor:	Odorless
Odor Threshold [ppm]:	Not applicable.
Molecular Weight:	56.11
Molecular Formula:	KOH
Boiling Point/Range:	Not applicable
Melting Point/Range:	752 °F (400 °C)
Vapor Pressure:	60 mmHg @ 1013 °C
Vapor Density (air=1):	Not applicable
Relative Density/Specific Gravity (water=1):	2.044 @ 20 °C
Density:	2.04 gm/cc @ 20 °C
Water Solubility:	100%
pH:	Not applicable
Volatility:	0%
Evaporation Rate (ether=1):	Not applicable
Partition Coefficient (n-octanol/water):	No information available
Flash point:	Not flammable
Flammability (solid, gas):	Not flammable
Lower Flammability Level (air):	Not flammable
Upper Flammability Level (air):	Not flammable
Auto-ignition Temperature:	Not determined
Viscosity:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity: Soluble in water, releasing heat sufficient to ignite combustibles. Reacts with acids, giving off heat.

Chemical Stability: Stable at normal temperatures and pressures.

DRY CAUSTIC POTASH (ALL GRADES)

SDS No.: M31867

SDS Revision Date: 04-Mar-2016

Possibility of Hazardous Reactions:

Mixing with water, acid, or incompatible materials may cause splattering and release of large amounts of heat. When moist, reacts with some metals forming flammable hydrogen gas. Carbon monoxide gas may form upon contact with reducing sugars, food and beverage products in enclosed spaces.

Conditions to Avoid: (e.g., static discharge, shock, or vibration) -. No information available.

Incompatibilities/ Materials to Avoid: Acids, halogenated compounds, and prolonged contact with aluminum, brass, bronze, copper, lead, tin, zinc or other alkali sensitive metals or alloys. water.

Hazardous Decomposition Products: None known

Hazardous Polymerization: Will not occur.

SECTION 11. TOXICOLOGICAL INFORMATION**TOXICITY DATA:****PRODUCT TOXICITY DATA: DRY CAUSTIC POTASH (ALL GRADES)**

LD50 Oral: 365 mg/kg oral-rat LD50	LD50 Dermal: No data available	LC50 Inhalation: No data available
--	--	--

COMPONENT TOXICITY DATA:

Note: The component toxicity data is populated by the LOLI database and may differ from the product toxicity data given.

Component	LD50 Oral:	LD50 Dermal:	LC50 Inhalation:
Potassium hydroxide 1310-58-3	284 mg/kg (Rat)	-----	-----
Water 7732-18-5	90 mL/kg (Rat)	-----	-----

POTENTIAL HEALTH EFFECTS:

- Eye contact:** Corrosive. Causes serious eye damage which can result in: severe irritation, pain and burns, and permanent damage including blindness.
- Skin contact:** Corrosive. Causes severe skin burns. Prolonged or repeat skin exposures can result in dermatitis.
- Inhalation:** May cause severe irritation of the respiratory tract with coughing, choking, pain and possibly burns of the mucous membranes. This material can be extremely destructive to the tissue of the mucus membranes and respiratory system.

DRY CAUSTIC POTASH (ALL GRADES)

SDS No.: M31867

SDS Revision Date: 04-Mar-2016

Ingestion:

Toxic if swallowed. Corrosive. May cause severe mucus membrane burns and gastrointestinal burns. If swallowed, may pose a lung aspiration hazard during vomiting. Lung aspiration may result in chemical pneumonitis, pulmonary edema, and damage to lung tissue or death.

SIGNS AND SYMPTOMS OF EXPOSURE:

Signs and symptoms of exposure vary, and are dependent on the route of exposure, degree of exposure, and duration of exposure.

Inhalation (Breathing): Respiratory System Effects: Exposure to airborne material may cause irritation, redness of upper and lower airways, coughing, laryngeal spasm and edema, shortness of breath, bronchio-constriction, and possible pulmonary edema. Severe and permanent scarring may occur. Aspiration of this material may cause the same conditions.

Skin: Skin Corrosion: When skin is exposed to solid product with moisture, may cause redness, itching, irritation, swelling, burns (first, second, or third degree), liquefaction of skin, and damage to underlying tissues (deep and painful wounds).

Eye: Serious Eye Damage. Eye exposures may cause eye lid burns, conjunctivitis, corneal edema, corneal burn, corneal perforation, damage to internal contents of the eye, permanent visual defects, and blindness and/or loss of the eye.

Ingestion (Swallowing): Gastrointestinal System Effects: Exposure by ingestion may cause irritation, swelling, and perforation of upper and lower gastrointestinal tissues. Permanent scarring may occur.

ACUTE TOXICITY:

When in solution, this material will affect all tissues with which it comes in contact. The severity of the tissue damage is a function of its concentration, the length of tissue contact time, and local tissue conditions. After exposure there may be a time delay before irritation and other effects occur. This material is a strong irritant and is corrosive to the skin, eyes, and mucous membranes. This material may cause severe burns and permanent damage to any tissue with which it comes into contact.

CHRONIC TOXICITY:

Repeated and prolonged skin contact may result in dermatitis.

GHS HEALTH HAZARDS:

Listed below.

GHS: ACUTE TOXICITY - ORAL: Category 4 - Harmful if swallowed.

GHS: CONTACT HAZARD - EYE: Category 1 - Causes serious eye damage

GHS: CONTACT HAZARD - SKIN: Category 1B - Causes severe skin burns and eye damage

Skin Absorbent / Dermal Route? No.

GHS: CARCINOGENICITY:

Not classified as a carcinogen per GHS criteria. This product is not classified as a carcinogen by NTP, IARC or OSHA.

DRY CAUSTIC POTASH (ALL GRADES)

SDS No.: M31867

SDS Revision Date: 04-Mar-2016

SECTION 12. ECOLOGICAL INFORMATION

ECOTOXICITY DATA:

Aquatic Toxicity:

This material is alkaline and may raise the pH of surface waters with low buffering capacity. This material has exhibited moderate toxicity to aquatic organisms.

FATE AND TRANSPORT:

BIODEGRADATION: This material is inorganic and not subject to biodegradation

PERSISTENCE: This material is alkaline and may raise the pH of surface waters with low buffering capacity
This material is believed to exist in the disassociated state in the environment

BIOCONCENTRATION: This material is not expected to bioconcentrate in organisms.

BIOACCUMULATIVE POTENTIAL: Potassium hydroxide is a strong alkaline substance that dissociates completely in water to K⁺ and OH⁻. Considering its high water solubility, potassium hydroxide is not expected to bioconcentrate in organisms. Log Pow is not applicable for an inorganic compound that dissociates.

MOBILITY IN SOIL: Potassium hydroxide is not expected to be absorbed in soil due to its dissociation properties and high water solubility.

ADDITIONAL ECOLOGICAL INFORMATION: This material has exhibited slight toxicity to terrestrial organisms. The risk that potassium hydroxide poses for the environment is essentially restricted to a pH increase of the aquatic compartment, which is dependent on the hardness of the waters.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste from material:

Reuse or reprocess, if possible. Dispose in accordance with all applicable regulations.

Container Management:

Dispose of container in accordance with applicable local, regional, national, and/or international regulations. Container rinsate must be disposed of in compliance with applicable regulations.

SECTION 14. TRANSPORT INFORMATION

LAND TRANSPORT

DRY CAUSTIC POTASH (ALL GRADES)

SDS No.: M31867

SDS Revision Date: 04-Mar-2016

U.S. DOT 49 CFR 172.101:

UN NUMBER: UN1813
PROPER SHIPPING NAME: Potassium hydroxide, solid
HAZARD CLASS/ DIVISION: 8
PACKING GROUP: II
LABELING REQUIREMENTS: 8
RQ (lbs): RQ 1,000 Lbs. (Potassium hydroxide)

CANADIAN TRANSPORTATION OF DANGEROUS GOODS:

UN NUMBER: UN1813
SHIPPING NAME: Potassium hydroxide, solid
CLASS OR DIVISION: 8
PACKING/RISK GROUP: II
LABELING REQUIREMENTS: 8

MARITIME TRANSPORT (IMO / IMDG) :

UN NUMBER: UN1813
PROPER SHIPPING NAME: Potassium hydroxide, solid
HAZARD CLASS / DIVISION: 8
Packing Group: II
LABELING REQUIREMENTS: 8

SECTION 15. REGULATORY INFORMATION**U.S. REGULATIONS****OSHA REGULATORY STATUS:**

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200)

CERCLA SECTIONS 102a/103 HAZARDOUS SUBSTANCES (40 CFR 302.4):

If a release is reportable under CERCLA section 103, notify the state emergency response commission and local emergency planning committee. In addition, notify the National Response Center at (800) 424-8802 or (202) 426-2675.

Component	CERCLA Reportable Quantities:
Potassium hydroxide	1000 lb (final RQ)

SARA EHS Chemical (40 CFR 355.30)

Not regulated

EPCRA SECTIONS 311/312 HAZARD CATEGORIES (40 CFR 370.10):

DRY CAUSTIC POTASH (ALL GRADES)

SDS No.: M31867

SDS Revision Date: 04-Mar-2016

Acute Health Hazard

EPCRA SECTION 313 (40 CFR 372.65):

Not regulated

OSHA PROCESS SAFETY (PSM) (29 CFR 1910.119):

Not regulated

FDA: This material has Generally Recognized as Safe (GRAS) status under specific FDA regulations. Additional information is available from the Code of Federal Regulations which is accessible on the FDA's website. This product is not produced under all current Good Manufacturing Practices (cGMP) requirements as defined by the Food and Drug Administration (FDA).

NATIONAL INVENTORY STATUS

Component	<u>U.S. INVENTORY STATUS: Toxic Substance Control Act (TSCA):</u>
Potassium hydroxide 1310-58-3 (84.0 - 92.0 %)	Listed

TSCA 12(b): This product is not subject to export notification.

Canadian Chemical Inventory: All components of this product are listed on either the DSL or the NDSL.

STATE REGULATIONS

Component	California Proposition 65 Cancer WARNING:	California Proposition 65 CRT List - Male reproductive toxin:	California Proposition 65 CRT List - Female reproductive toxin:	Massachusetts Right to Know Hazardous Substance List	New Jersey Right to Know Hazardous Substance List	New Jersey Special Health Hazards Substance List
Potassium hydroxide 1310-58-3	Not Listed	Not Listed	Not Listed	Listed	1571	Listed-corrosive

Component	New Jersey - Environmental Hazardous Substance List	Pennsylvania Right to Know Hazardous Substance List	Pennsylvania Right to Know Special Hazardous Substances	Pennsylvania Right to Know Environmental Hazard List	Rhode Island Right to Know Hazardous Substance List
Potassium hydroxide 1310-58-3	Not Listed	Listed	Not Listed	Present	Listed

CANADIAN REGULATIONS

• This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations

WHMIS - Classifications of Substances:

- D1B - Poisonous and Infectious Material; Materials causing immediate and serious toxic effects - Toxic material
- E - Corrosive material

DRY CAUSTIC POTASH (ALL GRADES)

SDS No.: M31867

SDS Revision Date: 04-Mar-2016

SECTION 16. OTHER INFORMATION

Prepared by: OxyChem Corporate HESS - Product Stewardship**Rev. Date:** 04-Mar-2016**Health Rating:** 3**Flammability Rating:** 0**Reactivity Rating:** 1**Health Rating:** 3**Flammability:** 0**Reactivity Rating:** 1**Reason for Revision:**

- Changed GHS Classification: SEE SECTION 2
- Updated First Aid Measures: SEE SECTION 4
- Toxicological Information has been revised: SEE SECTION 11

IMPORTANT:

The information presented herein, while not guaranteed, was prepared by technical personnel and is true and accurate to the best of our knowledge. NO WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTY OR GUARANTY OF ANY OTHER KIND, EXPRESSED OR IMPLIED, IS MADE REGARDING PERFORMANCE, SAFETY, SUITABILITY, STABILITY OR OTHERWISE. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, storage, disposal and other factors that may involve other or additional legal, environmental, safety or performance considerations, and OxyChem assumes no liability whatsoever for the use of or reliance upon this information. While our technical personnel will be happy to respond to questions, safe handling and use of the product remains the responsibility of the customer. No suggestions for use are intended as, and nothing herein shall be construed as, a recommendation to infringe any existing patents or to violate any Federal, State, local or foreign laws

OSHA Standard 29 CFR 1910.1200 requires that information be provided to employees regarding the hazards of chemicals by means of a hazard communication program including labeling, safety data sheets, training and access to written records. We request that you, and it is your legal duty to, make all information in this Safety Data Sheet available to your employees

End of Safety Data Sheet