Revision Date 08-08-2016 Revision Number 10



SECTION 1 Identification of the substance/mixture and of the company/undertaking

Product identification used on label

Product identifier 8570

DAUBOND® U8015-01

Details of the supplier of the safety

Daubert Chemical Com

data sheet

Daubert Chemical Company 4700 S. Central Avenue Chicago, IL 60638

Emergency telephone number Relevant identified uses of the substance or mixture and uses

advised against

708-496-7350 Chemtrec: (800) 424-9300 Hot melt urethane adhesive

SECTION 2 Hazards identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols



GHS Respiratory Sensitisation Category 1

Classification Skin Sensitisation Category 1

Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 1

Signal Word Danger

Hazard Molten material can cause thermal burns. When heated, the vapors/fumes given off

Statements may cause respiratory tract irritation.

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled. Causes damage to organs through prolonged or repeated exposure.

Precautionary Statements

Prevention Do not breathe dust/fume/gas/mist/vapours/spray.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

In case of inadequate ventilation wear respiratory protection.

Response IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a

position comfortable for breathing.

Get medical advice/attention if you feel unwell.

Revision Date 08-08-2016 Revision Number 10

Specific treatment: None known

If skin irritation or rash occurs: Get medical advice/attention.

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

Wash contaminated clothing before reuse.

Disposal Dispose of contents/container in accordance with

local/regional/national/international regulation for hazardous wastes.

SECTION 3 Composition/information on ingredients

Chemical Name	CAS#	%
4,4'-Diphenylmethane diisocyanate	101-68-8	3 - 7
2,4'-diphenylmethane diisocyanate	5873-54-1	0.1 - 1

Note: Specific chemical identities and/or exact percentages have been withheld as a trade secret.

SECTION 4 First aid measures

Inhalation	If symptoms are experienced remove source of contamination or move victim to fresh air	
	and obtain medical advice. Asthmatic-type symptoms potentially caused by the exposure,	
	may develop but the onset may be delayed for several hours.	
Eyes	Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often.	

Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician.

Skin ContactWash with soap and water. Get medical attention if irritation develops or persists. If burned by contact with hot material, molten material adhering to skin should be cooled as quickly as possible with water and see a physician for removal of adhering material and treatment.

as possible with water and see a physician for removal of adhering material and treatment of burn.

Ingestion Do not induce vomiting and seek medical attention immediately. Provide medical care

provider with this SDS. See Section 11

Most important symptoms/effects, acute and delayed

Indication of immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Suitable extinguishing media: Use water fog, foam, dry chemical or carbon dioxide (CO2) to

extinguish flames. Water spray

Unsuitable extinguishing media: No data available

Fire and/or Explosion Hazards Material may be ignited only if preheated to temperatures above the

high flash point, for example in a fire. If product is heated above its flash point it will release flammable vapors which can burn in the open or be explosive in confined spaces if exposed to ignition source..

Fire Fighting Methods and Protection Do not enter fire area without proper protection including self-

contained breathing apparatus and full protective equipment. Use

appropriate methods for the surrounding fire.

Revision Date 08-08-2016 Revision Number 10

Hazardous Combustion Products

Isocyanates, Carbon dioxide, Carbon monoxide, Toxic fumes, Oxides of nitrogen, Smoke, Isocyanic acid, Hydrogen cyanide

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures Methods and materials for containment and cleaning up Clean up spills immediately using Protective Equipment recommended in Section VIII at a minimum.

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section VIII at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

SECTION 7 Handling and storage

Precautions for safe handling Mildly irritating material. Avoid unnecessary exposure. Avoid

contact with molten material. When heated, the vapor/fumes

given off may cause respiratory tract irritation.

Conditions for safe storage, including any

incompatibilities

Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s) closed. Contents may develop pressure on prolonged exposure

to heat

Incompatible materials Strong oxidizing agents, Water, Strong alkalies, Alcohols,

Copper alloys

SECTION 8 Exposure controls/personal protection

Con	trol	<u>parameters</u>

<u>Chemical Name</u> <u>ACGIH TLV</u> <u>ACGIH STEL</u> <u>OSHA PEL</u>

4,4'-Diphenylmethane diisocyanate 0.005 ppm 0.002 ppm (ceiling)

Engineering Measures Local exhaust ventilation or other engineering controls are normally required when

handling or using this product to avoid overexposure.

Respiratory Protection Proper ventilation (at a minimum) will be required when handling this product. Use

respirators (NIOSH approved) only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels. If ventilation is not sufficient to effectively prevent buildup of vapor/mist/fume/dust, appropriate NIOSH/MSHA

respiratory protection must be provided.

Eye Protection Wear chemically resistant safety glasses with side shields when handling this product.

Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne

material. Do not wear contact lenses. Have an eye wash station available.

Revision Date 08-08-2016 **Revision Number 10**

Skin Protection Avoid skin contact by wearing chemically resistant gloves, an apron and other

protective equipment depending upon conditions of use. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. When handling material that has been heated, wear chemically resistant thermally insulating gloves, chemical resistant apron, long sleeves and other

clothing as necessary to protect against thermal burns.

Gloves Heat insulating gloves

SECTION 9 Physical and chemical properties (Typical, not specification)

Physical State Solid (room temperature), molten liquid as applied

Color No data available

Odor Slight

Odor Threshold No data available No data available Melting Point/freezing point, °C No data available **Initial boiling point and boiling** No data available

range, °C

Flash Point 412 °F(211 °C) **Evaporation Rate** No data available No data available Flammability (Solid, Gas) Lower Flammable/Explosive Limit, No data available

Upper Flammable/Explosive Limit, No data available

% in air

Vapor Pressure No data available **Vapor Density** No data available

Specific Gravity @ 25°C 1.15 Solubility in Water Insoluble

Octanol/Water Partition Coefficient No data available **Autoignition Temperature** No data available **Decomposition Temperature** No data available Typical 10000 cP Viscosity No data available Volatiles, % by weight VOC, lb/gal No data available No data available VOC, grams/liter

SECTION 10 Stability and reactivity

Reactivity No data available

Chemical stability Stable under normal conditions. Hazardous polymerization

may occur.

Possibility of hazardous reactions Under normal conditions of storage and use, hazardous

reactions will not occur.

Conditions to avoid Contact with water. Temperatures above 350°F (177°C). Strong oxidizing agents, Water, Strong alkalies, Alcohols, **Incompatible materials**

Copper alloys

Revision Date 08-08-2016 **Revision Number 10**

Hazardous decomposition products Under normal conditions of use & storage, decomposition and

hazardous decomposition products are unlikely.

SECTION 11 Toxicological information

Inhalation, Skin contact, Eye contact **Likely Routes of Entry**

Target Organs Potentially Affected by Exposure

Chemical Interactions That Change Toxicity

Medical Conditions Aggravated

No chemical interaction known to affect toxicity.

Respiratory disease including asthma and bronchitis, Skin

contact may aggravate existing skin disease

Immediate (Acute) Health Effects by Route of Exposure

Inhalation Irritation Vapors and/or aerosols that may be formed at elevated temperatures may be irritating to

> the respiratory tract. Other possible symptoms include; wheezing and coughing due to pulmonary edema (fluid build-up in lungs). Gas, vapor, mist, or dust may be harmful if

inhaled. May cause allergic respiratory reaction.

Skin Contact May cause sensitization.

Eye Contact Contact with the eyes may cause moderate to severe eye injury. Eye contact may result

in tearing and reddening, but not likely to permanently injure eye tissue. Temporary

vision impairment (cloudy or blurred vision) is possible.

Ingestion Irritation Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea,

vomiting and diarrhea.

Not believed to have any significant toxicity. **Ingestion Toxicity**

Long-Term (Chronic) Health Effects

Carcinogenicity There are no carcinogenic ingredients present at or over 0.1%.

Can cause systemic damage upon prolonged and/or repeated exposure (see "Target Inhalation

Organs)

Skin Contact Can cause isocyanate sensitization and respiratory reaction.

Skin Absorption Skin sensitization, characterized by redness, inflammation, itching and/or burning may

result from prolonged or repeated contact with this material.

Ingestion Under normal industrial usage conditions, ingestion is highly unlikely.

Additional Health Effects Harmful if inhaled or absorbed through skin. May cause delayed lung damage.

Component Toxicology Data

Chemical Name CAS Number LD50/LC50

4,4'-Diphenylmethane diisocyanate 101-68-8 Dermal LD50 Rabbit > 9400 mg/kg Oral LD50 Rat > 7616 mg/kg

Inhalation LC50 (4h) Rat 0.368 mg/L

SECTION 12 Ecological information

Overview No ecological information available

Mobility No data Persistence No data Bioaccumulation No data **Degradability** No data

Revision Date 08-08-2016 Revision Number 10

Ecotoxicity Data

mg/L

SECTION 13 Disposal considerations

Waste Description for Spent Product Spent or discarded material is not expected to be a hazardous waste.

Disposal MethodsDispose of in accordance with Local and National regulations.

Waste Disposal Code(s) Not applicable

SECTION 14 Transport information

Full shipping name for Cement, Adhesive / Non-Hazardous

Export, Air, Sea (any quantity unless flash pt. >150°F) or vessels of 119 GL or more

Domestic Ground in vessels < Non-Hazardous

119 gal.

SECTION 15 Regulatory information

Status of formula components on selected national regulatory inventories:

LIST STATUS
TSCA All components in this product are on the TSCA Inventory or exempt.

Canadian DSL Contact customer service (800-688-0459 or SDS@DAUBERT.COM) for registration status

of this product in Canada.

Chemical NameCAS #RegulationPercent4,4'-Diphenylmethane diisocyanate101-68-8CERCLA3 - 7RQ = 5000 lbs

4,4'-Diphenylmethane diisocyanate 101-68-8 SARA 313 3 - 7

No SARA 302 EHS-listed chemicals in SARA EHS

this product.

SECTION 16 Other information

Revision 08-08-2016

Date

Disclaimer Although the information contained herein is believed to be reliable, it is furnished without warranty

of any kind. This information is not intended to be all-inclusive as to the manner and conditions of

use, handling, and storage.

Version Reviewed

Comments Approved: M. Hogan