Revision Date 05-25-2017 Revision Number 11



SECTION 1 Identification of the substance/mixture and of the company/undertaking

Product identification used on label

Product identifier 8580

DAUBOND® U8119-01

Details of the supplier of the safety

Daubert Chemical Company

data sheet 4700 S. Central Avenue Chicago, IL 60638

708-496-7350

Emergency telephone number Relevant identified uses of the substance or mixture and uses

advised against

Chemtrec: (800) 424-9300 Hot melt urethane adhesive

SECTION 2 Hazards identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols



GHS Respiratory Sensitisation Category 1

Classification Skin Sensitisation Category 1

Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure Category 1

Signal Word Danger

Hazard May cause an allergic skin reaction

Statements May cause allergy or asthma symptoms or breathing difficulties if inhaled

Causes damage to organs through prolonged or repeated exposure.

Unclassified Molten material can cause thermal burns. When heated, the vapors/fumes given off

Hazards may cause respiratory tract irritation.

(HNOC): Precautionary Statements

Prevention Do not breathe dust/fume/gas/mist/vapours/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection.

Wear respiratory protection.

Response IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a

position comfortable for breathing.

Revision Date 05-25-2017 **Revision Number 11**

Get medical advice/attention if you feel unwell.

Specific treatment: None known

If skin irritation or rash occurs: Get medical advice/attention.

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

Wash contaminated clothing before reuse.

Disposal Dispose of contents/container in accordance with

local/regional/national/international regulation for hazardous wastes.

SECTION 3 Composition/information on ingredients

Chemical Name	CAS#	%	
4,4'-Diphenylmethane diisocyanate	101-68-8	1 - 5	

Note: Specific chemical identities and/or exact percentages have been withheld as a trade secret.

SECTION 4 First aid measures

Inhalation	If symptoms are experienced remove source of contamination or move victim to fresh air
	and obtain medical advice. Asthmatic-type symptoms potentially caused by the exposure,

may develop but the onset may be delayed for several hours.

Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. **Eyes**

Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician.

Skin Contact Wash with soap and water. Get medical attention if irritation develops or persists. If burned

by contact with hot material, molten material adhering to skin should be cooled as quickly as possible with water and see a physician for removal of adhering material and treatment

of burn.

Ingestion Do not induce vomiting and seek medical attention immediately. Provide medical care

provider with this SDS.

See Section 11

Most important symptoms/effects,

acute and delayed

Treat symptomatically.

Indication of immediate medical attention and special treatment needed

SECTION 5 Firefighting measures

Suitable extinguishing media: Use water fog, foam, dry chemical or carbon dioxide (CO2) to

extinguish flames. Water spray

Unsuitable extinguishing media: No data available

Fire and/or Explosion Hazards Material may be ignited only if preheated to temperatures above the

> high flash point, for example in a fire. If product is heated above its flash point it will release flammable vapors which can burn in the open or be

explosive in confined spaces if exposed to ignition source..

Do not enter fire area without proper protection including self-Fire Fighting Methods and Protection

contained breathing apparatus and full protective equipment. Use

appropriate methods for the surrounding fire.

Hazardous Combustion Products Isocyanates, Carbon dioxide, Carbon monoxide, Toxic fumes, Oxides of

nitrogen, Smoke, Isocyanic acid, Hydrogen cyanide

Revision Date 05-25-2017 Revision Number 11

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures Methods and materials for containment and cleaning up Clean up spills immediately using Protective Equipment recommended in Section VIII at a minimum.

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section VIII at a minimum. Dike with suitable absorbent material like granulated clay. Gather and store in a sealed container pending a waste disposal evaluation.

SECTION 7 Handling and storage

Precautions for safe handling Mildly irritating material. Avoid unnecessary exposure. Avoid

contact with molten material. When heated, the vapor/fumes

given off may cause respiratory tract irritation.

Conditions for safe storage, including any

incompatibilities

Store in a cool dry ventilated location. Isolate from incompatible materials and conditions. Keep container(s)

closed. Contents may develop pressure on prolonged exposure

to heat

Incompatible materials Strong oxidizing agents, Water, Strong alkalies, Alcohols,

Copper alloys

SECTION 8 Exposure controls/personal protection

(<u>Con</u>	trol	parameters

Chemical Name ACGIH TLV ACGIH STEL OSHA PEL

4,4'-Diphenylmethane diisocyanate 0.005 ppm 0.02 ppm (ceiling)

Engineering Measures Local exhaust ventilation or other engineering controls are normally required when

handling or using this product to avoid overexposure.

Respiratory Protection Proper ventilation (at a minimum) will be required when handling this product. Use

respirators (NIOSH approved) only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels. If ventilation is not sufficient to effectively prevent buildup of vapor/mist/fume/dust, appropriate NIOSH/MSHA

respiratory protection must be provided.

Eye Protection Wear chemically resistant safety glasses with side shields when handling this product.

Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne

material. Do not wear contact lenses. Have an eye wash station available.

Skin Protection Avoid skin contact by wearing chemically resistant gloves, an apron and other

protective equipment depending upon conditions of use. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. When handling material that has been heated, wear chemically resistant thermally insulating gloves, chemical resistant apron, long sleeves and other

clothing as necessary to protect against thermal burns.

Gloves Heat insulating gloves

Revision Date 05-25-2017 Revision Number 11

SECTION 9 Physical and chemical properties (Typical, not specification)

Physical State Solid (room temperature), molten liquid as applied

No data available

Color Off-white to tan

Odor Slight

Odor Threshold

pH

No data available

No data available

Melting Point/freezing point, °C

Initial boiling point and boiling

No data available

No data available

range, °C

Flash Point 412 °F(211 °C)
Evaporation Rate No data available
Flammability (Solid, Gas) No data available
Lower Flammable/Explosive Limit, No data available

% in air

Upper Flammable/Explosive Limit,

% in air

Vapor PressureNo data availableVapor DensityNo data available

Specific Gravity @ 25°C 1.17
Solubility in Water Insoluble

Octanol/Water Partition Coefficient
Autoignition Temperature
Decomposition Temperature
Viscosity @ 250°F
Volatiles, % by weight

No data available
Typical 20000 cP
No data available

VOC, Material, lb/gal 0 VOC, Material, grams/liter 0.0 VOC minus exempt solvents & water, 0

g/l

SECTION 10 Stability and reactivity

Reactivity No data available

Chemical stability Stable under normal conditions. Hazardous polymerization

nav occur.

Possibility of hazardous reactionsUnder normal conditions of storage and use, hazardous

reactions will not occur.

Conditions to avoid Contact with water. Temperatures above 350°F (177°C). Incompatible materials Strong oxidizing agents, Water, Strong alkalies, Alcohols,

buong oxidizing agents, water, buong arkanes, Alcohol

Copper alloys

Hazardous decomposition productsUnder normal conditions of use & storage, decomposition and

hazardous decomposition products are unlikely.

Revision Date 05-25-2017 Revision Number 11

SECTION 11 Toxicological information

Likely Routes of EntryInhalation, Skin contact, Eye contact

Target Organs Potentially Affected by Exposure Lungs

Chemical Interactions That Change ToxicityNo chemical interaction known to affect toxicity.

Medical Conditions Aggravated Respiratory disease including asthma and bronchitis, Skin

contact may aggravate existing skin disease

Immediate (Acute) Health Effects by Route of Exposure

Inhalation Irritation Vapors and/or aerosols that may be formed at elevated temperatures may be irritating to

the respiratory tract. Other possible symptoms include; wheezing and coughing due to pulmonary edema (fluid build-up in lungs). Gas, vapor, mist, or dust may be harmful if

inhaled. May cause allergic respiratory reaction.

Skin Contact May cause sensitization.

Eye Contact Contact with the eyes may cause moderate to severe eye injury. Eye contact may result

in tearing and reddening, but not likely to permanently injure eye tissue. Temporary

vision impairment (cloudy or blurred vision) is possible.

Ingestion Irritation Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea,

vomiting and diarrhea.

Ingestion Toxicity Not believed to have any significant toxicity.

Long-Term (Chronic) Health Effects

Carcinogenicity There are no carcinogenic ingredients present at or over 0.1%.

Inhalation Can cause systemic damage upon prolonged and/or repeated exposure (see "Target

Organs)

Skin Contact Can cause isocyanate sensitization and respiratory reaction.

Skin Absorption Skin sensitization, characterized by redness, inflammation, itching and/or burning may

result from prolonged or repeated contact with this material.

Ingestion Under normal industrial usage conditions, ingestion is highly unlikely.

Additional Health Effects Harmful if inhaled or absorbed through skin. May cause delayed lung damage.

Component Toxicology Data

Chemical Name CAS Number LD50/LC50

4,4'-Diphenylmethane diisocyanate 101-68-8 Dermal LD50 Rabbit > 9400 mg/kg Oral LD50 Rat > 7616 mg/kg

Inhalation LC50 (4h) Rat 0.368 mg/L

SECTION 12 Ecological information

Overview No ecological information available

MobilityNo dataPersistenceNo dataBioaccumulationNo dataDegradabilityNo data

Ecotoxicity Data

Chemical Name CAS Number Aquatic EC50 **Aquatic ERC50 Aquatic LC50** Crustacea Algae Fish 101-68-8 EC50 (24 hr) LC50 (24 hr) Zebra 4,4'-Diphenylmethane diisocyanate Water flea > 500 Fish > 500 mg/Lmg/L

DAUBOND® U8119-01

Page 5 of 6

Revision Date 05-25-2017 Revision Number 11

SECTION 13 Disposal considerations

Waste Description for Spent Product

Disposal Methods

Spent or discarded material is not expected to be a hazardous waste. Dispose of in accordance with Local and National regulations.

Waste Disposal Code(s) Not applicable

SECTION 14 Transport information

Full shipping name for

Cement, Adhesive / Non-Hazardous

Export, Air, Sea (any quantity unless flash pt. >150°F) or vessels of 119 GL or more

Domestic Ground in vessels <

Non-Hazardous

119 gal.

SECTION 15 Regulatory information

Status of formula components on selected national regulatory inventories:

LIST	STATUS
TSCA	All components in this product are on the TSCA Inventory or exempt.
Canadian DSL	Contact customer service (800-688-0459 or SDS@DAUBERT.COM) for registration status
	of this product in Canada.

Chemical Name 4,4'-Diphenylmethane diisocyanate	CAS # 101-68-8	Regulation CERCLA	Percent 1 - 5
			RQ = 5000 lbs
4,4'-Diphenylmethane diisocyanate	101-68-8	SARA 313	1 - 5
No SARA 302 EHS-listed chemicals in		SARA EHS	
this product.			

SECTION 16 Other information

Revision 05-25-2017

Date

Disclaimer Although the information contained herein is believed to be reliable, it is furnished without warranty

of any kind. This information is not intended to be all-inclusive as to the manner and conditions of

use, handling, and storage.

Version Reviewed

Comments Approved: M. Hogan