# **SAFETY DATA SHEET**



Defy Damage Pro 1 Bond-Protecting Color Optimizer Spray

# **Section 1. Identification**

Product Name : Defy Damage Pro 1 Bond-Protecting Color Optimizer Spray

Other means of identification

: Not available.

Recommended use : Hair Care Product

**Restrictions on use** : Use only as directed on the product label.

Manufacturer : Zotos International, INC

100 Tokeneke Road, Darien, CT 06820 www.zotos.com

Validation date : 12/17/2018

<u>In case of emergency</u> : (800) 584-8038 [24 Hours]

**Telephone number** : (203) 656-7859 [8:30 a.m. - 5:00 p.m.]

<u>Transportation Emergency</u>: Contact: CHEMTREC 1-800-424-9300 [US/Canada 24 Hours]

Product type : Aerosol.

# Section 2. Hazards identification

#### **Emergency overview**

NOT EXPECTED TO PRODUCE SIGNIFICANT ADVERSE HEALTH EFFECTS WHEN THE RECOMMENDED INSTRUCTIONS FOR USE ARE FOLLOWED. Additional information on toxicological endpoints is available from the supplier upon request

**OSHA/HCS** status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

: FLAMMABLE AEROSOLS - Category 1

GASES UNDER PRESSURE - Compressed gas

SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 17%

**GHS** label elements

Hazard pictograms :







Signal word : Danger

**Hazard statements** : Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

**Precautionary statements** 

General : Read label before use. Keep out of reach of children. If medical advice is needed,

have product container or label at hand.

Prevention: Wear eye or face protection. Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Wash hands thoroughly after handling. Pressurized container: Do not pierce or

burn, even after use.

Response : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Defy Damage Pro 1 Bond-Protecting Color Optimizer Spray

# Section 2. Hazards identification

**Storage** 

: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Store in a well-ventilated place.

**Disposal** Hazards not otherwise classified

: Not applicable. : None known.

# Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Name	%	CAS number
ethanol	15.24	64-17-5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

# Section 4. First aid measures

# Description of necessary first aid measures

**Eve contact** 

: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Seek medical attention if irritation persists.

Inhalation

: Move affected person to fresh air.

Skin contact

: Remove contaminated clothing and shoes. Wash with plenty of soap and water.

Ingestion

: NOT EXPECTED TO PRODUCE SIGNIFICANT ADVERSE HEALTH EFFECTS WHEN THE RECOMMENDED INSTRUCTIONS FOR USE ARE FOLLOWED. Treat symptomatically. Never give anything by mouth to an unconscious person. Call a

physician.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

: None.

**Specific treatments** 

: No specific treatment.

**Protection of first-aiders** 

: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

# Section 5. Fire-fighting measures

### **Extinguishing media**

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing** 

media

: None known.

Specific hazards arising from the chemical

Extremely flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard.

# Section 5. Fire-fighting measures

# Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon dioxide carbon monoxide

# Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

# Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

# Section 6. Accidental release measures

## Personal precautions, protective equipment and emergency procedures

# For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

### For emergency responders:

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

#### **Environmental precautions**

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

## Methods and materials for containment and cleaning up

# **Small spill**

: Stop leak if without risk. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble.

#### Large spill

: Stop leak if without risk. Use spark-proof tools and explosion-proof equipment. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

### **Precautions for safe handling**

### **Protective measures**

Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools.

# Section 7. Handling and storage

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, : including any incompatibilities

Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Eliminate all ignition sources.

# Section 8. Exposure controls/personal protection

### **United States**

### **Control parameters**

# Occupational exposure limits

Ingredient name	Exposure limits			
ethanol	ACGIH TLV (United States, 3/2015).			
	STEL: 1000 ppm 15 minutes.			
	OSHA PEL 1989 (United States, 3/1989).			
	TWA: 1000 ppm 8 hours.			
	TWA: 1900 mg/m <sup>3</sup> 8 hours.			
	NIOSH REL (United States, 10/2013).			
	TWA: 1000 ppm 10 hours.			
	TWA: 1900 mg/m³ 10 hours.			
	OSHA PEL (United States, 2/2013).			
	TWA: 1000 ppm 8 hours.			
	TWA: 1900 mg/m <sup>3</sup> 8 hours.			

# Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

# **Environmental exposure** controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## **Individual protection measures**

Hygiene measures

:

Hygiene measures

: When using do not eat, drink or smoke.

**Eye/face protection** 

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

# Skin protection

**Hand protection** 

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

# Section 8. Exposure controls/personal protection

**Body protection** 

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

**Respiratory protection** 

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Consult local authorities for acceptable exposure limits.

# Section 9. Physical and chemical properties

**Appearance** 

Physical state : Liquid. [Aerosol. Liquid. Watery liquid.]

Color : Clear.

Odor : Characteristic. Fragrance-like.

**pH** : 9 to 10

Flash point : Closed cup: 23 to 37.8°C (73.4 to 100°F)

Relative density : 0.93 to 0.96

**Aerosol product** 

Type of aerosol : Spray
Heat of combustion : 28.12 kJ/g

# Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

Date of previous issue

**Chemical stability**: The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : Avoid all possible sources of ignition (spark or flame).

**Incompatible materials**: No specific data.

Hazardous decomposition products

Date of issue/Date of revision

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

9254A

: 12/17/2018

: No previous validation Version : 1 5/11

# **Section 11. Toxicological information**

#### **United States**

# **Information on toxicological effects**

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
ethanol	LC50 Inhalation Vapor LD50 Oral	Rat Rat	124700 mg/m³ 7 g/kg	4 hours

# **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
ethanol	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	0.066666667 minutes 100 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	100 microliters	-
	Eyes - Severe irritant	Rabbit	-	500 milligrams	-

### **Sensitization**

Not available.

### **Mutagenicity**

Not available.

### Carcinogenicity

Not available.

# Reproductive toxicity

Not available.

### **Teratogenicity**

Not available.

### Specific target organ toxicity (single exposure)

Not available.

# Specific target organ toxicity (repeated exposure)

Not available.

# **Aspiration hazard**

Not available.

# Information on the likely

routes of exposure

: Not available.

# Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.
 Skin contact : No known significant effects or critical hazards.
 Ingestion : No known significant effects or critical hazards.
 Symptoms related to the physical, chemical and toxicological characteristics

# Section 11. Toxicological information

**Eye contact** : Adverse symptoms may include the following:

pain or irritation watering redness

**Inhalation** : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact : No specific data.

Ingestion : No specific data.

#### Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

**Long term exposure** 

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

### Potential chronic health effects

Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

#### **Numerical measures of toxicity**

## **Acute toxicity estimates**

Not available.

# Section 12. Ecological information

### **United States**

### **Toxicity**

Product/ingredient name	Result	Species	Exposure
ethanol	Acute EC50 17.921 mg/l Marine water Acute EC50 2000 μg/l Fresh water Acute LC50 25500 μg/l Marine water Acute LC50 42000 μg/l Fresh water	Algae - Ulva pertusa Daphnia - Daphnia magna Crustaceans - Artemia franciscana - Larvae Fish - Oncorhynchus mykiss	96 hours 48 hours 48 hours 4 days
	Chronic NOEC 4.995 mg/l Marine water Chronic NOEC 0.375 ul/L Fresh water	Algae - Ulva pertusa Fish - Gambusia holbrooki - Larvae	96 hours 12 weeks

#### Persistence and degradability

Not available.

**Bioaccumulative potential** 

# **Section 12. Ecological information**

Product/ingredient name	LogPow	BCF	Potential
ethanol	-0.35	-	low

# **Mobility in soil**

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

# Section 13. Disposal considerations

**Disposal methods** 

: Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

# **Section 14. Transport information**

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	UN1950	Aerosols	2.1	-	TRAMMAE GAS	Limited quantity Yes.  Packaging instruction Passenger aircraft Quantity limitation: 75 kg  Cargo aircraft Quantity limitation: 150 kg  Special provisions 153, N82
TDG Classification	UN1950	AEROSOLS	2.1	-		Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.13-2.17 (Class 2).  Explosive Limit and Limited Quantity Index 1  Passenger Carrying Road or Rail Index 75
Mexico Classification	UN1950	AEROSOLES	2.1	-		Special provisions 63, 190, 277
ADR/RID Class	UN1950	AEROSOLS	2	-		Limited quantity LQ2  Special provisions 190 327 625  Tunnel code (D)

9254A

Date of issue/Date of revision : 12/17/2018 Date of previous issue : No previous validation Version : 1 8/11

Defy Damage Pro 1 Bond-Protecting Color Optimizer Spray **Section 14. Transport information IMDG Class** UN1950 **AEROSOLS** 2.1 Emergency schedules (EmS) F-D, S-U **Special provisions** 63, 190, 277, 327, 959 **IATA-DGR Class** UN1950 Aerosols, flammable 2.1 Passenger and Cargo **Aircraft**Quantity limitation: 75 kg Packaging instructions: 203 Cargo Aircraft Only Quantity limitation: 150 kg Packaging instructions: 203 **Limited Quantities -**Passenger Aircraft Quantity limitation: 30 kg Packaging instructions:

PG\*: Packing group

# Section 15. Regulatory information

**U.S. Federal regulations** : TSCA 8(a) PAIR: 1,1'-oxydipropan-2-ol

TSCA 8(a) CDR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): Not determined.

Clean Air Act (CAA) 112 regulated flammable substances: butane; dimethyl ether

**Special provisions** 

A145

Clean Air Act Section 112

(b) Hazardous Air **Pollutants (HAPs)**  : Not listed

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

**Class II Substances** 

: Not listed

**DEA List I Chemicals** 

(Precursor Chemicals)

: Not listed

**DEA List II Chemicals** (Essential Chemicals) : Not listed

**SARA 302/304** 

Composition/information on ingredients

No products were found.

**SARA 304 RQ** : Not applicable.

**SARA 311/312** 

Classification : Fire hazard

> Sudden release of pressure Immediate (acute) health hazard

Composition/information on ingredients

# **Section 15. Regulatory information**

Name	%	hazard	Sudden release of pressure		(acute) health	Delayed (chronic) health hazard
ethanol	15.24	Yes.	No.	No.	Yes.	No.

### **State regulations**

Massachusetts : The following components are listed: BUTANE; ETHYL ALCOHOL; METHYL ETHER

**New York** : None of the components are listed.

New Jersey : The following components are listed: BUTANE; ETHYL ALCOHOL; ALCOHOL;

DIMETHYL ETHER; METHANE, OXYBIS-

Pennsylvania: The following components are listed: BUTANE; DENATURED ALCOHOL; ETHANOL;

METHANE, OXYBIS-

#### California Prop. 65

CALIFORNIA PROPOSITION 65: The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986. This product is not known to the State of California to cause cancer.

Not available.

### **International regulations**

# Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

#### Montreal Protocol (Annexes A, B, C, E)

Not listed.

### **Stockholm Convention on Persistent Organic Pollutants**

Not listed.

#### Rotterdam Convention on Prior Inform Consent (PIC)

Not listed.

### **UNECE Aarhus Protocol on POPs and Heavy Metals**

Not listed.

#### **Canada**

WHMIS (Canada) : Class B-2: Flammable liquid

Class B-5: Flammable aerosol.

Class D-2B: Material causing other toxic effects (Toxic).

**Canadian lists** 

**Canadian NPRI**: The following components are listed: Butane (all isomers); Ethanol; Dimethylether

**CEPA Toxic substances**: None of the components are listed.

Canada inventory : Not determined.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.


#### **Mexico**

Classification :



# Section 16. Other information

## **Hazardous Material Information System (U.S.A.)**



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on SDSs under 29 CFR 1910. 1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

### **National Fire Protection Association (U.S.A.)**



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

#### **History**

**Date of printing** : 12/17/2018 **Date of issue/Date of** : 12/17/2018

revision

Date of previous issue : No previous validation

Version : 1

References : Not available.

Indicates information that has changed from previously issued version.

#### **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.