

# Safety Data Sheet

Version 3.0 Revision Date 12/08/2016 SDS Number 30000005270 Print Date 12/16/2017

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name	:	LTO-410
Chemical formula	:	C4H12Si
Product Use Description	:	Semiconductor Processing
Manufacturer/Importer/Distribu tor	:	Versum Materials US, LLC 8555 South River Parkway Tempe, AZ 85284 Exporter EIN No.475632014 www.versummaterials.com
Telephone	:	(602)282-1000
Emergency telephone number (24h)	:	800-523-9374 USA +1 610 481 7711 International

### 2. HAZARDS IDENTIFICATION

#### **GHS** classification

Flammable liquids -Category 2 Skin irritation - Category 2 Eve irritation - Category 2A Specific target organ toxicity - single exposure - Inhalation Category 3

**GHS** label elements

Hazard pictograms/symbols



Signal Word: Danger

Hazard Statements:

H225: Highly flammable liquid and vapour.

#### H315:Causes skin irritation. H319:Causes serious eye irritation. H335:May cause respiratory irritation.

### Precautionary Statements:

Prevention	<ul> <li>P210:Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.</li> <li>P233:Keep container tightly closed.</li> <li>P240:Ground/Bond container and receiving equipment.</li> <li>P241:Use explosion-proof electrical/ventilating/lighting/equipment.</li> <li>P242:Use only non-sparking tools.</li> <li>P243:Take precautionary measures against static discharge.</li> <li>P261:Avoid breathing dust/fume/gas/mist/vapours/spray.</li> <li>P264:Wash hands thoroughly after handling.</li> <li>P271:Use only outdoors or in a well-ventilated area</li> <li>P280a:Wear protective gloves and eye/face protection.</li> </ul>
Response	<ul> <li>P303+P361+P353 :IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.</li> <li>P304+P340 :IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.</li> <li>P305+P351+P338 :IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P312 :Call a POISON CENTRE/doctor if you feel unwell.</li> <li>P332+P313 :If skin irritation occurs: Get medical advice/attention.</li> <li>P337+P313 :If eye irritation persists: Get medical advice/attention.</li> <li>P362 :Take off contaminated clothing and wash before re use.</li> <li>P370+P378 :In case of fire, use recommended extinguishing media for extinction.</li> </ul>
Storage	<ul> <li>P403+P233:Store in a well-ventilated place. Keep container tightly closed.</li> <li>P403+P235:Store in a well-ventilated place. Keep cool.</li> <li>P405:Store locked up.</li> </ul>
Disposal	: P501:Disposal of contents/container to be specified in accordance with regulations.

### Hazards not otherwise classified

None known.

## **3. COMPOSITION/INFORMATION ON INGREDIENTS**

Components	CAS Number	Concentration (Weight)
Diethylsilane	542-91-6	> 99%

Concentration is nominal. For the exact product composition, please refer to technical specifications. Contains no other components or impurities which will influence the classification of the product.

4. FIRST AID MEASURES		
General advice	:	Seek medical advice. If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately.
Eye contact	:	Rinse immediately with plenty of water also under the eyelids for at least 20 minutes. Remove contact lenses.
Skin contact	:	Wash off immediately with plenty of water for at least 20 minutes. Immediately remove contaminated clothing, and any extraneous chemical, if possible to do so without delay.
Ingestion	:	If a person vomits when lying on his back, place him in the recovery position. Prevent aspiration of vomit. Turn victim's head to the side.
Inhalation	:	If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately. Move to fresh air.
Most important symptoms/effects - acute and delayed	:	Repeated and/or prolonged exposure to low concentrations of vapors and/or aerosols may cause: Sore throat.Adverse respiratory effects (such as cough, tightness of chest or shortness of breath). Asthma. Skin disorders and Allergies. Adverse skin effects (such as rash, irritation or corrosion). Adverse eye effects (such as conjunctivitis or corneal damage). Eye disease.

## **5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media	<ul> <li>Alcohol-resistant foam.</li> <li>Carbon dioxide (CO2).</li> <li>Dry chemical.</li> <li>Dry sand.</li> <li>Limestone powder.</li> </ul>	
Specific hazards	: Incomplete combustion may form carbon monoxide. Fire or intense heat may cause violent rupture of packages. Flash back possible over considerable distance. May form explosive mixtures in air. Downwind personnel must be evacuated. Burning produces noxious and toxic fumes. In the event of fire, coor tanks with water spray. Vapor concentrations of 10% or greater can be explosive upon ignition.	bl
Special protective equipment for fire-fighters	: Use personal protective equipment. Wear self contained breathing apparatus for fire fighting if necessary.	
Further information	: Do not allow run-off from fire fighting to enter drains or water courses.	

## 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment, and Emergency Procedures	se self-contained breathing apparatus and chemically protective suitable protective clothing, gloves and eye/face prote	
Environmental precautions	hut off or remove all ignition sources. Construct a dike to pr revent spilled product from entering streams or drinking wa uthorities should be advised if significant spillages cannot b onstruct a dike to prevent spreading.	ter supplies. Local
Methods for cleaning up	pproach suspected leak areas with caution. Call Emergenc umber for advice. Absorb with inert absorbent materials suc ermiculite. Activated charcoal. Place in appropriate chemic	h as: Dry sand.
Additional advice	pen enclosed spaces to outside atmosphere. Prevent from asements and workpits, or any place where its accumulatio angerous. If possible, stop flow of product.	

## 7. HANDLING AND STORAGE

### Handling

Do not breathe vapors/dust. Emergency showers and eye wash stations should be readily accessible. Adhere to work practice rules established by government regulations. Avoid contact with eyes. See "Flammable and Combustible Liquid Code" NFPA No. 30, National Fire Protection Association, Boston, MA. Use personal protective equipment. When using, do not eat, drink or smoke.

### Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Keep away from heat and sources of ignition. Keep in a dry, cool place. Keep away from oxidizers.

### Technical measures/Precautions

Keep away from open flames, hot surfaces and sources of ignition.

: 32 - 104 °F (0 - 40 °C) Storage Temperature

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### Engineering measures

Use explosion-proof equipment. Provide readily accessible eye wash stations and safety showers. Provide natural or explosion-proof ventilation adequate to ensure concentrations are kept below exposure limits.

#### Personal protective equipment

Respiratory protection	Wear appropriate respirator when ventilation is inadequate. Us NIOSH/MSHA approved respirator with organic vapor cartridge	
Hand protection	Impervious gloves.	
	4/10	

	Neoprene gloves. Chemical-resistant, impervious gloves complying with an approved s should be worn at all times when handling chemical products if a ris assessment indicates this is necessary.	
Eye protection	Chemical resistant goggles must be worn.	
Skin and body protection	Long sleeve shirts and trousers without cuffs.	
Environmental exposure controls	Shut off or remove all ignition sources. Construct a dike to prevent s Prevent spilled product from entering streams or drinking water sup authorities should be advised if significant spillages cannot be conta	plies. Local
Special instructions for protection and hygiene	Provide readily accessible eye wash stations and safety showers. W at the end of each workshift and before eating, smoking or using the Provide readily accessible eye wash stations and safety showers.	

## 9. PHYSICAL AND CHEMICAL PROPERTIES

rsum Materials US_U_C	5/10	I T(
Relative vapor density	: 3 (air = 1) Heavier than air.	
Water solubility	: Insoluble.	
Vapor pressure	: 208.00 mmHg at 68 °F (20 °C)	
Upper/lower explosion/flammability limit	: > 10.0 %(V) / 1.1 %(V)	
Flammability (solid, gas)	: Not applicable.	
Evaporation rate	: No data available.	
Flash point	: -18 °F (-28 °C)	
Boiling point/range	: 133 °F (56 °C)	
Melting point/range	: -209 °F (-134 °C)	
рН	: Not applicable.	
Odor threshold	: No data available.	
Odor	: Odorless.	
Appearance	: Liquid. Colorless.	

Relative density	: 0.7 (water = 1)
Partition coefficient (n- octanol/water)	: No data available.
Auto-ignition temperature	: 218 °C
Decomposition temperature	: No data available.
Viscosity	: No data available.
Molecular Weight	: No data available.

## 10. STABILITY AND REACTIVITY

Chemical Stability	: Stable under normal conditions.
Conditions to avoid	: Heat, flames and sparks.
Materials to avoid	: Oxidizing agents. Bases. Mineral acids.
Hazardous decomposition products	: Carbon monoxide. Carbon dioxide (CO2). Silicon Dioxide. Hydrogen. Ethylene
Possibility of hazardous Reactions/Reactivity	: No data available.

### **11. TOXICOLOGICAL INFORMATION**

### 11.1. Information on toxicological effects

Likely routes of exposure	
Effects on Eye	: Contact with eyes may cause irritation.
Effects on Skin	: Causes skin irritation.
Inhalation Effects	: May cause nose, throat, and lung irritation. Inhalation of vapors and/or aerosols in high concentration may cause irritation of respiratory system.
Ingestion Effects	: No data available.
Symptoms	: Repeated and/or prolonged exposure to low concentrations of vapors and/or aerosols may cause: Sore throat. Adverse respiratory effects (such as cough, tightness of chest or shortness of breath)., Asthma., Skin disorders and
	6/10

	Allergies., Adverse skin effects (such as rash, irritation or corrosion)., Adverse eye effects (such as conjunctivitis or corneal damage)., Eye disease.
Acute toxicity	
Acute Oral Toxicity	LD50 : > 2,000 mg/kg Species : Rat.
Inhalation	No data is available on the product itself.
Inhalation - Components Diethylsilane	NOAEC (4 h) : 3093 ppm Species : Rat.
Acute Dermal Toxicity	No data is available on the product itself.
Skin corrosion/irritation	Irritating to skin.
Serious eye damage/eye irritation	Irritating to eyes.
Sensitization.	No data available.

Chronic toxicity or effects from long term exposures

Carcinogenicity	: No data available.	
Reproductive toxicity	: No data is available on the product itself.	
Germ cell mutagenicity	: No evidence of mutagenic activity was observed in a bacterial mutatic assay.	วท
Specific target organ systemic toxicity (single exposure)	: No data available.	
Specific target organ systemic toxicity (repeated exposure)	: No data available.	
Aspiration hazard	: No data available.	

Delayed and Immediate Effects and Chronic Effects from Short and Long Term Exposure

This product contains no listed carcinogens according to IARC, ACGIH, NTP and/or OSHA in concentrations of 0.1 percent or greater. Adverse respiratory effects (such as cough, tightness of chest or shortness of breath)., Asthma., Skin disorders and Allergies., Adverse skin effects (such as rash, irritation or corrosion)., Adverse eye effects (such as conjunctivitis or corneal damage)., Eye disease.

### 12. ECOLOGICAL INFORMATION

## Ecotoxicity effects

Aquatic toxicity	:	No data is available on the product itself.
Toxicity to other organisms	:	No data available.

## Persistence and degradability

Biodegradability	: No data is available on the product itself.
Mobility	: No data available.
Bioaccumulation	: No data is available on the product itself.

13. DISPOSAL CONSIDERATIONS				
Waste from residues / unused products	: Contact supplier if guidance is required.			
Contaminated packaging	: Dispose of container and unused contents in accordance with federal, state, and local requirements.			

## 14. TRANSPORT INFORMATION

DOT

UN/ID No. Proper shipping name	: UN1993 : Flammable liquids, n.o.s., (Diethylsilane)
Class or Division	: 3
Packing group	: 11
Label(s)	: 3
Marine Pollutant	: No

IATA

UN/ID No. :	UN1993
Proper shipping name :	Flammable liquid, n.o.s., (Diethylsilane)
Class or Division :	3
Packing group :	II
Label(s) :	3
Marine Pollutant :	No

### IMDG

UN/ID No.	: UN1993	
Proper shipping name	: FLAMMABLE LIQUID, N.O.S., (Diethylsilane)	

Class or Division	:	3
Packing group	:	II
Label(s)	:	3
Marine Pollutant	:	No

### TDG

UN/ID No.	: UN1993
Proper shipping name	: FLAMMABLE LIQUID, N.O.S., (Diethylsilane)
Class or Division	: 3
Packing group	: 11
Label(s)	: 3
Marine Pollutant	: No

#### **Further Information**

The transportation information is not intended to convey all specific regulatory data relating to this material. For complete transportation information, contact customer service.

### 15. REGULATORY INFORMATION

Toxic Substance Control Act (TSCA) 12(b) Component(s):

None.

Country	Regulatory list	Notification
USA	TSCA	Included on Inventory.
EU	EINECS	Included on EINECS inventory or polymer
		substance, monomers included on
		EINECS inventory or no longer polymer.
Canada	DSL	Not on Inventory.
Australia	AICS	Not on Inventory.
Japan	ENCS	Not on Inventory.
South Korea	ECL	Included on Inventory.
China	SEPA	Not on Inventory.
Philippines	PICCS	Not on Inventory.

EPA SARA Title III Section 312 (40 CFR 370) Hazard Classification Fire Hazard. Acute Health Hazard

- EPA SARA Title III Section 313 (40 CFR 372) Component(s) above 'de minimus' level None.
- US. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65) This product does not contain any chemicals known to State of California to cause cancer, birth defects or any other harm.

### **16. OTHER INFORMATION**

## NFPA Rating

Health Fire Instability	: : :	
HMIS Rating		
Health Flammability Physical hazard	: : :	3
Prepared by	:	Versum Materials, Product Regulatory Department
Telephone	:	(602)282-1000
Preparation Date	:	12/16/2017
For additional information, pleas	se v	isit Versum Materials' Product Stewardship web site.

For additional information, please visit Versum Materials' Product Stewardship web site. http://www.versummaterials.com/productstewardship/