

Safety Data Sheet

Version 5.0
Revision Date 12/08/2016

SDS Number 300000000113
Print Date 12/16/2017

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Phosphine

Chemical formula : PH₃

Synonyms : Phosphine, Hydrogen Phosphide, Phosphorated Hydrogen

Product Use Description : General Industrial

Manufacturer/Importer/Distributor : Versum Materials US, LLC
8555 South River Parkway
Tempe, AZ 85284
Exporter EIN No.475632014
www.versummaterials.com

Telephone : (602)282-1000

Emergency telephone number (24h) : 800-523-9374 USA
+1 610 481 7711 International

2. HAZARDS IDENTIFICATION

GHS classification

Flammable gases - Category 1
Gases under pressure - Liquefied gas.
Acute toxicity - Inhalation Category 1

GHS label elements

Hazard pictograms/symbols



Signal Word: Danger

Hazard Statements:

Safety Data Sheet

Version 5.0

Revision Date 12/08/2016

SDS Number 300000000113

Print Date 12/16/2017

H220:Extremely flammable gas.
H280:Contains gas under pressure; may explode if heated.
H330:Fatal if inhaled.
Symptoms may be delayed.
May form explosive mixtures in air.

Precautionary Statements:

Prevention : P210:Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.
P260:Do not breathe dust/fume/gas/mist/vapours/spray.
P271:Use only outdoors or in a well-ventilated area
P273:Avoid release to the environment.
P284:Wear respiratory protection.

Response : P304+P340 :IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P310 :Immediately call a POISON CENTRE/doctor.
P377 :Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381 :Eliminate all ignition sources if safe to do so.

Storage : P403+P233:Store in a well-ventilated place. Keep container tightly closed.
P405:Store locked up.
P410+P403:Protect from sunlight. Store in a well-ventilated place.

Disposal : P501:Disposal of contents/container to be specified in accordance with regulations.

Hazards not otherwise classified

May ignite spontaneously in contact with air.
Inhalation may be fatal.
Use a back flow preventative device in the piping.
Use only with equipment purged with and inert gas or evacuated prior to discharge.
Use only with equipment of compatible materials of construction, rated for cylinder pressure.
Do not open valve until connected to equipment prepared for use.
When returning cylinder install valve outlet cap or plug leak tight.
Close valve after each use and when empty.
Extremely flammable liquefied gas.
May form explosive mixtures in air.
Vapors may spread long distances and ignite.
Immediate fire and explosion hazard exists when mixed with air at concentrations exceeding the lower flammability limit (LFL).
Do not breathe gas.
Direct contact with liquid can cause frostbite.
Self contained breathing apparatus (SCBA) may be required.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Safety Data Sheet

Version 5.0

Revision Date 12/08/2016

SDS Number 300000000113

Print Date 12/16/2017

Components	CAS Number	Concentration (Volume)
Phosphine	7803-51-2	100 %

Concentration is nominal. For the exact product composition, please refer to technical specifications.

4. FIRST AID MEASURES

- General advice : Prompt medical attention is required in all cases of exposure. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
- Eye contact : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Keep eye wide open while rinsing.
- Skin contact : If liquid product comes in contact with skin, avoid breathing vapor. Remove contaminated clothing and flush with plenty of lukewarm water for several minutes. Wash frost-bitten areas with plenty of water. Do not remove clothing. Cover wound with sterile dressing.
- Ingestion : Ingestion is not considered a potential route of exposure.
- Inhalation : Move to fresh air. If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately. In case of shortness of breath, give oxygen. Consult a doctor.
- Most important symptoms/effects - acute and delayed : Headache. Nausea. Lachrymation. Cyanosis. Shortness of breath. Vomiting. Abdominal pain. Vertigo. Inhalation may provoke the following symptoms: Fatigue. Pulmonary irritation and edema.

Immediate Medical Attention and Special Treatment

- Treatment : If exposed or concerned: Get medical attention/advice.

5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : All known extinguishing media can be used.
- Specific hazards : May ignite spontaneously in contact with air. Cylinders containing this product do not have a pressure relief device. Gas is heavier than air and may collect in low areas or travel along the ground where there may be an ignition source present. If flames are accidentally extinguished, explosive re-ignition may occur; therefore, appropriate measures should be taken (e.g. total evacuation to protect persons from cylinder fragments and toxic fumes should a rupture occur). Upon exposure to intense heat or flame, cylinder will vent rapidly and or rupture violently. Combustion by-products may be toxic. Move away from container and cool with water from a protected position. Keep adjacent cylinders cool by spraying with large amounts of water until the fire burns itself out. Do not allow run-off from fire fighting to enter drains or water courses. If possible, shut off the source of gas and allow the fire to burn itself out.

Safety Data Sheet

Version 5.0

Revision Date 12/08/2016

SDS Number 300000000113

Print Date 12/16/2017

Extinguish fire only if gas flow can be stopped. Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire.

Special protective equipment for fire-fighters : Use self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

- Personal Precautions, Protective Equipment, and Emergency Procedures : Evacuate personnel to safe areas. Remove all sources of ignition. Use self-contained breathing apparatus or positive pressure air line with mask and escape pack in areas where concentration is unknown or above the exposure limits. Never enter a confined space or other area where the flammable gas concentration is greater than 10% of its lower flammable limit. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Ventilate the area.
- Environmental precautions : Should not be released into the environment. Prevent further leakage or spillage if safe to do so. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.
- Methods for cleaning up : Ventilate the area. Approach suspected leak areas with caution. Keep area evacuated and free from ignition sources until any spilled liquid has evaporated. (Ground free from frost).
- Additional advice : Large releases may require considerable downwind evacuation. If possible, stop flow of product. Increase ventilation to the release area and monitor concentrations. If leak is from cylinder or cylinder valve, call the emergency telephone number. If the leak is in the user's system, close the cylinder valve, safely vent the pressure, and purge with an inert gas before attempting repairs.

7. HANDLING AND STORAGE

Handling

Cylinders should be stored upright with valve protection cap in place and firmly secured to prevent falling or being knocked over. Protect cylinders from physical damage; do not drag, roll, slide or drop. Do not allow storage area temperature to exceed 50°C (122°F). Only experienced and properly instructed persons should handle compressed gases/cryogenic liquids. Before using the product, determine its identity by reading the label. Know and understand the properties and hazards of the product before use. When doubt exists as to the correct handling procedure for a particular gas, contact the supplier. Do not remove or deface labels provided by the supplier for the identification of the cylinder contents. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Use an adjustable strap wrench to remove over-tight or rusted caps. Before connecting the container, check the complete gas system for suitability, particularly for pressure rating and materials. Before connecting the container for use, ensure that back feed from the system into the container is prevented. Ensure the complete gas system is compatible for pressure rating and materials of construction. Ensure the complete gas system has been checked for leaks before use. Employ suitable pressure regulating devices on all containers when the gas is being emitted to systems with lower pressure rating than that of the container. Never insert an object (e.g. wrench, screwdriver, pry bar, etc.) into valve cap openings. Doing so may damage valve, causing a leak to

Safety Data Sheet

Version 5.0

Revision Date 12/08/2016

SDS Number 300000000113

Print Date 12/16/2017

occur. Open valve slowly. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Close valve after each use and when empty. Replace outlet caps or plugs and container caps as soon as container is disconnected from equipment. Do not subject containers to abnormal mechanical shock. Never attempt to lift a cylinder by its valve protection cap or guard. Do not use containers as rollers or supports or for any other purpose than to contain the gas as supplied. Never strike an arc on a compressed gas cylinder or make a cylinder a part of an electrical circuit. Do not smoke while handling product or cylinders. Never re-compress a gas or a gas mixture without first consulting the supplier. Never attempt to transfer gases from one cylinder/container to another. Always use backflow protective device in piping. Purge air from system before introducing gas. Installation of a cross purge assembly between the cylinder and the regulator is recommended. When returning cylinder install valve outlet cap or plug leak tight. Never use direct flame or electrical heating devices to raise the pressure of a container. Containers should not be subjected to temperatures above 50°C (122°F). Never attempt to increase liquid withdrawal rate by pressurizing the container without first checking with the supplier. Never permit liquefied gas to become trapped in parts of the system as this may result in hydraulic rupture. All piped systems and associated equipment must be grounded.

Storage

Use a back flow preventative device in the piping. Use only with equipment purged with and inert gas or evacuated prior to discharge. Use only with equipment of compatible materials of construction, rated for cylinder pressure. Do not open valve until connected to equipment prepared for use. When returning cylinder install valve outlet cap or plug leak tight. Close valve after each use and when empty. Read and follow the Safety Data Sheet (SDS) before use. Containers should be stored in a purpose build compound which should be well ventilated, preferably in the open air. Full containers should be stored so that oldest stock is used first. Observe all regulations and local requirements regarding storage of containers. Stored containers should be periodically checked for general condition and leakage. Local codes may have special requirements for toxic gas storage. Protect containers stored in the open against rusting and extremes of weather. Containers should not be stored in conditions likely to encourage corrosion. Containers should be stored in the vertical position and properly secured to prevent toppling. The container valves should be tightly closed and where appropriate valve outlets should be capped or plugged. Container valve guards or caps should be in place. Keep containers tightly closed in a cool, well-ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Full and empty cylinders should be segregated. Do not allow storage temperature to exceed 50°C (122°F). Smoking should be prohibited within storage areas or while handling product or containers. Display "No Smoking or Open Flames" signs in the storage areas. The amounts of flammable or toxic gases in storage should be kept to a minimum. Return empty containers in a timely manner. Flammable storage areas should be separated from oxygen and other oxidizers by a minimum distance of 20 ft. (6.1 m.) or by a barrier of non-combustible material at least 5 ft. (1.5 m.) high, having a fire resistance rating of at least 1/2 hour.

Technical measures/Precautions

Containers should be segregated in the storage area according to the various categories (e.g. flammable, toxic, etc.) and in accordance with local regulations. Provide sufficient air exchange and/or exhaust in work rooms.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures

Handle product only in closed system or provide appropriate exhaust ventilation at machinery.
Provide natural or explosion-proof ventilation adequate to ensure concentrations are kept below exposure limits.

Safety Data Sheet

Version 5.0

Revision Date 12/08/2016

SDS Number 300000000113

Print Date 12/16/2017

Personal protective equipment

- Respiratory protection : Keep self contained breathing apparatus readily available for emergency use. Use self-contained breathing apparatus or positive pressure air line with mask and escape pack in areas where concentration is unknown or above the exposure limits. Users of breathing apparatus must be trained.
- Hand protection : Sturdy work gloves are recommended for handling cylinders. Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety glasses recommended when handling cylinders. A full faceshield should be worn in addition to safety glasses when connecting, disconnecting or opening cylinders.
- Skin and body protection : Cold temperatures may cause embrittlement of protective material resulting in breakage and exposure. Contact with cold evaporating liquid on gloves or suit may cause cryogenic burns or frostbite. Safety shoes are recommended when handling cylinders. Wear as appropriate: Flame retardant protective clothing.
- Special instructions for protection and hygiene : Provide good ventilation and/or local exhaust to prevent accumulation of concentrations above exposure limits. Ensure adequate ventilation, especially in confined areas.

Exposure limit(s)

Phosphine	Time Weighted Average (TWA): ACGIH	0.3 ppm	-
Phosphine	Short Term Exposure Limit (STEL): ACGIH	1 ppm	-
Phosphine	Recommended exposure limit (REL): NIOSH	0.3 ppm	0.4 mg/m3
Phosphine	Short Term Exposure Limit (STEL): NIOSH	1 ppm	1 mg/m3
Phosphine	Permissible exposure limit: OSHA Z1	0.3 ppm	0.4 mg/m3
Phosphine	Time Weighted Average (TWA): OSHA Z1A	0.3 ppm	0.4 mg/m3
Phosphine	Short Term Exposure Limit (STEL): OSHA Z1A	1 ppm	1 mg/m3
Phosphine	Time Weighted Average (TWA) Permissible Exposure Limit (PEL): US CA OEL	0.3 ppm	0.4 mg/m3
Phosphine	Short Term Exposure Limit (STEL): US CA OEL	1 ppm	1 mg/m3
Phosphine	Time Weighted Average (TWA): TN OEL	0.3 ppm	0.4 mg/m3
Phosphine	Short Term Exposure Limit (STEL): TN OEL	1 ppm	1 mg/m3

9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Liquefied gas. Colorless gas
- Odor : Odor can persist. Poor warning properties at low concentrations. Rotten fish.

Safety Data Sheet

Version 5.0

Revision Date 12/08/2016

SDS Number 300000000113

Print Date 12/16/2017

Odor threshold	: No data available.
pH	: Not applicable.
Melting point/range	: -209 °F (-134 °C)
Boiling point/range	: -126 °F (-88 °C)
Flash point	: Not applicable.
Evaporation rate	: Not applicable.
Flammability (solid, gas)	: Refer to product classification in Section 2
Upper/lower explosion/flammability limit	: 95 %(V) / 1.6 %(V)
Vapor pressure	: 501.81 psia (34.60 bara) at 68 °F (20 °C)
Water solubility	: 0.3 g/l
Relative vapor density	: 1.2 (air = 1)
Relative density	: 0.74 (water = 1)
Partition coefficient (n-octanol/water)	: Not applicable.
Auto-ignition temperature	: < 0 °C
Decomposition temperature	: No data available.
Viscosity	: Not applicable.
Molecular Weight	: 34 g/mol
Density	: 0.087 lb/ft ³ (0.0014 g/cm ³) at 70 °F (21 °C) Note: (as vapor)
Specific Volume	: 11.36 ft ³ /lb (0.709 m ³ /kg) at 70 °F (21 °C)

10. STABILITY AND REACTIVITY

Chemical Stability	: Stable under normal conditions.
Conditions to avoid	: Heat, flames and sparks.
Materials to avoid	: Aluminium. Copper.

Safety Data Sheet

Version 5.0
Revision Date 12/08/2016

SDS Number 300000000113
Print Date 12/16/2017

Oxidizing agents.
Oxygen.

Hazardous decomposition products : Phosphorus.
Hydrogen.

Possibility of hazardous Reactions/Reactivity : No data available.

11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Likely routes of exposure

Effects on Eye : May cause eye irritation. Contact with liquid may cause cold burns/frostbite.

Effects on Skin : Contact with liquid may cause cold burns/frostbite.

Inhalation Effects : Fatal intoxication possible with low concentrations. Irritant and a general systemic poison. May be fatal if inhaled.

Ingestion Effects : Ingestion is not considered a potential route of exposure.

Symptoms : Headache. Nausea. Lachrymation. Cyanosis. Shortness of breath. Vomiting. Abdominal pain. Vertigo. Inhalation may provoke the following symptoms: Fatigue. Pulmonary irritation and edema.

Acute toxicity

Acute Oral Toxicity : No data is available on the product itself.

Inhalation : LC50 (1 h) : 20 ppm Species : Rat.

Acute Dermal Toxicity : No data is available on the product itself.

Skin corrosion/irritation : Reacts with water to form corrosive acids.

Serious eye damage/eye irritation : Reacts with water to form corrosive acids.

Sensitization. : No data available.

Chronic toxicity or effects from long term exposures

Carcinogenicity : No data available.

Reproductive toxicity : No data is available on the product itself.

Germ cell mutagenicity : No data is available on the product itself.

Safety Data Sheet

Version 5.0

Revision Date 12/08/2016

SDS Number 300000000113

Print Date 12/16/2017

Specific target organ systemic toxicity (single exposure) : No data available.

Specific target organ systemic toxicity (repeated exposure) : No data available.

Aspiration hazard : No data available.

Delayed and Immediate Effects and Chronic Effects from Short and Long Term Exposure

Chronic exposure may cause skeletal changes, cardiac abnormalities, pulmonary and liver dysfunction, jaundice, and kidney inflammation. Asthma.

Phosphine is an irritant to the eyes and airway and is a central nervous system depressant. Injury to the kidneys and other organs may also occur. Mechanisms of injury are not well defined but presumably involve damage to enzyme systems. Injury to the kidneys may result in albuminuria and hematuria. Severe exposure to phosphine may be lethal. Absorption of phosphine may be associated with disturbances in sight, speech and motor functions. Manifestations of chronic phosphorous poisoning may occur, namely, skeletal injury.

12. ECOLOGICAL INFORMATION

Ecotoxicity effects

Aquatic toxicity : May cause pH changes in aqueous ecological systems.

Toxicity to other organisms : No data available.

Persistence and degradability

Biodegradability : No data is available on the product itself.

Mobility : Because of its high volatility, the product is unlikely to cause ground pollution.

Bioaccumulation : Refer to Section 9 "Partition Coefficient (n-octanol/water)".

Further information

Toxic to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products : Destruction via incineration followed by scrubbing is the most commonly used method. In accordance with local and national regulations. Contact supplier if guidance is required. Return unused product in original cylinder to supplier. Must not be discharged to atmosphere.

Contaminated packaging : Return cylinder to supplier.

Safety Data Sheet

Version 5.0

Revision Date 12/08/2016

SDS Number 300000000113

Print Date 12/16/2017

14. TRANSPORT INFORMATION

DOT

UN/ID No. : UN2199
Proper shipping name : Phosphine
Class or Division : 2.3
Label(s) : 2.3 (2.1)
PIH Zone : A
RQ Substance : Yes
Marine Pollutant : No

* NOTE: This product contains a USDOT Hazardous Substance and will meet the Reportable Quantity definition when shipped to, from, or within the United States, in the amount specified in 49CFR 172.101 Appendix A.

IATA

Transport Forbidden

IMDG

UN/ID No. : UN2199
Proper shipping name : PHOSPHINE
Class or Division : 2.3
Label(s) : 2.3 (2.1)
RQ Substance : Yes
Marine Pollutant : Yes

* NOTE: This product contains a USDOT Hazardous Substance and will meet the Reportable Quantity definition when shipped to, from, or within the United States, in the amount specified in 49CFR 172.101 Appendix A.

** NOTE: This product contains a substance that: 1) is regulated as a Marine Pollutant, or 2) meets the definition of toxic to the aquatic environment.

TDG

UN/ID No. : UN2199
Proper shipping name : PHOSPHINE
Class or Division : 2.3
Label(s) : 2.3 (2.1)
RQ Substance : Yes
Marine Pollutant : Yes

* NOTE: This product contains a USDOT Hazardous Substance and will meet the Reportable Quantity definition when shipped to, from, or within the United States, in the amount specified in 49CFR 172.101

Safety Data Sheet

Version 5.0

Revision Date 12/08/2016

SDS Number 300000000113

Print Date 12/16/2017

Appendix A.

** NOTE: This product contains a substance that: 1) is regulated as a Marine Pollutant, or 2) meets the definition of toxic to the aquatic environment.

Further Information

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. The transportation information is not intended to convey all specific regulatory data relating to this material. For complete transportation information, contact customer service.

15. REGULATORY INFORMATION

Toxic Substance Control Act (TSCA) 12(b) Component(s):

None.

Country	Regulatory list	Notification
USA	TSCA	Included on Inventory.
EU	EINECS	Included on Inventory.
Canada	DSL	Included on Inventory.
Australia	AICS	Included on Inventory.
Japan	ENCS	Included on Inventory.
South Korea	ECL	Included on Inventory.
China	SEPA	Included on Inventory.
Philippines	PICCS	Included on Inventory.

EPA SARA Title III Section 312 (40 CFR 370) Hazard Classification

Acute Health Hazard

Fire Hazard. Sudden Release of Pressure Hazard.

EPA SARA Title III Section 313 (40 CFR 372) Component(s) above 'de minimus' level

Phosphine

US. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65)

This product does not contain any chemicals known to State of California to cause cancer, birth defects or any other harm.

16. OTHER INFORMATION

NFPA Rating

Health : 4
Fire : 4

Safety Data Sheet

Version 5.0

Revision Date 12/08/2016

SDS Number 300000000113

Print Date 12/16/2017

Instability : 2

HMIS Rating

Health : 4

Flammability : 4

Physical hazard : 3

Prepared by : Versum Materials, Product Regulatory Department

Telephone : (602)282-1000

Preparation Date : 12/16/2017

For additional information, please visit Versum Materials' Product Stewardship web site.
<http://www.versummaterials.com/productstewardship/>
