

Safety Data Sheet

Version 1.18

Revision Date 08/01/2016

SDS Number 300000000003

Print Date 12/16/2017

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : White Ammonia[®]

Chemical formula : NH₃

Synonyms : Ammonia, Anhydrous

Product Use Description : General Industrial

Manufacturer/Importer/Distributor : Versum Materials US, LLC
8555 South River Parkway
Tempe, AZ 85284
Exporter EIN No.475632014
www.versummaterials.com

Telephone : (602)282-1000

Emergency telephone number (24h) : 800-523-9374 USA
+1 610 481 7711 International

2. HAZARDS IDENTIFICATION

GHS classification

Flammable gases - Category 2
Gases under pressure - Liquefied gas.
Acute toxicity - Inhalation Category 4
Skin corrosion - Category 1B

GHS label elements

Hazard pictograms/symbols



Signal Word: Danger

Hazard Statements:

Safety Data Sheet

Version 1.18

Revision Date 08/01/2016

SDS Number 300000000003

Print Date 12/16/2017

H221:Flammable gas.
H280:Contains gas under pressure; may explode if heated.
H314:Causes severe skin burns and eye damage.
H332:Harmful if inhaled.
EUH071:Corrosive to the respiratory tract.

Precautionary Statements:

Prevention : P210:Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking.
P264:Wash hands thoroughly after handling.
P280:Wear protective gloves/protective clothing/eye protection/face protection.

Response : P301+P330+P331 :IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P305+P351+P338 :IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 :Immediately call a POISON CENTRE/doctor.
P377 :Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

Storage : P403+P233:Store in a well-ventilated place. Keep container tightly closed.
P405:Store locked up.

Disposal : P501:Disposal of contents/container to be specified in accordance with regulations.

Hazards not otherwise classified

Flammable.
Vapors may form explosive mixture with air.
Immediate fire and explosion hazard exists when mixed with air at concentrations exceeding the lower flammability limit (LFL).
Wear self-contained breathing apparatus and protective suit.
Direct contact with liquid can cause frostbite.
May react violently with water.
Do not breathe gas.
Corrosive to eyes, respiratory system and skin.
Compressed liquefied gas.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Concentration (Volume)
Ammonia	7664-41-7	100 %

Concentration is nominal. For the exact product composition, please refer to technical specifications.

4. FIRST AID MEASURES

Safety Data Sheet

Version 1.18

Revision Date 08/01/2016

SDS Number 300000000003

Print Date 12/16/2017

- General advice : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped. Use chemically protective clothing.
- Eye contact : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Keep eye wide open while rinsing.
- Skin contact : Flush with copious amounts of water until treatment is available. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and badly.
- Ingestion : Ingestion is not considered a potential route of exposure.
- Inhalation : Move to fresh air. If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped, trained personnel should begin cardiopulmonary resuscitation immediately. Mouth to mouth resuscitation is not recommended. Use a barrier device. If unconscious place in recovery position and seek medical advice. In case of shortness of breath, give oxygen. Consult a doctor.
- Most important symptoms/effects - acute and delayed : Aspiration may cause pulmonary edema and pneumonitis. Coughing, irritation in the throat and nasal tract. May cause severe chemical burns to skin and cornea. Suitable first-aid treatment should be immediately available. Seek medical advice before using product. Cough. Headache. Nausea.

Immediate Medical Attention and Special Treatment

- Treatment : Treat bronchospasm and laryngeal edema if present. Observe for delayed chemical pneumonitis, pulmonary hemorrhage or edema. Obtain medical attention. If exposed or concerned: Get medical attention/advice.

5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : All known extinguishing media can be used.
- Specific hazards : Extinguish fire only if gas flow can be stopped. If possible, shut-off source of gas and allow the fire to burn itself out. Downwind personnel must be evacuated. Ammonia can form explosive compounds when combined with mercury. Upon exposure to intense heat or flame, cylinder will vent rapidly and or rupture violently. Product is nonflammable and does not support combustion. Use of water may result in the formation of very toxic aqueous solutions. Move away from container and cool with water from a protected position. Do not allow run-off from fire fighting to enter drains or water courses. Keep containers and surroundings cool with water spray. If possible, stop flow of product. Most cylinders are designed to vent contents when exposed to elevated temperatures.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus. Use self-contained breathing apparatus and chemically protective clothing.
- Further information : Use of water may result in the formation of very toxic aqueous solutions.,

Safety Data Sheet

Version 1.18

Revision Date 08/01/2016

SDS Number 300000000003

Print Date 12/16/2017

Combustion by-products may be toxic., If flames are accidentally extinguished, explosive re-ignition may occur; therefore, appropriate measures should be taken(e.g. total evacuation to protect persons from cylinder fragments and toxic fumes) should a rupture occur., In the event of fire, cool tanks with water spray .

6. ACCIDENTAL RELEASE MEASURES

- Personal Precautions, Protective Equipment, and Emergency Procedures : Remove all sources of ignition. Evacuate personnel to safe areas. Ventilate the area. Approach suspected leak areas with caution. Use self-contained breathing apparatus or positive pressure air line with mask and escape pack in areas where concentration is unknown or above the exposure limits.
- Environmental precautions : Should not be released into the environment. Prevent further leakage or spillage if safe to do so. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.
- Methods for cleaning up : Keep area evacuated and free from ignition sources until any spilled liquid has evaporated. (Ground free from frost.) Ventilate the area. Wash contaminated equipment or sites of leaks with copious quantities of water. Reduce vapor with fog or fine water spray.
- Additional advice : If possible, stop flow of product. Increase ventilation to the release area and monitor concentrations. If leak is from cylinder or cylinder valve, call the emergency telephone number. If the leak is in the user's system, close the cylinder valve, safely vent the pressure, and purge with an inert gas before attempting repairs.

7. HANDLING AND STORAGE

Handling

Use equipment rated for cylinder pressure. Cylinders should be stored upright with valve protection cap in place and firmly secured to prevent falling or being knocked over. Protect cylinders from physical damage; do not drag, roll, slide or drop. Do not allow storage area temperature to exceed 50°C (122°F). Only experienced and properly instructed persons should handle compressed gases/cryogenic liquids. Before using the product, determine its identity by reading the label. Know and understand the properties and hazards of the product before use. When doubt exists as to the correct handling procedure for a particular gas, contact the supplier. Do not remove or deface labels provided by the supplier for the identification of the cylinder contents. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Use an adjustable strap wrench to remove over-tight or rusted caps. Before connecting the container, check the complete gas system for suitability, particularly for pressure rating and materials. Before connecting the container for use, ensure that back feed from the system into the container is prevented. Ensure the complete gas system is compatible for pressure rating and materials of construction. Ensure the complete gas system has been checked for leaks before use. Employ suitable pressure regulating devices on all containers when the gas is being emitted to systems with lower pressure rating than that of the container. Never insert an object (e.g. wrench, screwdriver, pry bar, etc.) into valve cap openings. Doing so may damage valve, causing a leak to occur. Open valve slowly. If user experiences any difficulty operating cylinder valve discontinue use and contact supplier. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Close valve after each use and when empty. Replace outlet caps or plugs and container caps as soon as container is disconnected from equipment. Do not subject

Safety Data Sheet

Version 1.18

Revision Date 08/01/2016

SDS Number 300000000003

Print Date 12/16/2017

containers to abnormal mechanical shock. Never attempt to lift a cylinder by its valve protection cap or guard. Do not use containers as rollers or supports or for any other purpose than to contain the gas as supplied. Never strike an arc on a compressed gas cylinder or make a cylinder a part of an electrical circuit. Keep container valve outlets clean and free from contaminants particularly oil and water. Do not smoke while handling product or cylinders. Never re-compress a gas or a gas mixture without first consulting the supplier. Never attempt to transfer gases from one cylinder/container to another. Always use backflow protective device in piping. Purge air from system before introducing gas. Purge system with dry inert gas (e.g. helium or nitrogen) before gas is introduced and when system is placed out of service. Avoid suckback of water, acid and alkalis. Installation of a cross purge assembly between the cylinder and the regulator is recommended. When returning cylinder install valve outlet cap or plug leak tight. Never use direct flame or electrical heating devices to raise the pressure of a container. Containers should not be subjected to temperatures above 50°C (122°F). Never attempt to increase liquid withdrawal rate by pressurizing the container without first checking with the supplier. Never permit liquefied gas to become trapped in parts of the system as this may result in hydraulic rupture.

Storage

Flammable storage areas should be separated from oxygen and other oxidizers by a minimum distance of 20 ft. (6.1 m.) or by a barrier of non-combustible material at least 5 ft. (1.5 m.) high, having a fire resistance rating of at least 1/2 hour. Post "No Smoking or Open Flames" signs in the storage areas. Use a back flow preventative device in the piping. Do not open valve until connected to equipment prepared for use. Use only with equipment of compatible materials of construction, rated for cylinder pressure. Close valve after each use and when empty. Read and follow the Safety Data Sheet (SDS) before use. Open/close valve slowly. Close when not in use. Wear Safety Eye Protection. Check Safety Data Sheet before use. Use a back flow preventative device in the piping. Do not open valve until connected to equipment prepared for use. Use only with equipment of compatible materials of construction, rated for cylinder pressure. Close valve after each use and when empty. Read and follow the Safety Data Sheet (SDS) before use. Full containers should be stored so that oldest stock is used first. Containers should be stored in a purpose build compound which should be well ventilated, preferably in the open air. Observe all regulations and local requirements regarding storage of containers. Stored containers should be periodically checked for general condition and leakage. Local codes may have special requirements for toxic gas storage. Protect containers stored in the open against rusting and extremes of weather. Containers should not be stored in conditions likely to encourage corrosion. Containers should be stored in the vertical position and properly secured to prevent toppling. The container valves should be tightly closed and where appropriate valve outlets should be capped or plugged. Container valve guards or caps should be in place. Keep containers tightly closed in a cool, well-ventilated place. Full and empty cylinders should be segregated. Do not allow storage temperature to exceed 50°C (122°F). Return empty containers in a timely manner.

Technical measures/Precautions

Containers containing flammable gases should be stored away from other combustible materials. Where necessary containers containing oxygen and oxidants should be separated from flammable gases by a fire resistant partition. Provide sufficient air exchange and/or exhaust in work rooms. Containers should be segregated in the storage area according to the various categories (e.g. flammable, toxic, etc.) and in accordance with local regulations.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures

Handle product only in closed system or provide appropriate exhaust ventilation at machinery.
Provide natural or explosion-proof ventilation adequate to ensure concentrations are kept below exposure limits.
Provide readily accessible eye wash stations and safety showers.

Safety Data Sheet

Version 1.18

Revision Date 08/01/2016

SDS Number 300000000003

Print Date 12/16/2017

Personal protective equipment

- Respiratory protection : Keep self contained breathing apparatus readily available for emergency use. Use self-contained breathing apparatus or positive pressure air line with mask and escape pack in areas where concentration is unknown or above the exposure limits. Users of breathing apparatus must be trained.
- Hand protection : Sturdy work gloves are recommended for handling cylinders. Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection : Safety glasses recommended when handling cylinders. A full faceshield should be worn in addition to safety glasses when connecting, disconnecting or opening cylinders.
- Skin and body protection : Use chemically protective clothing. Safety shoes are recommended when handling cylinders. Encapsulated chemical protective suit in emergency situations.
- Special instructions for protection and hygiene : Ensure adequate ventilation, especially in confined areas. Provide good ventilation and/or local exhaust to prevent accumulation of concentrations above exposure limits.

Exposure limit(s)

Ammonia	Time Weighted Average (TWA): ACGIH	25 ppm	-
Ammonia	Short Term Exposure Limit (STEL): ACGIH	35 ppm	-
Ammonia	Recommended exposure limit (REL): NIOSH	25 ppm	18 mg/m3
Ammonia	Short Term Exposure Limit (STEL): NIOSH	35 ppm	27 mg/m3
Ammonia	Permissible exposure limit: OSHA Z1	50 ppm	35 mg/m3
Ammonia	Short Term Exposure Limit (STEL): OSHA Z1A	35 ppm	27 mg/m3
Ammonia	Time Weighted Average (TWA) Permissible Exposure Limit (PEL): US CA OEL	25 ppm	18 mg/m3
Ammonia	Short Term Exposure Limit (STEL): US CA OEL	35 ppm	27 mg/m3
Ammonia	Short Term Exposure Limit (STEL): TN OEL	35 ppm	27 mg/m3

9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : Liquefied gas. Colorless gas
- Odor : Ammoniacal.
- Odor threshold : No data available.
- pH : Not applicable.
- Melting point/range : -108 °F (-77.7 °C)

Safety Data Sheet

Version 1.18

Revision Date 08/01/2016

SDS Number 300000000003

Print Date 12/16/2017

Boiling point/range	: -28 °F (-33.5 °C)
Flash point	: Not applicable.
Evaporation rate	: Not applicable.
Flammability (solid, gas)	: Refer to product classification in Section 2
Upper/lower explosion/flammability limit	: 28 %(V) / 15 %(V)
Vapor pressure	: 124.73 psia (8.60 bara) at 68 °F (20 °C)
Water solubility	: Hydrolyses.
Relative vapor density	: 0.588 (air = 1)
Relative density	: 0.7 (water = 1)
Partition coefficient (n-octanol/water)	: Not applicable.
Auto-ignition temperature	: 630 °C
Decomposition temperature	: No data available.
Viscosity	: Not applicable.
Molecular Weight	: 17.03 g/mol
Density	: 0.044 lb/ft ³ (0.0007 g/cm ³) at 70 °F (21 °C) Note: (as vapor)
Specific Volume	: 22.49 ft ³ /lb (1.4040 m ³ /kg) at 70 °F (21 °C)

10. STABILITY AND REACTIVITY

Chemical Stability	: Stable under normal conditions.
Conditions to avoid	: Heat, flames and sparks.
Materials to avoid	: Copper, silver, cadmium and zinc and their alloys; mercury, tin, acids, alcohols, aldehydes, halogens and oxidizers. Ammonia can form explosive compounds when combined with mercury. May react violently with oxidants. May react violently with acids. Reacts with water to form corrosive alkalis. Overexposure to the atmosphere results in water absorption.
Hazardous decomposition	: No decomposition if stored normally.

Safety Data Sheet

Version 1.18

Revision Date 08/01/2016

SDS Number 300000000003

Print Date 12/16/2017

products
Possibility of hazardous : Vapors may form explosive mixture with air.
Reactions/Reactivity

11. TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Likely routes of exposure

- Effects on Eye : Causes eye burns. May cause blindness. Irritating to eyes. Causes severe eye burns. May cause permanent eye injury.
- Effects on Skin : Causes skin burns. Contact with liquid may cause cold burns/frostbite. Causes skin irritation. Causes skin burns.
- Inhalation Effects : Toxic by inhalation. Can cause severe eye, skin and respiratory tract burns. Irritating to respiratory system. Can cause severe lung damage. May be fatal if inhaled. Delayed adverse effects possible. Prolonged exposure to small concentrations may result in pulmonary edema. Delayed fatal pulmonary edema possible.
- Ingestion Effects : Ingestion is not considered a potential route of exposure.
- Symptoms : Aspiration may cause pulmonary edema and pneumonitis. Coughing, irritation in the throat and nasal tract. May cause severe chemical burns to skin and cornea. Suitable first-aid treatment should be immediately available. Seek medical advice before using product. Cough. Headache. Nausea.

Acute toxicity

- Acute Oral Toxicity : No data is available on the product itself.
- Inhalation : LC50 (1 h) : 7338 ppm Species : Rat.
- Acute Dermal Toxicity : No data is available on the product itself.
- Skin corrosion/irritation : Causes skin burns.
- Serious eye damage/eye irritation : Risk of serious damage to eyes.
- Sensitization. : No data available.

Chronic toxicity or effects from long term exposures

- Carcinogenicity : This product contains no listed carcinogens according to IARC, ACGIH, NTP and/or OSHA in concentrations of 0.1 percent or greater.
- Reproductive toxicity : No data is available on the product itself.

Safety Data Sheet

Version 1.18

Revision Date 08/01/2016

SDS Number 300000000003

Print Date 12/16/2017

Germ cell mutagenicity : No data is available on the product itself.

Specific target organ systemic toxicity (single exposure) : No data available.

Specific target organ systemic toxicity (repeated exposure) : No data available.

Aspiration hazard : No data available.

Delayed and Immediate Effects and Chronic Effects from Short and Long Term Exposure

Asthma.

12. ECOLOGICAL INFORMATION

Ecotoxicity effects

Aquatic toxicity : May cause pH changes in aqueous ecological systems.

Toxicity to other organisms : No data available.

Persistence and degradability

Biodegradability : No data is available on the product itself.

Mobility : No data available.

Bioaccumulation : Refer to Section 9 "Partition Coefficient (n-octanol/water)".

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products : In accordance with local and national regulations. Return unused product in original cylinder to supplier. Contact supplier if guidance is required. Must not be discharged to atmosphere.

Contaminated packaging : Return cylinder to supplier.

14. TRANSPORT INFORMATION

DOT

UN/ID No. : UN1005

Proper shipping name : Ammonia, anhydrous

9/12

Safety Data Sheet

Version 1.18

Revision Date 08/01/2016

SDS Number 300000000003

Print Date 12/16/2017

Class or Division : 2.2
Label(s) : 2.2
RQ Substance : Yes
Marine Pollutant : Yes

* NOTE: This product contains a USDOT Hazardous Substance and will meet the Reportable Quantity definition when shipped to, from, or within the United States, in the amount specified in 49CFR 172.101 Appendix A.

** NOTE: This product contains a substance that is regulated as a Marine Pollutant when transported in bulk packages (liquid – volume exceeding 450 liters, gas – water capacity exceeding 454 kilograms).

IATA

Transport Forbidden

IMDG

UN/ID No. : UN1005
Proper shipping name : AMMONIA, ANHYDROUS
Class or Division : 2.3
Label(s) : 2.3 (8)
RQ Substance : Yes
Marine Pollutant : Yes

* NOTE: This product contains a USDOT Hazardous Substance and will meet the Reportable Quantity definition when shipped to, from, or within the United States, in the amount specified in 49CFR 172.101 Appendix A.

** NOTE: This product contains a substance that: 1) is regulated as a Marine Pollutant, or 2) meets the definition of toxic to the aquatic environment.

TDG

UN/ID No. : UN1005
Proper shipping name : AMMONIA, ANHYDROUS
Class or Division : 2.3
Label(s) : 2.3 (8)
RQ Substance : Yes
Marine Pollutant : Yes

* NOTE: This product contains a USDOT Hazardous Substance and will meet the Reportable Quantity definition when shipped to, from, or within the United States, in the amount specified in 49CFR 172.101 Appendix A.

** NOTE: This product contains a substance that: 1) is regulated as a Marine Pollutant, or 2) meets the definition of toxic to the aquatic environment.

Safety Data Sheet

Version 1.18

Revision Date 08/01/2016

SDS Number 300000000003

Print Date 12/16/2017

Further Information

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. The transportation information is not intended to convey all specific regulatory data relating to this material. For complete transportation information, contact customer service.

15. REGULATORY INFORMATION

Toxic Substance Control Act (TSCA) 12(b) Component(s):

None.

Country	Regulatory list	Notification
USA	TSCA	Included on Inventory.
EU	EINECS	Included on Inventory.
Canada	DSL	Included on Inventory.
Australia	AICS	Included on Inventory.
Japan	ENCS	Included on Inventory.
South Korea	ECL	Included on Inventory.
China	SEPA	Included on Inventory.
Philippines	PICCS	Included on Inventory.

EPA SARA Title III Section 312 (40 CFR 370) Hazard Classification
Acute Health Hazard Sudden Release of Pressure Hazard.

EPA SARA Title III Section 313 (40 CFR 372) Component(s) above 'de minimus' level
Ammonia

US. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65)
This product does not contain any chemicals known to State of California to cause cancer, birth defects or any other harm.

16. OTHER INFORMATION

NFPA Rating

Health : 3
Fire : 1
Instability : 0

HMIS Rating

Health : 3
Flammability : 1
Physical hazard : 2

Safety Data Sheet

Version 1.18

Revision Date 08/01/2016

SDS Number 3000000000003

Print Date 12/16/2017

Prepared by : Versum Materials, Product Regulatory Department

Telephone : (602)282-1000

Preparation Date : 12/16/2017

For additional information, please visit our Versum Materials' Product Stewardship web site.
<http://www.versummaterials.com/productstewardship/>
