

DOW CORNING(R) 680 SANITARY SEALANT WHITE

Version 2.0	Revision Date: 22.09.2015	SDS Number: 661372-00005	Date of last issue: 15.06.2015
			Date of first issue: 23.10.2014

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : DOW CORNING(R) 680 SANITARY SEALANT WHITE

Product code : 000000000004018316, 000000000004018316

Manufacturer or supplier's details

Company : Dow Corning Australia Pty Ltd, ABN 36 008 444 166

Address : Darling Park, Tower 2
Level 20, 201 Sussex Street
Sydney. NSW 2000

Locked Bag 2095
North Ryde, NSW 1670

Telephone : 1300-369-745

Emergency telephone number : 1300-360-732 (24 Hours)

Telefax : 1300-650-785

Recommended use of the chemical and restrictions on use

Recommended use : Construction materials and additives
Adhesive, binding agents

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Serious eye damage/eye irritation : Category 2A

Skin sensitisation : Category 1

GHS Label element

Hazard pictograms : 

Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

Precautionary statements : **Prevention:**
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/ eye protection/ face protection.

DOW CORNING(R) 680 SANITARY SEALANT WHITE

Version
2.0Revision Date:
22.09.2015SDS Number:
661372-00005Date of last issue: 15.06.2015
Date of first issue: 23.10.2014**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P363 Wash contaminated clothing before reuse.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Silicone Sealant

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Silicon dioxide	7631-86-9	< 10
Amorphous fumed silica	112945-52-5	< 10
Methyltri(ethylmethylketoxime)silane	22984-54-9	< 10
Distillates (petroleum), hydrotreated middle	64742-46-7	< 10
Vinyltri (methylethylketoxime) silane	2224-33-1	< 10
3-Aminopropyltriethoxysilane	919-30-2	< 10
Titanium dioxide	13463-67-7	< 10
Methyltri(ethylmethylketoxime)silane isomers and oligomers	Not Assigned	< 10
1-[[2-(2,4-dichlorophenyl)-4-propyl-1,3-dioxolan-2-yl]methyl]-1H-1,2,4-triazole	60207-90-1	< 10

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.

When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.
 Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.

**DOW CORNING(R) 680 SANITARY SEALANT
WHITE**
Version
2.0Revision Date:
22.09.2015SDS Number:
661372-00005Date of last issue: 15.06.2015
Date of first issue: 23.10.2014

Remove contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.

In case of eye contact

: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention.

If swallowed

: If swallowed, DO NOT induce vomiting.
Get medical attention if symptoms occur.
Rinse mouth thoroughly with water.

 Most important symptoms and effects, both acute and delayed

: May cause an allergic skin reaction.
Causes serious eye irritation.

Protection of first-aiders

: First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists.

Notes to physician

: Treat symptomatically and supportively.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media

: Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media

: None known.

Specific hazards during fire-fighting

: Exposure to combustion products may be a hazard to health.

Hazardous combustion products

: Carbon oxides
Silicon oxides
Formaldehyde
Nitrogen oxides (NO_x)

Specific extinguishing methods

: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.

Special protective equipment for firefighters

: In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.

DOW CORNING(R) 680 SANITARY SEALANT WHITE

Version 2.0	Revision Date: 22.09.2015	SDS Number: 661372-00005	Date of last issue: 15.06.2015 Date of first issue: 23.10.2014
----------------	------------------------------	-----------------------------	---

SECTION 6. ACCIDENTAL RELEASE MEASURES

- | | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | : Use personal protective equipment.
Follow safe handling advice and personal protective equipment recommendations. |
| Environmental precautions | : Discharge into the environment must be avoided.
Prevent further leakage or spillage if safe to do so.
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained. |
| Methods and materials for containment and cleaning up | : Soak up with inert absorbent material.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements. |

SECTION 7. HANDLING AND STORAGE

- | | |
|-----------------------------|---|
| Technical measures | : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : Use only with adequate ventilation. |
| Advice on safe handling | : Do not get on skin or clothing.
Do not swallow.
Do not get in eyes.
Handle in accordance with good industrial hygiene and safety practice.
Keep away from water.
Protect from moisture.
Take care to prevent spills, waste and minimize release to the environment. |
| Hygiene measures | : Ensure that eye flushing systems and safety showers are located close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.
These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions. |
| Conditions for safe storage | : Keep in properly labelled containers.
Store in accordance with the particular national regulations. |

**DOW CORNING(R) 680 SANITARY SEALANT
WHITE**

Version 2.0 Revision Date: 22.09.2015 SDS Number: 661372-00005 Date of last issue: 15.06.2015
 Date of first issue: 23.10.2014

Materials to avoid : Do not store with the following product types:
 Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Silicon dioxide	7631-86-9	TWA (Res- pirable dust)	2 mg/m3	AU OEL
Amorphous fumed silica	112945-52-5	TWA	10 mg/m3	AU OEL
Further information: This value is for inhalable dust containing no asbestos and < 1% crystalline silica				
Distillates (petroleum), hy- drotreated middle	64742-46-7	TWA (Mist)	5 mg/m3	AU OEL
Titanium dioxide	13463-67-7	TWA	10 mg/m3	AU OEL
Further information: This value is for inhalable dust containing no asbestos and < 1% crystalline silica				
		TWA	10 mg/m3 (Titanium dioxide)	ACGIH

Occupational exposure limits of decomposition products

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Ethyl methyl ketoxime	96-29-7	TWA	10 ppm	DCC OEL
Further information: Skin sensitisation				

Engineering measures : Processing may form hazardous compounds (see section 10).
 Ensure adequate ventilation, especially in confined areas.
 Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Organic vapour type

Hand protection
 Material : Impervious gloves

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to

**DOW CORNING(R) 680 SANITARY SEALANT
WHITE**
Version
2.0Revision Date:
22.09.2015SDS Number:
661372-00005Date of last issue: 15.06.2015
Date of first issue: 23.10.2014

chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

- | | |
|--------------------------|---|
| Eye protection | : Wear the following personal protective equipment:
Safety goggles |
| Skin and body protection | : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc). |

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: paste
Colour	: white
Odour	: slight
Odour Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: Not applicable
Flash point	: Not applicable
Evaporation rate	: Not applicable
Flammability (solid, gas)	: Not classified as a flammability hazard
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: Not applicable
Relative vapour density	: No data available
Relative density	: 0.985
Solubility(ies)	
Water solubility	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available

DOW CORNING(R) 680 SANITARY SEALANT WHITE

Version 2.0	Revision Date: 22.09.2015	SDS Number: 661372-00005	Date of last issue: 15.06.2015 Date of first issue: 23.10.2014
-------------	---------------------------	--------------------------	---

Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: Not applicable
Explosive properties	: Not explosive
Oxidizing properties	: The substance or mixture is not classified as oxidizing.
Molecular weight	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Not classified as a reactivity hazard.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Use at elevated temperatures may form highly hazardous compounds. Can react with strong oxidizing agents. Hazardous decomposition products will be formed upon contact with water or humid air. Hazardous decomposition products will be formed at elevated temperatures.
Conditions to avoid	: Exposure to moisture
Incompatible materials	: Oxidizing agents Water
Hazardous decomposition products	
Contact with water or humid air	: Ethyl methyl ketoxime
Thermal decomposition	: Formaldehyde

SECTION 11. TOXICOLOGICAL INFORMATION

Exposure routes	: Skin contact Ingestion Eye contact
-----------------	--

Acute toxicity

||| Not classified based on available information.

Components:

Silicon dioxide:

||| Acute oral toxicity : LD50 (Rat): > 3,300 mg/kg
Assessment: The substance or mixture has no acute oral toxicity

DOW CORNING(R) 680 SANITARY SEALANT WHITE

Version 2.0 Revision Date: 22.09.2015 SDS Number: 661372-00005 Date of last issue: 15.06.2015
Date of first issue: 23.10.2014

Remarks: Information taken from reference works and the literature.

Acute inhalation toxicity : LC50 (Rat): > 2.08 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Information taken from reference works and the literature.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Information taken from reference works and the literature.

Amorphous fumed silica:

Acute oral toxicity : LD50 (Rat): > 20,000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity
Remarks: Information taken from reference works and the literature.

Methyltri(ethylmethylketoxime)silane:

Acute oral toxicity : LD50 (Rat): > 2,520 mg/kg
Assessment: The substance or mixture has no acute oral toxicity
Remarks: Based on test data

Distillates (petroleum), hydrotreated middle:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity : LC50 (Rat): > 5,266 mg/m³
Exposure time: 4 h
Test atmosphere: dust/mist
Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Vinyltri (methylethylketoxime) silane:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity
Remarks: Based on test data
Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on test data

3-Aminopropyltriethoxysilane:

Acute oral toxicity : LD50 (Rat): 1.57 ml/kg

DOW CORNING(R) 680 SANITARY SEALANT WHITE

Version 2.0	Revision Date: 22.09.2015	SDS Number: 661372-00005	Date of last issue: 15.06.2015 Date of first issue: 23.10.2014
-------------	---------------------------	--------------------------	---

Remarks: Based on test data

Acute dermal toxicity : LD50 (Rabbit): 4.29 ml/kg
Remarks: Information taken from reference works and the literature.

Titanium dioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

1-[[2-(2,4-dichlorophenyl)-4-propyl-1,3-dioxolan-2-yl]methyl]-1H-1,2,4-triazole:

Acute oral toxicity : LD50 (Rat): 2,000 mg/kg
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.8 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 4,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Not classified based on available information.

Components:

Silicon dioxide:

Result: No skin irritation
Remarks: Information taken from reference works and the literature.

Methyltri(ethylmethylketoxime)silane:

Species: Rabbit
Result: No skin irritation
Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated middle:

Species: Rabbit
Method: OECD Test Guideline 404
Result: No skin irritation

3-Aminopropyltriethoxysilane:

Species: Rabbit
Result: Corrosive after 3 minutes to 1 hour of exposure
Remarks: Based on test data

DOW CORNING(R) 680 SANITARY SEALANT WHITE

Version 2.0	Revision Date: 22.09.2015	SDS Number: 661372-00005	Date of last issue: 15.06.2015 Date of first issue: 23.10.2014
----------------	------------------------------	-----------------------------	---

Titanium dioxide:

Species: Rabbit
Result: No skin irritation

1-[[2-(2,4-dichlorophenyl)-4-propyl-1,3-dioxolan-2-yl]methyl]-1H-1,2,4-triazole:

Result: No skin irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Components:

Silicon dioxide:

Result: No eye irritation
Remarks: Information taken from reference works and the literature.

Methyltri(ethylmethylketoxime)silane:

Species: Rabbit
Result: Irritation to eyes, reversing within 7 days
Remarks: Based on test data

Distillates (petroleum), hydrotreated middle:

Species: Rabbit
Result: No eye irritation
Method: OECD Test Guideline 405

Vinyltri (methylethylketoxime) silane:

Species: Rabbit
Result: Irreversible effects on the eye
Remarks: Based on test data

3-Aminopropyltriethoxysilane:

Species: Rabbit
Result: Irreversible effects on the eye
Remarks: Based on test data

Titanium dioxide:

Species: Rabbit
Result: No eye irritation

Methyltri(ethylmethylketoxime)silane isomers and oligomers:

Species: Rabbit
Result: Irritation to eyes, reversing within 7 days
Remarks: Based on data from similar materials

1-[[2-(2,4-dichlorophenyl)-4-propyl-1,3-dioxolan-2-yl]methyl]-1H-1,2,4-triazole:

Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.
Respiratory sensitisation: Not classified based on available information.

Components:

Silicon dioxide:

**DOW CORNING(R) 680 SANITARY SEALANT
WHITE**

Version 2.0	Revision Date: 22.09.2015	SDS Number: 661372-00005	Date of last issue: 15.06.2015 Date of first issue: 23.10.2014
----------------	------------------------------	-----------------------------	---

Assessment: Does not cause skin sensitisation.

Test Type: Skin: test type not specified

Species: Guinea pig

Remarks: Information taken from reference works and the literature.

Methyltri(ethylmethylketoxime)silane:

Assessment: Probability or evidence of skin sensitisation in humans

Test Type: Maximisation Test

Species: Guinea pig

Remarks: Based on test data

Distillates (petroleum), hydrotreated middle:

Test Type: Maximisation Test

Exposure routes: Skin contact

Species: Guinea pig

Result: negative

Remarks: Based on data from similar materials

Vinyltri (methylethylketoxime) silane:

Assessment: Probability or evidence of skin sensitisation in humans

Test Type: Maximisation Test

Species: Guinea pig

Remarks: Causes sensitisation.

Based on data from similar materials

3-Aminopropyltriethoxysilane:

Assessment: Probability or evidence of skin sensitisation in humans

Test Type: Maximisation Test

Species: Guinea pig

Remarks: Based on test data

Test Type: Buehler Test

Species: Guinea pig

Remarks: Based on test data

Titanium dioxide:

Test Type: Local lymph node assay (LLNA)

Exposure routes: Skin contact

Species: Mouse

Result: negative

Methyltri(ethylmethylketoxime)silane isomers and oligomers:

Assessment: Probability or evidence of skin sensitisation in humans

Test Type: Maximisation Test

Species: Guinea pig

Remarks: Causes sensitisation.

Based on data from similar materials

1-[[2-(2,4-dichlorophenyl)-4-propyl-1,3-dioxolan-2-yl]methyl]-1H-1,2,4-triazole:

**DOW CORNING(R) 680 SANITARY SEALANT
WHITE**

Version 2.0	Revision Date: 22.09.2015	SDS Number: 661372-00005	Date of last issue: 15.06.2015
			Date of first issue: 23.10.2014

Exposure routes: Skin contact

Species: Guinea pig

Result: positive

Assessment: Probability or evidence of skin sensitisation in humans

Chronic toxicity
Germ cell mutagenicity

Not classified based on available information.

Components:
Silicon dioxide:

Genotoxicity in vitro	: Result: negative Remarks: Information taken from reference works and the literature.
Genotoxicity in vivo	: Application Route: Ingestion Result: negative Remarks: Information taken from reference works and the literature.
Germ cell mutagenicity - Assessment	: Animal testing did not show any mutagenic effects.

Methyltri(ethylmethylketoxime)silane:

Genotoxicity in vitro	: Test Type: Mutagenicity (in vitro mammalian cytogenetic test) Result: negative Remarks: Based on test data
-----------------------	--

Distillates (petroleum), hydrotreated middle:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	: Test Type: Mutagenicity (in vivo mammalian bone-marrow cytogenetic test, chromosomal analysis) Species: Rat Application Route: Intraperitoneal injection Result: negative

Vinyltri (methylethylketoxime) silane:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative Remarks: Based on test data
Genotoxicity in vivo	: Test Type: In vivo micronucleus test Species: Mouse Application Route: Intraperitoneal injection Result: negative Remarks: Based on test data
Germ cell mutagenicity - Assessment	: Animal testing did not show any mutagenic effects.

DOW CORNING(R) 680 SANITARY SEALANT WHITE

Version 2.0	Revision Date: 22.09.2015	SDS Number: 661372-00005	Date of last issue: 15.06.2015 Date of first issue: 23.10.2014
----------------	------------------------------	-----------------------------	---

3-Aminopropyltriethoxysilane:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative Remarks: Based on test data
	: Test Type: Chromosome aberration test in vitro Result: negative Remarks: Based on test data
	: Test Type: Mutagenicity (in vitro mammalian cytogenetic test) Result: negative Remarks: Based on test data
	: Test Type: In vitro sister chromatid exchange assay in mammalian cells Result: negative Remarks: Based on test data
Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Result: negative Remarks: Based on test data
Germ cell mutagenicity - Assessment	: Animal testing did not show any mutagenic effects.

Titanium dioxide:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	: Test Type: In vivo micronucleus test Species: Mouse Result: negative

Carcinogenicity

Not classified based on available information.

Components:

3-Aminopropyltriethoxysilane:

Species: Mouse
Application Route: Skin contact
Result: negative
Remarks: Based on test data

Carcinogenicity - Assessment : Animal testing did not show any carcinogenic effects.

Titanium dioxide:

Species: Rat
Application Route: inhalation (dust/mist/fume)
Exposure time: 24 Months

**DOW CORNING(R) 680 SANITARY SEALANT
WHITE**

Version 2.0 Revision Date: 22.09.2015 SDS Number: 661372-00005 Date of last issue: 15.06.2015
 Date of first issue: 23.10.2014

Method: OECD Test Guideline 453

Result: positive

Remarks: The mechanism or mode of action may not be relevant in humans.

The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in inhalation studies with animals.

Reproductive toxicity

Not classified based on available information.

Components:
Methyltri(ethylmethylketoxime)silane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
 Species: Rat, male and female
 Application Route: Ingestion
 Symptoms: No effects on fertility
 Remarks: Based on test data

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
 Species: Rat, male and female
 Application Route: Ingestion
 Symptoms: No effects on foetal development
 Remarks: Based on test data

Reproductive toxicity - Assessment : No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.

Distillates (petroleum), hydrotreated middle:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test
 Species: Rat
 Application Route: Ingestion
 Method: OECD Test Guideline 422
 Result: negative
 Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development
 Species: Rat
 Application Route: Ingestion
 Method: OECD Test Guideline 414
 Result: negative

3-Aminopropyltriethoxysilane:

Effects on fertility : Species: Rat, male and female
 Application Route: Ingestion
 Symptoms: No effects on fertility
 Remarks: Based on test data

Effects on foetal development : Test Type: Prenatal development toxicity study (teratogenicity)

**DOW CORNING(R) 680 SANITARY SEALANT
WHITE**

Version 2.0	Revision Date: 22.09.2015	SDS Number: 661372-00005	Date of last issue: 15.06.2015 Date of first issue: 23.10.2014
----------------	------------------------------	-----------------------------	---

ment	Species: Rat Application Route: Ingestion Symptoms: No effects on foetal development Remarks: Based on test data
Reproductive toxicity - Assessment	: No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.

STOT - single exposure

|| Not classified based on available information.

STOT - repeated exposure

|| Not classified based on available information.

Components:
Methyltri(ethylmethylketoxime)silane:

Exposure routes: Ingestion
Target Organs: Blood
Assessment: Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

Vinyltri (methylethylketoxime) silane:

Exposure routes: Ingestion
Target Organs: Blood
Assessment: Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

3-Aminopropyltriethoxysilane:

Exposure routes: Ingestion
Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Exposure routes: inhalation (dust/mist/fume)

Assessment: No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d or less.

Exposure routes: Skin contact

Assessment: No significant health effects observed in animals at concentrations of 200 mg/kg bw or less.

Methyltri(ethylmethylketoxime)silane isomers and oligomers:

Exposure routes: Ingestion
Target Organs: Blood
Assessment: Shown to produce significant health effects in animals at concentrations of >10 to 100 mg/kg bw.

Repeated dose toxicity
Components:
Methyltri(ethylmethylketoxime)silane:

Species: Rat
Application Route: Ingestion
Target Organs: Blood

**DOW CORNING(R) 680 SANITARY SEALANT
WHITE**

Version 2.0 Revision Date: 22.09.2015 SDS Number: 661372-00005 Date of last issue: 15.06.2015
Date of first issue: 23.10.2014

Remarks: Based on test data

Distillates (petroleum), hydrotreated middle:

Species: Rat

NOAEL: >= 5,000 mg/kg

Application Route: Ingestion

Exposure time: 13 Weeks

Remarks: Based on data from similar materials

Vinyltri (methylethylketoxime) silane:

Species: Rat

Application Route: Ingestion

Target Organs: Blood

Remarks: Based on data from similar materials

3-Aminopropyltriethoxysilane:

Species: Rat

Application Route: Ingestion

Remarks: Based on test data

Species: Rat

Application Route: inhalation (dust/mist/fume)

Remarks: Based on test data

Species: Rabbit

Application Route: Skin contact

Remarks: Based on data from similar materials

Titanium dioxide:

Species: Rat

NOAEL: 24,000 mg/kg

Application Route: Ingestion

Exposure time: 28 d

Species: Rat

NOAEL: 10 mg/m³

Application Route: inhalation (dust/mist/fume)

Exposure time: 2 y

Remarks: The substance is inextricably bound in the product and therefore does not contribute to a dust inhalation hazard.

Methyltri(ethylmethylketoxime)silane isomers and oligomers:

Species: Rat

Application Route: Ingestion

Target Organs: Blood

Remarks: Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

Components:**Distillates (petroleum), hydrotreated middle:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be re-

DOW CORNING(R) 680 SANITARY SEALANT WHITE

Version 2.0 Revision Date: 22.09.2015 SDS Number: 661372-00005 Date of last issue: 15.06.2015
 Date of first issue: 23.10.2014

Regarded as if it causes a human aspiration toxicity hazard.

Further information

Product:

Remarks: During use of the material, small amounts of methylethylketoxime (MEKO) will be released. Rodents exposed to chronic MEKO inhalation throughout their lifetimes showed significant increases in liver tumour rates.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Methyltri(ethylmethylketoxime)silane:

Toxicity to fish	LC50 (Oncorhynchus mykiss (rainbow trout)): > 120 mg/l Exposure time: 96 h Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	EC50 (Daphnia magna (Water flea)): > 120 mg/l Exposure time: 48 h Method: OECD Test Guideline 202 Remarks: Based on data from similar materials
Toxicity to algae	ErC50 (Selenastrum capricornutum (green algae)): 94 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 Remarks: Based on data from similar materials

Ecotoxicology Assessment

Acute aquatic toxicity	: This product has no known ecotoxicological effects.
------------------------	---

Distillates (petroleum), hydrotreated middle:

Toxicity to fish	LL50 (Scophthalmus maximus (turbot)): > 1,028 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction
Toxicity to daphnia and other aquatic invertebrates	LL50 (Acartia tonsa): > 3,193 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction
Toxicity to algae	EL50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	NOELR (Ceriodaphnia dubia (water flea)): > 100 mg/l Exposure time: 8 d Test substance: Water Accommodated Fraction
Toxicity to bacteria	EC50: > 100 mg/l Exposure time: 3 h

DOW CORNING(R) 680 SANITARY SEALANT WHITE

Version 2.0 Revision Date: 22.09.2015 SDS Number: 661372-00005 Date of last issue: 15.06.2015
 Date of first issue: 23.10.2014

Method: OECD Test Guideline 209

3-Aminopropyltriethoxysilane:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 934 mg/l
 Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia sp.): 331 mg/l
 Exposure time: 48 h

Titanium dioxide:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
 Exposure time: 96 h
 Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
 Exposure time: 48 h

Toxicity to algae : EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l
 Exposure time: 72 h

Toxicity to bacteria : EC50: > 1,000 mg/l
 Exposure time: 3 h
 Method: OECD Test Guideline 209

1-[[2-(2,4-dichlorophenyl)-4-propyl-1,3-dioxolan-2-yl]methyl]-1H-1,2,4-triazole:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.3 mg/l
 Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia (water flea)): 10.2 mg/l
 Exposure time: 48 h

Toxicity to algae : EC50 (Scenedesmus subspicatus): 0.76 mg/l
 Exposure time: 72 h

M-Factor (Acute aquatic toxicity) : 1

Persistence and degradability

Components:

Methyltri(ethylmethylketoxime)silane:

Biodegradability : Result: Not readily biodegradable.
 Biodegradation: 14.5 %
 Exposure time: 21 d
 Method: OECD Test Guideline 302B
 Remarks: Based on data from similar materials

Distillates (petroleum), hydrotreated middle:

Biodegradability : Result: Readily biodegradable
 Biodegradation: 74 %
 Exposure time: 28 d
 Method: OECD Test Guideline 306

**DOW CORNING(R) 680 SANITARY SEALANT
WHITE**

Version 2.0	Revision Date: 22.09.2015	SDS Number: 661372-00005	Date of last issue: 15.06.2015 Date of first issue: 23.10.2014
----------------	------------------------------	-----------------------------	---

Not applicable for product as supplied.

National Regulations**ADG**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION**Safety, health and environmental regulations/legislation specific for the substance or mixture**

Prohibition/Licensing Requirements : There is no applicable prohibition or notification/licensing requirements, including for carcinogens under Commonwealth, State or Territory legislation.

The components of this product are reported in the following inventories:

NZIoC : All ingredients listed or exempt.

AICS : All ingredients listed or exempt.

REACH : All ingredients (pre-)registered or exempt.

TSCA : For R&D purposes only. One or more of the components of this product may not be listed on the TSCA inventory of chemical substances. Product should be used solely for scientific experimentation, research or analysis under the supervision of technically qualified individuals.

PICCS : Consult your local Dow Corning office.

KECI : All ingredients listed, exempt or notified.

IECSC : One or more components of this product may not be listed on the IECSC inventory, but this component(s) is (are) registered with volume limitation under Dow Corning entity in China. Consult your local Dow Corning office.

TCSI : All ingredients listed or exempt.

SECTION 16. OTHER INFORMATION**Further information**

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSS, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

**DOW CORNING(R) 680 SANITARY SEALANT
WHITE**

Version 2.0	Revision Date: 22.09.2015	SDS Number: 661372-00005	Date of last issue: 15.06.2015 Date of first issue: 23.10.2014
----------------	------------------------------	-----------------------------	---

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
AU OEL	: Australia. Workplace Exposure Standards for Airborne Contaminants.
DCC OEL	: Dow Corning Guide
ACGIH / TWA	: 8-hour, time-weighted average
AU OEL / TWA	: Exposure standard - time weighted average
DCC OEL / TWA	: Time weighted average

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; CPR - Controlled Products Regulations; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECL - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, un-

**DOW CORNING(R) 680 SANITARY SEALANT
WHITE**Version
2.0Revision Date:
22.09.2015SDS Number:
661372-00005Date of last issue: 15.06.2015
Date of first issue: 23.10.2014

less specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

AU / EN