

MATERIAL SAFETY DATA SHEET

Product Trade Name: **EH-3**

Revision Date: 02-Jan-2013

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Trade Name: EH-3
Synonyms: None
Chemical Family: Blend
Application: Hardener

Manufacturer/Supplier: Halliburton Energy Services
P.O. Box 1431
Duncan, Oklahoma 73536-0431
Emergency Telephone: (281) 575-5000

Prepared By: Chemical Compliance
Telephone: 1-580-251-4335
e-mail: fdunexchem@halliburton.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

Substances	CAS Number	PERCENT	ACGIH TLV-TWA	OSHA PEL-TWA
4,4' Methylene dianiline	101-77-9	30 - 60%	0.1 ppm	0.01 ppm
Methanol	67-56-1	30-32	200 ppm (S)	200 ppm

3. HAZARDS IDENTIFICATION

Hazard Overview May cause eye, skin, and respiratory irritation. May cause headache, dizziness, and other central nervous system effects. May be fatal if swallowed. May cause blindness. May be absorbed through the skin. May cause allergic skin reaction. Repeated overexposure may cause liver and kidney effects. Potential carcinogen. Flammable.

4. FIRST AID MEASURES

Inhalation If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.

Skin In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes. Get medical attention. Remove contaminated clothing and launder before reuse.

Eyes In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.

Ingestion Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

Notes to Physician Not Applicable

5. FIRE FIGHTING MEASURES

Flash Point/Range (F):	52
Flash Point/Range (C):	11
Flash Point Method:	PMCC
Autoignition Temperature (F):	Not Determined
Autoignition Temperature (C):	Not Determined
Flammability Limits in Air - Lower (%):	7.3
Flammability Limits in Air - Upper (%):	36

Fire Extinguishing Media Water fog, carbon dioxide, foam, dry chemical.

Special Exposure Hazards May be ignited by heat, sparks or flames. Use water spray to cool fire exposed surfaces. Closed containers may explode in fire. Decomposition in fire may produce toxic gases.

Special Protective Equipment for Fire-Fighters Full protective clothing and approved self-contained breathing apparatus required for fire fighting personnel.

NFPA Ratings: Health 3, Flammability 3, Reactivity 0
HMS Ratings: Health 3, Flammability 3, Reactivity 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautionary Measures Use appropriate protective equipment. Wear self-contained breathing apparatus in enclosed areas.

Environmental Precautionary Measures Prevent from entering sewers, waterways, or low areas.

Procedure for Cleaning / Absorption Isolate spill and stop leak where safe. Remove ignition sources and work with non-sparking tools. Contain spill with sand or other inert materials. Scoop up and remove.

7. HANDLING AND STORAGE

Handling Precautions Avoid contact with eyes, skin, or clothing. Avoid breathing vapors. Wash hands after use. Launder contaminated clothing before reuse. Ground and bond containers when transferring from one container to another.

Storage Information Store away from oxidizers. Keep from heat, sparks, and open flames. Keep container closed when not in use.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls Use in a well ventilated area. Local exhaust ventilation should be used in areas without good cross ventilation.

Respiratory Protection Positive pressure self-contained breathing apparatus if methanol is released.

Hand Protection Impervious rubber gloves.

Skin Protection Rubber apron.

Eye Protection Chemical goggles; also wear a face shield if splashing hazard exists.

Other Precautions Eyewash fountains and safety showers must be easily accessible.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Color:	Red brown
Odor:	Alcohol
pH:	6.9
Specific Gravity @ 20 C (Water=1):	1.04
Density @ 20 C (lbs./gallon):	8.7
Bulk Density @ 20 C (lbs/ft3):	Not Determined
Boiling Point/Range (F):	148
Boiling Point/Range (C):	64
Freezing Point/Range (F):	Not Determined
Freezing Point/Range (C):	Not Determined
Vapor Pressure @ 20 C (mmHg):	96
Vapor Density (Air=1):	Not Determined
Percent Volatiles:	31
Evaporation Rate (Butyl Acetate=1):	Not Determined
Solubility in Water (g/100ml):	Miscible
Solubility in Solvents (g/100ml):	Not Determined
VOCs (lbs./gallon):	Not Determined
Viscosity, Dynamic @ 20 C (centipoise):	Not Determined
Viscosity, Kinematic @ 20 C (centistokes):	Not Determined
Partition Coefficient/n-Octanol/Water:	Not Determined
Molecular Weight (g/mole):	Not Determined

10. STABILITY AND REACTIVITY

Stability Data:	Stable
Hazardous Polymerization:	Will Not Occur
Conditions to Avoid	Keep away from heat, sparks and flame.
Incompatibility (Materials to Avoid)	Strong oxidizers.
Hazardous Decomposition Products	Oxides of nitrogen. Carbon monoxide and carbon dioxide.
Additional Guidelines	Not Applicable

11. TOXICOLOGICAL INFORMATION

Principle Route of Exposure	Eye or skin contact, inhalation.
Inhalation	May cause central nervous system depression including headache, dizziness, drowsiness, incoordination, slowed reaction time, slurred speech, giddiness and unconsciousness. May cause liver damage. May cause thyroid damage.
Skin Contact	May be absorbed through the skin and produce effects similar to those caused by inhalation and/or ingestion. May cause skin irritation. May cause an allergic skin reaction.
Eye Contact	Causes severe eye irritation which may damage tissue.
Ingestion	May be fatal or cause blindness if swallowed. May cause central nervous system depression including headache, dizziness, drowsiness, muscular weakness, incoordination, slowed reaction time, fatigue blurred vision, slurred speech, giddiness, tremors and convulsions. May cause liver damage. May cause thyroid damage.

Aggravated Medical Conditions	Skin disorders. Eye ailments.
Chronic Effects/Carcinogenicity	Contains 4,4'-methylenedianiline (MDA), a potential human carcinogen of the liver and spleen. MDA may induce toxic hepatitis. Prolonged or repeated exposure may cause eye, blood, lung, liver, kidney, heart, central nervous system and spleen damage.
Other Information	None known.
Toxicity Tests	
Oral Toxicity:	Not determined
Dermal Toxicity:	Not determined
Inhalation Toxicity:	Not determined
Primary Irritation Effect:	Not determined
Carcinogenicity	Not determined
Genotoxicity:	Not determined
Reproductive / Developmental Toxicity:	Not determined

12. ECOLOGICAL INFORMATION

Mobility (Water/Soil/Air)	Not determined
Persistence/Degradability	Resistant
Bio-accumulation	Not determined

Ecotoxicological Information

Acute Fish Toxicity:	Not determined
Acute Crustaceans Toxicity:	Not determined
Acute Algae Toxicity:	Not determined
Chemical Fate Information	Not determined
Other Information	Not applicable

13. DISPOSAL CONSIDERATIONS

Disposal Method	Disposal should be made in accordance with federal, state, and local regulations.
Contaminated Packaging	Follow all applicable national or local regulations.

14. TRANSPORT INFORMATION

Land Transportation

DOT

UN1866, Resin Solution, 3, III, (24 C)
RQ (4,4'-Methylenedianiline - 9 kg.)
NAERG 127

Canadian TDG

Resin Solution, 3, UN1866, III, (24 C)

ADR

UN1866, Resin Solution, 3, III

Air Transportation**ICAO/IATA**

UN1866, Resin Solution, 3, III

RQ (4,4'-Methylenedianiline - 9 kg.)

Sea Transportation**IMDG**

UN1866, Resin Solution, 3, III, (24 C)

RQ (4,4'-Methylenedianiline - 9 kg.)

EmS F-E, S-E

Other Transportation Information

Labels: Flammable Liquid

15. REGULATORY INFORMATION**US Regulations**

US TSCA Inventory All components listed on inventory or are exempt.

EPA SARA Title III Extremely Hazardous Substances Not applicable

EPA SARA (311,312) Hazard Class Acute Health Hazard
Chronic Health Hazard
Fire Hazard

EPA SARA (313) Chemicals This product contains toxic chemical(s) listed below which is(are) subject to the reporting requirements of Section 313 of Title III of SARA and 40 CFR Part 372:
Methanol//67-56-1
4,4'-Methylene Dianiline//101-77-9

EPA CERCLA/Superfund Reportable Spill Quantity EPA Reportable Spill Quantity is 1 Gallon based on 4,4'-Methylene dianiline (CAS: 101-77-9).

EPA RCRA Hazardous Waste Classification If product becomes a waste, it does meet the criteria of a hazardous waste as defined by the US EPA, because of:

Ignitability D001

California Proposition 65 The California Proposition 65 regulations apply to this product.

MA Right-to-Know Law One or more components listed.

NJ Right-to-Know Law	One or more components listed.
PA Right-to-Know Law	One or more components listed.
Canadian Regulations	
Canadian DSL Inventory	All components listed on inventory or are exempt.
WHMIS Hazard Class	B2 Flammable Liquids D1A Very Toxic Materials D1B Toxic Materials

16. OTHER INFORMATION

The following sections have been revised since the last issue of this MSDS

Not applicable

Additional Information For additional information on the use of this product, contact your local Halliburton representative.

For questions about the Material Safety Data Sheet for this or other Halliburton products, contact Chemical Compliance at 1-580-251-4335.

Disclaimer Statement This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or in any process. Final determination of suitability of any material is the sole responsibility of the user.

*****END OF MSDS*****